FCC ID: 2AAQFM1

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

KDB447498 D01 General RF Exposure Guidance V06

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power	Average Time					
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)	· ·					
(A) Limits for Occupational/Control Exposures									
300-1500			F/300	6					
1500-100000			5	6					
(B) Limits for General Population/Uncontrol Exposures									
300-1500			F/1500	6					
1500-100000			1	30					

11.1 Friis transmission formula: Pd= (Pout*G)/(4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE,1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached. $mW = 10^{\circ} (dBm/10)$

11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz Power density limited: 1mW/ cm^{2;} Antenna gain: PCB Antenna 0dBi;

Bluetooth:

Operatio n Mode	Channel Frequenc y (MHz)	Output power (mW)	Output power (dBm)	Tune- up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Power density at 20cm(mW/c m2)	Power density Limits (mW/cm2)
GFSK	2402	1.294	1.12	1±1	2	1	0.00032	1
	2441	1.230	0.90	1±1	2	1	0.00032	1
	2480	1.057	0.24	1±1	2	1	0.00032	1
pi/4- DQPSK	2402	1.250	0.97	1±1	2	1	0.00032	1
	2441	1.183	0.73	1±1	2	1	0.00032	1
	2480	1.014	0.06	1±1	2	1	0.00032	1
8DPSK	2402	1.250	0.97	1±1	2	1	0.00032	1
	2441	1.186	0.74	1±1	2	1	0.00032	1
	2480	1.023	0.10	1±1	2	1	0.00032	1

Sincerely,

Company Name: EMTEK (Shenzhen) CO., LTD.
Address: Bldg 69, Majialong Industry Zone, NanshanDistrict, Shenzhen, China.
David Lee/ Manager