



<b>Prüfbericht-Nr.:</b> <i>Test report No.:</i>	<b>50316822 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	<b>168138892</b>	<b>Seite 1 von 26</b> <i>Page 1 of 26</i>
<b>Kunden-Referenz-Nr.:</b> <i>Client reference No.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date.:</i>	07.11.2019	
<b>Auftraggeber:</b> <i>Client:</i>	<b>UP Global Sourcing Ltd.</b> UP Global Sourcing, Manor Mill, Victoria Street, Chadderton, Oldham, OL9 0DD, United Kingdom			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Wireless Earphones			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	EE3576X (X means colour code), EE3576BLKPRIFOB (Trademark: Primark)			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC approval			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 CFR47 FCC Part 2: Section 2.1093			
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	11.11.2019	Please refer to photo documents		
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A001021117-001 to 002 A001018929-005			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	11.11.2019 - 28.11.2019			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>		
 28.11.2019 Ryan Yang / Assistant Project Manager		 28.11.2019 Winnie Hou / Technical Certifier		
<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>
<b>Sonstiges / Other:</b> FCC ID: 2AAR2EE35762				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		<b>Prüfmuster vollständig und unbeschädigt</b> <i>Test item complete and undamaged:</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n)		4 = ausreichend 5 = mangelhaft N/A = nicht anwendbar N/T = nicht getestet		
Legend: 1 = very good 2 = good 3 = satisfactory P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s)		4 = sufficient 5 = poor N/A = not applicable N/T = not tested		
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

## **Test Summary**

**5.1.1 ANTENNA REQUIREMENT***RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 99% BANDWIDTH***RESULT: Pass***5.1.4 20dB BANDWIDTH***RESULT: Pass***5.1.5 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.6 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.7 TIME OF OCCUPANCY***RESULT: Pass***5.1.8 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH***RESULT: Pass***5.1.9 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.10 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass***5.1.11 RADIATED EMISSION***RESULT: Pass*

## Contents

<b>1</b>	<b>GENERAL REMARKS.....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2</b>	<b>TEST SITES .....</b>	<b>5</b>
<b>2.1</b>	<b>TEST FACILITIES.....</b>	<b>5</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS .....</b>	<b>5</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>7</b>
<b>2.4</b>	<b>CALIBRATION.....</b>	<b>7</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>7</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING .....</b>	<b>7</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>8</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>8</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>8</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES.....</b>	<b>9</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS.....</b>	<b>10</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS .....</b>	<b>10</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES.....</b>	<b>11</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>11</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>11</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE .....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>13</b>
<b>5</b>	<b>TEST RESULTS.....</b>	<b>15</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>15</b>
<b>5.1.1</b>	<i>Antenna Requirement.....</i>	<i>15</i>
<b>5.1.2</b>	<i>Maximum Peak Conducted Output Power .....</i>	<i>16</i>
<b>5.1.3</b>	<i>99% Bandwidth.....</i>	<i>17</i>
<b>5.1.4</b>	<i>20dB Bandwidth.....</i>	<i>18</i>
<b>5.1.5</b>	<i>Carrier Frequency Separation .....</i>	<i>19</i>
<b>5.1.6</b>	<i>Number of Hopping Frequency.....</i>	<i>20</i>
<b>5.1.7</b>	<i>Time of Occupancy.....</i>	<i>21</i>
<b>5.1.8</b>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth .....</i>	<i>22</i>
<b>5.1.9</b>	<i>Radiated Spurious Emission .....</i>	<i>23</i>
<b>5.1.10</b>	<i>Conducted Emission on AC Mains .....</i>	<i>24</i>
<b>5.1.11</b>	<i>Radiated Emission.....</i>	<i>25</i>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>	<b>26</b>
<b>7</b>	<b>LIST OF TABLES .....</b>	<b>26</b>

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Bluetooth

Appendix C: Test Results of Part 15B

## 2 Test Sites

### 2.1 Test Facilities

**TÜV Rheinland (Shenzhen) Co., Ltd.**

1F East & 2-4F, Cybio Technology Building No. 1, No. 16 Kejibei 2nd Road, High-Tech Industrial Park  
North Nanshan District, Shenzhen, 518057

FCC accredited testing laboratory: CN1260

ISED wireless device testing laboratory: 25069

### 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

**TÜV Rheinland (Shenzhen) Co., Ltd.**

<b>Radio Spectrum Testing (TS8997)</b>					
<b>Equip. No.</b>	<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
1825795	Signal Analyzer	Rohde & Schwarz	FSV 40	101441	20.08.2020
1825798	OSP	Rohde & Schwarz	OSP 150	101017	20.12.2019
1825799	Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
1825800	Test Software	Rohde & Schwarz	WMS32 (V10.40.10)	N/A	N/A
1825801	Power Meter	Rohde & Schwarz	NRP2	107105	20.12.2019
1825802	Wideband Power Sensor	Rohde & Schwarz	NRP-Z81	105350	20.12.2019
1826431	Shielding Room 8#	Albatross	SR8	APC17151-SR8	23.07.2020
<b>Unwanted Emission Testing (TS9975)</b>					
<b>Equip. No.</b>	<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
1826021	EMI Test Receiver	Rohde & Schwarz	ESR 7	102021	19.08.2020
1826023	Signal Analyzer	Rohde & Schwarz	FSV 40	101439	21.08.2020
1826024	System Controller Interface	Rohde & Schwarz	SCI-100	S10010038	N/A
1826025	Filterbank	Rohde & Schwarz	Wlan	100759	21.08.2020
1826026	OSP	Rohde & Schwarz	OSP 120	102040	N/A
1826028	Pre-amplifier	Rohde & Schwarz	SCU08F1	08320031	20.08.2020
1826029	Amplifier	Rohde & Schwarz	SCU-18F	180070	20.08.2020
1826030	Amplifier	Rohde & Schwarz	SCU40A	100475	20.09.2020
1826031	Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	02.09.2020
1826032	Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	02.09.2020
1826033	Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	02.09.2020

1826034	Active Loop Antenna	Schwarzbeck	FMZB 1513	302	01.09.2020
1826035	Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18313	02.09.2020
1826036	Test software	Rohde & Schwarz	V10.40.10-EMC32	N/A	N/A
1826037	Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
1826433	3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	06.07.2020

**Conducted Emission on AC Mains**

Equip. No.	Equipment	Manufacturer	Model	Serial No.	Cal. until
1822625	EMI Test Receiver	R&S	ESR3	102428	03.09.2020
1822627	Artificial Mains Network	R&S	ENV216	102333	19.08.2020

**Radiated Emission (3m chamber)**

Equip. No.	Equipment	Manufacturer	Model No.	Serial No.	Cali. until
1822620	3m SAC	ETS	SAC3	CT001632-Q1362	23.08.2021
1825044	EMI Test Receiver	R&S	ESR7	102111	23.01.2020
1825004	Horn Antenna	R&S	HF907	102706	01.09.2020
1825005	Preamplifier	FIT	SCU-18F	180077	19.08.2020
1825042	Trilog-Broadband antenna	SCHWARZBECK	VULB9168	0945	12.09.2020
1825090	EMC Measurement Software	R&S	EMC32(Ver.10.30.01)	N/A	N/A

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF Power (conducted)	$\pm 2.5$ dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	$\pm 6$ dB
Radiated Emission of Receiver, valid up to 26.5 GHz	$\pm 6$ dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	$\pm 3.70$ dB / $\pm 3.30$ dB
Radiated Emission (3m SAC), 30MHz to 1000MHz	$\pm 4.52$ dB
Radiated Emission (3m SAC), above 1000MHz	$\pm 4.37$ dB
Temperature	$\pm 1$ °C
Humidity	$\pm 5$ %
Voltage (DC)	$\pm 1$ %
Voltage (AC, <10kHz)	$\pm 2$ %

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 1F East & 2-4F, Cybio Technology Building No. 1, No. 16 Kejibei 2nd Road, High-Tech Industrial Park North Nanshan District, Shenzhen, 518057 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

## 3 General Product Information

### 3.1 Product Function and Intended Use

The EUT is a Wireless Earphones, which support 2.4GHz Bluetooth technology.

According to the declaration of the applicant, the electrical circuit design, PCB layout and construction Design are identical for all models, only the model No. and color are different.

Model Name	Color
EE3576	Based model number
EE3576BLKPRIFOB	Black

Note: When the EUT is charged, other functions cannot be used.

For details refer to the User Manual, Technical Description and Circuit Diagram.

### 3.2 Ratings and System Details

**Table 2: Technical Specification of EUT**

General Information of EUT	Value
Kind of Equipment	Wireless Earphones
Type Designation	EE3576X (X means colour code), EE3576BLKPRIFOB
Trademark	Primark
FCC ID	2AAR2EE35762
Operating Voltage	DC 5.0V via USB port for charging DC 3.7V via internal rechargeable lithium battery
Testing Voltage	Fully charged battery AC 120V @60Hz
Battery #1	DC 3.7V @80mAh lithium battery
Technical Specification of Bluetooth	
Operating Frequency	2400 MHz to 2483.5 MHz
Type of Modulation	GFSK(BDR), $\pi/4$ DQPSK(EDR)
Channel Number	79 channels
Channel Separation	1MHz;
Antenna Type	Integral Antenna
Antenna Gain	0 dBi

**Table 3: Operating Frequencies/Channels of EUT**

Operating Mode	Description
Bluetooth®	<input checked="" type="checkbox"/> BDR/EDR $f_c = 2402 + k$ MHz, where $k = 0 \sim 78$ <input type="checkbox"/> Low Energy $f_c = 2402 + k*2$ MHz, where $k = 0 \sim 39$



**Table 4: Frequency Hopping Information**

Technical Specification	Description
Hopping Range	Hereby we declare that the frequency range of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V5.0 + EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E).
Hopping Sequence	Example of a 79 hopping sequence in data mode:  33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73,07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56,69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43,15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	<p>The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.</p> <p>Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.</p> <p>Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case.</p> <p>That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.</p>

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode (BDR & EDR mode)
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Transmitting on Hopping channel
- C. On, Bluetooth playing mode
- D. On, Charging mode
- E. On, TF Card playing mode
- F. Off

### **3.4 Noise Generating and Noise Suppressing Parts**

Refer to Circuit Diagram for further details.

### **3.5 Submitted Documents**

- |                                  |               |
|----------------------------------|---------------|
| - Block Diagram                  | - Schematics  |
| - FCC/IC Label and Location Info | - User Manual |

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

According to clause 3.1, all tests were performed on model EE3576BLKPRIFOB in this report.

**Table 5: List of Frequencies under Test**

<input checked="" type="checkbox"/> Bluetooth				
Operation mode	Frequencies under Test (MHz)			Power Level setting (dBm)
	CH <sub>Low</sub>	CH <sub>Mid</sub>	CH <sub>High</sub>	
<input checked="" type="checkbox"/> BDR/EDR	2402.0	2441.0	2480.0	Level 3

## 4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	T480	PF-16A6N8	N/A
Adapter	LETV	EQ-24ACN	15120303488	N/A
TF Card	igoz	Ultimate 3.0 8GB	HSP080S2D5 1AP16P26N	N/A

## 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)







Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



### Diagram of Measurement Configuration for Mains Conduction Measurement



### Diagram of Measurement Configuration for Conducted Transmitter Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

RESULT:

Pass

**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

## 5.1.2 Maximum Peak Conducted Output Power

**RESULT:**
**Pass**
**Test Specification**

Test standard : FCC Part 15.247(b)(1)  
 Basic standard : ANSI C63.10: 2013  
 Limits : DSS < 0.125 Watts  
 Kind of test site : Shielded Room

**Test Setup**

Date of testing : 21.11.2019  
 Input voltage : Fully charged battery  
 Operation mode : A  
 Test channel : Low / Middle / High  
 Ambient temperature : 25 °C  
 Relative humidity : 56 %  
 Atmospheric pressure : 101 kPa

**Table 7: Test Result of Maximum Peak Conducted Output Power, BDR & EDR Mode**

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
GFSK (BDR)	2402.0	-7.47	0.0002	< 0.125
	2441.0	-6.26	0.0002	
	2480.0	-5.94	0.0003	
Maximum Measured Value		-5.94	0.0003	

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
π/4DQPSK (EDR)	2402.0	-6.61	0.0002	< 0.125
	2441.0	-5.32	0.0003	
	2480.0	-5.11	0.0003	
Maximum Measured Value		-5.11	0.0003	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 0 dBi,  
 $e.i.r.p. = P_{(Peak\ power)} + G$ , which is far below the 4 W



### 5.1.3 99% Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(a)
Basic standard	: ANSI C63.10: 2013
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

**5.1.4 20dB Bandwidth****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10: 2013
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

## 5.1.5 Carrier Frequency Separation

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

## 5.1.6 Number of Hopping Frequency

**RESULT:****Pass****Test Specification**

Test standard	: FCC part 15.247(a)(1)(iii)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 15$ non-overlapping channels
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: B
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

## 5.1.7 Time of Occupancy

**RESULT:****Pass****Test Specification**

Test standard	: FCC part 15.247(a)(1)(iii)
Basic standard	: ANSI C63.10: 2013
Limits	: < 0.4s
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

**Note:**

Dwell time = Pulse width x Number of channels in Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds

For the measurement records, refer to the appendix B.

**5.1.8 Conducted Spurious Emissions Measured in 100 kHz Bandwidth****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 20.11.2019
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: 50316822 001**

Test Report No.

Seite 23 von 26

Page 23 of 26

## 5.1.9 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205
Basic standard	: ANSI C63.10: 2013
Limits	: Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	: 3m Semi-anechoic Chamber

**Test Setup**

Date of testing	: Refer to test result
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 23 °C
Relative humidity	: 49 %
Atmospheric pressure	: 101 kPa

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

**5.1.10 Conducted Emission on AC Mains****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.107(a)
Basic standard	: ANSI C63.4: 2014
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.107(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: Refer to test result
Input voltage	: AC 120V @60Hz
Operation mode	: D
Earthing	: Not connected
Ambient temperature	: 22 °C
Relative humidity	: 64 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix C.



**5.1.11 Radiated Emission****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.109(a)
Basic standard	: ANSI C63.4: 2014
Frequency range	: 30 - 6000MHz
Classification	: Class B
Limits	: FCC Part 15.109(a)
Kind of test site	: 3m Semi-anechoic Chamber

**Test Setup**

Date of testing	: Refer to test result
Input voltage	: Fully charged battery AC 120V @60Hz
Operation mode	: D, E
Earthing	: Not connected
Ambient temperature	: 24 °C
Relative humidity	: 50 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix C.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

## 7 List of Tables

Table 1: List of Test and Measurement Equipment .....	5
Table 2: Technical Specification of EUT .....	8
Table 3: Operating Frequencies/Channels of EUT .....	8
Table 4: Frequency Hopping Information .....	9
Table 5: List of Frequencies under Test.....	11
Table 6: Auxiliary Equipment Used during Test.....	12
Table 7: Test Result of Maximum Peak Conducted Output Power, BDR & EDR Mode.....	16