

TEST REPORT

Reference No. : WTU17S0373678E
FCC ID..... : 2AARJ-ELST4017
Applicant..... : Avision Technology (changzhou)Co.,Ltd
Address : No.28 Xinsi Road, Xinbei District, Changzhou, Jiangsu
Manufacturer : The same as above
Address : The same as above
Product Name : 40" FHD Digital LED TV
Model No. : ELST4017
Standards..... : FCC CFR47 Part 15 C Section 15.247:2016
Date of Receipt sample..... : Mar. 15, 2017
Date of Test..... : Mar. 16 – Apr. 05, 2017
Date of Issue : Apr. 11, 2017
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.
The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.


Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
2 REPORT REVISION HISTORY	4
3 GENERAL INFORMATION.....	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
3.2 DETAILS OF E.U.T.	5
3.3 CHANNEL LIST	5
3.4 TEST MODE	6
3.5 TEST FACILITY	6
4 EQUIPMENT USED DURING TEST	7
4.1 EQUIPMENTS LIST	7
4.2 MEASUREMENT UNCERTAINTY	8
4.3 TEST EQUIPMENT CALIBRATION	8
5 TEST SUMMARY	9
6 CONDUCTED EMISSION	10
6.1 E.U.T. OPERATION	10
6.2 EUT SETUP	10
6.3 MEASUREMENT DESCRIPTION	10
6.4 CONDUCTED EMISSION TEST RESULT	11
7 RADIATED EMISSIONS.....	13
7.1 EUT OPERATION.....	13
7.2 TEST SETUP	14
7.3 SPECTRUM ANALYZER SETUP	15
7.4 TEST PROCEDURE	16
7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	16
7.6 SUMMARY OF TEST RESULTS	17
8 BAND EDGE MEASUREMENT	29
8.1 TEST PRODUCE	29
8.2 TEST RESULT	30
9 BANDWIDTH MEASUREMENT.....	34
9.1 TEST PROCEDURE:	34
9.2 TEST RESULT:	34
10 MAXIMUM PEAK OUTPUT POWER	41
10.1 TEST PROCEDURE:	41
10.2 TEST RESULT:	41
11 POWER SPECTRAL DENSITY	48
11.1 TEST PROCEDURE:	48
11.2 TEST RESULT:	48
12 ANTENNA REQUIREMENT	55
13 RF EXPOSURE.....	56
13.1 REQUIREMENTS.....	56
13.2 THE PROCEDURES / LIMIT	56
13.3 MPE CALCULATION METHOD	57
14 PHOTOGRAPHS – MODEL ELST4017 TEST SETUP.....	58
14.1 RADIATED EMISSION	58

14.2 CONDUCTED EMISSION AT TEST SITE 2#60

15 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS61

15.1 MODEL ELST4017–EXTERNAL PHOTOS61

15.2 MODEL ELST4017– INTERNAL PHOTOS.....66

2 Report Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTU17S0373678E	Mar. 15, 2017	Mar. 16 – Apr. 05, 2017	Apr. 11, 2017	original	-	Valid

3 General Information

3.1 General Description of E.U.T.

Product Name:	40" FHD Digital LED TV
Model No.:	ELST4017
Model Difference:	N/A
Operation Frequency:	802.11b/g/n HT20: 2412MHz ~ 2462MHz, 802.11n HT40: 2422MHz~2452MHz
The Lowest Oscillator:	:24MHz
Antenna Gain:	:2.0 dBi
Type of modulation:	IEEE 802.11b (CCK/QPSK/BPSK,11Mbps max.) IEEE 802.11g (BPSK/QPSK/16QAM/64QAM,54Mbps max.) IEEE 802.11n (BPSK/QPSK/16QAM/64QAM,HT20:72Mbps max., HT40:150Mbps max.)

3.2 Details of E.U.T.

Technical Data:	Input: AC 120V~ 60Hz, 75W
-----------------	---------------------------

3.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

3.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Frequency Range	802.11b	11 Mbps	1/11	TX
	802.11g	54 Mbps	1/11	TX
	802.11n HT20	108 Mbps	1/11	TX
	802.11n HT40	150 Mbps	3/9	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

3.5 Test Facility

The test facility has a test site registered with the following organizations:

- IC – Registration No.: 7760A-1**
 Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.
 Registration number 7760A-1, October 15, 2015.
- FCC Test Site 1#– Registration No.: 880581**
 Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.
- FCC Test Site 2#– Registration No.: 328995**
 Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

4 Equipment Used during Test

4.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.12, 2016	Sep.11, 2017
2.	LISN	R&S	ENV216	101215	Sep.12, 2016	Sep.11, 2017
3.	Cable	Top	TYPE16(3.5M)	-	Sep.12, 2016	Sep.11, 2017
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.12, 2016	Sep.11, 2017
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.12, 2016	Sep.11, 2017
3.	Limiter	York	MTS-IMP-136	261115-001-0024	Sep.12, 2016	Sep.11, 2017
4.	Cable	LARGE	RF300	-	Sep.12, 2016	Sep.11, 2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	Apr. 29, 2016	Apr. 28, 2017
2	Amplifier	Agilent	8447D	2944A10178	Jan. 12, 2017	Jan. 11, 2018
3	Active Loop Antenna	Beijing Dazhi	ZN30900A	0703	Oct. 17, 2016	Oct. 16, 2017
4	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr. 07, 2016	Apr. 06, 2017
5	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.12, 2016	Sep.11, 2017
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr. 07, 2016	Apr. 06, 2017
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Apr. 07, 2016	Apr. 06, 2017
8	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	Apr. 07, 2016	Apr. 06, 2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Apr. 07, 2016	Apr. 06, 2017
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Apr. 07, 2016	Apr. 06, 2017
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Apr. 07, 2016	Apr. 06, 2017
4	Cable	HUBER+SUHNER	CBL2	525178	Apr. 07, 2016	Apr. 06, 2017

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.12, 2016	Sep.11, 2017
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.12, 2016	Sep.11, 2017
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.12, 2016	Sep.11, 2017

4.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

4.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Emissions	15.247 15.205(a) 15.209(a)	C
Conducted Emissions	15.207(a)	C
Bandwidth	15.247(a)(2)	C
Maximum Peak Output Power	15.247(b)(3),(4)	C
Power Spectral Density	15.247(e)	C
Band Edge	15.247(d)	C
Antenna Requirement	15.203	C
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	C
Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable		

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013&ANSI C63.4:2014
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	21.5 °C
Humidity:	51.9 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in Wi-Fi Transmitting mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.4 Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	41.70	10.06	51.76	65.99	-14.23	QP	
2	0.1500	17.74	10.06	27.80	55.99	-28.19	AVG	
3	0.1900	47.68	9.87	57.55	64.03	-6.48	QP	
4	0.1900	29.76	9.87	39.63	54.03	-14.40	AVG	
5	0.1980	46.23	9.87	56.10	63.69	-7.59	QP	
6	0.1980	28.42	9.87	38.29	53.69	-15.40	AVG	
7	0.2100	44.33	9.90	54.23	63.20	-8.97	QP	
8	0.2100	23.47	9.90	33.37	53.20	-19.83	AVG	
9	0.2740	36.60	10.00	46.60	60.99	-14.39	QP	
10	0.2740	19.14	10.00	29.14	50.99	-21.85	AVG	
11	0.5980	26.66	10.06	36.72	56.00	-19.28	QP	
12	0.5980	23.58	10.06	33.64	46.00	-12.36	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	40.68	10.06	50.74	65.99	-15.25	QP	
2	0.1500	16.78	10.06	26.84	55.99	-29.15	AVG	
3	0.1860	46.10	9.87	55.97	64.21	-8.24	QP	
4	0.1860	26.29	9.87	36.16	54.21	-18.05	AVG	
5	0.2020	43.96	9.88	53.84	63.52	-9.68	QP	
6	0.2020	26.32	9.88	36.20	53.52	-17.32	AVG	
7	0.2700	35.35	10.00	45.35	61.12	-15.77	QP	
8	0.2700	18.93	10.00	28.93	51.12	-22.19	AVG	
9	0.4020	26.54	10.03	36.57	57.81	-21.24	QP	
10	0.4020	13.71	10.03	23.74	47.81	-24.07	AVG	
11	0.5980	25.93	10.06	35.99	56.00	-20.01	QP	
12	0.5980	22.27	10.06	32.33	46.00	-13.67	AVG	

7 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013&ANSI C63.4:2014

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	$10000 * 2400/F(kHz)$	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	$100 * 24000/F(kHz)$	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in Wi-Fi transmitting mode, the test data were shown in the report.

7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

- Sweep Speed Auto
- IF Bandwidth.....10kHz
- Video Bandwidth.....10kHz
- Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

- Sweep Speed Auto
- DetectorPK
- Resolution Bandwidth.....100kHz
- Video Bandwidth.....300kHz

Above 1GHz

- Sweep Speed Auto
- DetectorPK
- Resolution Bandwidth.....1MHz
- Video Bandwidth.....3MHz
- DetectorAve.
- Resolution Bandwidth.....1MHz
- Video Bandwidth.....10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

7.6 Summary of Test Results

Test Frequency : 9KHz to 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.45	42.23	QP	207.18	1.21	H	11.62	30.61	46.00	-15.39
223.45	34.56	QP	162.86	1.39	V	11.62	22.94	46.00	-23.06
4824.00	48.23	PK	255.68	1.12	V	1.06	47.17	74.00	-26.83
4824.00	45.66	Ave	255.68	1.12	V	1.06	44.60	54.00	-9.40
7236.00	42.89	PK	91.30	1.83	H	1.33	44.22	74.00	-29.78
7236.00	40.88	Ave	91.30	1.83	H	1.33	42.21	54.00	-11.79
2338.77	46.29	PK	277.83	1.09	V	13.19	33.10	74.00	-40.90
2338.77	38.48	Ave	277.83	1.09	V	13.19	25.29	54.00	-28.71
2383.50	42.27	PK	328.78	1.66	H	13.14	29.13	74.00	-44.87
2383.50	36.00	Ave	328.78	1.66	H	13.14	22.86	54.00	-31.14
2499.75	42.32	PK	31.90	2.00	V	13.08	29.24	74.00	-44.76
2499.75	36.39	Ave	31.90	2.00	V	13.08	23.31	54.00	-30.69

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	42.46	QP	133.09	1.83	H	11.62	30.84	46.00	-15.16
223.45	33.90	QP	270.81	1.26	V	11.62	22.28	46.00	-23.72
4874.00	48.20	PK	187.21	1.48	V	0.62	47.58	74.00	-26.42
4874.00	45.71	Ave	187.21	1.48	V	0.62	45.09	54.00	-8.91
7311.00	42.07	PK	306.96	1.09	H	2.21	44.28	74.00	-29.72
7311.00	40.00	Ave	306.96	1.09	H	2.21	42.21	54.00	-11.79
2347.12	46.20	PK	97.22	1.94	V	13.19	33.01	74.00	-40.99
2347.12	37.37	Ave	97.22	1.94	V	13.19	24.18	54.00	-29.82
2376.32	43.98	PK	56.95	1.63	H	13.14	30.84	74.00	-43.16
2376.32	38.33	Ave	56.95	1.63	H	13.14	25.19	54.00	-28.81
2496.14	43.85	PK	291.69	1.15	V	13.08	30.77	74.00	-43.23
2496.14	37.55	Ave	291.69	1.15	V	13.08	24.47	54.00	-29.53

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
223.45	41.06	QP	80.60	1.91	H	11.62	29.44	46.00	-16.56
223.45	32.63	QP	182.00	1.65	V	11.62	21.01	46.00	-24.99
4924.00	47.22	PK	286.31	1.51	V	0.24	46.98	74.00	-27.02
4924.00	45.90	Ave	286.31	1.51	V	0.24	45.66	54.00	-8.34
7386.00	42.22	PK	205.72	1.34	H	2.84	45.06	74.00	-28.94
7386.00	40.08	Ave	205.72	1.34	H	2.84	42.92	54.00	-11.08
2336.98	45.99	PK	101.57	1.03	V	13.19	32.80	74.00	-41.20
2336.98	38.38	Ave	101.57	1.03	V	13.19	25.19	54.00	-28.81
2371.45	43.95	PK	34.30	1.54	H	13.14	30.81	74.00	-43.19
2371.45	38.45	Ave	34.30	1.54	H	13.14	25.31	54.00	-28.69
2490.22	42.08	PK	342.19	1.97	V	13.08	29.00	74.00	-45.00
2490.22	38.44	Ave	342.19	1.97	V	13.08	25.36	54.00	-28.64

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
223.45	42.32	QP	337.47	1.03	H	11.62	30.70	46.00	-15.30
223.45	33.71	QP	319.45	1.69	V	11.62	22.09	46.00	-23.91
4824.00	47.89	PK	222.74	1.04	V	1.06	46.83	74.00	-27.17
4824.00	46.27	Ave	222.74	1.04	V	1.06	45.21	54.00	-8.79
7236.00	42.11	PK	270.10	1.56	H	1.33	43.44	74.00	-30.56
7236.00	39.09	Ave	270.10	1.56	H	1.33	40.42	54.00	-13.58
2324.88	45.71	PK	354.42	1.82	V	13.19	32.52	74.00	-41.48
2324.88	37.89	Ave	354.42	1.82	V	13.19	24.70	54.00	-29.30
2380.63	42.33	PK	27.70	1.64	H	13.14	29.19	74.00	-44.81
2380.63	37.35	Ave	27.70	1.64	H	13.14	24.21	54.00	-29.79
2489.37	42.65	PK	58.13	1.09	V	13.08	29.57	74.00	-44.43
2489.37	37.93	Ave	58.13	1.09	V	13.08	24.85	54.00	-29.15

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
223.45	43.64	QP	278.76	1.81	H	11.62	32.02	46.00	-13.98
223.45	35.10	QP	212.91	1.39	V	11.62	23.48	46.00	-22.52
4874.00	47.85	PK	207.33	1.78	V	0.62	47.23	74.00	-26.77
4874.00	46.97	Ave	207.33	1.78	V	0.62	46.35	54.00	-7.65
7311.00	41.64	PK	167.50	1.32	H	2.21	43.85	74.00	-30.15
7311.00	40.04	Ave	167.50	1.32	H	2.21	42.25	54.00	-11.75
2311.75	46.82	PK	14.24	1.66	V	13.19	33.63	74.00	-40.37
2311.75	39.13	Ave	14.24	1.66	V	13.19	25.94	54.00	-28.06
2372.06	44.83	PK	265.81	1.37	H	13.14	31.69	74.00	-42.31
2372.06	37.90	Ave	265.81	1.37	H	13.14	24.76	54.00	-29.24
2484.53	42.41	PK	195.60	1.95	V	13.08	29.33	74.00	-44.67
2484.53	38.90	Ave	195.60	1.95	V	13.08	25.82	54.00	-28.18

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
223.45	44.33	QP	200.02	1.60	H	11.62	32.71	46.00	-13.29
223.45	34.91	QP	328.78	1.03	V	11.62	23.29	46.00	-22.71
4924.00	48.53	PK	122.46	1.84	V	0.24	48.29	74.00	-25.71
4924.00	48.19	Ave	122.46	1.84	V	0.24	47.95	54.00	-6.05
7386.00	41.78	PK	65.99	1.07	H	2.84	44.62	74.00	-29.38
7386.00	40.93	Ave	65.99	1.07	H	2.84	43.77	54.00	-10.23
2325.33	46.14	PK	289.50	1.74	V	13.19	32.95	74.00	-41.05
2325.33	37.97	Ave	289.50	1.74	V	13.19	24.78	54.00	-29.22
2366.65	43.21	PK	344.22	1.51	H	13.14	30.07	74.00	-43.93
2366.65	37.20	Ave	344.22	1.51	H	13.14	24.06	54.00	-29.94
2491.68	42.69	PK	205.81	1.89	V	13.08	29.61	74.00	-44.39
2491.68	36.43	Ave	205.81	1.89	V	13.08	23.35	54.00	-30.65

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: Low Channel 2412MHz									
223.45	44.34	QP	44.35	1.13	H	11.62	32.72	46.00	-13.28
223.45	34.19	QP	163.23	1.05	V	11.62	22.57	46.00	-23.43
4824.00	48.48	PK	354.40	1.21	V	1.06	47.42	74.00	-26.58
4824.00	48.58	Ave	354.40	1.21	V	1.06	47.52	54.00	-6.48
7236.00	41.41	PK	269.30	1.24	H	1.33	42.74	74.00	-31.26
7236.00	41.66	Ave	269.30	1.24	H	1.33	42.99	54.00	-11.01
2333.31	46.02	PK	250.97	1.43	V	13.19	32.83	74.00	-41.17
2333.31	37.08	Ave	250.97	1.43	V	13.19	23.89	54.00	-30.11
2388.05	42.06	PK	190.59	1.84	H	13.14	28.92	74.00	-45.08
2388.05	36.60	Ave	190.59	1.84	H	13.14	23.46	54.00	-30.54
2484.49	43.37	PK	283.42	1.60	V	13.08	30.29	74.00	-43.71
2484.49	37.46	Ave	283.42	1.60	V	13.08	24.38	54.00	-29.62

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: Middle Channel 2437MHz									
223.45	44.83	QP	71.35	1.13	H	11.62	33.21	46.00	-12.79
223.45	35.68	QP	145.37	1.93	V	11.62	24.06	46.00	-21.94
4874.00	48.18	PK	314.72	1.17	V	0.62	47.56	74.00	-26.44
4874.00	49.22	Ave	314.72	1.17	V	0.62	48.60	54.00	-5.40
7311.00	41.60	PK	200.21	1.77	H	2.21	43.81	74.00	-30.19
7311.00	42.87	Ave	200.21	1.77	H	2.21	45.08	54.00	-8.92
2349.22	46.01	PK	259.80	1.02	V	13.19	32.82	74.00	-41.18
2349.22	39.75	Ave	259.80	1.02	V	13.19	26.56	54.00	-27.44
2364.44	44.87	PK	359.46	1.84	H	13.14	31.73	74.00	-42.27
2364.44	37.65	Ave	359.46	1.84	H	13.14	24.51	54.00	-29.49
2497.37	45.00	PK	187.95	1.38	V	13.08	31.92	74.00	-42.08
2497.37	37.98	Ave	187.95	1.38	V	13.08	24.90	54.00	-29.10

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: High Channel 2462MHz									
223.45	45.80	QP	300.31	1.84	H	11.62	34.18	46.00	-11.82
223.45	36.71	QP	245.68	1.03	V	11.62	25.09	46.00	-20.91
4924.00	46.95	PK	268.34	1.90	V	0.24	46.71	74.00	-27.29
4924.00	49.24	Ave	268.34	1.90	V	0.24	49.00	54.00	-5.00
7386.00	40.75	PK	218.27	1.91	H	2.84	43.59	74.00	-30.41
7386.00	41.61	Ave	218.27	1.91	H	2.84	44.45	54.00	-9.55
2324.34	45.00	PK	1.91	1.94	V	13.19	31.81	74.00	-42.19
2324.34	38.55	Ave	1.91	1.94	V	13.19	25.36	54.00	-28.64
2374.43	43.88	PK	91.96	1.46	H	13.14	30.74	74.00	-43.26
2374.43	36.15	Ave	91.96	1.46	H	13.14	23.01	54.00	-30.99
2487.71	42.39	PK	205.64	1.71	V	13.08	29.31	74.00	-44.69
2487.71	36.14	Ave	205.64	1.71	V	13.08	23.06	54.00	-30.94

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n40: Low Channel 2422MHz									
223.45	45.05	QP	15.03	1.51	H	11.62	33.43	46.00	-12.57
223.45	36.90	QP	14.19	1.79	V	11.62	25.28	46.00	-20.72
4844.00	44.55	PK	144.95	1.51	V	1.06	43.49	74.00	-30.51
4844.00	47.18	Ave	144.95	1.51	V	1.06	46.12	54.00	-7.88
7266.00	38.12	PK	116.14	1.00	H	1.33	39.45	74.00	-34.55
7266.00	38.78	Ave	116.14	1.00	H	1.33	40.11	54.00	-13.89
2335.37	46.35	PK	100.48	1.25	V	13.19	33.16	74.00	-40.84
2335.37	37.27	Ave	100.48	1.25	V	13.19	24.08	54.00	-29.92
2388.32	42.01	PK	308.16	1.90	H	13.14	28.87	74.00	-45.13
2388.32	38.42	Ave	308.16	1.90	H	13.14	25.28	54.00	-28.72
2495.64	44.93	PK	208.82	1.85	V	13.08	31.85	74.00	-42.15
2495.64	37.19	Ave	208.82	1.85	V	13.08	24.11	54.00	-29.89

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n40: Middle Channel 2437MHz									
223.45	45.11	QP	48.43	1.41	H	11.62	33.49	46.00	-12.51
223.45	37.61	QP	129.88	1.71	V	11.62	25.99	46.00	-20.01
4874.00	44.62	PK	113.42	1.06	V	0.62	44.00	74.00	-30.00
4874.00	47.22	Ave	113.42	1.06	V	0.62	46.60	54.00	-7.40
7311.00	37.26	PK	9.34	1.15	H	2.21	39.47	74.00	-34.53
7311.00	37.82	Ave	9.34	1.15	H	2.21	40.03	54.00	-13.97
2329.71	45.10	PK	150.86	1.82	V	13.19	31.91	74.00	-42.09
2329.71	38.36	Ave	150.86	1.82	V	13.19	25.17	54.00	-28.83
2376.44	43.21	PK	241.40	1.41	H	13.14	30.07	74.00	-43.93
2376.44	38.43	Ave	241.40	1.41	H	13.14	25.29	54.00	-28.71
2495.64	44.69	PK	12.53	1.79	V	13.08	31.61	74.00	-42.39
2495.64	38.13	Ave	12.53	1.79	V	13.08	25.05	54.00	-28.95

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n40: High Channel 2452MHz									
223.45	45.08	QP	8.29	1.08	H	11.62	33.46	46.00	-12.54
223.45	36.95	QP	11.30	1.83	V	11.62	25.33	46.00	-20.67
4904.00	45.61	PK	328.25	1.42	V	0.24	45.37	74.00	-28.63
4904.00	47.39	Ave	328.25	1.42	V	0.24	47.15	54.00	-6.85
7356.00	36.61	PK	92.48	1.22	H	2.84	39.45	74.00	-34.55
7356.00	37.66	Ave	92.48	1.22	H	2.84	40.50	54.00	-13.50
2345.97	46.97	PK	270.17	1.74	V	13.19	33.78	74.00	-40.22
2345.97	37.45	Ave	270.17	1.74	V	13.19	24.26	54.00	-29.74
2386.09	44.52	PK	261.14	1.68	H	13.14	31.38	74.00	-42.62
2386.09	37.63	Ave	261.14	1.68	H	13.14	24.49	54.00	-29.51
2489.45	44.82	PK	292.36	1.31	V	13.08	31.74	74.00	-42.26
2489.45	38.48	Ave	292.36	1.31	V	13.08	25.40	54.00	-28.60

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

8 Band Edge Measurement


Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	558074 D01 DTS Meas Guidance v04, April 5, 2017
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

8.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.2 Test Result


Test result plots shown as follows:




TX 11b: Band edge-right side







TX 11g: Band edge-left side



TX 11g: Band edge-right side







9 Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 DTS Meas Guidance v04, April 5, 2017



9.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



9.2 Test Result:



Operation mode	6dB Bandwidth (MHz)			99% Bandwidth (MHz)		
TX 11b	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	10.092	10.092	10.092	12.615	14.978	14.786
TX 11g	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	16.417	16.417	16.417	16.567	16.417	16.567
TX 11n HT20	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	17.623	17.623	17.623	17.731	17.569	17.731
TX 11n HT40	Channel 3	Channel 6	Channel 9	Channel 3	Channel 6	Channel 9
	36.120	36.120	36.120	36.008	36.008	36.008



Test result plot as follows:















10 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 DTS Meas Guidance v04, April 5, 2017

10.1 Test Procedure:

558074 D01 DTS Meas Guidance v04, April 5, 2017

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.



10.2 Test Result:


Test mode :TX 11b		
Maximum Peak Output Power (dBm)		
Channel 1	Channel 6	Channel 11
18.04	17.95	17.91
Limit: 1W/30dBm		

Test mode :TX 11g		
Maximum Peak Output Power (dBm)		
Channel 1	Channel 6	Channel 11
16.51	16.23	16.19
Limit: 1W/30dBm		


Test mode :TX 11n HT20		
Maximum Peak Output Power (dBm)		
Channel 1	Channel 6	Channel 11
14.00	13.95	14.49
Limit: 1W/30dBm		



Test mode : TX 11n HT40		
Maximum Peak Output Power (dBm)		
Channel 3	Channel 6	Channel 9
14.24	14.35	14.24
Limit: 1W/30dBm		






Mode :TX 11g channel 1










Mode: TX 11n HT20 channel 1



Mode: TX 11n HT20 channel 6







11 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 DTS Meas Guidance v04, April 5, 2017

11.1 Test Procedure:

558074 D01 DTS Meas Guidance v04, April 5, 2017

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



11.2 Test Result:



Test mode :TX 11b		
Power Spectral (dBm per 3kHz)		
Channel 1	Channel 6	Channel 11
-8.26	-7.52	-8.30
Limit: 8dBm per 3kHz		



Test mode :TX 11g		
Power Spectral (dBm per 3kHz)		
Channel 1	Channel 6	Channel 11
-16.31	-17.11	-17.38
Limit: 8dBm per 3kHz		



Test mode :TX 11n HT20		
Power Spectral (dBm per 3kHz)		
Channel 1	Channel 6	Channel 11
-19.18	-19.56	-17.52
Limit: 8dBm per 3kHz		



Test mode : TX 11n HT40		
Power Spectral (dBm per 3kHz)		
Channel 3	Channel 6	Channel 9
-22.60	-23.11	-22.89
Limit: 8dBm per 3kHz		
















12 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has one Internal Integrated Antenna, the gain is 2.0 dBi. meets the requirements of FCC 15.203.



13 RF Exposure

Test Requirement: FCC Part 1.1307

Evaluation Method: FCC Part 2.1091 & KDB 447498 D01 General RF Exposure Guidance v06

13.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

13.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

13.3 MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)


From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
2.0	1.585	18.04	63.68	0.020	1


14 Photographs – Model ELST4017 Test Setup


14.1 Radiated Emission

Test frequency 9KHz to 30MHz at Test Site 2#



Test frequency from 30MHz to 1GHz at Test Site 2#





Test frequency above 1GHz at Test Site 1#






14.2 Conducted Emission at Test Site 2#



15 Photographs - Constructional Details

15.1 Model ELST4017-External Photos
















15.2 Model ELST4017– Internal Photos







Wi-Fi Module



====End of Report====