



TEST REPORT

Report Reference No. TRE1507003101 R/C.....:89374

FCC ID 2AAS7-BFZ

Applicant's name Shenzhen Pump Medical System Co.,Ltd.

Address 2/F West, M-7 Sinosteel Building, Maqueling Estate, Hi-Tech Industrial Park, Nanshan District, Shenzhen 518057, China

Manufacturer.....: Shenzhen Pump Medical System Co.,Ltd.

Address.....: 2/F West, M-7 Sinosteel Building, Maqueling Estate, Hi-Tech Industrial Park, Nanshan District, Shenzhen 518057, China

Test item description..... Arm Automatic Blood Pressure Monitor

Trade Mark..... -

Model/Type reference BF1204B

Listed Model(s) BF1100B,BF1110B,BF1102B,BF1112B,BF1205B,BF1215(0B), BF1206B,BF1216(0B), BF1207B,BF1217(0B),BF3203B,BF3213(0B), BF1214(0B),BF6004B,BF6104B, BF6002B,BF6102B,BF6023A, BF6123A,BF6023B,BF6123B,BF6025A,BF6125A, BF6025B, BF6125B,BF6026A,BF6126A,BF6026B,BF6126B,BF6027A, BF6127A, BF6027B,BF6127B,BF6028A,BF6128A,BF6028B, BF6128B, BF6032B,BF6132B, BF6032A,BF6132A,BF6033B,BF6133B,BF6033A,BF6133A,BF6042B,BF6142B,BF6042A, BF6142A,BF6043A,BF6143A,BF6043B,BF6143B, BF6012C,BF6112C,BF6012I,BF6112I, BF6015C,BF6115C, BF6015I,BF6115I,BF6018C,BF6118C,BF6018I,BF6118I,BF6019C, BF6119C,BF6019I,BF6119I,BF6022C,BF6122C,BF6022I,BF6122I, BF1115(0B),BF1113(0B), BF3201B,BF3211(0B),BF6024A,BF6124A,BF6024B,BF6124B,BF6039B,BF6139B,BF6039A, BF6139A,BA2311,BF6020I,BF6120I,BF6020C,BF6120C,BF6021I,BF6121I,BF6021C, BF6121C

Standard FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample.....: Aug 04, 2015

Date of testing.....: Aug 04, 2015- Aug 11, 2015

Date of issue.....: Aug 11, 2015

Result PASS

Compiled by
(position+printedname+signature) File administrators Yingchun Shan

Yingchun Shan

Supervised by
(position+printed name+signature) Project Engineer Yingchun Shan

Yingchun Shan

Approved by
(position+printed name+signature) RF Manager Hans Hu

Hans Hu

Testing Laboratory Name..... Shenzhen Huatongwei International Inspection Co., Ltd

Address Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>APPLICABLE STANDARDS AND TEST DESCRIPTION</u>	<u>3</u>
1.1.	Applicable Standards	3
1.2.	Test Description	3
<u>2.</u>	<u>SUMMARY</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Operation state	5
2.4.	EUT configuration	5
2.5.	Modifications	5
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Equipments Used during the Test	7
3.4.	Environmental conditions	8
3.5.	Statement of the measurement uncertainty	8
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>9</u>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	15
4.4.	Power Spectral Density	16
4.5.	6dB bandwidth	18
4.6.	Restricted band (Conducted)	20
4.7.	Band edge and Spurious Emission (conducted)	22
4.8.	Spurious Emission (radiated)	26
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>31</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>32</u>

1. APPLICABLE STANDARDS AND TEST DESCRIPTION

1.1. Applicable Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V03R02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS)

1.2. Test Description

Report Section	Test Item	FCC Rule	Result
4.1	Antenna requirement	15.203/15.247 (c)	Pass
4.2	Line Conducted Emission (AC Main)	15.207	Pass
4.3	Conducted Peak Output Power	15.247 (b)(3)	Pass
4.4	Power Spectral Density	15.247 (e)	Pass
4.5	6dB Bandwidth	15.247 (a)(2)	Pass
4.6	Restricted band	15.247(d)/15.205	Pass
4.7/4.8	Spurious Emission	15.247(d)/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

2. SUMMARY

2.1. Client Information

Applicant:	Shenzhen Pump Medical System Co.,Ltd.
Address:	2/F West, M-7 Sinosteel Building, Maqueling Estate, Hi-Tech Industrial Park, Nanshan District, Shenzhen 518057, China
Manufacturer:	Shenzhen Pump Medical System Co.,Ltd.
Address:	2/F West, M-7 Sinosteel Building, Maqueling Estate, Hi-Tech Industrial Park, Nanshan District, Shenzhen 518057, China

2.2. Product Description

Name of EUT	Arm Automatic Blood Pressure Monitor
Trade Mark:	-
Model No.:	BF1204B
Listed Model(s):	BF1100B,BF1110B,BF1102B,BF1112B,BF1205B,BF1215(0B), BF1206B,BF1216(0B), BF1207B,BF1217(0B),BF3203B,BF3213(0B), BF1214(0B),BF6004B,BF6104B, BF6002B,BF6102B,BF6023A, BF6123A,BF6023B,BF6123B,BF6025A,BF6125A, BF6025B, BF6125B,BF6026A,BF6126A,BF6026B,BF6126B,BF6027A, BF6127A, BF6027B,BF6127B,BF6028A,BF6128A,BF6028B, BF6128B, BF6032B,BF6132B, BF6032A,BF6132A,BF6033B,BF6133B,BF6033A,BF6133A,BF6042B,BF6142B,BF6042A, BF6142A,BF6043A,BF6143A,BF6043B,BF6143B, BF6012C,BF6112C,BF6012I,BF6112I, BF6015C,BF6115C, BF6015I,BF6115I,BF6018C,BF6118C,BF6018I,BF6118I,BF6019C, BF6119C,BF6019I,BF6119I,BF6022C,BF6122C,BF6022I,BF6122I, BF1115(0B),BF1113(0B), BF3201B,BF3211(0B),BF6024A,BF6124A,BF6024B,BF6124B,BF6039B,BF6139B,BF6039A, BF6139A,BA2311,BF6020I,BF6120I,BF6020C,BF6120C,BF6021I,BF6121I,BF6021C, BF6121C
Power supply:	AC120V/60Hz
Adapter information:	Model:BPE001 Input:100-240Vac ,50/60Hz,400mA Output: 6.0Vd.c.,0.5A
Bluetooth	
Version:	Supported BT4.0+BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Internal Antenna
Antenna gain:	1.60dBi

2.3. Operation state

◆ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
00	2402
01	2404
:	:
19	2440
:	:
38	2478
39	2480

◆ Test mode

For RF test items:

the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

2.5. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming)
Address: Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China
Phone: 86-755-26748019 Fax: 86-755-26748089

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: Mar. 01, 2012. Valid time is until February 28, 2015.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date April. 24, 2015, valid time is until April. 24, 2018

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date July 18, 2014, valid time is until July. 18, 2017.

IC-Registration No.: 5377A

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

IC-Registration No.: 5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on September 3, 2014, valid time is until September 3, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

DNV

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

3.3. Equipments Used during the Test

Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2014/11/01
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2014/11/01
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2014/11/01
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2014/11/01
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2014/11/01
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORN ANTENNA	ShwarzBeck	9120D	1011	2014/11/01
8	Amplifer	Sonoma	310N	E009-13	2014/11/01
9	JS amplifer	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2014/11/01
10	High pass filter	Compliance Direction systems	BSU-6	34202	2014/11/01
11	HORN ANTENNA	ShwarzBeck	9120D	1012	2014/11/01
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2014/11/01
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2014/11/01
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2014/11/01
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2014/11/01

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2014/11/01

The Cal.Interval was one year

3.4. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4. TEST CONDITIONS AND RESULTS

4.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The antenna is integral antenna, the best case gain of the antenna is 1.60dBi



BT Antenna

4.2. Conducted Emission (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

TEST RESULTS

AC 120V/60Hz:

Test mode:	BT	Polarization	L
------------	----	--------------	---

**MEASUREMENT RESULT: "GM0807506_fin"**

8/7/2015 11:06AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.451500	37.70	10.2	57	19.1	QP	L1	GND
0.582000	42.30	10.2	56	13.7	QP	L1	GND
21.750000	28.00	11.0	60	32.0	QP	L1	GND
21.885000	27.50	11.0	60	32.5	QP	L1	GND
22.312500	27.50	11.0	60	32.5	QP	L1	GND
23.208000	25.60	11.0	60	34.4	QP	L1	GND

MEASUREMENT RESULT: "GM0807506_fin2"

8/7/2015 11:06AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.586500	29.40	10.2	46	16.6	AV	L1	GND
20.224500	20.70	11.0	50	29.3	AV	L1	GND
21.192000	20.60	11.0	50	29.4	AV	L1	GND
21.606000	21.00	11.0	50	29.0	AV	L1	GND
21.840000	20.70	11.0	50	29.3	AV	L1	GND
22.326000	20.20	11.0	50	29.8	AV	L1	GND

Test mode:	BT	Polarization	N
------------	----	--------------	---



MEASUREMENT RESULT: "GM0807507_fin"

8/7/2015 11:09AM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.442500	37.80	10.2	57	19.2	QP	N	GND
0.550500	42.30	10.2	56	13.7	QP	N	GND
0.582000	41.90	10.2	56	14.1	QP	N	GND
0.591000	41.40	10.2	56	14.6	QP	N	GND
0.816000	28.20	10.2	56	27.8	QP	N	GND
0.960000	28.30	10.2	56	27.7	QP	N	GND

MEASUREMENT RESULT: "GM0807507_fin2"

8/7/2015 11:09AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.231000	28.30	10.2	52	24.1	AV	N	GND
0.442500	23.00	10.2	47	24.0	AV	N	GND
0.537000	26.20	10.2	46	19.8	AV	N	GND
0.546000	26.70	10.2	46	19.3	AV	N	GND
0.996000	17.10	10.2	46	28.9	AV	N	GND
1.725000	17.40	10.2	46	28.6	AV	N	GND

AC 240V/60Hz:

**MEASUREMENT RESULT: "GM0911516_fin"**


9/11/2015 17:19PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	48.70	10.2	66	17.3	QP	L1	GND
0.186000	44.50	10.2	64	19.7	QP	L1	GND
0.244500	46.10	10.2	62	15.8	QP	L1	GND
0.298500	42.40	10.2	60	17.9	QP	L1	GND
0.370500	34.60	10.2	59	23.9	QP	L1	GND
0.429000	33.90	10.2	57	23.4	QP	L1	GND

MEASUREMENT RESULT: "GM0911516_fin2"

9/11/2015 17:19PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	31.50	10.2	56	24.5	AV	L1	GND
0.249000	33.80	10.2	52	18.0	AV	L1	GND
0.298500	27.20	10.2	50	23.1	AV	L1	GND
0.352500	21.30	10.2	49	27.6	AV	L1	GND
0.402000	20.00	10.2	48	27.8	AV	L1	GND
0.550500	23.80	10.2	46	22.2	AV	L1	GND



MEASUREMENT RESULT: "GM0911515_fin"

9/11/2015 17:15PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	49.70	10.2	66	16.3	QP	N	GND
0.244500	45.50	10.2	62	16.4	QP	N	GND
0.303000	42.30	10.2	60	17.9	QP	N	GND
0.366000	35.60	10.2	59	23.0	QP	N	GND
0.429000	32.70	10.2	57	24.6	QP	N	GND

MEASUREMENT RESULT: "GM0911515_fin2"

9/11/2015 17:15PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.199500	29.00	10.2	54	24.6	AV	N	GND
0.249000	32.70	10.2	52	19.1	AV	N	GND
0.303000	27.70	10.2	50	22.5	AV	N	GND
0.402000	18.50	10.2	48	29.3	AV	N	GND
0.496500	16.70	10.2	46	29.4	AV	N	GND
0.555000	17.80	10.2	46	28.2	AV	N	GND

4.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 V03R02 for compliance to FCC 47CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST RESULTS

Type	Channel	Output power (dBm)	Limit (dBm)	Result
BT-BLE	00	-6.83	30.00	Pass
	19	-6.91		
	39	-6.19		


4.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e): **8dBm/3KHz**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION




TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
BT-BLE	00	-16.53	8.00	Pass
	19	-16.35		
	38	-16.42		

Test plot as follows:




4.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2): **at least 500KHz**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION




TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST RESULTS

Type	Channel	6dB Bandwidth(KHz)	Limit (KHz)	Result
BT-BLE	00	714.94	≥500	Pass
	19	711.06		
	38	714.33		

Test plot as follows:




4.6. Restricted band (Conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. According to KDB 558074 D01 V03R02 for Antenna-port conducted measurement.
Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands.
 - 1) Measure the conducted output power (in dBm) using the Peak /average detector
 - 2) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level
 - 3) Add the appropriate maximum ground reflection factor to the EIRP level
6 dB for frequencies ≤ 30 MHz
4.7 dB for frequencies between 30 MHz and 1000 MHz
0 dB for frequencies > 1000 MHz
 - 4) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms
 - 5) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:
 $E = \text{EIRP} - 20\log D + 104.8$
where:
E = electric field strength in dB μ V/m,
EIRP = equivalent isotropic radiated power in dBm
D = specified measurement distance in meters.
 - 6) Compare the resultant electric field strength level to the applicable limit
2. **Peak power measurement procedure**
Peak emission levels are measured by setting the instrument as follows
RBW = 1MHz, VBW $\geq 3 \times$ RBW
Detector = Peak, Sweep time = auto
Trace mode = max hold
Allow sweeps to continue until the trace stabilizes.

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement

3. **Average power measurement procedure**


Duty cycle < 98 percent, but the duty cycle is not constant

- a) RBW = 1 MHz, VBW $\geq 1/T$.
- b) Video bandwidth mode or display mode
 - 1) The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).
 - 2) As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some

instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

- c) Detector = Peak, Sweep time = auto.
- d) Trace mode = max hold.
- e) Allow max hold to run for at least 50 times (1/duty cycle) traces.

TEST RESULTS



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Limit (dBuV/m)	Result	Test Value
2310.00	-39.84	1.60	0.00	57.02	74.00	Pass	Peak
2390.00	-38.07	1.60	0.00	58.79	74.00	Pass	
2483.50	-33.92	1.60	0.00	63.67	74.00	Pass	
2500.00	-39.37	1.60	0.00	58.22	74.00	Pass	
2310.00	-48.10	1.60	0.00	48.76	54.00	Pass	Average
2390.00	-47.86	1.60	0.00	49.00	54.00	Pass	
2483.50	-43.85	1.60	0.00	53.01	54.00	Pass	
2500.00	-47.83	1.60	0.00	49.76	54.00	Pass	

Note:

EIRP=Conducted Power + Antenna Gain + Ground Reflection factor

E = EIRP – 20log D + 104.8


4.7. Band edge and Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE


1. Connect the antenna port(s) to the spectrum analyzer input.
2. **Establish a reference level by using the following procedure**
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.


3. **Emission level measurement**
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emissions relative to the limit.

TEST RESULTS

Test plot as follows:







4.8. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9KHz ~30MHz



- 30MHz ~ 1GHz



- Above 1GHz




TEST PROCEDURE

1. The EUT tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna, In order to find the maximum emission.
5. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold; *If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.*
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=10Hz for Average value.


TEST RESULTS**Measurement data:****■ 9kHz ~ 30MHz**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

■ 30MHz ~ 1GHz**MEASUREMENT RESULT: "GM0807613_red"**

8/7/2015 11:16AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
147.370000	22.70	-18.0	43.5	20.8	QP	100.0	237.00	HORIZONTAL
163.860000	25.00	-16.9	43.5	18.5	QP	100.0	222.00	HORIZONTAL
195.870000	23.80	-14.0	43.5	19.7	QP	100.0	222.00	HORIZONTAL
212.360000	22.30	-14.1	43.5	21.2	QP	100.0	222.00	HORIZONTAL
552.830000	24.80	-4.7	46.0	21.2	QP	300.0	360.00	HORIZONTAL
949.560000	34.90	3.7	46.0	11.1	QP	100.0	337.00	HORIZONTAL



MEASUREMENT RESULT: "GM0807614_red"

8/7/2015 11:19AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	21.80	-16.8	40.0	18.2	QP	100.0	117.00	VERTICAL
47.460000	23.10	-14.5	40.0	16.9	QP	100.0	25.00	VERTICAL
53.280000	22.50	-14.5	40.0	17.5	QP	100.0	117.00	VERTICAL
60.070000	21.30	-14.9	40.0	18.7	QP	100.0	0.00	VERTICAL
71.710000	23.00	-17.2	40.0	17.0	QP	100.0	241.00	VERTICAL
954.410000	34.30	3.8	46.0	11.7	QP	100.0	260.00	VERTICAL

■ Above 1GHz

CH00 for BT-BLE									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4809.50	40.91	31.09	9.21	38.53	42.68	74.00	-31.32	Vertical	Peak
7206.00	36.27	36.22	6.87	35.15	44.21	74.00	-29.79	Vertical	
9608.00	36.46	37.85	8.80	35.55	47.56	74.00	-26.44	Vertical	
12010.00	*					74.00		Vertical	
4809.50	42.97	31.09	9.21	38.53	44.74	74.00	-29.26	Horizontal	
7206.00	35.02	36.22	6.87	35.15	42.96	74.00	-31.04	Horizontal	
9608.00	36.61	37.85	8.80	35.55	47.71	74.00	-26.29	Horizontal	
12010.00	*							Horizontal	
4809.50	31.09	31.09	9.21	38.53	32.86	54.00	-21.14	Vertical	Average
7206.00	29.18	36.22	6.87	35.15	37.12	54.00	-16.88	Vertical	
9608.00	31.55	37.85	8.80	35.55	42.65	54.00	-11.35	Vertical	
12010.00	*							Vertical	
4809.50	34.7	31.09	9.21	38.53	36.47	54.00	-17.53	Horizontal	
7206.00	25.75	36.22	6.87	35.15	33.69	54.00	-20.31	Horizontal	
9608.00	31.07	37.85	8.80	35.55	42.17	54.00	-11.83	Horizontal	
12010.00	*							Horizontal	
CH19 for BT-BLE									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4882.00	39.15	31.26	5.65	35.27	40.79	74.00	-33.21	Vertical	Peak
7323.00	37.3	36.20	6.86	35.13	45.23	74.00	-28.77	Vertical	
9764.00	36.89	37.83	8.79	35.53	47.98	74.00	-26.02	Vertical	
12205.00	*							Vertical	
7880.00	43.15	31.26	5.65	35.27	44.79	74.00	-29.21	Horizontal	
7323.00	36.11	36.20	6.86	35.13	44.04	74.00	-29.96	Horizontal	
9764.00	36.79	37.83	8.79	35.53	47.88	74.00	-26.12	Horizontal	
12205.00	*							Horizontal	
4882.00	28.33	31.26	5.65	35.27	29.97	54.00	-24.03	Vertical	Average
7323.00	29.39	36.20	6.86	35.13	37.32	54.00	-16.68	Vertical	
9764.00	32.80	37.83	8.79	35.53	43.89	54.00	-10.11	Vertical	
12205.00	*							Vertical	
7880.00	35.33	31.26	5.65	35.27	36.97	54.00	-17.03	Horizontal	
7323.00	28.50	36.20	6.86	35.13	36.43	54.00	-17.57	Horizontal	
9764.00	31.82	37.83	8.79	35.53	42.91	54.00	-11.09	Horizontal	
12205.00	*							Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

CH39 for BT-BLE									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4960.00	37.83	31.44	5.87	35.46	39.68	74.00	-34.32	Vertical	Peak
7440.00	37.66	36.38	7.08	35.32	45.80	74.00	-28.2	Vertical	
9920.00	36.82	38.01	9.01	35.72	48.12	74.00	-25.88	Vertical	
12400.00	*							Vertical	
4958.68	42.78	31.18	9.31	38.62	44.65	74.00	-29.35	Horizontal	
7440.00	37.02	36.38	7.08	35.32	45.16	74.00	-28.84	Horizontal	
9920.00	36.59	38.01	9.01	35.72	47.89	74.00	-26.11	Horizontal	
12400.00	*							Horizontal	
4960.00	28.01	31.44	5.87	35.46	29.86	54.00	-24.14	Vertical	Average
7440.00	29.94	36.38	7.08	35.32	38.08	54.00	-15.92	Vertical	
9920.00	30.91	38.01	9.01	35.72	42.21	54.00	-11.79	Vertical	
12400.00	*							Vertical	
4958.68	42.78	31.18	9.31	38.62	36.56	54.00	-17.44	Horizontal	
7440.00	29.47	36.38	7.08	35.32	37.61	54.00	-16.39	Horizontal	
9920.00	30.68	38.01	9.01	35.72	41.98	54.00	-12.02	Horizontal	
12400.00	*							Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

5. Test Setup Photos of the EUT

Radiated Emission
30MHz-1GHz:



Above 1GHz:




Conducted Emission (AC Mains)




6. External and Internal Photos of the EUT

External Photos of the EUT









Internal Photos of EUT






BT ANT









.....End of Report.....