

## **FCC RADIO TEST REPORT FCC ID: 2AASCGGBSSRC**

**Product**: Bluetooth Speaker

Trade Name: N/A

Model Name: GGBSSRC

**Serial Model :** BT-831,BT-830,BT-860,BT-832,BT-833,

BT-835,BT-836,BT-838,BT-810

**Report No.**: NTEK-2013NT0807832F

#### **Prepared for**

Shenzhen Alpinor Technology Company Limited JingHua Industrial Park, PingHu LongGang ShenZhen China

## **Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

> Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



## **TEST RESULT CERTIFICATION**

Applicant's name	. Snenzner	Alpinor Techi	nology Company Limited	
Address	. JingHua I	ndustrial Park	, PingHu LongGang ShenZl	hen China
Manufacture's Name	. Shenzher	n Alpinor Techi	nology Company Limited	
Address	· JingHua I	ndustrial Park	, PingHu LongGang ShenZl	hen China
Product description				
Product name		-		
Model and/or type reference	GGBSSR	С		
Serial Model :	BT-831,B		BT-832,BT-833,BT-835,BT-	836,
Standards	FCC Part	15.247		
Test procedure	. ANSI C63	3.4-2003		
This device described above equipment under test (EUT) is to the tested sample identified	s in compli	ance with the		
This report shall not be reproducted or in the document.  Date of Test	revised by	•	• •	
Date (s) of performance of tes	sts	07 Aug. 2013	~19 Aug. 2013	
Date of Issue				
Test Result		Pass		
Testing Eng	ineer	:	Jolo cha (Polo Cha)	
Technical M	lanager	:	Brown Lu)	
Authorized \$	Signatory	:	Korey Yong (Bovey Yang)	



## **Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE 3.1.3 DEVIATION FROM TEST STANDARD	14 14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS 3.2.2 TEST PROCEDURE	17 18
3.2.2 TEST PROCEDURE  3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BELOW 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ) 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	22 24
· ·	
4 . NUMBER OF HOPPING CHANNEL	34
4.1 APPLIED PROCEDURES / LIMIT 4.1.1 TEST PROCEDURE	34 34
4.1.2 DEVIATION FROM STANDARD	34
4.1.3 TEST SETUP	34
4.1.4 EUT OPERATION CONDITIONS	34
4.1.5 TEST RESULTS	35
5 . AVERAGE TIME OF OCCUPANCY	37
5.1 APPLIED PROCEDURES / LIMIT	37



#### Table of Contents

Table of Contents	D
	Page
5.1.1 TEST PROCEDURE	37
5.1.2 DEVIATION FROM STANDARD	37
5.1.3 TEST SETUP	38
5.1.4 EUT OPERATION CONDITIONS	38
5.1.5 TEST RESULTS	39
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	45
6.1 APPLIED PROCEDURES / LIMIT	45
6.1.1 TEST PROCEDURE	45
6.1.2 DEVIATION FROM STANDARD	45
6.1.3 TEST SETUP 6.1.4 EUT OPERATION CONDITIONS	45 45
6.1.5 TEST RESULTS	45 46
7 . BANDWIDTH TEST	52
	_
7.1 APPLIED PROCEDURES / LIMIT 7.1.1 TEST PROCEDURE	52 52
7.1.2 DEVIATION FROM STANDARD	52 52
7.1.3 TEST SETUP	52 52
7.1.4 EUT OPERATION CONDITIONS	52
7.1.5 TEST RESULTS	53
8 . PEAK OUTPUT POWER TEST	59
8.1 APPLIED PROCEDURES / LIMIT	59
8.1.1 TEST PROCEDURE	59
8.1.2 DEVIATION FROM STANDARD	59
8.1.3 TEST SETUP	59 50
8.1.4 EUT OPERATION CONDITIONS 8.1.5 TEST RESULTS	59 60
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	66
9.1 DEVIATION FROM STANDARD 9.2 TEST SETUP	66
9.2 TEST SETUP 9.3 EUT OPERATION CONDITIONS	66 66
9.4 TEST RESULTS	67
10 . ANTENNA REQUIREMENT	74
10.1 STANDARD REQUIREMENT	74
10.2 EUT ANTENNA	74
11 . EUT TEST PHOTO	75
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

#### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



#### 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $\mathbf{y} \pm \mathbf{U}$ , where expended uncertainty  $\mathbf{U}$  is based on a standard uncertainty multiplied by a coverage factor of  $\mathbf{k=2}$ , providing a level of confidence of approximately 95 %  $^{\circ}$ 

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



## 2. GENERAL INFORMATION

## 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth Speaker		
Trade Name	N/A		
Model Name	GGBSSRC		
Serial Model	BT-831,BT-830,BT-860, BT-838,BT-810	BT-832,BT-833,BT-835,BT-836,	
Model Difference	All models are identical	except model name and length.	
	The EUT is a Bluetooth	Speaker	
	Operation Frequency:	2402~2480 MHz	
	Modulation Type:	BT(1Mbps): GFSK	
		BT EDR(2Mbps):∏/4-DQPSK	
		BT EDR(3Mbps): 8-DPSK	
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps	
	Number Of Channel 79 CH		
Product Description	Antenna Designation:	Please see Note 3.	
	Output	BT(1Mbps): -2.604dBm	
	Power(Conducted):	BT EDR(2Mbps): -3.817dBm	
		BT EDR(3Mbps): -3.782dBm	
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.		
Adapter	N/A		
Battery	DC 3.7V		

#### Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

	Channel List				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.0	BT Antenna



#### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Link Mode

For Conducted Emission			
Final Test Mode Description			
Mode 4	Link Mode		

For Radiated Emission			
Final Test Mode Description			
Mode 1	CH00		
Mode 2	CH39		
Mode 3	CH78		

#### Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

#### 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom			
Frequency	2402 MHz 2441 MHz 2480 MHz			
Parameters(1/2/3Mbps)	DEF	DEF	DEF	



## 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

**Conducted Emission Test** 



Radiated Spurious Test

E-1 EUT



#### 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Bluetooth Speaker	N/A	GGBSSRC	N/A	EUT
E-2	PC	N/A	N/A	N/A	
E-3	Adapter	Lenovo	CPA-A090	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	120cm	
C-2	NO	NO	120cm	

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>『Length』</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2013.06.07	2014.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2013.06.07	2014.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2013.06.07	2014.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2012.12.22	2013.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2013.06.08	2014.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2013.07.06	2014.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufactu rer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2012.08.24	2013.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2012.08.24	2013.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2013.06.07	2014.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2013.06.07	2014.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2013.06.08	2014.06.07	1 year



## 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

## 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
TREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



#### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




## 3.1.6 TEST RESULTS

EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from PC	Test Mode:	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Detector Type
0.1620	39.97	11.29	51.26	65.36	-14.10	QP
0.1620	17.93	11.29	29.22	55.36	-26.14	AVG
0.2179	35.77	10.72	46.49	62.89	-16.40	QP
0.2179	19.54	10.72	30.26	52.89	-22.63	AVG
0.5180	23.51	10.58	34.09	56.00	-21.91	QP
0.5180	11.28	10.58	21.86	46.00	-24.14	AVG
1.8899	23.62	10.52	34.14	56.00	-21.86	QP
1.8899	14.27	10.52	24.79	46.00	-21.21	AVG
3.1499	26.96	10.56	37.52	56.00	-18.48	QP
3.1499	11.15	10.56	21.71	46.00	-24.29	AVG
4.4099	27.70	10.62	38.32	56.00	-17.68	QP
4.4099	20.61	10.62	31.23	46.00	-14.77	AVG

#### Remark:

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.






EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from PC	Test Mode:	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Detector Type
0.1685	38.75	11.43	50.18	65.03	-14.85	QP
0.1685	15.17	11.43	26.60	55.03	-28.43	AVG
0.2099	35.73	11.06	46.79	63.21	-16.42	QP
0.2099	17.79	11.06	28.85	53.21	-24.36	AVG
1.3020	20.75	10.52	31.27	56.00	-24.73	QP
1.3020	6.41	10.52	16.93	46.00	-29.07	AVG
2.5219	24.60	10.53	35.13	56.00	-20.87	QP
2.5219	16.03	10.53	26.56	46.00	-19.44	AVG
6.4179	27.92	10.70	38.62	60.00	-21.38	QP
6.4179	16.72	10.70	27.42	50.00	-22.58	AVG
18.9739	24.82	11.07	35.89	60.00	-24.11	QP
18.9739	13.77	11.07	24.84	50.00	-25.16	AVG

#### Remark:

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.





#### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)		
PREQUENCT (WITZ)	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook 1 MHz / 10Hz for Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


#### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

## (A) Radiated Emission Test-Up Frequency Below 30MHz




## (B) Radiated Emission Test-Up Frequency 30MHz~1GHz





## (C) Radiated Emission Test-Up Frequency Above 1GHz



#### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>20</b> ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dBuV/m) (dB)	
				PASS
				PASS

## NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =20 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.



## 3.2.7 TEST RESULTS (BETWEEN 30M - 1000 MHZ)

EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	Horizontal
Test Voltage :	DC3.7V	Test Mode:	TX

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Detector Type
32.7486	16.54	17.04	33.58	40	-6.42	QP
49.7068	27.75	8.39	36.14	40	-3.86	QP
251.1803	26.34	13.68	40.02	46	-5.98	QP
296.1836	26.45	14.68	41.13	46	-4.87	QP
330.1949	24.43	15.85	40.28	46	-5.72	QP
962.1622	17.32	29.87	47.19	54	-6.81	QP

#### Remark:

All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.



EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Vertical
Test Voltage :	DC3.7V	Test Mode:	TX

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Detector Type
32.7486	15.54	17.04	32.58	40	-7.42	QP
49.7068	16.93	8.39	25.32	40	-14.68	QP
251.1803	27.18	13.68	40.86	46	-5.14	QP
296.1836	26.64	14.68	41.32	46	-4.68	QP
330.1949	24.86	15.85	40.71	46	-5.29	QP
962.1622	16.97	29.87	46.84	54	-7.16	QP

#### Remark:

All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.



## 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC3.7V
Test Mode :	TX 2402MHz – CH 00(1Mbps)		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Туре
			Frequency	y:2402MHz			
V	4803.681	48.01	-3.64	44.37	74	-29.63	peak
V	7206.283	46.38	-0.95	45.43	74	-28.57	peak
Н	4803.681	49.03	-3.64	45.39	74	-28.61	peak
Н	7206.283	44.8	-0.95	43.85	74	-30.15	peak
			Frequency	/:2441MHz			
V	4883.409	51.29	-3.67	47.62	74	-26.38	peak
V	7323.472	48.9	-0.82	48.08	74	-25.92	peak
Н	4883.409	51.51	-3.68	47.83	74	-26.17	peak
Н	7323.472	48.79	-0.82	47.97	74	-26.03	peak
			Frequency	/:2480MHz			
V	4959.308	51.97	-3.59	48.38	74	-25.62	peak
V	7440.506	45.77	-0.68	45.09	74	-28.91	peak
Н	4959.308	50.51	-3.59	46.92	74	-27.08	peak
Н	7440.506	48.89	-0.68	48.21	74	-25.79	peak


## Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Mode 3Mbps is the worst mode.





# Conducted Spurious Emissions at Antenna Port: CH00 -1Mbps





































































#### 4. NUMBER OF HOPPING CHANNEL

#### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C						
Section	Test Item	Limit	Frequency Range (MHz)	Result		
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS		

Spectrum Parameters	Setting	
Attenuation	Auto	
Span Frequency	= the frequency band of operation	
RB	RBW ≥ 1% of the span	
VB	VBW ≥ RBW	
Detector	Peak	
Trace	Max Hold	
Sweep Time	Auto	

#### 4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz, VBW=3MHz, Sweep time = Auto.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### **4.1.4 EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




#### 4.1.5 TEST RESULTS

EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode		

Number of Hopping Channel 79









#### 5. AVERAGE TIME OF OCCUPANCY

#### 5.1 APPLIED PROCEDURES / LIMIT

	,,, ,,, , <u></u>				
FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS	

#### **5.1.1 TEST PROCEDURE**

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. A Period Time = (channel number)\*0.4

  - DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)
    DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)
    DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

#### **5.1.2 DEVIATION FROM STANDARD**

No deviation.




NTEK	Page 38 of 76	Report No.:NTEK- 2013NT0807832F
5.1.3 TEST SETUP	)	
EUT		SPECTRUM
		ANALYZER
5.1.4 EUT OPERAT	TION CONDITIONS	
	tem was configured as the statements of is specified in the follows during the testin	




EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	25 ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH5,2DH5,3DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2441 MHz	2.95	0.31	0.4
2DH5	2441 MHz	2.99	0.32	0.4
3DH5	2441 MHz	2.96	0.32	0.4



1 of 2










EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH3,2DH3,3DH3		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH3	2441 MHz	1.71	0.18	0.4
2DH3	2441 MHz	1.71	0.18	0.4
3DH3	2441 MHz	1.73	0.18	0.4














EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441 MHz	0.45	0.05	0.4
2DH1	2441 MHz	0.48	0.05	0.4
3DH1	2441 MHz	0.44	0.05	0.4











#### 6. HOPPING CHANNEL SEPARATION MEASUREMENT

#### **6.1 APPLIED PROCEDURES / LIMIT**

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting	
Attenuation	Auto	
Span Frequency	> Measurement Bandwidth or Channel Separation	
RB	30 kHz	
VB	100 kHz	
Detector	Peak	
Trace	Max Hold	
Sweep Time	Auto	


## **6.1.1 TEST PROCEDURE**

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

## **6.1.2 DEVIATION FROM STANDARD**

No deviation.

## 6.1.3 TEST SETUP



## **6.1.4 EUT OPERATION CONDITIONS**


The EUT was programmed to be in continuously transmitting mode.




EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	DC 3.7V	
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.005	Complies
2441 MHz	1.005	Complies
2480 MHz	1.015	Complies

# Ch. Separation Limits: >20dB bandwidth











EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa Test Voltage : DC 3.7V		
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	0.990	Complies
2441 MHz	1.004	Complies
2480 MHz	1.004	Complies

## Ch. Separation Limits: >2/3 of 20dB bandwidth











EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (3Mbps M	ode)	

Frequency	Ch. Separation (MHz)	Result
2402 MHz	0.990	Complies
2441 MHz	0.998	Complies
2480 MHz	0.998	Complies

## Ch. Separation Limits: >2/3 of 20dB bandwidth









#### 7. BANDWIDTH TEST

## 7.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C				
Section Test Item Limit Frequency Range (MHz)		Result			
	15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

## 7.1.2 DEVIATION FROM STANDARD

No deviation.

## 7.1.3 TEST SETUP




#### 7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(1Mbps)		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	789.961	PASS
2441 MHz	868.168	PASS
2480 MHz	826.66	PASS











EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(2Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.243	PASS
2441 MHz	1.239	PASS
2480 MHz	1.222	PASS











EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.214	PASS
2441 MHz	1.211	PASS
2480 MHz	1.194	PASS









#### 8. PEAK OUTPUT POWER TEST

## 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section Test Item Limit Frequency Range (MHz) Result				Result
15.247 (b)(i)	Peak Output Power	0.125 w or 1w	2400-2483.5	PASS

## **8.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

 $VBW \geq RBW$ 

Sweep = auto

Detector function = peak

Trace = max hold

## **8.1.2 DEVIATION FROM STANDARD**

No deviation.

## 8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER


## **8.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps						
Test Channel	Frequency	Peak Output Power	LIMIT			
rest orianner	(MHz)	(dBm)	(dBm)			
CH00	2402	-3.368	30			
CH39	2441	-2.604	30			
CH78	2480	-2.874	30			
	2Mbps					
CH00	2402	-4.530	20.96			
CH39	2441	-4.168	20.96			
CH78	2480	-3.817	20.96			
3Mbps						
CH00	2402	-4.391	20.96			
CH39	2441	-3.782	20.96			
CH78	2480	-3.795	20.96			


























# 9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **TEST PROCEDURE**

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

#### 9.1 DEVIATION FROM STANDARD

No deviation.

#### 9.2 TEST SETUP

EUT	SPECTRUM
	ANALYZER

#### 9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# 9.4 TEST RESULTS


EUT:	Bluetooth Speaker	Model Name :	GGBSSRC
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V


Frequency Band	Delta Peak to band emission(Non-hopping) (dBc)	Delta Peak to band emission(Hopping) (dBc)	>Limit (dBc)	Result	
	11	Mbps			
Left-band	52.20	44.67	20	Pass	
Right-band	54.03	54.28	20	Pass	
	2	Mbps			
Left-band	51.47	44.53	20	Pass	
Right-band	53.59	52.78	20	Pass	
3Mbps					
Left-band	53.30	47.83	20	Pass	
Right-band	52.76	53.04	20	Pass	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	6
(MHz)	(dBμV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Comment
			1Mbps				
2390	58.45	-13.06	45.39	74	-28.61	peak	Vertical
2390	59.13	-13.06	46.07	74	-27.93	peak	Horizontal
2483.5	56.95	-12.78	44.17	74	-29.83	peak	Vertical
2483.5	56.74	-12.78	43.96	74	-30.04	peak	Horizontal
	2Mbps						
2390	57.90	-13.06	44.84	74	-29.16	peak	Vertical
2390	59.18	-13.06	46.12	74	-27.88	peak	Horizontal
2483.5	55.53	-12.78	42.75	74	-31.25	peak	Vertical
2483.5	56.97	-12.78	44.19	74	-29.81	peak	Horizontal
3Mbps							
2390	55.67	-13.06	42.61	74	-31.39	peak	Vertical
2390	54.6	-13.06	41.54	74	-32.46	peak	Horizontal
2483.5	57.19	-12.78	44.41	74	-29.59	peak	Vertical
2483.5	56.71	-12.78	43.93	74	-30.07	peak	Horizontal


Note: Test method to see chapter  $3.2\ .$ 
















































## **10. ANTENNA REQUIREMENT**

## **10.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## **10.2 EUT ANTENNA**

The EUT antenna is Integrated(PCB) antenna. It	comply with	the standard requirement.
--	-------------	---------------------------



# 11. EUT TEST PHOTO



