

FCC TEST REPORT

FCC 47 CFR Part 15C
Industry Canada RSS-210

Intentional radiator operating within the 5725 - 5875 MHz band

Report Reference No. : G0M-1308-3085-TFC249D-V01

Testing Laboratory : Eurofins Product Service GmbH

Address : Storkower Str. 38c
15526 Reichenwalde
Germany

Accreditation :



A2LA Accredited Testing Laboratory, Certificate No.: 1983.01
FCC Filed Test Laboratory, Reg.-No.: 96970
IC OATS Filing assigned code: 3470A

Applicant's name : inmotiotec GmbH

Address : Oberregauer Straße 48
4844 Regau
AUSTRIA

Test specification:

Standard..... : 47 CFR Part 15C
RSS-210, Issue 8, 2010-12
RSS-Gen, Issue 3, 2010-12
ANSI C63.4:2009

Equipment under test (EUT):

Product description	Transponder
Model No.	LPM Min T13
Hardware version	H1.3
Firmware / Software version	fcc0
	FCC-ID: 2AATD-MINTV13

Test result **Passed**

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Date of receipt of test item: 2013-08-05

Date (s) of performance of tests: 2013-08-26

Compiled by: Antje Bartusch

Tested by (+ signature).....: Wilfried Treffke
(Testing Manager)

W. Treffke

Approved by (+ signature): Christian Weber
(Test Lab Manager)

C. Weber

Date of issue: 2013-09-19

Total number of pages: 32

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

The transmission mode of the EUT combines two different transmissions; a chirp spread spectrum mode that shifts an unmodulated carrier over the frequency range of 5735 – 5865 MHz and a single channel FSK modulated telemetry transmission mode on the frequency of 5862 MHz. Each transmission cycle starts with the chirp transmission mode and is ended with the telemetry data transmission mode.

Version History

Version	Issue Date	Remarks	Revised by
01	2013-09-19	Initial Release	


REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment External	6
1.2	Photos – Equipment internal	7
1.3	Photos – Test setup	8
1.4	Supporting Equipment Used During Testing	9
1.5	Test Modes	10
1.6	Test Equipment Used During Testing	11
1.7	Sample emission level calculation	12
2	RESULT SUMMARY	13
3	TEST CONDITIONS AND RESULTS	14
3.1	Test Conditions and Results – Fundamental field strength emissions	14
3.2	Test Conditions and Results – Emissions radiated outside the specified frequency band	16
3.3	Test Conditions and Results – AC power line conducted emissions	18
ANNEX A	Fundamental field strength emissions	21
ANNEX B	Transmitter radiated spurious emissions	23


1 Equipment (Test item) Description

Description	Transponder	
Model	LPM Min T13	
Serial number	None	
Hardware version	H1.3	
Software / Firmware version	fcc0	
FCC-ID	2AATD-MINTV13	
Equipment type	End product	
Radio type	Transceiver	
Radio technology	custom	
Operating frequency range	5735 - 5865 MHz	
Assigned frequency band	5725 - 5875 MHz	
Frequency range CSS	F _{MID}	5735 - 5865 MHz
Frequency range FSK	F _{MID}	5862 MHz
Spreading	CSS & None (FSK)	
Modulations	None (CSS) & FSK for telemetry mode	
Channel spacing	None	
Number of antennas	1	
Antenna	Type	integrated
	Model	PCB Antenna
	Manufacturer	Abatec
	Gain	2 dBi
Manufacturer	Abatec Group AG Oberregauerstraße 48 4844 Regau Austria	
Power supply	V _{NOM}	3.7 VDC (Lithium-Battery) 120VAC (Charging station)
	V _{MIN}	N/A
	V _{MIN}	N/A
AC/DC-Adaptor	Model	N/A
	Vendor	N/A
	Input	N/A
	Output	N/A



1.1 Photos – Equipment External



1.2 Photos – Equipment internal



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
AE	Charging Station	Inmotiotec	LPM	
<p>*Note: Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

1.5 Test Modes

Mode #	Description	
Single	General conditions:	EUT powered by fully charged battery
	Radio conditions:	Mode = standalone transmit Modulation = FMCW / FSK Power level = Maximum

1.6 Test Equipment Used During Testing

Field strength emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 5	EF00395	calibration	calibration
Spectrum Analyzer	R&S	FSIQ26	EF00242	2013-06	2014-06
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00187	2011-02	2014-02
LPD Antenna	R&S	HL 025	EF00327	2013-02	2016-02

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2012-10	2014-10
AMN	R&S	ESH3-Z5	EF00036	2012-11	2014-11
EMI Test Receiver	R&S	ESCS 30	EF00295	2012-09	2013-09

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dBμV. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dBμV/m). The FCC limits are given in units of μV/m. The following formula is used to convert the units of μV/m to dBμV/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:


Reading	+	AF	=	Net Reading	:	Net reading - FCC limit	=	Margin
21.5 dBμV	+	26 dB	=	47.5 dBμV/m	:	47.5 dBμV/m - 57.0 dBμV/m	=	-9.5 dB

2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 4.6.1	Occupied Bandwidth	RSS-Gen 4.6.1	N/N	
FCC 15.249(a),(c),(e) IC RSS-210 A2.9(a)	Fundamental field strength emissions	ANSI C63.4	PASS	
FCC 15.249(a),(c),(d),(e) IC RSS-210 A2.9(a),(b)	Emission radiated outside the specified frequency band	ANSI C63.4	PASS	
IC RSS-210 Section 2.3 IC RSS-Gen 4.10 6.1	Receiver radiated spurious emissions	ANSI C63.4	N/N	
FCC § 15.207 IC RSS-Gen 7.2.4	AC power line conducted emissions	ANSI C63.4	PASS	
Remarks:				

3 Test Conditions and Results


3.1 Test Conditions and Results – Fundamental field strength emissions

Field strength emissions acc. FCC 47 CFR 15.249 / IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	FCC 15.249(a),(c),(e) / IC RSS-210 A2.9(a)			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	F _{MID}			
EUT test mode	Single			
Limits				
Frequency range [MHz]	Detector	Limit [mV/m]	Limit [dBµV/m]	Limit Distance [m]
902 – 928	Quasi-Peak	50	94	3
2400 – 2483.5	Average	50	94	3
5725 - 5875	Average	50	94	3
FCC 15.249(e) : for frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.				
Below 1GHz a CISPR quasi-peak detector is used.				
Test setup				
<div></div>				

Test procedure								
<ol style="list-style-type: none"> 1. EUT set to test mode 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to maximum emission levels 								
Test results								
Channel	Frequency [MHz]	Emission [MHz]	Level [dBμV/m]	Detector	Pol.	Limit [dBμV/m]	Limit distance [m]*	Margin [dB]
F _{MID}	5735 - 5865	5736	110.13	pk	ver	114.00	3	-03.87
F _{MID}	5735 - 5865	5736	66.21	avg	ver	94.00	3	-27.79
F _{MID}	5735 - 5865	5777	102.62	pk	hor	114.00	3	-11.38
F _{MID}	5735 - 5865	5777	62.40	avg	hor	94.00	3	-31.60
F _{MID}	5735 - 5865	5862	102.09	pk	hor	114.00	3	-11.91
F _{MID}	5735 - 5865	5862	81.63	avg	hor	94.00	3	-12.37
F _{MID}	5735 - 5865	5862	105.79	pk	ver	114.00	3	-08.21
F _{MID}	5735 - 5865	5862	84.96	avg	ver	94.00	3	-09.04
Comments: * Physical distance between EUT and measurement antenna.								

3.2 Test Conditions and Results – Emissions radiated outside the specified frequency band

Radiated out-of-band band emissions acc. FCC 47 CFR 15.249 / IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	FCC 15.249(a),(c),(d),(e) / IC RSS-210 A2.9(a),(b)			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 10 th harmonic			
EUT test mode	Single			
Limits - Harmonics				
Frequency range [MHz]	Detector	Limit [µV/m]	Limit [dBµV/m]	Limit Distance [m]
902 – 928	Quasi-Peak	500	54	3
2400 – 2483.5	Average	500	54	3
5725 - 5875	Average	500	54	3
Limits - General				
Frequency range [MHz]	Detector	Limit [µV/m]	Limit [dBµV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
FCC 15.249(e) : for frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.				
Except the higher order harmonics, emission radiated outside the specified frequency band shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in 15.209 / RSS-Gen, whichever is less stringent.				

Test setup								
								
Test procedure								
<ol style="list-style-type: none"> 5. EUT set to test mode 6. Span it set according to measurement range 7. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 8. Markers are set to maximum emission levels 								
Test results								
Channel	Frequency [MHz]	Emission [MHz]	Level [dBμV/m]	Detector	Pol.	Limit [dBμV/m]	Limit distance [m]*	Margin [dB]
F _{MID}	5735 - 5865	5718	71.54	pk	ver	74.00	3	-02.46
F _{MID}	5735 - 5865	5718	32.6	avg	ver	54.00	3	-21.40
F _{MID}	5735 - 5865	5725	58.43	pk	hor	74.00	3	-15.57
F _{MID}	5735 - 5865	5725	31.35	avg	hor	54.00	3	-22.65
F _{MID}	5735 - 5865	5875	68.3	pk	hor	74.00	3	-05.70
F _{MID}	5735 - 5865	5875	32.17	avg	hor	54.00	3	-21.83
F _{MID}	5735 - 5865	5875	70.9	pk	ver	74.00	3	-03.10
F _{MID}	5735 - 5865	5875	32.49	avg	ver	54.00	3	-21.51
F _{MID}	5735 - 5865	11612	53.19	pk	hor	74.00	3	-20.81
F _{MID}	5735 - 5865	11612	30.29	avg	hor	54.00	3	-23.71
F _{MID}	5735 - 5865	11703	61.77	pk	ver	74.00	3	-12.23
F _{MID}	5735 - 5865	11703	30.61	avg	ver	54.00	3	-23.39
Comments: * Physical distance between EUT and measurement antenna.								

3.3 Test Conditions and Results – AC power line conducted emissions

Power line conducted emissions acc. FCC 47 CFR 15.207 / IC RSS-Gen				Verdict: PASS	
Test according referenced standards		Reference Method			
		ANSI C63.4			
Fully configured sample scanned over the following frequency range		Frequency range			
		0.15 MHz to 30 MHz			
Points of Application		Application Interface			
AC Mains		LISN			
EUT test mode		AC-Powerline			
Limits and results					
Frequency [MHz]		Quasi-Peak [dBµV]	Result	Average [dBµV]	Result
0.15 to 5		66 to 56*	PASS	56 to 46*	PASS
0.5 to 5		56	PASS	46	PASS
5 to 30		60	PASS	50	PASS
Comments:					
* Limit decreases linearly with the logarithm of the frequency.					


Conducted Emissions

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
EUT Name: Minitransponder
Model: LPM Min T13
Test Site: Eurofins Product Service GmbH
Operator: Mr. Handrik
Test Conditions: Tnom: 23°C, Vnom: 3.7 V DC
LISN: ESH2-Z5 N
Mode: active; charging
Test Date: 2013-08-26
Note:

Index 5



Test Report No.: G0M-1308-3085-TFC249D-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany


Conducted Emissions

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Minitransponder
 Model: LPM Min T13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Handrik
 Test Conditions: Tnom: 23°C, Vnom: 3.7 V DC
 LISN: ESH2-Z5 L
 Mode: active; charging
 Test Date: 2013-08-26
 Note:

Index 6




ANNEX A Fundamental field strength emissions

Field Strength of Emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 17



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
5.777 GHz	102.62 dBµV/m	114 dBµV/m	-11.38 dB	Pass
5.862 GHz	102.09 dBµV/m	114 dBµV/m	-11.91 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
5.777 GHz	62.4 dBµV/m	94 dBµV/m	-31.6 dB	Pass
5.862 GHz	81.63 dBµV/m	94 dBµV/m	-12.37 dB	Pass

Test Report No.: G0M-1308-3085-TFC249D-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Field Strength of Emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 13



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
5.736 GHz	110.13 dBµV/m	114 dBµV/m	-3.87 dB	Pass
5.862 GHz	105.79 dBµV/m	114 dBµV/m	-8.21 dB	Pass

Frequency	Average	Average Limit	Average Difference	Average Status
5.736 GHz	66.21 dBµV/m	94 dBµV/m	-27.79 dB	Pass
5.862 GHz	84.96 dBµV/m	94 dBµV/m	-9.04 dB	Pass


ANNEX B Transmitter radiated spurious emissions

Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HK 116, Horizontal
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 24




Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HK 116, Vertical
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 25




Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HL 223, Horizontal
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 22




Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HL 223, Vertical
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 23




Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 18



Test Report No.: G0M-1308-3085-TFC249D-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 14




Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 19



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
5.725 GHz	58.43 dBµV/m	74 dBµV/m	-15.57 dB	Pass
5.875 GHz	68.3 dBµV/m	74 dBµV/m	-5.7 dB	Pass

Frequency	Average	Average Limit	Average Difference	Average Status
5.725 GHz	31.35 dBµV/m	54 dBµV/m	-22.65 dB	Pass
5.875 GHz	32.17 dBµV/m	54 dBµV/m	-21.83 dB	Pass

Test Report No.: G0M-1308-3085-TFC249D-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-26
 Note:

Index 16



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
5.718 GHz	71.54 dBµV/m	74 dBµV/m	-2.46 dB	Pass
5.875 GHz	70.9 dBµV/m	74 dBµV/m	-3.1 dB	Pass

Frequency	Average	Average Limit	Average Difference	Average Status
5.718 GHz	32.6 dBµV/m	54 dBµV/m	-21.4 dB	Pass
5.875 GHz	32.49 dBµV/m	54 dBµV/m	-21.51 dB	Pass

Test Report No.: G0M-1308-3085-TFC249D-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 100 cm converted to 3m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-27
 Note:

Index 31



Frequency 11.612 GHz	Peak 53.19 dBuV/m	Peak Limit 74 dBuV/m	Peak Difference -20.81 dB	Peak Status Pass
Frequency 11.612 GHz	Average 30.29 dBuV/m	Average Limit 54 dBuV/m	Average Difference -23.71 dB	Average Status Pass

Test Report No.: G0M-1308-3085-TFC249D-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.249

Project number: G0M-1308-3085

Manufacturer: inmotiotec GmbH
 EUT Name: Transponder
 Model: LPM MinT13
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 25°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 100 cm converted to 3m
 Mode: TX; Chirp + FSK Telemetry
 Test Date: 2013-08-27
 Note:

Index 30



Frequency 11.703 GHz	Peak 61.77 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -12.23 dB	Peak Status Pass
Frequency 11.703 GHz	Average 30.61 dBµV/m	Average Limit 54 dBµV/m	Average Difference -23.39 dB	Average Status Pass

Test Report No.: G0M-1308-3085-TFC249D-V01

Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany