

Appendix for the SAR Test Report

Dosimetric Assessment of the ADTS TOUCH Hand Terminal from GE Druck (FCC ID: 2AAVWADTSTOUCH-01) (IC: 12097A-ADTSTOUCH01)

According to the FCC Requirements SAR Distribution Plots

November 21, 2014

IMST GmbH
Carl-Friedrich-Gauß-Str. 2 - 4
D-47475 Kamp-Lintfort

Customer
TRaC Global Limited
Unit 1, Pendle Place, Skelmersdale
West Lancashire, WN8 9PN,
UK

The test results only relate to the items tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

1 SAR Distribution Plots

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [ADTS_899_bhm_front.da4](#)

DUT: GE Druck; Type: ADTS Touch; Serial: 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.94$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (9x22x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.076 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.01 V/m; Power Drift = -0.195 dB

Peak SAR (extrapolated) = 0.162 W/kg

SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.042 mW/g

Maximum value of SAR (measured) = 0.081 mW/g




Fig. 1: SAR distribution for Bluetooth, channel 39, front side, gap = 0 mm (October 30, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [ADTS 899 bhm back.da4](#)

DUT: GE Druck; **Type:** ADTS Touch; **Serial:** 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.94$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (9x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.136 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.59 V/m; Power Drift = 0.158 dB

Peak SAR (extrapolated) = 0.294 W/kg

SAR(1 g) = 0.139 mW/g; SAR(10 g) = 0.073 mW/g

Maximum value of SAR (measured) = 0.153 mW/g




Fig. 2: SAR distribution for Bluetooth, channel 39, back side, gap = 0 mm (October 30, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [ADTS 899 bhm top.da4](#)

DUT: GE Druck; **Type:** ADTS Touch; **Serial:** 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.94$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x11x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.197 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.04 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.374 W/kg

SAR(1 g) = 0.181 mW/g; SAR(10 g) = 0.093 mW/g

Maximum value of SAR (measured) = 0.202 mW/g




Fig. 3: SAR distribution for Bluetooth, channel 39, top side, gap = 0 mm (October 30, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [ADTS 899 bhm left.da4](#)

DUT: GE Druck; **Type:** ADTS Touch; **Serial:** 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.94$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.048 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.45 V/m; Power Drift = 0.096 dB

Peak SAR (extrapolated) = 0.097 W/kg

SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.026 mW/g

Maximum value of SAR (measured) = 0.051 mW/g




Fig. 4: SAR distribution for Bluetooth, channel 39, left side, gap = 0 mm (October 30, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [ADTS 899 bhl top.da4](#)

DUT: GE Druck; **Type:** ADTS Touch; **Serial:** 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2402$ MHz; $\sigma = 1.88$ mho/m; $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x11x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.125 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.07 V/m; Power Drift = 0.060 dB

Peak SAR (extrapolated) = 0.235 W/kg

SAR(1 g) = 0.117 mW/g; SAR(10 g) = 0.062 mW/g

Maximum value of SAR (measured) = 0.129 mW/g




Fig. 5: SAR distribution for Bluetooth, channel 0, top side, gap = 0 mm (October 30, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [ADTS 899 bhh top.da4](#)

DUT: GE Druck; **Type:** ADTS Touch; **Serial:** 4294899

Program Name: Bluetooth

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1.3

Medium parameters used: $f = 2480$ MHz; $\sigma = 2.01$ mho/m; $\epsilon_r = 51.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.34, 7.34, 7.34); Calibrated: 24.07.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2014
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x11x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.182 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.55 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 0.355 W/kg

SAR(1 g) = 0.171 mW/g; SAR(10 g) = 0.086 mW/g

Maximum value of SAR (measured) = 0.189 mW/g




Fig. 6: SAR distribution for Bluetooth, channel 78, top side, gap = 0 mm (October 30, 2014)