




RF TEST REPORT



Report No.: 17070182-FCC-R1

Supersede Report No.: N/A

Applicant	Jethro Trading LTD.	
Product Name	Jethro 3G Senior Cell Phone	
Model No.	SC318	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; ANSI/TIA-603-D: 2010	
Test Date	March 15 to March 21, 2017	
Issue Date	March 22, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070182-FCC-R1
Page	3 of 87

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	11
6.1 RF EXPOSURE (SAR)	11
6.2 RF OUTPUT POWER	12
6.3 PEAK-AVERAGE RATIO	23
6.4 OCCUPIED BANDWIDTH	26
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	37
6.6 SPURIOUS RADIATED EMISSIONS	50
6.7 BAND EDGE	56
6.8 FREQUENCY STABILITY	66
ANNEX A. TEST INSTRUMENT	70
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	72
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	83
ANNEX C.II. EUT OPERATING CONKITIONS	85
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	86
ANNEX E. DECLARATION OF SIMILARITY	87

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070182-FCC-R1	NONE	Original	March 22, 2017

2. Customer information

Applicant Name	Jethro Trading LTD.
Applicant Add	505 - 8840 210TH STREET, #231 Langley, Canada V1M2Y2
Manufacturer	Shenzhen Bayuda Technologies,co.,ltd
Manufacturer Add	Room A433 A Block,Shenzhen Industrial products exhibition procurement center the baoyuan road baoan distric

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1

4. Equipment under Test (EUT) Information

Description of EUT:	Jethro 3G Senior Cell Phone
Main Model:	SC318
Serial Model:	N/A
Date EUT received:	March 14, 2017
Test Date(s):	March 15 to March 21, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: 0.5dBi PCS1900: 1.0dBi UMTS-FDD Band V: 1.0dBi UMTS-FDD Band II: 1.0dBi Bluetooth: 0.5dBi
Antenna Type:	GSM/PCS/UMTS-FDD :PIFA antenna BT : Monopole antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz Bluetooth: 2402-2480 MHz
Maximum Conducted AV Power to Antenna:	GSM Voice:GSM850: 32.42 dBm PCS1900: 29.60 dBm GPRS:GSM850: 32.40 dBm

Test Report	17070182-FCC-R1
Page	7 of 87

	PCS1900: 29.68 dBm
	EGPRS(MCS1):GSM850: 32.39 dBm
	PCS1900: 29.69 dBm
	RMC:UMTS-FDD Band 5: 22.90 dBm
	UMTS-FDD Band 2: 22.97 dBm
	HSUPA:UMTS-FDD Band 5: 21.65 dBm
	UMTS-FDD Band 2: 21.95 dBm
	HSDPA:UMTS-FDD Band 5: 21.65 dBm
	UMTS-FDD Band 2: 21.95 dBm
	GSM Vioce:GSM850: 30.77 dBm / ERP
	PCS1900: 30.60 dBm / EIRP
	GPRS:GSM850: 30.75 dBm / ERP
	PCS1900: 30.68 dBm / EIRP
	EGPRS(MCS1):GSM850: 30.74 dBm / ERP
ERP/EIRP:	PCS1900: 30.69 dBm / EIRP
	RMC:UMTS-FDD Band 5: 21.75 dBm / ERP
	UMTS-FDD Band 2: 23.97 dBm / EIRP
	HSDPA:UMTS-FDD Band 5: 20.50 dBm / ERP
	UMTS-FDD Band 2: 22.95 dBm / EIRP
	HSUPA:UMTS-FDD Band 5: 20.50 dBm / ERP
	UMTS-FDD Band 2: 22.95 dBm / EIRP
	GSM 850: 124CH
	PCS1900: 299CH
Number of Channels:	UMTS-FDD Band V: 102CH
	UMTS-FDD Band II: 277CH
	Bluetooth: 79CH
Port:	USB Port, Earphone Port
	Adapter:
	Model: HJ-050050-US
	Input: AC100-240V~50/60Hz,0.1A
	Output: DC 5.0V,500mA
Input Power:	Battery:
	Model:SC318
	Spec: 3.7V,800mAh,2.96Wh
	Voltage: 4.2V

Test Report	17070182-FCC-R1
Page	8 of 87

Trade Name : Jethro

GPRS/ EGPRS Multi-slot class 8/10/12

FCC ID: 2AAWJSC318

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	$\pm 3.71\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.12\text{dB}$
Radiated Emission(1GHz~6GHz)	$\pm 5.34\text{dB}$

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;


Please refer to RF Exposure Evaluation Report: 17070182-SAR-H.

6.2 RF Output Power

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	March 20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station EUT</p>
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental frequency was investigated.
----------------	---

Test Report	17070182-FCC-R1
Page	13 of 87

	<ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.17	32.38	32.42	32±1	29.45	29.60	29.59	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.12	32.34	32.40	32±1	29.53	29.61	29.68	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	29.89	30.01	30.02	30±1	27.63	27.73	27.68	27±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	26.13	26.13	26.19	26±1	27.58	27.68	27.69	27±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.08	32.33	32.39	32±1	29.57	29.69	29.68	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	29.88	29.97	30.08	30±1	27.64	27.71	27.7	27±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	26.09	26.13	26.17	26±1	23.65	23.78	23.84	23±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	22.90	22±1
	4175	835	22.75	22±1
	4233	846.6	22.60	22±1
HSDPA Subtest1	4132	826.4	21.65	21.5±1
	4175	835	21.59	21.5±1
	4233	846.6	21.45	21.5±1
HSDPA Subtest2	4132	826.4	21.59	21.5±1
	4175	835	21.56	21.5±1
	4233	846.6	21.65	21.5±1
HSDPA Subtest3	4132	826.4	21.63	21.5±1
	4175	835	21.61	21.5±1
	4233	846.6	21.59	21.5±1
HSDPA Subtest4	4132	826.4	21.58	21.5±1
	4175	835	21.57	21.5±1
	4233	846.6	21.62	21.5±1
HSUPA Subtest1	4132	826.4	21.56	21.5±1
	4175	835	21.62	21.5±1
	4233	846.6	21.61	21.5±1
HSUPA Subtest2	4132	826.4	21.60	21.5±1
	4175	835	21.59	21.5±1
	4233	846.6	21.51	21.5±1
HSUPA Subtest3	4132	826.4	21.58	21.5±1
	4175	835	21.58	21.5±1
	4233	846.6	21.57	21.5±1
HSUPA Subtest4	4132	826.4	21.59	21.5±1
	4175	835	21.54	21.5±1
	4233	846.6	21.59	21.5±1
HSUPA Subtest5	4132	826.4	21.65	21.5±1
	4175	835	21.62	21.5±1
	4233	846.6	21.59	21.5±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.97	22±1
	9400	1880	22.95	22±1
	9538	1907.6	22.92	22±1
HSDPA Subtest1	9262	1852.4	21.87	21.5±1
	9400	1880	21.86	21.5±1
	9538	1907.6	21.82	21.5±1
HSDPA Subtest2	9262	1852.4	21.83	21.5±1
	9400	1880	21.82	21.5±1
	9538	1907.6	21.92	21.5±1
HSDPA Subtest3	9262	1852.4	21.93	21.5±1
	9400	1880	21.91	21.5±1
	9538	1907.6	21.88	21.5±1
HSDPA Subtest4	9262	1852.4	21.87	21.5±1
	9400	1880	21.89	21.5±1
	9538	1907.6	21.95	21.5±1
HSUPA Subtest1	9262	1852.4	21.84	21.5±1
	9400	1880	21.94	21.5±1
	9538	1907.6	21.95	21.5±1
HSUPA Subtest2	9262	1852.4	21.89	21.5±1
	9400	1880	21.89	21.5±1
	9538	1907.6	21.86	21.5±1
HSUPA Subtest3	9262	1852.4	21.88	21.5±1
	9400	1880	21.89	21.5±1
	9538	1907.6	21.87	21.5±1
HSUPA Subtest4	9262	1852.4	21.86	21.5±1
	9400	1880	21.82	21.5±1
	9538	1907.6	21.91	21.5±1
HSUPA Subtest5	9262	1852.4	21.88	21.5±1
	9400	1880	21.85	21.5±1
	9538	1907.6	21.87	21.5±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.25	V	6.8	0.53	30.52	38.45
824.2	23.21	H	6.8	0.53	29.48	38.45
836.6	24.46	V	6.8	0.53	30.73	38.45
836.6	23.37	H	6.8	0.53	29.64	38.45
848.8	24.4	V	6.9	0.53	30.77	38.45
848.8	23.32	H	6.9	0.53	29.69	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.42	V	7.88	0.85	30.45	33
1850.2	22.3	H	7.88	0.85	29.33	33
1880	23.57	V	7.88	0.85	30.60	33
1880	22.38	H	7.88	0.85	29.41	33
1909.8	23.58	V	7.86	0.85	30.59	33
1909.8	22.35	H	7.86	0.85	29.36	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.2	V	6.8	0.53	30.47	38.45
824.2	23.08	H	6.8	0.53	29.35	38.45
836.6	24.42	V	6.8	0.53	30.69	38.45
836.6	23.15	H	6.8	0.53	29.42	38.45
848.8	24.38	V	6.9	0.53	30.75	38.45
848.8	23.21	H	6.9	0.53	29.58	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.5	V	7.88	0.85	30.53	33
1850.2	22.4	H	7.88	0.85	29.43	33
1880	23.58	V	7.88	0.85	30.61	33
1880	22.51	H	7.88	0.85	29.54	33
1909.8	23.67	V	7.86	0.85	30.68	33
1909.8	22.55	H	7.86	0.85	29.56	33

EGPRS (MCS1):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.16	V	6.8	0.53	30.43	38.45
824.2	22.84	H	6.8	0.53	29.11	38.45
836.6	24.41	V	6.8	0.53	30.68	38.45
836.6	23.3	H	6.8	0.53	29.57	38.45
848.8	24.37	V	6.9	0.53	30.74	38.45
848.8	23.36	H	6.9	0.53	29.73	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.54	V	7.88	0.85	30.57	33
1850.2	22.52	H	7.88	0.85	29.55	33
1880	23.66	V	7.88	0.85	30.69	33
1880	22.56	H	7.88	0.85	29.59	33
1909.8	23.67	V	7.86	0.85	30.68	33
1909.8	22.62	H	7.86	0.85	29.63	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	15.48	V	6.8	0.53	21.75	38.45
826.4	14.46	H	6.8	0.53	20.73	38.45
835	15.33	V	6.8	0.53	21.60	38.45
835	14.21	H	6.8	0.53	20.48	38.45
846.6	15.08	V	6.9	0.53	21.45	38.45
846.6	13.95	H	6.9	0.53	20.32	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.94	V	7.88	0.85	23.97	33
1852.4	15.73	H	7.88	0.85	22.76	33
1880	16.92	V	7.88	0.85	23.95	33
1880	15.68	H	7.88	0.85	22.71	33
1907.6	16.91	V	7.86	0.85	23.92	33
1907.6	15.67	H	7.86	0.85	22.68	33

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	14.23	V	6.8	0.53	20.50	38.45
826.4	13.04	H	6.8	0.53	19.31	38.45
835	14.19	V	6.8	0.53	20.46	38.45
835	13.02	H	6.8	0.53	19.29	38.45
846.6	14.13	V	6.9	0.53	20.50	38.45
846.6	13	H	6.9	0.53	19.37	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.9	V	7.88	0.85	22.93	33
1852.4	14.78	H	7.88	0.85	21.81	33
1880	15.88	V	7.88	0.85	22.91	33
1880	14.72	H	7.88	0.85	21.75	33
1907.6	15.94	V	7.86	0.85	22.95	33
1907.6	14.82	H	7.86	0.85	21.83	33

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	14.23	V	6.8	0.53	20.50	38.45
826.4	13.05	H	6.8	0.53	19.32	38.45
835	14.2	V	6.8	0.53	20.47	38.45
835	13.18	H	6.8	0.53	19.45	38.45
846.6	14.09	V	6.9	0.53	20.46	38.45
846.6	12.9	H	6.9	0.53	19.27	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.86	V	7.88	0.85	22.89	33
1852.4	14.7	H	7.88	0.85	21.73	33
1880	15.91	V	7.88	0.85	22.94	33
1880	14.82	H	7.88	0.85	21.85	33
1907.6	15.94	V	7.86	0.85	22.95	33
1907.6	14.8	H	7.86	0.85	21.81	33

6.3 Peak-Average Ratio

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	March 20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>

Test Setup	<p>Base Station Spectrum Analyzer EUT</p>
------------	---

Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>
----------------	--

Test Report	17070182-FCC-R1
Page	24 of 87

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.41	29.45	0.96
1880	30.52	29.6	0.92
1909.8	30.55	29.59	0.96

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.55	29.53	1.02
1880	30.66	29.61	1.05
1909.8	30.71	29.68	1.03

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.99	22.97	2.02
1880	24.95	22.95	2
1907.6	24.91	22.92	1.99

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.95	21.87	3.08
1880	24.89	21.86	3.03
1907.6	24.91	21.82	3.09

HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.88	21.84	3.04
1880	24.89	21.94	2.95
1907.6	24.92	21.95	2.97

6.4 Occupied Bandwidth

Temperature	23 °C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	March 18, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup	<p>Base Station Spectrum Analyzer EUT</p>		
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	248.1672	325.184
190	836.6	247.0645	320.035
251	848.8	244.9870	323.510

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.3234	317.547
661	1880.0	245.3418	316.057
810	1909.8	247.3566	317.404

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	248.9820	323.285
190	836.6	242.2544	319.546
251	848.8	247.1132	323.240

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	243.5217	317.361
661	1880.0	251.1087	317.415
810	1909.8	244.3808	319.234

EGPRS (MCS 1):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.1512	322.289
190	836.6	244.2436	318.085
251	848.8	245.6792	319.148

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	251.2129	320.123
661	1880.0	247.0637	317.998
810	1909.8	244.3630	319.142

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.0940	4.706
4175	835.0	4.0995	4.716
4233	846.6	4.1225	4.714

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1074	4.696
9400	1880.0	4.1093	4.671
9538	1907.6	4.1292	4.742

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1178	4.689
4175	835.0	4.1137	4.706
4233	846.6	4.1086	4.693

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1100	4.685
9400	1880.0	4.1014	4.684
9538	1907.6	4.1104	4.698

HSUPA:

UMTS-FDD Band V (Part 22H)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1071	4.681
4175	835.0	4.0970	4.702
4233	846.6	4.1075	4.708

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1031	4.691
9400	1880.0	4.1079	4.687
9538	1907.6	4.1105	4.729

Test Plots


GSM Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz


EGPRS (MCS5):




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz



RMC:





HSDPA:





HSUPA:



Band V BW - Low CH 826.6 MHz



Band V BW - High CH 846.4 MHz



Band II BW - Mid CH 1880 MHz

Band II BW - High CH 1907.6 MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	March 20, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup	<p>Base Station Spectrum Analyzer EUT</p>		
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




EGPRS (MCS 1):

Cellular Band (Part 22H) result




PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSDPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2

UMTS-FDD Band II (Part 24E)




HSUPA:


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	March 21, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	17070182-FCC-R1
Page	51 of 87

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.67	V	7.95	0.78	-36.5	-13	-23.5
1648.4	-44.34	H	7.95	0.78	-37.17	-13	-24.17
325.8	-52.81	V	6.4	0.26	-46.67	-13	-33.67
606.6	-52.99	H	6.8	0.37	-46.56	-13	-33.56

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.69	V	7.95	0.78	-36.52	-13	-23.52
1673.2	-44.12	H	7.95	0.78	-36.95	-13	-23.95
326.5	-52.57	V	6.4	0.26	-46.43	-13	-33.43
605.2	-52.73	H	6.8	0.37	-46.3	-13	-33.3

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.52	V	7.95	0.78	-36.35	-13	-23.35
1697.6	-44.05	H	7.95	0.78	-36.88	-13	-23.88
327.3	-52.85	V	6.4	0.26	-46.71	-13	-33.71
604.7	-52.88	H	6.8	0.37	-46.45	-13	-33.45

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.76	V	10.25	2.73	-41.24	-13	-28.24
3700.4	-49.51	H	10.25	2.73	-41.99	-13	-28.99
326.7	-53.45	V	6.4	0.26	-47.31	-13	-34.31
605.5	-53.89	H	6.8	0.37	-47.46	-13	-34.46

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.79	V	10.25	2.73	-41.27	-13	-28.27
3760	-49.61	H	10.25	2.73	-42.09	-13	-29.09
327.1	-53.37	V	6.4	0.26	-47.23	-13	-34.23
605.9	-53.92	H	6.8	0.37	-47.49	-13	-34.49

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.84	V	10.36	2.73	-41.21	-13	-28.21
328.4	-49.77	H	10.36	2.73	-42.14	-13	-29.14
327.1	-53.65	V	6.4	0.26	-47.51	-13	-34.51
606.1	-52.16	H	6.8	0.37	-45.73	-13	-32.73

Note:

- 1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice , GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.59	V	7.95	0.78	-39.42	-13	-26.42
1652.8	-45.93	H	7.95	0.78	-38.76	-13	-25.76
329.4	-53.04	V	6.4	0.26	-46.9	-13	-33.9
609.4	-53.41	H	6.8	0.37	-46.98	-13	-33.98

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.75	V	7.95	0.78	-39.58	-13	-26.58
1670	-45.88	H	7.95	0.78	-38.71	-13	-25.71
328.8	-52.63	V	6.4	0.26	-46.49	-13	-33.49
608.5	-53.18	H	6.8	0.37	-46.75	-13	-33.75

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.84	V	7.95	0.78	-39.67	-13	-26.67
1693.2	-45.72	H	7.95	0.78	-38.55	-13	-25.55
328.3	-52.96	V	6.4	0.26	-46.82	-13	-33.82
609.2	-53.31	H	6.8	0.37	-46.88	-13	-33.88

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.55	V	10.25	2.73	-42.03	-13	-29.03
3704.8	-50.13	H	10.25	2.73	-42.61	-13	-29.61
329.7	-53.49	V	6.4	0.26	-47.35	-13	-34.35
608.1	-53.67	H	6.8	0.37	-47.24	-13	-34.24

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.63	V	10.25	2.73	-42.11	-13	-29.11
3760	-50.07	H	10.25	2.73	-42.55	-13	-29.55
328.6	-53.86	V	6.4	0.26	-47.72	-13	-34.72
606.8	-53.64	H	6.8	0.37	-47.21	-13	-34.21

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-49.7	V	10.36	2.73	-42.07	-13	-29.07
3815.2	-49.99	H	10.36	2.73	-42.36	-13	-29.36
329.5	-53.76	V	6.4	0.26	-47.62	-13	-34.62
607.7	-53.92	H	6.8	0.37	-47.49	-13	-34.49

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

6.7 Band Edge

Temperature	22 °C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	March 21, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram illustrates the test setup. A Base Station (green box) and a Spectrum Analyzer (green box) are connected to a power divider (black box). The power divider is then connected to the EUT (blue box). The Base Station and Spectrum Analyzer are both connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-16.68	-13
849.0025	-16.50	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.45	-13
1910.0225	-15.12	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9800	-16.35	-13
849.0200	-15.81	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.05	-13
1910.0250	-15.77	-13

EGPRS (MCS1):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9989	-14.55	-13
849.0025	-14.00	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-13.71	-13
1910.0200	-16.43	-13

RMC:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824.000	-22.57	-13
849.275	-23.57	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-21.8	-13
1910.075	-20.06	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.550	-21.90	-13
849.200	-22.67	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.900	-21.27	-13
1910.050	-19.37	-13

HSUPA:

UMTS-FDD Band V (Part 22H)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.825	-21.64	-13
849.875	-23.28	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-22.75	-13
1910.025	-19.93	-13


GSM Voice:

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.25/3)=4.0+0.4=4.4dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.23/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.17/3)=4.5+0.2=4.7dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.17/3)=4.5+0.2=4.7dB


GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.06/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.14/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.96/30)=4.5+1.9=6.4 dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.42/30)=4.5+2.0=6.5 dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.89/30)=4.0+1.9=5.9 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(46.93/30)=4.0+1.9=5.9 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.85/30)=4.0+2.4=6.4 dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(46.98/30)=4.0+2.4=6.4 dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.81/30)=4.0+1.9=5.9 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.08/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(46.91/30)=4.5+1.9=6.4dB





UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.29/30)=4.5+2.0=6.5 dB

6.8 Frequency Stability

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (m)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 929</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (m)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 929	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (m)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 929	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p style="text-align: center;">Base Station EUT Thermal Chamber</p>																																		

Test Report	17070182-FCC-R1
Page	67 of 87

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0215	2.5
0		17	0.0203	2.5
10		16	0.0191	2.5
20		15	0.0179	2.5
30		17	0.0203	2.5
40		15	0.0179	2.5
50		12	0.0143	2.5
55		17	0.0203	2.5
25	4.2	16	0.0191	2.5
	3.5	17	0.0203	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		18	0.0096	2.5
10		16	0.0085	2.5
20		17	0.0090	2.5
30		19	0.0101	2.5
40		20	0.0106	2.5
50		20	0.0106	2.5
55		16	0.0085	2.5
25	4.2	19	0.0101	2.5
	3.5	17	0.0090	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0216	2.5
0		16	0.0192	2.5
10		18	0.0216	2.5
20		17	0.0204	2.5
30		20	0.0240	2.5
40		20	0.0240	2.5
50		16	0.0192	2.5
55		19	0.0228	2.5
25	4.2	17	0.0204	2.5
	3.5	13	0.0156	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		16	0.0085	2.5
10		17	0.0090	2.5
20		15	0.0080	2.5
30		12	0.0064	2.5
40		19	0.0101	2.5
50		20	0.0106	2.5
55		15	0.0080	2.5
25	4.2	13	0.0069	2.5
	3.5	20	0.0106	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>

Test Report	17070182-FCC-R1
Page	71 of 87

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View



EUT - Front View




EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2



Test Report	17070182-FCC-R1
Page	77 of 87


Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View



Mainboard without Shielding - Rear View




Remove the Key Board– Front View




Remove the Key Board - Rear View



LCD – Front View




LCD – Rear View



GSM/PCS/UMTS-FDD Antenna View




BT-FDD Antenna View



Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Jethro Trading LTD.	Adapter	HJ-050050-US	SZ521

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	SZ521

Test Report	17070182-FCC-R1
Page	85 of 87

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	17070182-FCC-R1
Page	86 of 87

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	17070182-FCC-R1
Page	87 of 87

Annex E. DECLARATION OF SIMILARITY

N/A