

RF TEST REPORT



Report No.: 17071000-FCC-R1

Supersede Report No.: N/A

Applicant	Jethro Trading LTD.	
Product Name	Jethro 3G Flip Mobile Phone	
Model No.	SC729	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; ANSI/TIA-603-D: 2010	
Test Date	September 28 to November 01, 2017	
Issue Date	November 02, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17071000-FCC-R1
Page	3 of 79

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 RF EXPOSURE (SAR)	9
6.2 RF OUTPUT POWER	10
6.3 PEAK-AVERAGE RATIO	20
6.4 OCCUPIED BANDWIDTH	23
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	32
6.6 SPURIOUS RADIATED EMISSIONS	43
6.7 BAND EDGE	49
6.8 FREQUENCY STABILITY	58
ANNEX A. TEST INSTRUMENT	62
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	64
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	75
ANNEX C.II. EUT OPERATING CONKITIONS	77
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	78
ANNEX E. DECLARATION OF SIMILARITY	79

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071000-FCC-R1	NONE	Original	November 02, 2017

2. Customer information

Applicant Name	Jethro Trading LTD.
Applicant Add	505 - 8840 210TH STREET, #231 Langley, Canada V1M2Y2
Manufacturer	SIMDO Technology CO.,Ltd.
Manufacturer Add	5F,Block 9,Changyuan New Material Port, Science &Technology Park, Nanshan District, Shenzhen, Guangdong, PRC.

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Jethro 3G Flip Mobile Phone
Main Model:	SC729
Serial Model:	N/A
Date EUT received:	September 27, 2017
Test Date(s):	September 28 to November 01, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: -0.5dBi PCS1900: 0dBi UMTS-FDD Band V: -0.5dBi UMTS-FDD Band II: 0dBi Bluetooth: -1.5dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK UMTS-FDD: QPSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz Bluetooth: 2402-2480 MHz
Maximum Conducted AV Power to Antenna:	GSM Voice: GSM850: 32.29dBm PCS1900: 29.53 dBm GPRS: GSM850: 32.29dBm PCS1900: 29.45 dBm RMC: UMTS-FDD Band V: 21.54dBm UMTS-FDD Band II: 21.72dBm

	HSUPA:UMTS-FDD Band V: 20.91dBm
	UMTS-FDD Band II: 21.11dBm
	HSDPA:UMTS-FDD Band V: 20.93dBm
	UMTS-FDD Band II: 21.10dBm
	GSM Voice:GSM850: 29.64dBm / ERP
	PCS1900: 29.53dBm / EIRP
	GPRS:GSM850: 29.64dBm / ERP
	PCS1900:29.45dBm / EIRP
ERP/EIRP:	RMC:UMTS-FDD Band V: 18.89dBm / ERP
	UMTS-FDD Band II: 21.72dBm / EIRP
	HSDPA:UMTS-FDD Band V: 18.28dBm / ERP
	UMTS-FDD Band II: 21.10dBm / EIRP
	HSUPA:UMTS-FDD Band V: 18.26dBm / ERP
	UMTS-FDD Band II: 21.11dBm / EIRP
	GSM 850: 124CH
	PCS1900: 299CH
Number of Channels:	UMTS-FDD Band V: 102CH
	UMTS-FDD Band II: 277CH
	Bluetooth: 79CH
Port:	USB Port, Earphone Port
	Adapter:
	Model: S050-050-US
	Input: AC100-240V~50/60Hz,0.2A
Input Power:	Output: DC 5.0V, 0.5A
	Battery:
	Model: AK-V99
	Spec: 1100mAh, 4.07Wh, 3.7V
Trade Name :	Jethro
GPRS/ EGPRS Multi-slot class	8/10/11/12
FCC ID:	2AAWJSC729

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 17071000-FCC-H.

6.2 RF Output Power

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1018mbar
Test date :	October 19, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station EUT</p>
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental frequency was investigated.
----------------	---

	<ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.29	32.04	31.86	32±1	29.53	29.49	29.46	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.29	32.02	31.84	32±1	29.45	29.42	29.41	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.51	31.27	31.05	31±1	28.57	28.54	28.55	28±1
GPRS Multi-Slot Class 11 (3 uplink) GMSK	29.95	29.78	29.56	30±1	26.9	26.85	26.85	27±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.25	29.01	28.81	29±1	26.04	25.97	25.98	26±1
Remark : GPRS, CS1 coding scheme. Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link								

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	21.32	21.3±1
	4175	835	21.54	21.3±1
	4233	846.6	21.39	21.3±1
HSDPA Subtest1	4132	826.4	20.66	21.3±1
	4175	835	20.93	21.3±1
	4233	846.6	20.66	21.3±1
HSDPA Subtest2	4132	826.4	20.76	21.3±1
	4175	835	20.91	21.3±1
	4233	846.6	20.83	21.3±1
HSDPA Subtest3	4132	826.4	20.7	21.3±1
	4175	835	20.78	21.3±1
	4233	846.6	20.7	21.3±1
HSDPA Subtest4	4132	826.4	20.76	21.3±1
	4175	835	20.81	21.3±1
	4233	846.6	20.82	21.3±1
HSUPA Subtest1	4132	826.4	20.64	21.3±1
	4175	835	20.91	21.3±1
	4233	846.6	20.75	21.3±1
HSUPA Subtest2	4132	826.4	20.58	21.3±1
	4175	835	20.65	21.3±1
	4233	846.6	20.67	21.3±1
HSUPA Subtest3	4132	826.4	20.69	21.3±1
	4175	835	20.87	21.3±1
	4233	846.6	20.7	21.3±1
HSUPA Subtest4	4132	826.4	20.33	21.3±1
	4175	835	20.68	21.3±1
	4233	846.6	20.42	21.3±1
HSUPA Subtest5	4132	826.4	20.58	21.3±1
	4175	835	20.77	21.3±1
	4233	846.6	20.81	21.3±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	21.72	21.3±1
	9400	1880	21.54	21.3±1
	9538	1907.6	21.31	21.3±1
HSDPA Subtest1	9262	1852.4	21.03	21.3±1
	9400	1880	20.78	21.3±1
	9538	1907.6	20.7	21.3±1
HSDPA Subtest2	9262	1852.4	21.05	21.3±1
	9400	1880	20.86	21.3±1
	9538	1907.6	20.79	21.3±1
HSDPA Subtest3	9262	1852.4	21.08	21.3±1
	9400	1880	20.85	21.3±1
	9538	1907.6	20.69	21.3±1
HSDPA Subtest4	9262	1852.4	21.1	21.3±1
	9400	1880	20.89	21.3±1
	9538	1907.6	20.65	21.3±1
HSUPA Subtest1	9262	1852.4	21.02	21.3±1
	9400	1880	20.83	21.3±1
	9538	1907.6	20.64	21.3±1
HSUPA Subtest2	9262	1852.4	20.85	21.3±1
	9400	1880	20.83	21.3±1
	9538	1907.6	20.48	21.3±1
HSUPA Subtest3	9262	1852.4	21.11	21.3±1
	9400	1880	20.87	21.3±1
	9538	1907.6	20.58	21.3±1
HSUPA Subtest4	9262	1852.4	21	21.3±1
	9400	1880	20.83	21.3±1
	9538	1907.6	20.47	21.3±1
HSUPA Subtest5	9262	1852.4	20.99	21.3±1
	9400	1880	20.98	21.3±1
	9538	1907.6	20.78	21.3±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.07	V	6.1	0.53	29.64	38.45
824.2	22.34	H	6.1	0.53	27.91	38.45
836.6	23.72	V	6.2	0.53	29.39	38.45
836.6	22.88	H	6.2	0.53	28.55	38.45
848.8	23.54	V	6.2	0.53	29.21	38.45
848.8	22.76	H	6.2	0.53	28.43	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.37	V	7.88	0.72	29.53	33
1850.2	21.51	H	7.88	0.72	28.67	33
1880	22.33	V	7.88	0.72	29.49	33
1880	20.98	H	7.88	0.72	28.14	33
1909.8	22.32	V	7.86	0.72	29.46	33
1909.8	21.47	H	7.86	0.72	28.61	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.07	V	6.1	0.53	29.64	38.45
824.2	23.35	H	6.1	0.53	28.92	38.45
836.6	23.7	V	6.2	0.53	29.37	38.45
836.6	22.6	H	6.2	0.53	28.27	38.45
848.8	23.52	V	6.2	0.53	29.19	38.45
848.8	22.34	H	6.2	0.53	28.01	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.29	V	7.88	0.72	29.45	33
1850.2	20.33	H	7.88	0.72	27.49	33
1880	22.26	V	7.88	0.72	29.42	33
1880	21.08	H	7.88	0.72	28.24	33
1909.8	22.27	V	7.86	0.72	29.41	33
1909.8	21.17	H	7.86	0.72	28.31	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.1	V	6.1	0.53	18.67	38.45
826.4	11.78	H	6.1	0.53	17.35	38.45
835	13.22	V	6.2	0.53	18.89	38.45
835	11.77	H	6.2	0.53	17.44	38.45
846.6	13.07	V	6.2	0.53	18.74	38.45
846.6	11.09	H	6.2	0.53	16.76	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.56	V	7.88	0.72	21.72	33
1852.4	13.01	H	7.88	0.72	20.17	33
1880	14.38	V	7.88	0.72	21.54	33
1880	12.95	H	7.88	0.72	20.11	33
1907.6	14.17	V	7.86	0.72	21.31	33
1907.6	12.84	H	7.86	0.72	19.98	33

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.54	V	6.1	0.53	18.11	38.45
826.4	11.37	H	6.1	0.53	16.94	38.45
835	12.61	V	6.2	0.53	18.28	38.45
835	11.33	H	6.2	0.53	17	38.45
846.6	12.51	V	6.2	0.53	18.18	38.45
846.6	11.26	H	6.2	0.53	16.93	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.94	V	7.88	0.72	21.1	33
1852.4	12.34	H	7.88	0.72	19.5	33
1880	13.73	V	7.88	0.72	20.89	33
1880	12.59	H	7.88	0.72	19.75	33
1907.6	13.65	V	7.86	0.72	20.79	33
1907.6	11.7	H	7.86	0.72	18.84	33

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.47	V	6.1	0.53	18.04	38.45
826.4	10.93	H	6.1	0.53	16.5	38.45
835	12.59	V	6.2	0.53	18.26	38.45
835	11.67	H	6.2	0.53	17.34	38.45
846.6	12.49	V	6.2	0.53	18.16	38.45
846.6	11.28	H	6.2	0.53	16.95	38.45

EIRP for UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.95	V	7.88	0.72	21.11	33
1852.4	12.49	H	7.88	0.72	19.65	33
1880	13.82	V	7.88	0.72	20.98	33
1880	12.14	H	7.88	0.72	19.3	33
1907.6	13.64	V	7.86	0.72	20.78	33
1907.6	12.17	H	7.86	0.72	19.31	33

6.3 Peak-Average Ratio

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1018mbar
Test date :	October 19, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station Spectrum Analyzer EUT</p>
------------	---

Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>
----------------	--

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.62	29.53	1.09
1880	30.49	29.49	1
1909.8	30.71	29.46	1.25

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.62	29.45	1.17
1880	30.49	29.42	1.07
1909.8	30.55	29.41	1.14

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.18	21.72	2.46
1880	24.29	21.54	2.75
1907.6	24.43	21.31	3.12

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.19	21.03	3.16
1880	24.22	20.78	3.44
1907.6	24.36	20.7	3.66


HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.52	21.02	3.5
1880	24.29	20.83	3.46
1907.6	24.33	20.64	3.69

6.4 Occupied Bandwidth

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1014mbar
Test date :	October 20, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.3917	320.460
190	836.6	245.3656	320.770
251	848.8	245.1934	319.661

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850	247.7331	320.733
661	1880	248.2710	319.771
810	1910	246.6799	320.880

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.3743	320.313
190	836.6	253.8276	319.927
251	848.8	248.1549	321.033

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850	247.9719	320.602
661	1880	243.6255	320.465
810	1910	247.6972	319.935

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1726	4.725
4175	835.0	4.1628	4.707
4233	846.4	4.1941	4.715

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.1943	4.769
9400	1880	4.1710	4.725
9538	1907	4.1702	4.723

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1859	4.722
4175	835.0	4.1725	4.711
4233	846.4	4.1689	4.713

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.2047	4.764
9400	1880	4.1743	4.698
9538	1907	4.1788	4.733

HSUPA:

UMTS-FDD Band V (Part 22H)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1724	4.716
4175	835.0	4.1649	4.706
4233	846.4	4.1872	4.713

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.1983	4.778
9400	1880	4.1804	4.713
9538	1907	4.1732	4.738

Test Plots


GSM Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850MHz





PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1910MHz



RMC:



Band V BW - Low CH 826.6 MHz




Band V BW - High CH 846.4 MHz





Band II BW - Mid CH 1880 MHz

Band II BW - High CH 1907 MHz


HSDPA:




HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz

Band II BW - High CH 1907MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1014mbar
Test date :	October 20, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:


Cellular Band (Part 22H) result




PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

RMC


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSDPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSUPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	25 °C
Relative Humidity	55%
Atmospheric Pressure	1022mbar
Test date :	October 31, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	17071000-FCC-R1
Page	44 of 79

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-42.94	V	7.95	0.67	-35.66	-13	-22.66
1648.4	-43.76	H	7.95	0.67	-36.48	-13	-23.48
319.9	-52.98	V	5.56	0.22	-47.64	-13	-34.64
415.5	-52.64	H	5.96	0.3	-46.98	-13	-33.98

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-44.2	V	7.95	0.67	-36.92	-13	-23.92
1673.2	-44.83	H	7.95	0.67	-37.55	-13	-24.55
585.8	-52.71	V	6.4	0.36	-46.67	-13	-33.67
884.1	-53.4	H	6.25	0.44	-47.59	-13	-34.59

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.99	V	7.95	0.68	-36.72	-13	-23.72
1697.6	-43.63	H	7.95	0.68	-36.36	-13	-23.36
170.5	-52.11	V	1	0.16	-51.27	-13	-38.27
722.2	-52.04	H	6.34	0.39	-46.09	-13	-33.09

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.18	V	10.25	1	-38.93	-13	-25.93
3700.4	-48.25	H	10.25	1	-39	-13	-26
807.5	-53.15	V	6.19	0.47	-47.43	-13	-34.43
502.5	-53.18	H	6.37	0.36	-47.17	-13	-34.17

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.18	V	10.25	1.01	-38.94	-13	-25.94
3760	-49.33	H	10.25	1.01	-40.09	-13	-27.09
325	-52.92	V	5.94	0.31	-47.29	-13	-34.29
602.2	-53.97	H	6.36	0.34	-47.95	-13	-34.95

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-47.96	V	10.36	1.02	-38.62	-13	-25.62
3819.6	-50	H	10.36	1.02	-40.66	-13	-27.66
546.8	-53.38	V	6.37	0.36	-47.37	-13	-34.37
521.6	-50.87	H	6.37	0.36	-44.86	-13	-31.86

Note:

1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-45.88	V	7.95	0.67	-38.6	-13	-25.6
1652.8	-46.01	H	7.95	0.67	-38.73	-13	-25.73
179.4	-52.42	V	6.04	0.28	-46.66	-13	-33.66
488.8	-53.81	H	6.1	0.34	-48.05	-13	-35.05

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-45.52	V	7.95	0.67	-38.24	-13	-25.24
1670	-46.31	H	7.95	0.67	-39.03	-13	-26.03
200.5	-51.73	V	5.95	0.25	-46.03	-13	-33.03
881.7	-53.76	H	6.14	0.35	-47.97	-13	-34.97

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.94	V	7.95	0.68	-39.67	-13	-26.67
1693.2	-45.75	H	7.95	0.68	-38.48	-13	-25.48
669.6	-52.79	V	6.1	0.4	-47.09	-13	-34.09
477.9	-53	H	6.13	0.36	-47.23	-13	-34.23

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.9	V	10.25	1	-39.65	-13	-26.65
3704.8	-50.58	H	10.25	1	-41.33	-13	-28.33
942.7	-53.85	V	6.31	0.48	-48.02	-13	-35.02
661.2	-53.05	H	6.05	0.38	-47.38	-13	-34.38

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.93	V	10.25	1.01	-40.69	-13	-27.69
3760	-49.35	H	10.25	1.01	-40.11	-13	-27.11
210.9	-54.25	V	5.96	0.28	-48.57	-13	-35.57
843.6	-53.33	H	6.25	0.48	-47.56	-13	-34.56

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.6	V	10.36	1.02	-39.26	-13	-26.26
3815.2	-48.58	H	10.36	1.02	-39.24	-13	-26.24
606.6	-54.36	V	6.06	0.38	-48.68	-13	-35.68
309.7	-54.19	H	5.98	0.25	-48.46	-13	-35.46

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases


4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

6.7 Band Edge

Temperature	25 °C
Relative Humidity	55%
Atmospheric Pressure	1022mbar
Test date :	October 31, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram shows a Base Station (green box) and a Spectrum Analyzer (green box) connected to an EUT (blue box) via a power divider (black box). The Base Station and Spectrum Analyzer are connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.997	-14.92	-13
849.005	-16.57	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.997	-17.35	-13
1910.003	-15.4	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.992	-14.50	-13
849.012	-15.63	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.997	-15.34	-13
1910.008	-14.85	-13

RMC:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.19	-21.86	-13
849.02	-26.87	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.02	-16.42	-13
1910.01	-23.58	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
822.83	-22.98	-13
849.89	-25.91	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.06	-15.04	-13
1910.01	-23.30	-13

HSUPA:

UMTS-FDD Band V (Part 22H)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
822.83	-23.33	-13
849.02	-27.15	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.13	-15.03	-13
1910.01	-23.47	-13


GSM Voice:

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.19/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.5+0.3=4.8dB




PCS Band - High Channel


Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.5+0.3=4.8dB

GPRS:

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.25/30)=4.0+2.0=6.0dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.15/30)=4.0+2.0=6.0dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.69/30)=4.5+2.0=6.5dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.23/30)=4.5+2.0=6.5dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.22/30)=4.0+2.0=6.0dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.13/30)=4.0+2.0=6.0dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.64/30)=4.5+2.0=6.5dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.33/30)=4.5+2.0=6.5dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.16/30)=4.0+2.0=6.0dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.13/30)=4.0+2.0=6.0dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.78/30)=4.5+2.0=6.5dB





UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.38/30)=4.5+2.0=6.5dB

6.8 Frequency Stability

Temperature	23 °C
Relative Humidity	51%
Atmospheric Pressure	1020mbar
Test date :	October 30, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≥ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>450 to 512</td><td>2.5</td><td>5.0</td><td>5.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 929</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≥ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	5.0	821 to 896	1.5	2.5	2.5	928 to 929	5.0	N/A	N/A	929 to 960	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≥ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
450 to 512	2.5	5.0	5.0																																
821 to 896	1.5	2.5	2.5																																
928 to 929	5.0	N/A	N/A																																
929 to 960	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p style="text-align: center;">Base Station Thermal Chamber</p>																																		

Procedure	<p>A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage.</p> <p>Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0239	2.5
0		17	0.0203	2.5
10		15	0.0179	2.5
20		16	0.0191	2.5
30		14	0.0167	2.5
40		17	0.0203	2.5
50		18	0.0215	2.5
55		20	0.0239	2.5
25	4.2	17	0.0203	2.5
	3.5	18	0.0215	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		14	0.0074	2.5
10		11	0.0059	2.5
20		15	0.0080	2.5
30		17	0.0090	2.5
40		15	0.0080	2.5
50		18	0.0096	2.5
55		15	0.0080	2.5
25	4.2	18	0.0096	2.5
	3.5	18	0.0096	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		12	0.0144	2.5
10		17	0.0204	2.5
20		15	0.0180	2.5
30		11	0.0132	2.5
40		11	0.0132	2.5
50		21	0.0251	2.5
55		17	0.0204	2.5
25	4.2	16	0.0192	2.5
	3.5	15	0.0180	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	22	0.0117	2.5
0		15	0.0080	2.5
10		17	0.0090	2.5
20		16	0.0085	2.5
30		15	0.0080	2.5
40		13	0.0069	2.5
50		21	0.0112	2.5
55		18	0.0096	2.5
25	4.2	21	0.0112	2.5
	3.5	19	0.0101	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/14/2017	09/13/2018	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/07/2017	10/06/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/26/2017	05/25/2018	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>

Test Report	17071000-FCC-R1
Page	63 of 79

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Label View




EUT - Front View




EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View




Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1



Cover Off - Top View 2




Battery - Front View




Battery - Rear View



Mainboard with Shielding – Front View




Mainboard with Shielding – Rear View




Mainboard without Shielding – Front View



LCD – Front View



LCD – Rear View




GSM/PCS/UMTS-FDD - Antenna View




BT - Antenna View



Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Jethro Trading LTD.	Adapter	S050-050-US	N/A
SAMSUNG	headset	HS330	N/A
Agilent	Wireless Connectivity Test Set	N4010A	N/A
OEM	omnidirectional antenna	AntSuck	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A