

RF EXPOSURE REPORT

Applicant	The Singing Machine Company, Inc.
Address	6301 NW 5th Way, Suite 2900, Fort Lauderdale, FL 33309, USA

Manufacturer or Supplier	SHENZHEN JUNLAN ELECTRONIC LTD			
Address	lo.277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, henzhen, China			
Product	ORTABLE SOUND CHANGER KARAOKE PLAYER WITH BLUETOOTH			
Brand Name	Singing Machine			
Model	SMK1010			
Additional Model & Model Difference	Kids Pedestal, SMK1011, SMK1011XX, SMK1010XX (XX means unit color, it can be A to Z or N/A)			
Date of tests	Jan. 25, 2018 ~ Jun. 20, 2018			

- **KDB 447498 D01**
- **☐** IEEE C95.1

CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department
- Crim	AM

Date: Jul. 06, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



TABLE OF CONTENTS

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM180125N023	Original release	Jul. 06, 2018

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



1. CERTIFICATION

FCC ID:	2AAXO-SMK1010
PRODUCT:	PORTABLE SOUND CHANGER KARAOKE PLAYER WITH BLUETOOTH
BRAND NAME:	Singing Machine
MODEL NO.: SMK1010	
ADDITIONAL NO.:	Kids Pedestal, SMK1011, SMK1011XX, SMK1010XX (XX means unit color, it can be A to Z or N/A)
APPLICANT:	The Singing Machine Company, Inc.
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

		MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)			
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE							
300-1500			F/1500	30			
1500-100,000			1.0	30			

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 6 Report Version 1



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	0	Integral PCB Antenna	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

The tailed bolidabled / Welage i ower (debiated by blieft)					
Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	-18	+-2	-20	-16
8DPSK	2402-2480	-18	+-2	-20	-16

The measured conducted Average Power

no mededica conducted tronage i ever					
Mode	Frequency (MHz)	Averaged Power (dBm)			
GFSK	2480	-17.54			
8DPSK	2480	-17.63			

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	-16	0	20	0.000005	1.0

--- END ---

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080