







#### ISO/IEC17025Accredited Lab.

Report No: FCC 1312137-01 File reference No: 2013-12-27

Applicant: TD Semi,Inc.

Product: Tron Tab Mega

Model No: T4238

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4 and FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: December 27, 2013

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to

withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F, Block 4, Anhua Industrial Zone., No.8 TaiRan Rd.CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1312137-01 Page 2 of 90

Date: 2013-12-27



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

## **CNAL-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

#### **IC- Registration No.: IC5205A-02**

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 90

Report No: 1312137-01

Date: 2013-12-27



# **Test Report Conclusion**

#### Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	9
3.1	Summary of Test Results	9
3.2	Test Standards.	9
4.0	EUT Modification.	9
5.0	Power Line Conducted Emission Test.	10
5.1	Schematics of the Test.	10
5.2	Test Method and Test Procedure.	10
5.3	Configuration of the EUT	10
5.4	EUT Operating Condition.	11
5.5	Conducted Emission Limit.	11
5.6	Test Result.	11
6.0	Radiated Emission test.	14
6.1	Test Method and Test Procedure.	14
6.2	Configuration of the EUT	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit.	15
7.0	6dB Bandwidth Measurement.	34
8.0	Maximum Peak Output Power	50
9.0	Power Spectral Density Measurement.	53
10.0	Out of Band Measurement.	68
11.0	Antenna Requirement.	77
12.0	FCC ID Label	78
13.0	Photo of Test Setup and EUT View.	79

Date: 2013-12-27



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

#### 1.2 Applicant Details

Applicant: TD Semi, Inc.

Address: 3704 Marlborough Ct., Plano, TX 75075, USA

Telephone: (972) 346-1201 Fax: (972) 810-4326

#### 1.3 Description of EUT

Product: Tron Tab Mega

Manufacturer: Shenzhen Jizhao Information Technology Co., Ltd

Address: 4th Floor, Yuxing Sanwei Tech Park, HangKong Road, Xixiang Town,

Bao'an, Shenzhen, China.

Brand Name: N/A
Model Number: T4238
Additional Model Number: N/A
Additional Trade Name: N/A

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20): OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz;

Channel Spacing IEEE 802.11b/g/n (HT20) : 5MHz Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1312137-01 Page 5 of 90

TIMEWAY TO TO THE TOTAL TH

Antenna: Integral Antenna with maximum gain 2.0dBi

Power Supply: Model No.: DSA-20PFE-05 FCH 050300

Input: 100-240V, 50/60Hz, 0.7A MAX; Output: 5V, 3A

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

Date: 2013-12-27

2013-12-25 to 2013-12-27

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 90

Report No: 1312137-01

Date: 2013-12-27



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2013-08-23	2014-08-22
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2013-08-23	2014-08-22
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2013-08-23	2014-08-22
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2013-08-25	2014-08-24
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2013-08-23	2014-08-22
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2013-08-24	2014-08-23
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-
Loop Antenna	EMCO	6502	00042960	2013-08-23	2014-08-22
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2013-08-23	2014-08-22
3m OATS			N/A	2013-08-22	2014-08-21
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2013-08-24	2014-08-23
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2013-08-24	2014-08-23
Power meter	Anritsu	ML2487A	6K00003613	2013-08-24	2014-08-23
Power sensor	Anritsu	MA2491A	32263	2013-08-24	2014-08-23
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2013-08-24	2014-08-23
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22
9*6*6 Anechoic			N/A	2013-08-22	2014-08-21
EMI Test Receiver	RS	ESCS30	100139	2013-08-23	2014-08-22
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22

Report No: 1312137-01 Page 7 of 90



2.1 **Auxiliary Equipment** 

Date: 2013-12-27

	7 1 1				
Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
TF Card			Kingston		
Earphone					
LCD Monitor	PH2450		SAMSANG		DOC

Date: 2013-12-27



Page 8 of 90

#### 3. DESCRIPTION OF TEST MODES

## IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 65Mbps data rate (worst case) were chosen for full testing

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Report No: 1312137-01 Date: 2013-12-27



#### 3.0 **Technical Details**

#### 3.1 **Summary of test results**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	<b>Conducted Emission Test</b>	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

#### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

#### 4.0 **EUT Modification**

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Page 10 of 90

Report No: 1312137-01 Date: 2013-12-27



#### 5. Power Line Conducted Emission Test

#### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



#### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

# A. EUT

Device	Manufacturer	Model	FCC ID
Torn Tab Mega	Shenzhen Jizhao Information Technology Co., Ltd.	T4238	2AAY2-T4238

#### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312137-01 Page 11 of 90

Date: 2013-12-27



# C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207.

Frequency	requency Class A Limit		Class B	Limits (dB \mu V)
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No: 1312137-01 Page 12 of 90

Date: 2013-12-27



## A: Conducted Emission on Live Terminal (150kHz to 30MHz)

**EUT Operating Environment** 

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Charging and Keep WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



Frequency	uency Line Reading(dBµV)		Limit(dBµV)		
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.2698	Live	44.53	29.13	61.12	51.12
0.4360	Live	39.20	22.80	57.14	47.14
9.0452	Live	41.00	30.60	60.00	50.00

Report No: 1312137-01 Page 13 of 90

Date: 2013-12-27



## B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Charging and Keep Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



Frequency	Line Reading(dBµV)		Limit(dBµV)		
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.2757	Neutral	44.13	26.93	60.91	50.91
0.4416	Neutral	40.01	24.11	60.00	50.00
9.0040	Neutral	41.12	30.32	60.00	50.00

Report No: 1312137-01 Page 14 of 90

Date: 2013-12-27



#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier Turn-table Receiver

- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

Report No: 1312137-01 Page 15 of 90

Date: 2013-12-27



#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

#### Frequencies in restricted band are complied to limit on Paragraph 15.209

		8 1
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
A ove 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1312137-01 Page 16 of 90

Date: 2013-12-27



#### Test result

#### General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

**EUT set Condition:** Charging and Keep WIFI Transmitting

**Results:** Pass


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ		
		-	V m)		
63.640	36.30	Н	40.00		
127.280	35.28	Н	43.50		
445.440	44.14	Н	46.00		
63.640	29.29	V	40.00		
127.280	39.83	V	43.50		
445.440	31.73	V	46.00		

Report No: 1312137-01 Page 17 of 90

Date: 2013-12-27



#### Test Figure:



Date: 24.DEC.2013 16:45:23


Page 18 of 90

Report No: 1312137-01

Date: 2013-12-27



#### Test Figure:



Date: 24.DEC.2013 16:47:21

Report No: 1312137-01 Page 19 of 90

Date: 2013-12-27



## Operation Mode: Transmitting under CH01 for 11g at 54Mbps

Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
88.10 (PK)	Н	Even do monto 1 Eno aven ave
89.08 (PK)	V	Fundamental Frequency
	Н	74(Peak)/ 54(AV)
	V	74(Peak)/ 54(AV)
	H/V	74(Peak)/ 54(AV)
	88.10 (PK)	88.10 (PK) H 89.08 (PK) V H V H/V H/V H/V H/V H/V H/V H/V H/V

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

<sup>3.</sup> For 802.11g mode 54Mbps

Date: 2013-12-27



## Operation Mode: Transmitting under CH06 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2437.00	88.92 (PK)	Н	Fundamental Frequency
2437.00	88.72 (PK)	V	Fundamental Frequency
4874.00		Н	74(Peak)/ 54 AV)
4874.00		V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak / 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

#### Operation Mode: Transmitting under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)	
2462.00	88.81 (PK)	Н	Fundamental Frequency	
2462.00	88.06 (PK)	V	Fundamental Frequency	
4924	-	Н	74(Peak)/ 54(AV)	
4924	-	V	74(Peak)/ 54(AV)	
7368	-	H/V	74(Peak / 54 AV)	
9848	-	H/V	74(Peak)/ 54(AV)	
12310	-	H/V	74(Peak)/ 54(AV)	
14772		H/V	74(Peak)/ 54(AV)	
17234		H/V	74(Peak)/ 54(AV)	
19696	-1	H/V	74(Peak)/ 54(AV)	
22158		H/V	74(Peak)/ 54(AV)	
24620		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-12-27



Please refer to the following test plots for details:

# CH01 for 11g at 54Mbps: Horizontal



9500.00

11200.00

12900.00

14600.00

18000.00 MHz

#### CH01 for 11g at 54Mbps: Vertical


4400.00

6100.00

7800.00

7.0

1000.000 2700.00



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-12-27




# CH06 for 11g at 54Mbps: Vertical





# CH06 for 11g at 54Mbps: Horizontal

#### 107.0 dBuV/m




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-12-27



#### CH11 for 11g at 54Mbps: Vertical



# CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-12-27



## Operation Mode: Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2412.00	89.10 (PK)	Н	Fundamental Frequency
2412.00	88.58 (PK)	V	Fundamental Frequency
4824.00		Н	74(Peak)/ 54(AV)
4824.00		V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

#### Operation Mode: Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
2437.00	88.42 (PK)	Н	Fundamental Frequency
2437.00	88.72 (PK)	V	Fundamental Frequency
4874.00	-	Н	74(Peak)/ 54(AV)
4874.00	-	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496	-1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312137-01 Page 25 of 90

Date: 2013-12-27



## Operation Mode: Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2462.00	88.81 (PK)	Н	Fundamental Frequency
2462.00	88.56 (PK)	V	Fundamental Frequency
4924		Н	74(Peak)/ 54(AV)
4924		V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2013-12-27




Please refer to the following test plots for details:

## CH01 for 11b at 11Mbps: Horizontal



#### CH01 for 11b at 11Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2013-12-27



# CH06 for 11b at 11Mbps: Vertical



# CH06 for 11b at 11Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-12-27



## CH11 for 11b at 11Mbps: Vertical



# CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-12-27



## Operation Mode: Transmitting under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2412.00	88.11 (PK)	Н	Fundamental Frequency
2412.00	88.41 (PK)	V	Fundamental Frequency
4824.00		Н	74(Peak)/ 54(AV)
4824.00		V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

#### Operation Mode: Transmitting under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
2437.00	88.92 (PK)	Н	Fundamental Frequency
2437.00	89.47 (PK)	V	Fundamental Frequency
4874.00	-	Н	74(Peak)/ 54(AV)
4874.00	-	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496	-1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312137-01 Page 30 of 90

Date: 2013-12-27



## Operation Mode: Transmitting under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2462.00	88.53 (PK)	Н	Eundomontal Evoquenay
2462.00	88.96 (PK)	V	Fundamental Frequency
4924		Н	74(Peak)/ 54(AV)
4924		V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Date: 2013-12-27




Please refer to the following test plots for details:

# CH01 for 11n HT20 at 65Mbps: Horizontal



#### CH01 for 11n HT20 at 65Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-12-27



## CH06 for 11n HT20 at 65Mbps: Vertical



# CH06 for 11n HT20 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2013-12-27



# CH11 for 11n HT20 at 65Mbps: Vertical



#### CH11 for 11n HT20 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1312137-01 Page 34 of 90

Date: 2013-12-27



# 7.0 6dB Bandwidth Measurement

# 7.1 Test Setup



#### 7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

#### 7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Report No: 1312137-01 Page 35 of 90

Date: 2013-12-27



# 7.4 Test Result 6dB Occupied Bandwidth


EU	Γ	Tron Tab Mega Model Tab		Tron Tab Mega		Model		T4238
Mod	le	802.111	)	Input Voltage		DC3.7V		
Temper	ature	24 deg. (	C,	Humidit	y		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		num Limit MHz)	Pass/ Fail	
1		2412	1	10.08		0.5	Pass	
6		2437	1	10.08		0.5	Pass	
11		2462	1	10.08		0.5	Pass	
1		2412	11	8.70		0.5	Pass	
6		2437	11	8.70		0.5	Pass	
11		2462	11	8.70		0.5	Pass	

Report No: 1312137-01 Page 36 of 90

Date: 2013-12-27



## 1. 802.11b at 1Mbps of CH01




Date: 24.DEC.2013 15:38:16

Report No: 1312137-01 Page 37 of 90

Date: 2013-12-27



# 2. 802.11b at 1Mbps of CH06




Date: 24.DEC.2013 15:39:50

Report No: 1312137-01 Page 38 of 90

Date: 2013-12-27



# 3. 802.11b at 1Mbps of CH11




Date: 24.DEC.2013 15:40:44

Report No: 1312137-01 Page 39 of 90

Date: 2013-12-27



# 4. 802.11b at 11Mbps of CH01




Date: 24.DEC.2013 15:42:49

Report No: 1312137-01 Page 40 of 90

Date: 2013-12-27



# 5. 802.11b at 11Mbps of CH06




Date: 24.DEC.2013 15:42:09

Report No: 1312137-01 Page 41 of 90

Date: 2013-12-27



# 6. 802.11b at 11Mbps of CH11



Date: 24.DEC.2013 15:41:27

Report No: 1312137-01 Page 42 of 90

Date: 2013-12-27



# 6dB Occupied Bandwidth

EUT		Tron Tab Mega	on Tab Mega Model			T4238		
Mode		802.11g	Input Voltag	e		DC3.7V		
Temperate	ure	24 deg. C,	Humidity			56% RH		
Channel	Ch	nannel Frequency (MHz)	Data Transfer Rate (Mbps)	Baı	6 dB ndwidth MHz)	Minimum Limit (MHz)	Pass/ Fail	
1		2412	54	16.56		0.5	Pass	
6		2437	54	54 16.56		0.5	Pass	
11		2462	54		16.56	0.5	Pass	


Report No: 1312137-01 Page 43 of 90

Date: 2013-12-27



#### **Test Plots:**

# 1. 802.11g at 54Mbps of CH01




Date: 24.DEC.2013 15:43:53

Report No: 1312137-01 Page 44 of 90

Date: 2013-12-27



# 2. 802.11g at 54Mbps of CH06




Date: 24.DEC.2013 15:44:44

Report No: 1312137-01 Page 45 of 90

Date: 2013-12-27



# 3. 802.11g at 54Mbps of CH11



Date: 24.DEC.2013 15:45:53

Report No: 1312137-01 Page 46 of 90

Date: 2013-12-27



# 6dB Occupied Bandwidth

EU'	Γ	Tron Tab Mega			Model		T4238			
Mod	le	802.11n HT20			Input Vo	oltage		DC3.7V		
Temper	ature		24 deg. C,		Humi	dity		56% RH		
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)			Minimum Limit (MHz)		Pass/ Fail		
1		2412	65	17.76			0.5	Pass		
6		2437	65	17	17.76		17.76 0.5		0.5	Pass
11		2462	65	17	.76		0.5	Pass		


Report No: 1312137-01 Page 47 of 90

Date: 2013-12-27



#### **Test Plots:**

#### 1. 802.11n at HT20 of CH01




Date: 24.DEC.2013 15:49:27

Report No: 1312137-01 Page 48 of 90

Date: 2013-12-27



#### 2. 802.11n at HT20 of CH06




Date: 24.DEC.2013 15:48:36

Report No: 1312137-01 Page 49 of 90

Date: 2013-12-27



#### 3. 802.11n at HT20 of CH11



Date: 24.DEC.2013 15:47:18

Report No: 1312137-01


Date: 2013-12-27



Page 50 of 90

# 8. Maximum Peak Output Power

# 8.1 Test Setup



## 8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

#### **8.3 Test Procedure**

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: 1312137-01

Date: 2013-12-27



#### **8.4Test Results**

EUT		Tron Tab M	lega Model			T4238	
Mode		802.11b		Input Voltage		DC3.7V	
Temperat	Temperature 24 deg. C,		· ,	Humidity		4	56% RH
Channel	Cha	* *		ower Output		Peak Power Limit (dBm)	Pass/ Fail
1		2412		8.51		30	Pass
6		2437		8.56		30	Pass
11		2462		8.41		30	Pass

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	Tron Tab Mega	Model		T4238		
Mode	802.11g	Input Voltage		DC3.7V		
Temperature	e 24 deg. C,	Humidity		56% RH		
Channel	Channel Frequency	Channel Frequency Peak Power Output		Pass/ Fail		
Chamiei	(MHz)	(dBm)	(dBm)			
1	2412	6.55	30	Pass		
6	2437	6.53	30	Pass		
11	2462	6.50	30	Pass		

Note: 1. At finial test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Report No: 1312137-01 Page 52 of 90

Date: 2013-12-27



EUT		Tron Tab Mega		Model		T4238
Mode		802.11n (HT20) Input Voltage			DC3.7V	
Temperate	ure 24 deg. C, Humidity			56% RH		
Channel	Cha	annel Frequency (MHz)	Peak Power Output (dBm)		Peak Power Limit (dBm)	Pass/ Fail
1		2412		6.75	30	Pass
6		2437	6.74		30	Pass
11		2462		6.81	30	Pass

Note: 1. At finial test to get the worst-case emission at 65Mbps 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow: Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded


Report No: 1312137-01 Page 53 of 90

Date: 2013-12-27



# 9. Power Spectral Density Measurement

# 9.1 Test Setup



## 9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

#### 9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW  $\geq$  30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be  $\leq 8$  dBm.

Report No: 1312137-01 Page 54 of 90

Date: 2013-12-27



#### 9.4Test Result

EUT		Tron Tab Mega		ga Model		T4238	
Mode		802.11b 11Mbps		Input Voltage	e	DC3.7V	
Temperati	ure	re 24 deg. C, Humidity			56% RH		
Channel	Cha			RF Power vel (dBm)	Maximum Limit (dBm)	Pass/ Fail	
				11Mbps			
1		2412	2412 -		8	Pass	
6		2437		-16.32	8	Pass	
11		2462		-16.37	8	Pass	

EUT		Tron Tab Mega		Model		T4238	
Mode		802.11b 1Mbps Ir		Input Voltage		DC3.7V	
Temperat	ure	24 deg. C	deg. C, Humidity			56% RH	
Channel	Cha	annel Frequency (MHz)	* *		Maximum Limit (dBm)	Pass/ Fail	
				1Mbps			
1		2412	2412		8	Pass	
6		2437		-17.92	8	Pass	
11		2462		-18.11	8	Pass	

Report No: 1312137-01 Page 55 of 90

Date: 2013-12-27



EUT		Tron Tab Mega	Model Model		T4238	
Mode		802.11g	Input Voltage		DC3.7V	
Temperature	;	24 deg. C,	Humidity		56% RH	
Channel	Ch	annel Frequency (MHz)	Final RF Power Level (dBm)		Maximum Limit (dBm) Pass/ Fail	
			54Mbps			
1		2412	-23.93		8	Pass
6		2437	-23.97		8	Pass
11		2462	-24.02		8	Pass

EUT		Tron Tab Mega	Model		T4238		
Mode	Mode 802.11n HT20		Input Voltage		DC3.7V		
Temperat	ure	24 deg. C,	Humidity		56% RH		
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)	M	(dBm)	Pass/ Fail	
			65Mbps				
1		2412	-23.13		8	Pass	
6		2437	-23.49		8	Pass	
11		2462	-23.48		8	Pass	


Report No: 1312137-01 Page 56 of 90

Date: 2013-12-27



# 9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01




Date: 24.DEC.2013 16:01:52

Report No: 1312137-01 Page 57 of 90

Date: 2013-12-27



## 2. 802.11b at 11Mbps at CH06




Date: 24.DEC.2013 16:01:32

Report No: 1312137-01 Page 58 of 90

Date: 2013-12-27



## 3. 802.11b at 11Mbps of CH11




Date: 24.DEC.2013 16:01:13

Report No: 1312137-01 Page 59 of 90

Date: 2013-12-27



# 4. 802.11b at 1Mbps of CH1




Date: 24.DEC.2013 15:59:45

Report No: 1312137-01 Page 60 of 90

Date: 2013-12-27



# 5. 802.11b at 1Mbps of CH6




Date: 24.DEC.2013 16:00:15

Report No: 1312137-01 Page 61 of 90

Date: 2013-12-27



# 6. 802.11b at 1Mbps of CH11




Date: 24.DEC.2013 16:00:37

Report No: 1312137-01 Page 62 of 90

Date: 2013-12-27



# 7. 802.11g at 54Mbps of CH1




Date: 24.DEC.2013 16:02:31

Report No: 1312137-01 Page 63 of 90

Date: 2013-12-27



# 8. 802.11g at 54Mbps of CH6




Date: 24.DEC.2013 16:03:05

Report No: 1312137-01 Page 64 of 90

Date: 2013-12-27



# 9. 802.11g at 54Mbps of CH11




Date: 24.DEC.2013 16:03:31

Report No: 1312137-01 Page 65 of 90

Date: 2013-12-27



#### 10. 802.11n at HT20 of CH01




Date: 24.DEC.2013 16:05:11

Report No: 1312137-01 Page 66 of 90

Date: 2013-12-27



#### 11. 802.11n at HT20 of CH06




Date: 24.DEC.2013 16:04:37

Report No: 1312137-01 Page 67 of 90

Date: 2013-12-27



#### 12. 802.11n at HT20 of CH11



Date: 24.DEC.2013 16:04:07


Report No: 1312137-01 Page 68 of 90

Date: 2013-12-27



## 10 Out of Band Measurement

# 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

#### 10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### **10.3 Test Procedure**

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.( Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

## 10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position. the worse case was recorded

2. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Report No: 1312137-01

Date: 2013-12-27




# For 802.11b mode

## CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tron	Tab Mega	Model	T4238			
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:	Pass		Detector	PK			
2400	PK (dBµV/m)	46.50	T :	$74(dB\mu V/m)$			
2400	AV (dBμV/m)		Limit	$54(dB\mu V/m)$			
2200	PK (dBμV/m)	37.77	Limit	74(dBμV/m)			
2390	AV (dBμV/m)		Liffill	54(dBμV/m)			

#### **Test Figure:**



Date: 24.DEC.2013 15:58:36

Page 70 of 90

Report No: 1312137-01

Date: 2013-12-27




#### CH11 at 11Mbps

#### **10.4** Band-edge and Restricted band Measurement

EUT	Tron	Tab Mega	Model	T4238
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V
Temperature	24	4 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2492.5	PK (dBμV/m)	43.16	Limit	$74(dB\mu V/m)$
2483.5	AV (dBμV/m)	AV (dBμV/m)		$54(dB\mu V/m)$

## **Test Figure:**



Date: 24.DEC.2013 15:54:54

Report No: 1312137-01

Date: 2013-12-27




#### For 802.11b mode

# CH01 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tron	Tab Mega	Model	T4238					
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V					
Temperature	24 deg. C,		Humidity	56% RH					
Test Result:	Pass		Detector	PK					
2400	PK (dBµV/m)	45.05	T ::4	$74(dB\mu V/m)$					
2400	AV (dBμV/m)		Limit	54(dBμV/m)					
2200	PK (dBμV/m)	36.88	Limit	74(dBμV/m)					
2390	AV (dBμV/m)		Liffill	54(dBμV/m)					

#### **Test Figure:**



Date: 24.DEC.2013 15:59:02

Page 72 of 90

Report No: 1312137-01

Date: 2013-12-27




## CH11 at 1Mbps

#### **10.4** Band-edge and Restricted band Measurement

EUT	Tron Tab Mega		Model	T4238
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	43.61	Limit	74(dBμV/m)
	AV (dBμV/m)			54(dBμV/m)

# **Test Figure:**



Date: 24.DEC.2013 15:54:28

Page 73 of 90

Report No: 1312137-01

Date: 2013-12-27




## For 802.11g mode

## CH01 at 54Mbps

10.4 Band-edge and Restricted band Measurement

2 min 4 ago and 1 control out a 11 control of the 11 control of th					
EUT	Tron Tab Mega		Model	T4238	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:	Pass		Detector	PK	
2400	PK (dBμV/m)	44.01	Limit	$74(dB\mu V/m)$	
	AV (dBμV/m)			54(dBμV/m)	
2390	PK (dBμV/m)	37.18	Limit	74(dBμV/m)	
	AV (dBμV/m)			54(dBμV/m)	

### **Test Figure:**



Date: 24.DEC.2013 15:57:41

Note: The Max. FS in Restrict Band are measured in conventional method.

Page 74 of 90

Report No: 1312137-01

Date: 2013-12-27




### CH11 at 54Mbps

### **10.4** Band-edge and Restricted band Measurement

EUT	Tron Tab Mega		Model	T4238
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	43.43	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			$54(dB\mu V/m)$

### **Test Figure:**



Date: 24.DEC.2013 15:55:54

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2013-12-27




### For 802.11n (HT20) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tron Tab Mega		Model	T4238	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:	Pass		Detector	PK	
2400	PK (dBμV/m)	43.31	Limit	$74(dB\mu V/m)$	
	AV (dBμV/m)			54(dBμV/m)	
2390	PK (dBμV/m)	37.90	Limit	74(dBμV/m)	
	AV (dBμV/m)			54(dBμV/m)	

### **Test Figure:**



Date: 24.DEC.2013 15:56:59

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 76 of 90

Report No: 1312137-01

Date: 2013-12-27




### CH11 at 65Mbps

### **10.4** Band-edge and Restricted band Measurement

EUT	Tron Tab Mega		Model	T4238
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	42.96	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			54(dBμV/m)

### **Test Figure:**



Date: 24.DEC.2013 15:55:54

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2013-12-27



Page 77 of 90

## 11.0 Antenna Requirement

## 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

### 11.2 Antenna Connected construction

Integral Antenna used. The maximum Gain of the antennas is 2.0dBi.

Report No: 1312137-01 Page 78 of 90

Date: 2013-12-27




### 12.0 FCC ID Label

**FCC ID: 2AAY2-T4238** 

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### Mark Location:



Report No: 1312137-01 Page 79 of 90

Date: 2013-12-27



## 13.0 Photo of testing

Conducted Emission Test Setup:



Page 80 of 90

Report No: 1312137-01

Date: 2013-12-27



# Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 81 of 90

Report No: 1312137-01

Date: 2013-12-27



### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 82 of 90

Report No: 1312137-01

Date: 2013-12-27



### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 83 of 90

Report No: 1312137-01 Date: 2013-12-27



### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 84 of 90

Report No: 1312137-01

Date: 2013-12-27



## Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2013-12-27



## Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 86 of 90

Report No: 1312137-01

Date: 2013-12-27



## Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 87 of 90


Report No: 1312137-01

Date: 2013-12-27



## Photo for the EUT






The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 88 of 90

Report No: 1312137-01 Date: 2013-12-27

## Photo for the EUT






The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

Date: 2013-12-27



## Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312137-01 Page 90 of 90

Date: 2013-12-27



## Photo for the EUT



End of the report