







### ISO/IEC17025 Accredited Lab.

Report No: FCC 1312137-03

File reference No: 2014-01-15

Applicant: TD Semi,Inc.

Product: Tron Tab Mega

Model No: T4238

Trademark: N/A

Test Standards: FCC Part 15 Subpart B: 2012

Test result: It is herewith confirmed and found to comply with the requirements

set up by ANSI C63.4&FCC Part 15 regulations for the evaluation of

electromagnetic compatibility

Approved By

# Jack Chung

Jack Chung

Manager

Dated: Jan 15, 2014

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. Chegongmiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1312137-03 Page 2 of 17

Date: 2014-01-15



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

#### **CNAS-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

# IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.



Date: 2014-01-15



# **Test Report Conclusion**

#### Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Test Uncertainty	4
1.5	Submitted Sample	4
1.6	Test Duration.	4
2.0	List of Measurement Equipment.	5
2.1	Conducted Emission Test.	5
2.2	Radiated electromagnetic disturbance test.	5
2.3	Auxiliary Equipment.	5
3.0	Technical Details	6
3.1	Investigations Requested.	6
3.2	Test Standards.	6
4.0	Power line Conducted Emission Test.	7
5.0	Radiated Disturbance Test.	11



#### 1.0 General Details

Date: 2014-01-15

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian

District, Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

1.2 Applicant Details

Applicant: TD Semi, Inc.

Address: 3704 Marlborough Ct., Plano, TX 75075, USA

Telephone: (972) 346-1201 Fax: (972) 810-4326

1.3 Description of EUT

Product: Tron Tab Mega

Manufacturer: Shenzhen Jizhao Information Technology Co., Ltd

Address: 4th Floor, Yuxing Sanwei Tech Park, HangKong Road, Xixiang Town,

Bao'an, Shenzhen, China.

Brand Name: N/A
Model Number: T4238
Additional Model Number: N/A

1.4 Submitted Sample: 2 Sample

1.5 Test Duration: 2014-01-04 to 2014-01-14

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

The sample tested by

Teng Tang

Print Name: Terry Tong

Date: 2014-01-15



#### List of Measurement Equipment 2.0

#### 2.1 Conducted Emission Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESH3	860905/006	RS	2013-08-23	1Year
Spectrum Analyzer	ESA-L1500A	US37451154	HP	2013-08-23	1Year
PULSE LIMITER	ESH3-Z2	100281	RS	2013-08-23	1Year
LISN	ESH3-Z5	100294	RS	2013-08-23	1Year
LISN	ESH3-Z5	100253	RS	2013-08-23	1Year
LISN	LS16C	10010947251	AFJ	2013-08-23	1Year
LISN (Three Phase)	NSLK 8126	8126453	Schwarebeck	2013-08-23	1Year

#### 2.2 Radiated electromagnetic disturbance test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESVD	100008	RS	2013-08-23	1Year
Coaxial Switch	MP59B	M70585	ANRITSU	2013-08-23	1Year
Test Receiver	ESI26	838786/013	RS	2013-08-23	1Year
Amplifier	8447D	2727A05017	HP	2013-07-24	1Year
Bilog Antenna	VULB9163	9163/340	Schwarebeck	2013-08-24	1Year
Horn Antenna	BBHA 9120D	9120D-631	Schwarebeck	2013-08-23	1Year

#### 2.3 **Auxiliary Equipment**

					FCC DOC/
Name	Model No.	Serial No.	Manufacturer	Cable	ID
U-disk	U208		Netac		FCC DOC
SD			Kingston		
PC	R400		IBM		FCC DOC
Mouse	M-F105		L.SEletron		FCC DOC
TF					
Monitor	IN1920c		DELL		DOC

Report No: 1312137-03 Page 6 of 17

#### 3.0 **Technical Details**

Date: 2014-01-15

3.1 Investigations Requested Perform Electromagnetic Interference [EMI] tests for FCC Requirement.

3.2 Test Standards


FCC Part 15 Subpart B: 2012

Date: 2014-01-15



#### 4.0 Conducted Power line Test

#### 4.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 4.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2009. Cables and peripherals were moved to find the maximum emission levels for each frequency.

Actual Working Voltage and Frequency: 120V~, 60Hz

Block diagram of Test setup



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1312137-03 Page 8 of 17

Date: 2014-01-15



#### 4.3 Power line conducted Emission Limit

Eraguanay (MUz)	Class A Limits dB(μV)		Class B Limits dB(µV)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
0.15 ~ 0.50	79.00	66.00	66.00~56.00*	56.00~46.00*	
0.50 ~ 5.00	73.00	60.00	56.00	46.00	
5.00 ~ 30.00	73.00	60.00	60.00	50.00	

Notes: 1. \*decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

### 4.4 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2014-01-15



### A: Conducted Emission on Live Terminal (150kHz to 30MHz)

#### **EUT Operating Environment**


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: data communicate with PC by USB port

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



Frequency	Line	Reading(dBµV)		Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.270	Live	45.24	30.18	61.11	51.11
0.436	Live	39.55	24.00	57.14	47.14
9.045	Live	41.81	30.91	60.00	50.00

Date: 2014-01-15



### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

### **EUT Operating Environment**


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: data communicate with PC by USB port

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



Frequency	Lina	Line Reading(dBµV)		Limit(dBμV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.277	Neutral	43.61	27.44	60.88	50.91
0.443	Neutral	40.51	24.73	57.01	47.01
9.013	Neutral	34.72	29.67	60.00	50.00


Report No: 1312137-03 Page 11 of 17

Date: 2014-01-15



#### 5.0 Radiated Disturbance Test

#### 5.1 Schematics of the test




#### 5.2 Test Method and test Procedure:

The EUT was tested according to ANSI C63.4 –2009; The frequency spectrum from 30MHz to 18GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. For measurement above 1GHz, peak values with RBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector


Actual Working Voltage and Frequency: 120V~, 60Hz

## **Block diagram of Test setup**



Date: 2014-01-15





#### 5.3 Radiated Emission Limit

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.00
88-216	3	43.50
216-960	3	46.00
Above 960	3	54.00

Note: 1. The lower limit shall apply at the transition frequencies

2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

#### 5.4 Test result

The frequency spectrum from 30MHz to 18GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1312137-03 Page 13 of 17

Date: 2014-01-15



#### Test result

#### General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

**EUT set Condition:** data communicate with PC by USB port

**Results:** Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
63.720	32.88	Н	40.00
127.280	40.13	Н	43.50
159.080	35.80	Н	43.50
445.520	42.32	Н	46.00
63.640	33.69	V	40.00
95.400	34.26	V	43.50
158.960	30.05	V	43.50
445.560	43.86	V	46.00


Page 14 of 17

Report No: 1312137-03

Date: 2014-01-15



### Test Figure:



Date: 13.JAN.2014 15:54:40


Page 15 of 17

Report No: 1312137-03

Date: 2014-01-15



### Test Figure:



Date: 13.JAN.2014 15:50:35

Date: 2014-01-15



### Radiated Disturbance (1000MHz----18000MHz)

### **EUT Operating Environment**


Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: data communicate with PC by USB port

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
3044.088	48.96 (PK)	Н	54(AV)
4270.541	50.26 (PK)	Н	54(AV)

Note: Due to the final PK measurement level much less than the AV limit, so no necessary to take down final AV measurement level.

Date: 2014-01-15



### Radiated Disturbance (1000MHz----18000MHz)

#### **EUT Operating Environment**


Temperature:25 ℃ Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: data communicate with PC by USB port

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



Frequency (M	IHz)	Level@3m (dBμV/m)	Antenna Polarity	Limit@3m (dBµV/m)
4543.086		49.01 (PK)	V	54(AV)
5428.858		49.41 (PK)	V	54(AV)

Note: Due to the final PK measurement level much less than the AV limit, so no necessary to take down final AV measurement level.

#### -- End of the Report--