TEST REPORT

of

FCC Part 15 Subpart C §15.247/RSS-201 Issue 8, RSS-Gen Issue 3

FCC ID / IC Certification: 2AAZ2-MVB-100 / 11410A-MVB100

Equipment Under Test	:	T4F Bluetooth Keypad
Model Name	:	MVB-100
Serial No.	:	N/A
Applicant	:	Metis Communication Co., Ltd.
Manufacturer	:	Metis Communication Co., Ltd.
Date of Test(s)	:	2013.09.26 ~ 2013.11.05
Date of Issue	:	2013.11.12

In the configuration tested, the EUT complied with the standards specified above.

Tested By: **Alvin Kim** **Date:** **2013.11.12**

Approved By: **Feel Jeong** **Date:** **2013.11.12**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

Table of Contents Page

1. General Information ---------- 3

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission ------ 7

3. 20㏈ Bandwidth and 99% BW---------- 48

4. Maximum Peak Output Power ---------- 75

5. Hopping Channel Separation ---------- 78

6. Number of Hopping Frequency ---------- 82

7. Time of Occupancy(Dwell Time) ---------- 88

8 Antenna Requirement ---------- 107

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)
- Wireless Div. 3FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 428 5700
FAX : +82 31 427 2371

1.2. Details of Applicant

Applicant : Metis Communication Co., Ltd.
Address : #102-805 Digital Empire2, 486 Sin-Dong, YeongTong-Gu, Suwon-Si, GyeongGi-Do Korea 443-734
Contact Person : Kim, Chang-Woo
Phone No. : + 82 31 695 5767

1.3. Description of EUT

Kind of Product	T4F Bluetooth Keypad
Model Name	MVB-100
Serial Number	N/A
Power Supply	DC 12 V / 24V (Vehicle battery)
Frequency Range	2 402 ㎒ ~ 2 480 ㎒ (BT)
Modulation Technique	GFSK, π/4DQPSK, 8DPSK
Number of Channels	79
Antenna Type	Internal type
Antenna Gain	1.99 ㏈i

1.4. Declaration by the manufacturer

- Adaptive Frequency Hopping is supported and use at least 20 channels

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.5. Information about the FHSS characteristics:

1.5.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

1.5.2. Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

1.5.3. System Receiver Input Bandwidth

Each channel bandwidth is 1 ㎒

1.5.4. Equipment Description

15.247(a)(1) that the rx input bandwidths shift frequencies in synchronization with the transmitted

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate it channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.6. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal Date	Cal Interval	Cal Due.
Signal Generator	R&S	SMBV100A	255834	Jun. 26, 2013	Annual	Jun. 26, 2014
Signal Generator	R&S	SMR40	100272	Aug. 10, 2013	Annual	Aug. 10, 2014
Spectrum Analyzer	Agilent	N9030A	US51350132	Oct. 08, 2013	Annual	Oct. 08, 2014
Spectrum Analyzer	Agilent	E4440A	MY43362142	Mar. 28, 2013	Annual	Mar. 28, 2014
Spectrum Analyzer	R&S	FSV30	100955	Mar. 28, 2013	Annual	Mar. 28, 2014
Bluetooth Tester	TESCOM	TC-3000C	3000C000142	Dec. 24, 2012	Annual	Dec. 24, 2013
Directional Coupler	KRYTAR	152613	122660	Jun. 07, 2013	Annual	Jun. 07, 2014
High Pass Filter	Wainwright	WHK3.0/18G-10SS	344	Jun. 08, 2013	Annual	Jun. 08, 2014
High Pass Filter	Wainwright	WHK7.5/26.5G-6SS	11	Jun. 08, 2013	Annual	Jun. 08, 2014
Low Pass Filter	Mini circuits	NLP-1200+	V8979400903-2	Mar. 30, 2013	Annual	Mar. 30, 2014
Power Sensor	R&S	NRP-Z81	100669	Apr. 05. 2013	Annual	Apr. 05. 2014
DC Power Supply	Agilent	U8002A	MY50060028	Mar. 28, 2013	Annual	Mar. 28, 2014
Preamplifier	H.P.	8447F	2944A03909	Jun. 28, 2013	Annual	Jun. 28, 2014
Preamplifier	R&S	SCU 18	10117	Jan. 14, 2013	Annual	Jan. 14, 2014
Preamplifier	MITEQ Inc.	JS44-18004000-35-8P	1546891	Jun. 13, 2013	Annual	Jun. 13, 2014
Test Receiver	R&S	ESU26	100109	Feb. 28, 2013	Annual	Feb. 28, 2014
Loop Antenna	R&S	HFH2-Z2	100118	Jul. 12, 2013	Biennial	Jul. 12, 2015
Bilog Antenna	SCHWARZBECK MESSELEKTRONIK	VULB9163	396	Jun. 07, 2013	Biennial	Jun. 07, 2015
Horn Antenna	R&S	HF906	100326	Nov. 23, 2011	Biennial	Nov. 23, 2013
Horn Antenna	SCHWARZBECK MESSELEKTRONIK	BBHA9170	BBHA9170431	May 15, 2012	Biennial	May 15, 2014
Antenna Master	INN-CO	MM4000	N/A	N.C.R.	N/A	N.C.R.
Turn Table	INN-CO	DS 1200S	N/A	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD:FCC Part15 subpart C, RSS-210, RSS-Gen			
Section in FCC 15	**Section in RSS-210**	**Test Item**	**Result**
15.205(a) 15.209 15.247(d)	RSS-210 A8.5	Transmitter Radiated Spurious Emissions Conducted Spurious Emission	Complied
15.247(a)(1)	RSS-210 A8.1(a) RSS-Gen 4.6.1	20 dB Bandwidth and 99% BW	Complied
15.247(b)(1)	RSS-210 A8.4(2)	Maximum Peak Output Power	Complied
15.247(a)(1)	RSS-210 A8.1(b)	Frequency Separation	Complied
15.247(a)(1)(iii)	RSS-210 A8.4(2)	Number of Hopping Frequency	Complied
15.247(a)(1)(iii)	RSS-210 A8.1(d)	Time of Occupancy (Dwell Time)	Complied

1.8. Sample calculation

Where relevant, the following sample calculation is provided:

1.8.1. Conducted test

Offset value (dB) = Directional Coupler(dB) + Cable loss (dB)

1.8.2. Radiation test

Field strength level (dBμV/m) = Measured level (dBμV) + Antenna factor (dB) + Cable loss (dB) – amplifier gain (dB)

1.9. Test report revision

Revision	Report number	Description
0	F690501/RF-RTL007016	Initial
1	F690501/RF-RTL007016-1	Retest due to power class change

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

2.1. Test Setup

2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission .The spurious emissions were investigated form 1 ㎓ to the 10th harmonic of the highest fundamental frequency or 40 ㎓, whichever is lower.



2.1.2. Conducted Spurious Emissions



2.2. Limit

According to §15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement , provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table：

Frequency (㎒)	Distance (Meters)	Field Strength (㏈μV/m)	Field Strength (μV/m)
30 - 88	3	40.0	100
88 – 216	3	43.5	150
216 – 960	3	46.0	200
Above 960	3	54.0	500

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of DA000705 and ANSI 63.4 2003

2.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 ㎓, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 ㎓, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 ㏈ lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 ㏈ margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE ;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 ㎑ for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 ㎓.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 ㎒ for Peak detection and frequency above 1 ㎓.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 ㎒ and the video bandwidth is $1/T_{on}$ ㎐ (T_{on} = On-time of the Pulsed emission) for Average detection (AV) at frequency above 1 ㎓.
4. When Average result is different from peak result over 20 dB (over-averaging), According to 15.35 (c), as a “duty cycle correction factor”, pulse averaging with 20 log(duty cycle) has to be used.
5. To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3.2. Test Procedures for Conducted Spurious Emissions

NOTE ;

All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

2.3.2.1. Band-edge Compliance of RF Conducted Emissions

The transmitter output was connected to the spectrum analyzer.
Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.
RBW ≥ 100 ㎑
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.3.2.2. Spurious RF Conducted Emissions

The transmitter output was connected to the spectrum analyzer.
RBW = 100 ㎑
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4. Test Results

Ambient temperature : (23 ± 1)℃
Relative humidity : 47 % R.H.

2.4.1. Spurious Radiated Emission (Worst case configuration_ GFSK mode, 1 Mbps, Middle channel)

The frequency spectrum from 9 ㎑ to 1 000 ㎒ was investigated. Emission levels are not reported much lower than the limits by over 30 ㏈. All reading values are peak values.

DC 12V

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (㏈㎶)	Detect Mode	Pol.	AF (㏈/m)	AMP + CL (㏈)	Actual (㏈㎶/m)	Limit (㏈㎶/m)	Margin (㏈)
44.27	33.83	Peak	H	14.67	-26.80	21.70	40.00	18.30
59.22	34.78	Peak	H	13.04	-26.62	21.20	40.00	18.80
368.57	32.97	Peak	V	16.08	-25.05	24.00	46.00	22.00
Above 400.00	Not detected	-	-	-	-	-	-	-

DC 24V

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (㏈㎶)	Detect Mode	Pol.	AF (㏈/m)	AMP + CL (㏈)	Actual (㏈㎶/m)	Limit (㏈㎶/m)	Margin (㏈)
53.16	33.85	Peak	H	14.03	-26.68	21.20	40.00	18.80
97.54	34.11	Peak	H	12.18	-26.29	20.00	43.50	23.50
272.82	33.33	Peak	V	13.71	-24.94	22.10	46.00	23.90
860.08	33.01	Peak	V	22.61	-24.32	31.30	46.00	14.70
Above 900.00	Not detected	-	-	-	-	-	-	-

Remark:

1. All spurious emissions at channels are almost the same below 1 ㎓, so that middle channel was chosen at representative in final test.
2. Actual = Reading + AF + AMP + CL

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4.2. Spurious Radiated Emission

The frequency spectrum above 1 000 ㎒ was investigated. Emission levels are not reported much lower than the limits by over 30 ㏈.

DC 12V
Operating Mode: GFSK(1 Mbps)

A. Low Channel (2 402 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (㏈㎶)	Detect Mode	Pol.	AF (㏈/m)	CL (㏈)	Actual (㏈㎶/m)	Limit (㏈㎶/m)	Margin (㏈)
*2 390.00	23.48	Peak	H	28.05	6.67	58.20	74.00	15.80
*2 390.00	12.87	Average	H	28.05	6.67	47.59	54.00	6.41
Above 2 400.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (㏈㎶)	Detect Mode	Pol.	AF (㏈/m)	AMP+CL (㏈)	Actual (㏈㎶/m)	Limit (㏈㎶/m)	Margin (㏈)
*4 804.07	50.34	Peak	H	32.28	-33.71	48.91	74.00	25.09
*4 804.07	47.94	Average	H	32.28	-33.71	46.51	54.00	7.49
Above 4 900.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

B. Middle Channel (2 441 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 882.09	48.19	Peak	H	32.85	-33.25	47.79	74.00	26.21
*4 882.09	39.34	Average	H	32.85	-33.25	38.94	54.00	15.06
Above 4 900.00	Not detected	-	-	-	-	-	-	-

C. High Channel (2 480 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 483.50	23.40	Peak	H	28.31	6.87	58.58	74.00	15.42
*2 483.50	13.34	Average	H	28.31	6.87	48.52	54.00	5.48
Above 2 500.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 959.87	44.64	Peak	H	33.31	-32.93	45.02	74.00	28.98
*4 959.87	37.39	Average	H	33.31	-32.93	37.77	74.00	36.23
Above 5 000.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK(3 Mbps)

A. Low Channel (2 402 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 390.00	23.74	Peak	H	28.05	6.67	58.46	74.00	15.54
*2 390.00	12.92	Average	H	28.05	6.67	47.64	54.00	6.36
Above 2 400.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 804.21	46.42	Peak	H	32.28	-33.71	44.99	74.00	29.01
*4 804.21	38.08	Average	H	32.28	-33.71	36.65	54.00	17.35
Above 4 900.00	Not detected	-	-	-	-	-	-	-

B. Middle Channel (2 441 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 881.81	43.93	Peak	H	32.85	-33.25	43.53	74.00	30.47
*4 881.81	30.88	Average	H	32.85	-33.25	30.48	54.00	23.52
Above 4 900.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

C. High Channel (2 480 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 483.50	23.92	Peak	H	28.31	6.87	59.10	74.00	14.90
*2 483.50	13.08	Average	H	28.31	6.87	48.26	54.00	5.74
Above 2 500.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 959.93	41.25	Peak	H	33.31	-32.93	41.63	74.00	32.37
*4 959.93	29.85	Average	H	33.31	-32.93	30.23	54.00	23.77
Above 5 000.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK(1 Mbps)

A. Low Channel (2 402 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 390.00	24.70	Peak	V	28.05	6.67	59.42	74.00	14.58
*2 390.00	12.77	Average	V	28.05	6.67	47.49	54.00	6.51
Above 2 400.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 804.09	49.85	Peak	V	32.28	-33.71	48.42	74.00	25.58
*4 804.09	47.11	Average	V	32.28	-33.71	45.68	54.00	8.32
Above 4 900.00	Not detected	-	-	-	-	-	-	-

B. Middle Channel (2 441 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 881.96	46.16	Peak	V	32.85	-33.25	45.76	74.00	28.24
*4 881.96	38.00	Average	V	32.85	-33.25	37.60	54.00	16.40
Above 4 900.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

C. High Channel (2 480 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 483.50	24.49	Peak	V	28.31	6.87	59.67	74.00	14.33
*2 483.50	13.26	Average	V	28.31	6.87	48.44	54.00	5.56
Above 2 500.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 959.73	46.89	Peak	V	33.31	-32.93	47.27	74.00	26.73
*4 959.73	40.02	Average	V	33.31	-32.93	40.40	54.00	13.60
Above 5 000.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK(3 Mbps)

A. Low Channel (2 402 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 390.00	25.26	Peak	V	28.05	6.67	59.98	74.00	14.02
*2 390.00	12.80	Average	V	28.05	6.67	47.52	54.00	6.48
Above 2 400.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 803.97	46.42	Peak	V	32.28	-33.71	44.99	74.00	29.01
*4 803.97	37.18	Average	V	32.28	-33.71	35.75	54.00	18.25
Above 4 900.00	Not detected	-	-	-	-	-	-	-

B. Middle Channel (2 441 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 882.11	42.70	Peak	V	32.85	-33.25	42.30	74.00	31.70
*4 882.11	30.22	Average	V	32.85	-33.25	29.82	54.00	24.18
Above 4 900.00	Not detected	-	-	-	-	-	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

C. High Channel (2 480 ㎒)

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*2 483.50	23.79	Peak	V	28.31	6.87	58.97	74.00	15.04
*2 483.50	13.07	Average	V	28.31	6.87	48.25	54.00	5.75
Above 2 500.00	Not detected	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (㎒)	Reading (dB㎶)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
*4 959.70	42.11	Peak	V	33.31	-32.93	42.49	74.00	31.51
*4 959.70	30.56	Average	V	33.31	-32.93	30.94	54.00	23.06
Above 5 000.00	Not detected	-	-	-	-	-	-	-

Remarks:

1. "*" means the restricted band.
2. Measuring frequencies from 1 ㎓ to the 10th harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 ㎒ were made with an instrument using peak/average detector mode.
4. Average test would be performed if the peak result were greater than the average limit.
5. Actual = Reading + AF + AMP + CL

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4.3. Spurious RF Conducted Emissions: Plot of Spurious RF Conducted Emission

DC 12V
Operating Mode: GFSK(1 Mbps)

Low Channel





Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Band edge at Hopping



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode : 8DPSK(3 Mbps)

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel





Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Band edge at Hopping



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK(1 Mbps)

Low Channel





Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel





Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Band edge at Hopping



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode : 8DPSK(3 Mbps)

Low Channel





Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Band edge at Hopping



Note:
Offset (dB) = Directional Coupler(dB) + Cable loss (dB)
All offset values from 30 MHz to 26.5 GHz were compensated to spectrum analyzer as TDF function.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. 20 ㏈ Bandwidth Measurement and 99% BW

3.1. Test Setup



3.2. Limit

Limit: Not Applicable

3.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

The test follows DA000705.
The 20 ㏈ band width was measured with a spectrum analyzer connected to RF antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

Use the following spectrum analyzer setting :

Span = approximately 2 to 3 times the 20 ㏈ bandwidth, centered on a hopping channel.
RBW = greater than 1 % of the 20 ㏈ bandwidth
VBW ≥ RBW
Sweep = auto
Detector = peak
Trace = max hold

The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 ㏈ down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is 20 ㏈ bandwidth of the emission.

3.3.2. 99% Bandwidth

Set the spectrum analyzer as SPAN = 2 or 3 times necessary bandwidth, RBW = approximately 1 % of the SPAN, VBW is set to 3 times RBW, Detector = sampling, Trace mode = max hold.
Measure lowest and highest frequencies are placed in a running sum until 0.5 % and 99.5 % of the total is reached.
Record the SPAN between the lowest and the highest frequencies for the 99 % occupied bandwidth.
Repeat until all the test channels are investigated.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.4. Test Results

Ambient temperature : (23 ± 1) ℃
Relative humidity : 47 % R.H.

DC 12V

Operation Mode	Data Rate	Channel	Channel Frequency (㎒)	20 ㏈ Bandwidth(㎒)	99 % Bandwidth(㎒)
GFSK	1 Mbps	Low	2 402	0.930	0.869
		Middle	2 441	0.930	0.851
		High	2 480	0.925	0.853
π/4DQPSK	2 Mbps	Low	2 402	1.305	1.187
		Middle	2 441	1.260	1.181
		High	2 480	1.310	1.185
8DPSK	3 Mbps	Low	2 402	1.280	1.185
		Middle	2 441	1.265	1.176
		High	2 480	1.265	1.175

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V

Operation Mode	Data Rate	Channel	Channel Frequency (㎒)	20 ㏈ Bandwidth(㎒)	99 % Bandwidth(㎒)
GFSK	1 Mbps	Low	2 402	0.920	0.866
		Middle	2 441	0.935	0.870
		High	2 480	0.915	0.855
π/4DQPSK	2 Mbps	Low	2 402	1.270	1.179
		Middle	2 441	1.255	1.171
		High	2 480	1.250	1.181
8DPSK	3 Mbps	Low	2 402	1.265	1.186
		Middle	2 441	1.265	1.187
		High	2 480	1.265	1.179

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
20 dB Bandwidth

Operating Mode: GFSK
Low Channel



Middle Channel



High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: π/4DQPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

99 % Bandwidth

Operating Mode: GFSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: π/4DQPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
20 dB Bandwidth

Operating Mode: GFSK
Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: π/4DQPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

99 % Bandwidth

Operating Mode: GFSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: π/4DQPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode: 8DPSK

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. Maximum Peak Output Power Measurement

4.1. Test Setup



4.2. Limit

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.
2. §15.247(b)(1), For frequency hopping systems operating in the 2 400 – 2 483.5 ㎒ employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 – 5 805 ㎒ band: 1 Watt.

4.3. Test Procedure

All data rates and modes were investigated for this test. The test follows DA000705. Using the power sensor instead of a spectrum analyzer.

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
3. Test program : (S/W name : R&S Power Viewer, Version : 3.2.0)
4. Measure peak & average power each channel.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4.4. Test Results

Ambient temperature : (23 ± 1) ℃
Relative humidity : 47 % R.H.

DC 12V

Operation Mode	Data Rate	Channel	Channel Frequency (㎒)	Attenuator + Cable offset (㏈)	Average Power Result (㏈m)	Peak Power Result (㏈m)	Peak Power Limit (㏈m)
GFSK	1 Mbps	Low	2 402	16.40	-0.15	3.56	30.00
		Middle	2 441	16.41	-1.71	2.27	30.00
		High	2 480	16.38	-2.85	1.22	30.00
π/4DQPSK	2 Mbps	Low	2 402	16.40	-1.73	3.65	20.97
		Middle	2 441	16.41	-3.42	2.20	20.97
		High	2 480	16.38	-4.74	1.06	20.97
8DPSK	3 Mbps	Low	2 402	16.40	-1.71	3.71	20.97
		Middle	2 441	16.41	-3.43	2.30	20.97
		High	2 480	16.38	-4.71	1.23	20.97

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V

Operation Mode	Data Rate	Channel	Channel Frequency (㎒)	Attenuator + Cable offset (㏈)	Average Power Result (㏈m)	Peak Power Result (㏈m)	Peak Power Limit (㏈m)
GFSK	1 Mbps	Low	2 402	16.40	-0.18	3.48	30.00
		Middle	2 441	16.41	-1.64	2.12	30.00
		High	2 480	16.38	-2.88	1.20	30.00
π/4DQPSK	2 Mbps	Low	2 402	16.40	-1.77	3.55	20.97
		Middle	2 441	16.41	-3.47	2.15	20.97
		High	2 480	16.38	-4.74	1.05	20.97
8DPSK	3 Mbps	Low	2 402	16.40	-1.73	3.73	20.97
		Middle	2 441	16.41	-3.46	2.26	20.97
		High	2 480	16.38	-4.77	1.23	20.97

Remark:
In the case of AFH, the limit for peak power is 0.125 W

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5. Hopping Channel Separation

5.1. Test Setup



5.2. Limit

§15.247(a)(1) Frequency hopping system operating in 2 400 – 2 483.5 ㎒. Band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-third of 20 ㏈ bandwidth of the hopping channel, whichever is is greater, provided the systems operate with an output power no greater than 125 ㎽.

5.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section. The test follows DA000705.

The device is operating in hopping mode between 79 channels and also supporting Adaptive Frequency Hopping with hopping between 20 channels. As compared with each operating mode, 79 channels are chosen as a representative for test.
Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels.
RBW = 1 % of the span.
VBW = RBW
Sweep = auto
Detector = peak
Trace = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the between the peaks of the adjacent channels.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5.4. Test Results

Ambient temperature : (23 ± 1) ℃
Relative humidity : 47 % R.H.

DC 12V

Operation Mode	Channel (Middle)	Adjacent Hopping Channel Separation (㎑)	Two-third of 20 ㏈ Bandwidth (㎑)	Minimum Bandwidth (㎑)
GFSK	2 441 ㎒	1 000	0.620	25
8DPSK	2 441 ㎒	1 000	0.843	25

DC 24V

Operation Mode	Channel (Middle)	Adjacent Hopping Channel Separation (㎑)	Two-third of 20 ㏈ Bandwidth (㎑)	Minimum Bandwidth (㎑)
GFSK	2 441 ㎒	1 000	0.623	25
8DPSK	2 441 ㎒	1 000	0.843	25

Note;
Measurement is made with EUT operating in hopping mode between 79 channels providing a worse case scenario as compared to AFH mode hopping between 20 channels.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6. Number of Hopping Frequency

6.1. Test Setup



6.2. Limit

§15.247(a)(1)(iii), Frequency hopping systems in the 2 400–2 483.5 ㎒ band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

6.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section. The test follows DA000705.

The device supports Adaptive Frequency Hopping and will use a minimum of 20 channels of the 79 available channels.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna the port to the Spectrum analyzer
3. Set spectrum analyzer Start = 2 400 ㎒, Stop = 2 441.5 ㎒, Sweep=sweep and Start = 2 441.5 ㎒, Stop = 2 483.5 ㎒, Sweep = sweep. Detector = peak.
4. Set the spectrum analyzer as RBW, VBW = 500 ㎑.
5. Max hold, allow the trace to stabilize and count how many channel in the band.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.4. Test Results

Ambient temperature : (23 ± 1) ℃
Relative humidity : 47 % R.H.

DC 12V / DC 24V

Operation Mode	Number of Hopping Frequency	Limit
GFSK	79	≥ 15
8DPSK	79	≥ 15

Remark:
Measurement is made with EUT operating in hopping mode between 79 channels providing a worse case scenario as compared to AFH mode hopping between 20 channels.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode : 8DPSK





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Operating Mode : 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

7. Time of Occupancy (Dwell Time)

7.1. Test Set up



7.2. Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2 400 – 2 483.5 ㎒ band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

A period time = 0.4(s) * 79 = 31.6(s)

***Adaptive Frequency Hopping**

A period time = 0.4(s) * 20 = 8 (s)

7.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section. The test follows DA000705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable.
3. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
4. The Bluetooth has 3 type of payload, DH1, DH3, DH5 and 3-DH1, 3-DH3, 3-DH5.The hopping rate is insisted of 1 600 per second.

The EUT must have its hopping function enabled. Use the following spectrum analyzer setting:

Span = zero span, centered on a hopping channel
RBW = 1 ㎒
VBW = RBW
Sweep = as necessary to capture the entire dwell time per hopping channel
Detector = peak
Trace = max hold
Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation repeat this test for each variation.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

7.4. Test Results

Ambient temperature : (23 ± 1) ℃
Relative humidity : 47 % R.H.

DC 12V
7.4.1. Packet Type: DH1, 3-DH1

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	0.40	128.0	400
8DPSK	2 441 ㎒	0.41	131.2	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 0.40 × {(1600 ÷ 2) / 79} × 31.6 = 128.0 ㎳
In case of 8DPSK, 0.41 × {(1600 ÷ 2) / 79} × 31.6 = 131.2 ㎳

DC 24V
7.4.2. Packet Type: DH1, 3-DH1

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	0.40	128.0	400
8DPSK	2 441 ㎒	0.41	131.2	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 0.40 × {(1600 ÷ 2) / 79} × 31.6 = 128.0 ㎳
In case of 8DPSK, 0.41 × {(1600 ÷ 2) / 79} × 31.6 = 131.2 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
7.4.3. Packet Type: DH3, 3-DH3

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	1.66	265.6	400
8DPSK	2 441 ㎒	1.66	265.6	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 1.66 × {(1600 ÷ 4) / 79} × 31.6 = 265.6 ㎳
In case of 8DPSK, 1.66 × {(1600 ÷ 4) / 79} × 31.6 = 265.6 ㎳

DC 24V
7.4.4. Packet Type: DH3, 3-DH3

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	1.66	265.6	400
8DPSK	2 441 ㎒	1.67	267.2	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 1.66 × {(1600 ÷ 4) / 79} × 31.6 = 265.6 ㎳
In case of 8DPSK, 1.67 × {(1600 ÷ 4) / 79} × 31.6 = 267.2 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



DC 12V
7.4.5. Packet Type: DH5, 3-DH5

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	2.90	309.3	400
8DPSK	2 441 ㎒	2.92	311.5	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 2.90 × {(1600 ÷ 6) / 79} × 31.6 = 309.3 ㎳
In case of 8DPSK, 2.92 × {(1600 ÷ 6) / 79} × 31.6 = 311.5 ㎳

DC 24V
7.4.6. Packet Type: DH5, 3-DH5

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 31.6 sec (㎳)	Limit for time of occupancy on the Tx Channel in 31.6 sec (㎳)
GFSK	2 441 ㎒	2.91	310.4	400
8DPSK	2 441 ㎒	2.91	310.4	400

Note:
Time of occupancy on the TX channel in 31.6 sec
In case of GFSK, 2.91 × {(1600 ÷ 6) / 79} × 31.6 = 310.4 ㎳
In case of 8DPSK, 2.91 × {(1600 ÷ 6) / 79} × 31.6 = 310.4 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V

7.4.7. Packet Type: DH1, 3-DH1 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	0.40	128.0	400
8DPSK	2 441 ㎒	0.41	131.2	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 0.40 × {(1600 ÷ 2) / 20} × 8 = 128.0 ㎳
In case of 8DPSK, 0.41 × {(1600 ÷ 2) / 20} × 8 = 131.2 ㎳

DC 24V

7.4.8. Packet Type: DH1, 3-DH1 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	0.40	128.0	400
8DPSK	2 441 ㎒	0.41	131.2	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 0.40 × {(1600 ÷ 2) / 20} × 8 = 128.0 ㎳
In case of 8DPSK, 0.41 × {(1600 ÷ 2) / 20} × 8 = 131.2 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V

7.4.9. Packet Type: DH3, 3-DH3 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	1.64	262.4	400
8DPSK	2 441 ㎒	1.66	265.6	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 1.64 × {(1600 ÷ 4) / 20} × 8 = 262.4 ㎳
In case of 8DPSK, 1.66 × {(1600 ÷ 4) / 20} × 8 = 265.6 ㎳

DC 24V

7.4.10. Packet Type: DH3, 3-DH3 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	1.64	262.4	400
8DPSK	2 441 ㎒	1.66	265.6	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 1.64 × {(1600 ÷ 4) / 20} × 8 = 262.4 ㎳
In case of 8DPSK, 1.66 × {(1600 ÷ 4) / 20} × 8 = 265.6 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V

7.4.11. Packet Type: DH5, 3-DH5 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	2.91	310.4	400
8DPSK	2 441 ㎒	2.91	310.4	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 2.91 × {(1600 ÷ 6) / 20} × 8 = 310.4 ㎳
In case of 8DPSK, 2.91 × {(1600 ÷ 6) / 20} × 8 = 310.4 ㎳

DC 24V

7.4.12. Packet Type: DH5, 3-DH5 (Adaptive Frequency Hopping)

Operation Mode	Frequency	Dwell Time (㎳)	Time of occupancy on the Tx Channel in 8 sec (㎳)	Limit for time of occupancy on the Tx Channel in 8 sec (㎳)
GFSK	2 441 ㎒	2.91	310.4	400
8DPSK	2 441 ㎒	2.91	310.4	400

Note:
Time of occupancy on the TX channel in 8 sec
In case of GFSK, 2.91 × {(1600 ÷ 6) / 20} × 8 = 310.4 ㎳
In case of 8DPSK, 2.91 × {(1600 ÷ 6) / 20} × 8 = 310.4 ㎳

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 12V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

DC 24V
Operating Mode: GFSK



Operating Mode: 8DPSK



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

8. Antenna Requirement

8.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section §15.247 (b) if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6 dBi.

8.2. Antenna Connected Construction

Antenna used in this product is Internal type with gain of 1.99 dBi.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.