


FCC PART 27
FCC PART 22H, PART 24E
TEST REPORT

For

NEG TECHNOLOGY CO., LIMITED

Rm 1406, Block B, Jinsejiari, Jingtian south road, Futian district, Shenzhen, China

FCC ID: 2AAZ8-F1040D

Report Type: Original Report	Product Type: Mobile Phone
Report Number: RSZ170531001-00D	
Report Date: 2017-06-28	
Oscar Ye	
Reviewed By: Engineer	
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C); §27.50 (D) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS.....	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	56
FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST DATA	59
FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY.....	82
APPLICABLE STANDARD	82
TEST PROCEDURE	82
TEST DATA	83

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *NEG TECHNOLOGY CO., LIMITED*'s product, model number: *F1040D (FCC ID: 2AAZ8-F1040D)* in this report is a *Mobile Phone*, which was measured approximately: 12.5 cm (L) * 5.5 cm (W) * 1.5 cm (H), rated with input voltage: DC 3.7V from Li-ion battery or DC 5.0V from adapter.

Adapter information

Model: F1040D

Input: AC 100-240V, 50/60Hz, 0.15A

Output: 5.0V, 500 mA

** All measurement and test data in this report was gathered from production sample serial number: 1701193 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-05-31.*

Objective

This test report is prepared on behalf of *NEG TECHNOLOGY CO., LIMITED* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Part 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS & DSS and Part 15B JBP submissions with FCC ID: 2AAZ8-F1040D.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
RF conducted test with spectrum		$\pm 0.9\text{dB}$
RF Output Power with Power meter		$\pm 0.5\text{dB}$
Radiated emission	30MHz~1GHz	$\pm 5.91\text{dB}$
	Above 1G	$\pm 4.92\text{dB}$
Occupied Bandwidth		$\pm 0.5\text{kHz}$
Temperature		$\pm 1.0^{\circ}\text{C}$
Humidity		$\pm 6\%$

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Bay Area Compliance Laboratories Corp. (Kunshan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L9963). And accredited to ISO/IEC 17025 by A2LA(Lab code: 4323.01), the FCC Designation No. CN1185 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Kunshan) was registered with ISED Canada under ISED Canada Registration Number 3062E.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-116218-UY
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (d)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrument	Amplifier	330	171377	2016-12-12	2017-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	9510-2384	2015-11-07	2018-11-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-01-11	2017-01-10
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2017-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
WEINSCHL	3dB Attenuator	5326	N/A	2016-06-18	2017-06-18
WEINSCHL	3dB Attenuator	5326	N/A	2017-06-18	2018-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-116218-UY	2016-10-08	2017-10-08
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2016-06-12	2017-06-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ170531001-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H, 24E & Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50 (d) - RF OUTPUT POWER**Applicable Standard**


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz. The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

Test Procedure*Conducted method:*

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.

*Radiated method:*

TIA 603-D section 2.2.17

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-06-13.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.59	38.45
	190	836.6	32.58	38.45
	251	848.8	32.40	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.56	31.73	29.94	28.67	38.45
	190	836.6	32.57	31.72	29.82	28.70	38.45
	251	848.8	32.38	31.50	29.65	28.50	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	26.88	25.09	22.18	21.18	38.45
	190	836.6	26.97	25.18	22.27	21.32	38.45
	251	848.8	26.90	25.10	22.17	21.30	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.58	22.56	22.33
		HSDPA	1	21.51	21.49	21.24
			2	21.39	21.44	21.18
			3	21.60	21.55	21.34
			4	21.42	21.37	21.13
		HSUPA	1	21.52	21.51	21.27
			2	21.48	21.41	21.19
			3	21.56	21.62	21.35
			4	21.41	21.39	21.21
			5	21.56	21.57	21.38
		HSPA+	1	21.40	21.39	21.21

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.08	33
	661	1880.0	28.78	33
	810	1909.8	28.62	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	29.06	28.32	26.64	25.43	33
	661	1880.0	28.75	28.01	26.24	25.10	33
	810	1909.8	28.64	27.89	26.15	24.95	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	25.07	23.70	21.29	19.40	33
	661	1880.0	24.68	23.27	20.79	19.00	33
	810	1909.8	24.00	22.58	20.07	18.28	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.40	22.17	21.87
		HSDPA	1	21.28	21.40	20.99
			2	21.19	21.31	20.92
			3	21.32	21.45	20.32
			4	21.15	21.32	20.86
		HSUPA	1	21.40	21.63	20.40
			2	21.28	21.52	20.33
			3	21.43	21.69	20.35
			4	21.27	21.59	20.41
			5	21.44	21.75	20.38
		HSPA+	1	21.29	21.54	20.41

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.20	13
	Middle	0.14	13
	High	0.20	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.35	13
	Middle	0.32	13
	High	0.27	13

Mode	Channel	PAR (dB)	Limit (dBm)
WCDMA (BPSK)	Low	2.92	13
	Middle	3.41	13
	High	3.72	13
HSDPA (16QAM)	Low	2.87	13
	Middle	3.16	13
	High	3.28	13
HSUPA (BPSK)	Low	3.17	13
	Middle	2.98	13
	High	3.60	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.22	13
	Middle	0.06	13
	High	0.12	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.31	13
	Middle	0.25	13
	High	0.43	13

Mode	Channel	PAR (dB)	Limit (dBm)
WCDMA (BPSK)	Low	5.59	13
	Middle	3.15	13
	High	3.17	13
HSDPA (16QAM)	Low	5.86	13
	Middle	3.30	13
	High	3.16	13
HSUPA (BPSK)	Low	5.92	13
	Middle	3.01	13
	High	3.18	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	86.84	282	1	H	17.1	0.26	4.75	21.59	38.45	16.86
836.6	99.66	128	2.4	V	25.9	0.26	4.75	30.39	38.45	8.06
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	74.09	49	1.9	H	12.6	0.45	8.84	20.99	33	12.01
1880.00	82.32	38	1.5	V	18.6	0.45	8.84	26.99	33	6.01

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	83.34	32	1.5	H	13.6	0.26	4.75	18.09	38.45	20.36
836.6	96.80	139	2.4	V	23.1	0.26	4.75	27.59	38.45	10.86
EIRP, PCS Band (Part 24E), Middle Channel										
1880.00	72.89	43	1.1	H	11.4	0.45	8.84	19.79	33	13.21
1880.00	79.42	94	1.3	V	15.7	0.45	8.84	24.09	33	8.91

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	79.24	83	1	H	9.5	0.26	4.75	13.99	38.45	24.46
836.6	91.56	79	2.4	V	17.8	0.26	4.75	22.29	38.45	16.16
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.00	68.99	66	2.5	H	7.5	0.45	8.84	15.89	33	17.11
1880.00	76.72	132	1.9	V	13.0	0.45	8.84	21.39	33	11.61

Note:

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB Size=1, RB Offset=0	23.30	22.73	22.86
		RB Size=1, RB Offset=2	23.22	22.62	22.79
		RB Size=1, RB Offset=5	23.42	22.78	22.98
		RB Size=3, RB Offset=0	23.26	22.62	22.75
		RB Size=3, RB Offset=1	23.42	22.85	22.95
		RB Size=3, RB Offset=2	23.33	22.71	22.84
		RB Size=6, RB Offset=0	22.22	21.62	21.79
	16QAM	RB Size=1, RB Offset=0	22.28	21.78	21.94
		RB Size=1, RB Offset=2	22.19	21.65	21.84
		RB Size=1, RB Offset=5	22.34	21.85	22.01
		RB Size=3, RB Offset=0	22.17	21.66	21.86
		RB Size=3, RB Offset=1	22.32	21.88	21.98
		RB Size=3, RB Offset=2	22.25	21.69	21.94
		RB Size=6, RB Offset=0	21.19	20.65	20.84
3M	QPSK	RB Size=1, RB Offset=0	23.27	22.74	22.88
		RB Size=1, RB Offset=7	23.20	22.70	22.82
		RB Size=1, RB Offset=14	23.34	22.77	23.00
		RB Size=8, RB Offset=0	23.15	22.62	22.81
		RB Size=8, RB Offset=4	23.31	22.84	23.01
		RB Size=8, RB Offset=7	23.24	22.80	22.93
		RB Size=15, RB Offset=0	22.20	21.70	21.82
	16QAM	RB Size=1, RB Offset=0	22.39	22.31	21.88
		RB Size=1, RB Offset=7	22.31	22.20	21.76
		RB Size=1, RB Offset=14	22.50	22.38	21.99
		RB Size=8, RB Offset=0	22.29	22.18	21.82
		RB Size=8, RB Offset=4	22.49	22.42	21.93
		RB Size=8, RB Offset=7	22.34	22.30	21.81
		RB Size=15, RB Offset=0	21.31	21.20	20.76

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.39	22.92	22.22
		RB Size=1, RB Offset=12	23.32	22.87	22.12
		RB Size=1, RB Offset=24	23.50	23.03	22.28
		RB Size=12, RB Offset=0	23.32	22.84	22.18
		RB Size=12, RB Offset=6	23.51	23.04	22.32
		RB Size=12, RB Offset=11	23.37	22.97	22.16
		RB Size=25, RB Offset=0	22.32	21.87	21.12
	16QAM	RB Size=1, RB Offset=0	22.63	21.78	21.39
		RB Size=1, RB Offset=12	22.53	21.66	21.35
		RB Size=1, RB Offset=24	22.75	21.82	21.47
		RB Size=12, RB Offset=0	22.56	21.67	21.34
		RB Size=12, RB Offset=6	22.66	21.82	21.46
		RB Size=12, RB Offset=11	22.57	21.76	21.47
		RB Size=25, RB Offset=0	21.53	20.66	20.35
10.0	QPSK	RB Size=1, RB Offset=0	23.43	22.95	22.94
		RB Size=1, RB Offset=24	23.40	22.91	22.91
		RB Size=1, RB Offset=49	23.47	23.02	22.99
		RB Size=25, RB Offset=0	23.32	22.82	22.85
		RB Size=25, RB Offset=12	23.48	23.07	22.98
		RB Size=25, RB Offset=24	23.48	22.96	22.95
		RB Size=50, RB Offset=0	22.40	21.91	21.91
	16QAM	RB Size=1, RB Offset=0	22.54	22.49	21.82
		RB Size=1, RB Offset=24	22.44	22.45	21.76
		RB Size=1, RB Offset=49	22.66	22.60	21.94
		RB Size=25, RB Offset=0	22.47	22.44	21.71
		RB Size=25, RB Offset=12	22.64	22.61	21.92
		RB Size=25, RB Offset=24	22.48	22.50	21.87
		RB Size=50, RB Offset=0	21.44	21.45	20.76

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	23.46	23.05	22.92
		RB Size=1, RB Offset=37	23.33	22.96	22.81
		RB Size=1, RB Offset=74	23.58	23.10	22.96
		RB Size=36, RB Offset=0	23.40	22.98	22.83
		RB Size=36, RB Offset=18	23.50	23.09	23.04
		RB Size=36, RB Offset=37	23.37	23.03	22.93
		RB Size=75, RB Offset=0	22.33	21.96	21.81
	16QAM	RB Size=1, RB Offset=0	22.56	22.59	22.09
		RB Size=1, RB Offset=37	22.49	22.50	21.99
		RB Size=1, RB Offset=74	22.59	22.64	22.19
		RB Size=36, RB Offset=0	22.51	22.52	21.96
		RB Size=36, RB Offset=18	22.69	22.67	22.14
		RB Size=36, RB Offset=37	22.59	22.54	22.09
		RB Size=75, RB Offset=0	21.49	21.50	20.99
20.0	QPSK	RB Size=1, RB Offset=0	23.59	23.13	22.98
		RB Size=1, RB Offset=49	23.52	23.02	22.87
		RB Size=1, RB Offset=99	23.63	23.24	23.05
		RB Size=50, RB Offset=0	23.49	23.02	22.85
		RB Size=50, RB Offset=24	23.62	23.23	23.07
		RB Size=50, RB Offset=49	23.60	23.07	22.96
		RB Size=100, RB Offset=0	22.52	22.02	21.87
	16QAM	RB Size=1, RB Offset=0	23.03	22.48	22.29
		RB Size=1, RB Offset=49	22.94	22.41	22.21
		RB Size=1, RB Offset=99	23.09	22.52	22.34
		RB Size=50, RB Offset=0	22.97	22.39	22.22
		RB Size=50, RB Offset=24	23.07	22.55	22.36
		RB Size=50, RB Offset=49	23.00	22.51	22.28
		RB Size=100, RB Offset=0	21.94	21.41	21.21

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.68	13	Pass
QPSK (100%RB Size)	5.32	13	Pass
16QAM (1RB Size)	4.98	13	Pass
16QAM (100%RB Size)	5.77	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	71.77	351	1.0	H	8.2	0.40	8.52	16.32	30
1732.50	79.54	269	1.4	V	14.0	0.40	8.52	22.12	30
3 MHz Bandwidth									
1732.50	71.27	38	2.0	H	7.7	0.40	8.52	15.82	30
1732.50	79.94	184	1.2	V	14.4	0.40	8.52	22.52	30
5 MHz Bandwidth									
1732.50	71.17	79	1.6	H	7.6	0.40	8.52	15.72	30
1732.50	78.44	94	1.5	V	12.9	0.40	8.52	21.02	30
10 MHz Bandwidth									
1732.50	71.07	18	1.4	H	7.5	0.40	8.52	15.62	30
1732.50	78.64	84	1.9	V	13.1	0.40	8.52	21.22	30
15 MHz Bandwidth									
1732.50	71.47	189	1.4	H	7.9	0.40	8.52	16.02	30
1732.50	78.14	74	2.1	V	12.6	0.40	8.52	20.72	30
20 MHz Bandwidth									
1732.50	71.27	221	1.9	H	7.7	0.40	8.52	15.82	30
1732.50	77.34	158	1.2	V	11.8	0.40	8.52	19.92	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	72.07	178	1.5	H	8.5	0.40	8.52	16.62	30
1732.50	80.64	216	2.2	V	15.1	0.40	8.52	23.22	30
3 MHz Bandwidth									
1732.50	71.77	294	1.1	H	8.2	0.40	8.52	16.32	30
1732.50	80.14	73	1.5	V	14.6	0.40	8.52	22.72	30
5 MHz Bandwidth									
1732.50	71.47	67	1.8	H	7.9	0.40	8.52	16.02	30
1732.50	79.64	106	1.8	V	14.1	0.40	8.52	22.22	30
10 MHz Bandwidth									
1732.50	71.27	140	1.1	H	7.7	0.40	8.52	15.82	30
1732.50	78.74	135	2.3	V	13.2	0.40	8.52	21.32	30
15 MHz Bandwidth									
1732.50	72.27	266	1.9	H	8.7	0.40	8.52	16.82	30
1732.50	78.04	16	1.7	V	12.5	0.40	8.52	20.62	30
20 MHz Bandwidth									
1732.50	71.87	137	1.0	H	8.3	0.40	8.52	16.42	30
1732.50	76.84	134	2.0	V	11.3	0.40	8.52	19.42	30

Note:

All above data were tested with no amplifier

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	23~25 °C
Relative Humidity:	49~57 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Echo Wu on 2017-06-22 and 2017-06-23.

EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)



Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	318.6
EGPRS(8PSK)	836.6	246.5	318.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.208	4.930
HSUPA (BPSK)	836.6	4.228	4.950
HSDPA (16QAM)	836.6	4.208	4.910


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	240.5	308.6
EGPRS(8PSK)	1880.0	246.5	324.6


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.188	4.910
HSUPA (BPSK)	1880.0	4.228	4.930
HSDPA (16QAM)	1880.0	4.228	4.910



Cellular Band (Part 22H)**26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode****26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode**



26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode





26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode





26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**PCS Band (Part 24E)****26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**

26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode**26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**

26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**

LTE Band 4: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.105	1.279
	16QAM	1.111	1.285
3.0	QPSK	2.693	2.910
	16QAM	2.693	2.958
5.0	QPSK	4.529	5.050
	16QAM	4.549	5.110
10.0	QPSK	8.978	9.739
	16QAM	8.938	9.619
15.0	QPSK	13.527	15.090
	16QAM	13.527	14.970
20.0	QPSK	17.956	19.479
	16QAM	17.956	19.559

QPSK (1.4 MHz) - 26 dB Bandwidth, Middle channel**16-QAM (1.4 MHz) -26 dB Bandwidth, Middle channel**

Ref Lvl 34 dBm
 Marker 1 [T1 ndB] 26.00 dB
 BW 2.90981964 MHz
 RBW 30 kHz
 VBW 100 kHz
 RF Att 30 dB
 Unit dBm
 14 dB Offset
 17 ms
 1.7325 GHz
 600 kHz/
 Span 6 MHz
 Date: 23.JUN.2017 21:12:36

Ref Lvl 34 dBm Marker 1 [T1 ndB] 26.00 dB RBW 30 kHz RF Att 30 dB
 BW 2.95791583 MHz VSW 100 kHz Unit dBm

14 dB Offset

1

T1 [T1] 16.50 dBm

1.73218136 GHz

ndB 26.00 dB

BW 2.95791583 MHz

T1 [T1] -15.48 dBm

1.73103908 GHz


T2 [T1] -16.18 dBm

1.73399699 GHz


Center 1.7325 GHz 600 kHz/ Span 6 MHz

Date: 23.JUN.2017 21:13:31


QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel




QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel




QPSK (15.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (15.0 MHz) - 26 dB Bandwidth, Middle channel





QPSK (20.0 MHz) - 26 dB Bandwidth, Middle channel




16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel




QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**


QPSK (3.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (3.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel




QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel





QPSK (15.0 MHz) - 99% Occupied Bandwidth, Middle channel



16-QAM (15.0 MHz) - 99% Occupied Bandwidth, Middle channel



QPSK (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	23~25 °C
Relative Humidity:	49~57 %
ATM Pressure:	100.0~101.0 kPa


The testing was performed by Echo Wu on 2017-06-22 and 2017-06-27.

EUT operation mode: transmitting


Test result: Compliance, please refer to the following plots.

Cellular Band (Part 22H)


30 MHz – 1 GHz (GSM Mode)




1 GHz – 10 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)




PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)




Fundamental test


2 GHz – 20 GHz (GSM Mode)




30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 2 GHz (WCDMA Mode)




2 GHz – 20 GHz (WCDMA Mode)




LTE Band 4:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)



30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




Fundamental test


2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)



1 GHz – 2 GHz (20.0 MHz, Middle Channel)



2 GHz – 20 GHz (20.0 MHz, Middle Channel)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Spurious attenuation limit in dB = $55 + 10 \log_{10} (\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-06-13.

EUT operation mode: transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
356.75	33.75	65	1.4	H	-68.3	0.23	4.65	-63.88	-13	50.88
356.75	35.49	84	2.1	V	-69.7	0.23	4.65	-65.28	-13	52.28
1673.20	51.00	227	1.2	H	-50.8	0.40	8.52	-42.68	-13	29.68
1673.20	56.77	33	1.2	V	-47.0	0.40	8.52	-38.88	-13	25.88
WCDMA Mode, Middle channel										
356.75	33.45	265	1.1	H	-68.6	0.23	4.65	-64.18	-13	51.18
356.75	36.79	106	1.6	V	-68.4	0.23	4.65	-63.98	-13	50.98
1673.20	46.00	168	1.9	H	-55.8	0.40	8.52	-47.68	-13	34.68
1673.20	47.47	173	1.3	V	-56.3	0.40	8.52	-48.18	-13	35.18

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
356.75	33.55	198	1.8	H	-68.5	0.23	4.65	-64.08	-13	51.08
356.75	36.29	190	1.6	V	-68.9	0.23	4.65	-64.48	-13	51.48
3760.00	43.32	353	1.5	H	-52.7	0.59	9.72	-43.57	-13	30.57
3760.00	50.11	338	1.5	V	-47.0	0.59	9.72	-37.87	-13	24.87
WCDMA Mode, Middle channel										
356.75	32.95	96	2.3	H	-69.1	0.23	4.65	-64.68	-13	51.68
356.75	36.99	42	1.7	V	-68.2	0.23	4.65	-63.78	-13	50.78
3760.00	37.02	314	1.0	H	-59.0	0.59	9.72	-49.87	-13	36.87
3760.00	39.91	64	1.8	V	-57.2	0.59	9.72	-48.07	-13	35.07

LTE Band:

Test mode: Transmitting (Pre-scan with all the bandwidth, and worse case as below)

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Band 4										
Test frequency range:30 MHz ~ 20 GHz										
356.75	32.95	117	2.4	H	-69.1	0.23	4.65	-64.68	-13	51.68
356.75	36.89	91	1.9	V	-68.3	0.23	4.65	-63.88	-13	50.88
3465.00	41.53	283	1.8	H	-55.5	0.54	9.90	-46.14	-13	33.14
3465.00	42.83	89	1.8	V	-55.5	0.54	9.90	-46.14	-13	33.14

Note:

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit - Absolute Level

FCC § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) - BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to § 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC § 27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**


Temperature:	23~25 °C
Relative Humidity:	50~58 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Echo Wu on 2017-06-22 and 2017-06-25.


EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following plots.


Cellular Band, Left Band Edge for GSM (GMSK) Mode




Cellular Band, Right Band Edge for GSM (GMSK) Mode







Cellular Band, Left Band Edge for EDGE Mode





Cellular Band, Right Band Edge for EDGE Mode




Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**


Cellular Band, Left Band Edge for HSDPA (16QAM) Mode**Cellular Band, Right Band Edge for HSDPA (16QAM) Mode**

Cellular Band, Left Band Edge for HSUPA (BPSK) Mode**Cellular Band, Right Band Edge for HSUPA (BPSK) Mode**


PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode



PCS Band, Left Band Edge for EDGE Mode



PCS Band, Right Band Edge for EDGE Mode



Marker 1 [T1]
 Ref Lvl -13.23 dBm
 34 dBm 1.84998998 GHz
 RBW 50 kHz
 VBW 200 kHz
 RF Att 30 dB
 Unit dBm
 SWT 10 ms

14 dB Offset
 1 [T1] -13.23 dBm
 1.84998998 GHz


-13 dBm
 -13.23 dBm
 1.84998998 GHz

Center 1.85 GHz
 1 MHz/
 Span 10 MHz


Date: 25.JUN.2017 15:50:23

The screenshot displays a spectrum analyzer interface. At the top, a red diamond icon with the letter 'A' is visible. The main display area shows a blue trace of a signal. A horizontal red line is drawn across the plot at -18.10 dBm. The x-axis is labeled 'Center 1.91 GHz' and the y-axis is labeled 'Span 10 MHz'. The signal trace shows a peak at 1.91 GHz with a power level of -18.10 dBm. The noise floor is also at -18.10 dBm. The signal is centered at 1.91 GHz and has a span of 10 MHz. The peak is labeled '1.91001002 GHz' and the power level is '-18.10 dBm'. The noise floor is labeled '-18.10 dBm'.

PCS Band, Left Band Edge for HSDPA (16QAM) Mode



PCS Band, Right Band Edge for HSDPA (16QAM) Mode



Marker 1 [T1]
 Ref Lvl -14.76 dBm
 34 dBm 1.84998998 GHz
 RBW 50 kHz VBW 200 kHz RF Att 30 dB
 SWT 10 ms Unit dBm

14 dB Offset
 -14.76 dBm
 1.84998998 GHz

-13 dBm

Center 1.85 GHz 1 MHz/ Span 10 MHz

Date: 25 JUN 2017 15:53:51

Ref Lvl 34 dBm

Marker 1 [T1] -17.93 dBm

RBW 50 kHz RF Att 30 dB

VBW 200 kHz

SWT 10 ms Unit dBm

1.91001002 GHz

14 dB Offset

1 [T1] -17.93 dBm

1.91001002 GHz

01 -13 dBm

Center 1.91 GHz


1 MHz/

Span 10 MHz


Date: 25.JUN.2017 15:54:27



LTE Band 4:



QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**

QPSK (3.0 MHz, FULL RB) - Left Band Edge**QPSK (3.0 MHz, FULL RB) - Right Band Edge**


16-QAM (3.0 MHz, FULL RB) - Left Band Edge




16-QAM (3.0 MHz, FULL RB) - Right Band Edge




QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge




16-QAM (15.0 MHz, FULL RB) - Left Band Edge




16-QAM (15.0 MHz, FULL RB) - Right Band Edge





QPSK (20.0 MHz, FULL RB) - Left Band Edge



QPSK (20.0 MHz, FULL RB) - Right Band Edge



16-QAM (20.0 MHz, FULL RB) - Left Band Edge**16-QAM (20.0 MHz, FULL RB) - Right Band Edge**

FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235 and & §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2017-06-25.

EUT operation mode: transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0=836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-4	-0.0048	2.5
-20		-5	-0.0060	2.5
-10		-4	-0.0048	2.5
0		-3	-0.0036	2.5
10		-8	-0.0096	2.5
20		-1	-0.0012	2.5
30		-4	-0.0048	2.5
40		-5	-0.0060	2.5
50		4	0.0048	2.5
25	$V_{min}=3.5$	-4	-0.0048	2.5
25	$V_{max}=4.2$	-2	-0.0024	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-20	3.7	6	0.0072	2.5
-10		-2	-0.0024	2.5
0		3	0.0036	2.5
10		-3	-0.0036	2.5
20		1	0.0012	2.5
30		-6	-0.0072	2.5
40		-4	-0.0048	2.5
50		3	0.0036	2.5
25	$V_{min.} = 3.5$	-4	-0.0048	2.5
25	$V_{max.} = 4.2$	-1	-0.0012	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	25	0.0299	2.5
-20		26	0.0311	2.5
-10		24	0.0287	2.5
0		25	0.0299	2.5
10		22	0.0263	2.5
20		0	0.0000	2.5
30		21	0.0251	2.5
40		24	0.0287	2.5
50		22	0.0263	2.5
25	$V_{min.} = 3.5$	24	0.0287	2.5
25	$V_{max.} = 4.2$	25	0.0299	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	14	0.0074	pass
-20		8	0.0043	pass
-10		16	0.0085	pass
0		10	0.0053	pass
10		8	0.0043	pass
20		3	0.0016	pass
30		7	0.0037	pass
40		8	0.0043	pass
50		6	0.0032	pass
25	V _{min.} = 3.5	4	0.0021	pass
25	V _{max.} = 4.2	5	0.0027	pass

EDGE Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-16	-0.0085	pass
-20		-9	-0.0048	pass
-10		-12	-0.0064	pass
0		-10	-0.0053	pass
10		9	0.0048	pass
20		-7	-0.0037	pass
30		-8	-0.0043	pass
40		-5	-0.0027	pass
50		-4	-0.0021	pass
25	V _{min.} = 3.5	-7	-0.0037	pass
25	V _{max.} = 4.2	-16	-0.0085	pass

WCDMA Mode

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	28	0.0149	pass
-20		28	0.0149	pass
-10		24	0.0128	pass
0		24	0.0128	pass
10		25	0.0133	pass
20		0	0.0000	pass
30		23	0.0122	pass
40		23	0.0122	pass
50		25	0.0133	pass
25	$V_{min}=3.5$	23	0.0122	pass
25	$V_{max}=4.2$	24	0.0128	pass

LTE Band 4:

20 MHz Middle Channel, $f_0=1732.5$ MHz(QPSK)				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	5	0.002886	pass
-20		1	0.000577	pass
-10		3	0.001732	pass
0		0	0.000000	pass
10		6	0.003463	pass
20		1	0.000577	pass
30		4	0.002309	pass
40		2	0.001154	pass
50		1	0.000577	pass
20	$V_{min}=3.5$	-1	-0.000577	pass
	$V_{max}=4.2$	0	0.000000	pass

20 MHz Middle Channel, $f_o=1732.5$ MHz(16-QAM)				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	5	0.002886	pass
-20		1	0.000577	pass
-10		3	0.001732	pass
0		0	0.000000	pass
10		6	0.003463	pass
20		1	0.000577	pass
30		4	0.002309	pass
40		3	0.001732	pass
50		1	0.000577	pass
20	$V_{min}=3.5$	-1	-0.000577	pass
	$V_{max}=4.2$	1	0.000577	pass

***** END OF REPORT *****