

APPLICATION FOR VERIFICATION
On Behalf of
Carewell Electric Technology (Zhongshan) Co., Ltd.

REMOTE CONTROL
Model No.: FAN42R-T190W

FCC ID: 2AAZPFAN42R

Prepared for : Carewell Electric Technology (Zhongshan) Co., Ltd.
Address : Torch Development Zone, No.2, Ouya Road, Zhongshan,
Guangdong, China

Prepared by : Accurate Technology Co., Ltd.
Address : F1, Bldg. A&D, Changyuan New Material Port, Keyuan
Rd., Science & Industry Park, Nanshan District, Shenzhen
518057, P.R. China

Tel: +86-755-26503290
Fax: +86-755-26503396

Report No. : ATE20150048
Date of Test : Jan 06-08,2015
Date of Report : Jan 08,2015

TABLE OF CONTENTS

| Description | Page |
|--|-----------|
| Test Report Declaration | |
| 1. TEST RESULTS SUMMARY | 4 |
| 2. GENERAL INFORMATION | 5 |
| 2.1. Product of Device (EUT) | 5 |
| 2.2. Accessory and Auxiliary Equipment | 5 |
| 2.3. Description of Test Facility | 6 |
| 2.4. Measurement Uncertainty | 6 |
| 3. MEASURING DEVICE AND TEST EQUIPMENT | 7 |
| 4. POWER LINE CONDUCTED MEASUREMENT | 8 |
| 4.1. Block Diagram of Test Setup | 8 |
| 4.2. The Emission Limit | 8 |
| 4.3. Configuration of EUT on Measurement | 9 |
| 4.4. Operating Condition of EUT | 9 |
| 4.5. Test Procedure | 9 |
| 4.6. Power Line Conducted Emission Measurement Results | 10 |
| 5. RADIATED EMISSION MEASUREMENT | 13 |
| 5.1. Block Diagram of Test Setup | 13 |
| 5.2. The Emission Limit For Section 15.109 (a) | 14 |
| 5.3. EUT Configuration on Measurement | 14 |
| 5.4. Operating Condition of EUT | 14 |
| 5.5. Test Procedure | 14 |
| 5.6. Radiated Emission Noise Measurement Result | 15 |

Test Report Declaration



Applicant : Carewell Electric Technology (Zhongshan) Co., Ltd.
Manufacturer : Carewell Electric Technology(Zhongshan)Co.,Ltd.
EUT Description : REMOTE CONTROL
(A) MODEL NO.: FAN42R-T190W
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: AC 120V

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart B ANSI C63.4: 2009

The device described above is tested by Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both radiated and conducted emissions. The measurement results are contained in this test report and Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

| | |
|--------------------------------|--|
| Date of Test : | Nov 20-Jan 08,2015 |
| Date of Report : | Jan 08,2015 |
| Prepared by : |  (Eric Zhang, Engineer) |
| Approved & Authorized Signer : |  (Sean Liu, Manager) |

1. TEST RESULTS SUMMARY

| Test Items | Test Standard | Test Results |
|-------------------------------|-----------------------|--------------|
| Power Line Conducted Emission | FCC Part 15 Subpart B | Pass |
| Radiated Emission | FCC Part 15 Subpart B | Pass |

2. GENERAL INFORMATION

2.1.Product of Device (EUT)

| | |
|-------------------------|--|
| EUT | : REMOTE CONTROL |
| Model Number | : FAN42R-T190W |
| Power Supply | : AC 120V |
| Modulation: | : ASK |
| Receiver Frequency | : 315MHz RX |
| Applicant | : Carewell Electric Technology (Zhongshan) Co., Ltd. |
| Address | : Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China |
| Manufacturer | : Carewell Electric Technology(Zhongshan)Co.,Ltd. |
| Address | : Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China |
| Date of sample received | : Jan 06, 2015 |
| Date of Test | : Jan 06-08,2015 |

2.2.Accessory and Auxiliary Equipment

NA

2.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen, May 10, 2004

Listed by FCC

The Registration Number is 253065

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-1

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee for Laboratories

The Certificate Registration Number is L3193

Name of Firm : Accurate Technology Co., Ltd.

Site Location : F1, Bldg. A&D, Changyuan New Material Port, Keyuan Rd., Science & Industry Park, Nanshan District, Shenzhen 518057, P.R. China

2.4. Measurement Uncertainty

Conducted emission expanded uncertainty : U=2.23dB, k=2

Power disturbance expanded uncertainty : U=2.92dB, k=2

Radiated emission expanded uncertainty : U=3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty : U=4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty : U=4.06dB, k=2
(Above 1GHz)

3. MEASURING DEVICE AND TEST EQUIPMENT


Table 1: List of Test and Measurement Equipment

| Kind of equipment | Manufacturer | Type | S/N | Calibrated date | Calibrated until |
|-------------------------------|---------------|--------------------|------------|-----------------|------------------|
| EMI Test REMOTE CONTROL | Rohde&Schwarz | ESCS30 | 100307 | Jan. 11, 2014 | Jan. 10, 2015 |
| EMI Test REMOTE CONTROL | Rohde&Schwarz | ESPI3 | 101526/003 | Jan. 11, 2014 | Jan. 10, 2015 |
| Spectrum Analyzer | Agilent | E7405A | MY45115511 | Jan. 11, 2014 | Jan. 10, 2015 |
| Pre-Amplifier | Rohde&Schwarz | CBLU118354 0-01 | 3791 | Jan. 11, 2014 | Jan. 10, 2015 |
| Loop Antenna | Schwarzbeck | FMZB1516 | 1516131 | Jan. 15, 2014 | Jan. 14, 2015 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 9163-323 | Jan. 15, 2014 | Jan. 14, 2015 |
| Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-655 | Jan. 15, 2014 | Jan. 14, 2015 |
| Horn Antenna | Schwarzbeck | BBHA9170 | 9170-359 | Jan. 15, 2014 | Jan. 14, 2015 |
| LISN | Rohde&Schwarz | ESH3-Z5 | 100305 | Jan. 11, 2014 | Jan. 10, 2015 |
| LISN | Schwarzbeck | NSLK8126 | 8126431 | Jan. 11, 2014 | Jan. 10, 2015 |


4. POWER LINE CONDUCTED MEASUREMENT

4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



4.1.2. Shielding Room Test Setup Diagram



4.2. The Emission Limit

4.2.1. Conducted Emission Measurement Limits According to Section 15.107(a)

| Frequency (MHz) | Limit dB(μ V) | |
|--------------------|--------------------|---------------|
| | Quasi-peak Level | Average Level |
| 0.15 - 0.50 | 66.0 – 56.0 * | 56.0 – 46.0 * |
| 0.50 - 5.00 | 56.0 | 46.0 |
| 5.00 - 30.00 | 60.0 | 50.0 |

* Decreases with the logarithm of the frequency.

4.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

4.3.1.REMOTE CONTROL (EUT)

Model Number: FAN42R-T190W

Serial Number: N/A

Manufacturer: Carewell Electric Technology (Zhongshan) Co., Ltd.

4.4. Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 3.2.

4.4.2.Turn on the power of all equipment.

4.4.3.Let the EUT work in test mode and measure it.

4.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Measurement.

The bandwidth of test REMOTE CONTROL (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

4.6. Power Line Conducted Emission Measurement Results

PASS.

| | | | | | | | | |
|--|---------------|--------------|---------------|--------------|----------|------|-----|--|
| Test Mode: RX | | | | | | | | |
| MEASUREMENT RESULT: "TB0106-6_fin" | | | | | | | | |
| 2015-1-6 15:28 | | | | | | | | |
| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE | |
| 0.150000 | 62.80 | 10.3 | 66 | 3.2 | QP | L1 | GND | |
| 0.168000 | 61.80 | 10.5 | 65 | 3.3 | QP | L1 | GND | |
| 1.020000 | 40.20 | 11.6 | 56 | 15.8 | QP | L1 | GND | |
| MEASUREMENT RESULT: "TB0106-6_fin2" | | | | | | | | |
| 2015-1-6 15:28 | | | | | | | | |
| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE | |
| 0.150000 | 42.10 | 10.3 | 56 | 13.9 | AV | L1 | GND | |
| 2.193500 | 16.70 | 11.7 | 46 | 29.3 | AV | L1 | GND | |
| 19.158500 | 35.60 | 11.9 | 50 | 14.4 | AV | L1 | GND | |
| MEASUREMENT RESULT: "TB0106-7_fin" | | | | | | | | |
| 2015-1-6 15:31 | | | | | | | | |
| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE | |
| 0.150000 | 61.70 | 10.3 | 66 | 4.3 | QP | N | GND | |
| 0.166000 | 62.40 | 10.4 | 65 | 2.8 | QP | N | GND | |
| 18.884000 | 46.30 | 11.9 | 60 | 13.7 | QP | N | GND | |
| MEASUREMENT RESULT: "TB0106-7_fin2" | | | | | | | | |
| 2015-1-6 15:31 | | | | | | | | |
| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE | |
| 0.166000 | 39.60 | 10.4 | 55 | 15.6 | AV | N | GND | |
| 2.225000 | 17.00 | 11.7 | 46 | 29.0 | AV | N | GND | |
| 19.239500 | 40.00 | 11.9 | 50 | 10.0 | AV | N | GND | |

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are shown in the following pages.


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: REMOTE CONTROL M/N:FAN42R-T190W
 Manufacturer: CAREWELL
 Operating Condition: RX
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: L 120V/60Hz
 Comment:

Report NO.:ATE20150048

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz LISN (ESH3-Z5)
 Average



MEASUREMENT RESULT: "TB0106-6_fin"

2015-1-6 15:28

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000 | 62.80 | 10.3 | 66 | 3.2 | QP | L1 | GND |
| 0.168000 | 61.80 | 10.5 | 65 | 3.3 | QP | L1 | GND |
| 1.020000 | 40.20 | 11.6 | 56 | 15.8 | QP | L1 | GND |

MEASUREMENT RESULT: "TB0106-6_fin2"

2015-1-6 15:28

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000 | 42.10 | 10.3 | 56 | 13.9 | AV | L1 | GND |
| 2.193500 | 16.70 | 11.7 | 46 | 29.3 | AV | L1 | GND |
| 19.158500 | 35.60 | 11.9 | 50 | 14.4 | AV | L1 | GND |


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: REMOTE CONTROL M/N:FAN42R-T190W
 Manufacturer: CAREWELL
 Operating Condition: RX
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: N 120V/60Hz
 Comment:

Report NO.:ATE20150048

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz LISN (ESH3-Z5)
 Average



MEASUREMENT RESULT: "TB0106-7_fin"

2015-1-6 15:31

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000 | 61.70 | 10.3 | 66 | 4.3 | QP | N | GND |
| 0.166000 | 62.40 | 10.4 | 65 | 2.8 | QP | N | GND |
| 18.884000 | 46.30 | 11.9 | 60 | 13.7 | QP | N | GND |

MEASUREMENT RESULT: "TB0106-7_fin2"


2015-1-6 15:31

| Frequency MHz | Level dBuV | Transd dB | Limit dBuV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.166000 | 39.60 | 10.4 | 55 | 15.6 | AV | N | GND |
| 2.225000 | 17.00 | 11.7 | 46 | 29.0 | AV | N | GND |
| 19.239500 | 40.00 | 11.9 | 50 | 10.0 | AV | N | GND |


5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



5.1.2. Semi-Anechoic Chamber Test Setup Diagram



5.2.The Emission Limit For Section 15.109 (a)

5.2.1.Radiation Emission Measurement Limits According to Section 15.109 (a).

| Frequency MHz | Distance Meters | Field Strengths Limit | |
|---|--------------------|-----------------------|----------------------------|
| | | $\mu\text{V/m}$ | $\text{dB}(\mu\text{V/m})$ |
| 30-88 | 3 | 100 | 40.0 |
| 88-216 | 3 | 150 | 43.5 |
| 216-960 | 3 | 200 | 46.0 |
| 960-1000 | 3 | 500 | 54.0 |
| Remark: (1) Emission level $\text{dB}(\mu\text{V}) = 20 \log$ Emission level $\mu\text{V/m}$. (2)The smaller limit shall apply at the cross point between two frequency bands. (3)Distance is the distance in meters between the measuring instrument antenna and the closest point of any part of the device or system. | | | |

5.3.EUT Configuration on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.REMOTE CONTROL

Model Number: FAN42R-T190W

Serial Number: N/A

Manufacturer: Carewell Electric Technology (Zhongshan) Co., Ltd.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 4.2.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in test mode (Rx) and measure it.

5.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement.

The bandwidth of the EMI test REMOTE CONTROL (R&S ESCS30) is set at

120kHz from 30MHz to 1000MHz.

The frequency range from 30MHz to 2000MHz is checked.

5.6.Radiated Emission Noise Measurement Result

PASS.

| | | | | | | | | |
|----------------------------|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|
| Model Number: FAN42R-T190W | | | | | | | | |
| Test mode: RX | | | | | | | | |
| Horizontal | No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
| | 1 | 154.2786 | 54.63 | -15.11 | 39.52 | 43.50 | -3.98 | QP |
| | 2 | 291.2906 | 53.03 | -9.53 | 43.50 | 46.00 | -2.50 | QP |
| | 3 | 381.2485 | 50.31 | -7.32 | 42.99 | 46.00 | -3.01 | QP |
| Vertical | No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
| | 1 | 63.4401 | 50.88 | -15.18 | 35.70 | 40.00 | -4.30 | QP |
| | 2 | 154.2786 | 50.90 | -15.11 | 35.79 | 43.50 | -7.71 | QP |
| | 3 | 383.9318 | 47.40 | -7.30 | 40.10 | 46.00 | -5.90 | QP |
| Above 1G | | | | | | | | |
| Horizontal | No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
| | 1 | 1079.393 | 42.02 | -12.80 | 29.22 | 74.00 | -44.78 | peak |
| | 2 | 1413.232 | 41.82 | -11.77 | 30.05 | 74.00 | -43.95 | peak |
| | 3 | 1881.422 | 41.94 | -9.62 | 32.32 | 74.00 | -41.68 | peak |
| Vertical | No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
| | 1 | 1013.988 | 41.80 | -12.66 | 29.14 | 74.00 | -44.86 | peak |
| | 2 | 1238.520 | 41.38 | -12.45 | 28.93 | 74.00 | -45.07 | peak |
| | 3 | 1823.529 | 42.82 | -9.76 | 33.06 | 74.00 | -40.94 | peak |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20150048

Page 16 of 19

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: CAREWELL #10

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: REMOTE CONTROL

Mode: RX

Model: FAN42R-T190W

Manufacturer: CAREWELL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 15/01/06/

Time: 13/46/09

Engineer Signature:Ricky

Distance: 3m

Note: Report NO.:ATE20150048



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|----------------|------------------|--------|
| 1 | 63.4401 | 50.88 | -15.18 | 35.70 | 40.00 | -4.30 | QP | | | |
| 2 | 154.2786 | 50.90 | -15.11 | 35.79 | 43.50 | -7.71 | QP | | | |
| 3 | 383.9318 | 47.40 | -7.30 | 40.10 | 46.00 | -5.90 | QP | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20150048

Page 17 of 19

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: CAREWELL #11

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: REMOTE CONTROL

Mode: RX

Model: FAN42R-T190W

Manufacturer: CAREWELL

Polarization: Horizontal

Power Source: AC 120V/60Hz

Date: 15/01/06/

Time: 13/48/27

Engineer Signature:Ricky

Distance: 3m

Note: Report NO.:ATE20150048



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|----------------|------------------|--------|
| 1 | 154.2786 | 54.63 | -15.11 | 39.52 | 43.50 | -3.98 | QP | | | |
| 2 | 291.2906 | 53.03 | -9.53 | 43.50 | 46.00 | -2.50 | QP | | | |
| 3 | 381.2485 | 50.31 | -7.32 | 42.99 | 46.00 | -3.01 | QP | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20150048

Page 18 of 19

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY2015 #25

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: REMOTE CONTROL

Mode: RX

Model: FAN42R-T190W

Manufacturer: CAREWELL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 15/01/07/

Time: 10/00/40

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20150048



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|----------------|------------------|--------|
| 1 | 1079.393 | 42.02 | -12.80 | 29.22 | 74.00 | -44.78 | peak | | | |
| 2 | 1413.232 | 41.82 | -11.77 | 30.05 | 74.00 | -43.95 | peak | | | |
| 3 | 1881.422 | 41.94 | -9.62 | 32.32 | 74.00 | -41.68 | peak | | | |



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20150048

Page 19 of 19

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY2015 #26

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: REMOTE CONTROL

Mode: RX

Model: FAN42R-T190W

Manufacturer: CAREWELL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 15/01/07/

Time: 10/01/12

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20150048



| No. | Freq. (MHz) | Reading (dBuV/m) | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Degree (deg.) | Remark |
|-----|----------------|---------------------|----------------|--------------------|-------------------|----------------|----------|----------------|------------------|--------|
| 1 | 1013.988 | 41.80 | -12.66 | 29.14 | 74.00 | -44.86 | peak | | | |
| 2 | 1238.520 | 41.38 | -12.45 | 28.93 | 74.00 | -45.07 | peak | | | |
| 3 | 1823.529 | 42.82 | -9.76 | 33.06 | 74.00 | -40.94 | peak | | | |