



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

RSS-GEN, ISSUE 5, MARCH 2019

RSS-247, ISSUE 2, FEBRUARY 2017

TEST REPORT

For

LEEDARSON LIGHTING CO., LTD.

Xingda Road, Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China

FCC ID:2AB2Q8ZA806STQ4G
IC:10256A-8ZA806STQ4G


| | |
|--|---|
| Report Type: Original Report | Product Name: LED Lamps |
| Report Number: RXM191127050-00B | |
| Report Date: 2020-01-16 | |
| Reviewed By: | Gavin Xu RF Engineer  |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn |

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| MEASUREMENT UNCERTAINTY..... | 5 |
| TEST FACILITY | 5 |
| DECLARATIONS..... | 5 |
| SYSTEM TEST CONFIGURATION..... | 6 |
| DESCRIPTION OF TEST CONFIGURATION | 6 |
| EQUIPMENT MODIFICATIONS | 6 |
| EUT EXERCISE SOFTWARE | 7 |
| SUPPORT CABLE LIST AND DETAILS | 9 |
| BLOCK DIAGRAM OF TEST SETUP | 9 |
| SUMMARY OF TEST RESULTS..... | 10 |
| FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)..... | 11 |
| APPLICABLE STANDARD | 11 |
| RSS-102 § 2.5.2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION – RF EXPOSURE EVALUATION | 12 |
| APPLICABLE STANDARD | 12 |
| FCC §15.203& RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT | 13 |
| APPLICABLE STANDARD | 13 |
| ANTENNA INFORMATION AND CONNECTOR CONSTRUCTION..... | 14 |
| FCC §15.207 (a) & RSS-GEN CLAUSE 8.8– AC LINE CONDUCTED EMISSIONS..... | 15 |
| APPLICABLE STANDARD | 15 |
| EUT SETUP | 15 |
| EMI TEST RECEIVER SETUP..... | 15 |
| TEST PROCEDURE | 16 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 16 |
| TEST EQUIPMENT LIST AND DETAILS..... | 16 |
| TEST DATA | 16 |
| FCC §15.209, §15.205, §15.247(d) & RSS-247 CLAUSE 5.5, RSS-GEN CLAUSE 8.10- SPURIOUS EMISSIONS..... | 19 |
| APPLICABLE STANDARD | 19 |
| EUT SETUP | 19 |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 20 |
| TEST PROCEDURE | 20 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 20 |
| TEST EQUIPMENT LIST AND DETAILS..... | 21 |
| TEST DATA | 21 |
| FCC §15.247(a) (2) & RSS-247 CLAUSE 5.2 a) &RSS-GEN CLAUSE 6.7–6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH | 27 |
| APPLICABLE STANDARD | 27 |
| TEST PROCEDURE | 28 |
| TEST EQUIPMENT LIST AND DETAILS..... | 28 |
| TEST DATA | 29 |
| FCC §15.247(b) (3)& RSS-247 CLAUSE 5.4 d) - MAXIMUM PEAK CONDUCTED OUTPUT POWER | 34 |
| APPLICABLE STANDARD | 34 |
| TEST PROCEDURE | 34 |

| | |
|---|-----------|
| TEST EQUIPMENT LIST AND DETAILS..... | 34 |
| TEST DATA | 35 |
| FCC §15.247(d)& RSS-247 CLAUSE 5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE..... | 36 |
| APPLICABLE STANDARD | 36 |
| TEST PROCEDURE | 36 |
| TEST EQUIPMENT LIST AND DETAILS..... | 37 |
| TEST DATA | 37 |
| FCC §15.247(e) & RSS-247 CLAUSE 5.2 b - POWER SPECTRAL DENSITY | 39 |
| APPLICABLE STANDARD | 39 |
| TEST PROCEDURE | 39 |
| TEST EQUIPMENT LIST AND DETAILS..... | 39 |
| TEST DATA | 40 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|--|--|
| EUT Name: | LED Lamps |
| EUT Model: | 8ZA-A806ST-Q4G |
| Multiple Models: | 8Zy-A806ST-Q4G, AE 280 C, 8ZB-A806ST-Q4G, 8ZC-A806ST-Q4G |
| Operation Frequency: | 2405-2480MHz |
| Maximum Output Power (Conducted): | 13.79 dBm |
| Rated Input Voltage: | AC 120V |
| Serial Number: | RXM191127050-RF-S1 |
| EUT Received Date: | 2019.11.27 |
| EUT Status: | Good |

Note:

Model **8ZA-A806ST-Q4G** was selected for fully testing, the detailed information about the difference among **8Zy-A806ST-Q4G**, **AE 280 C**, **8ZB-A806ST-Q4G**, **8ZC-A806ST-Q4G** and model **8ZA-A806ST-Q4G** can be referred to the declaration letter which was stated and guaranteed by the manufacturer.

Objective

This report is prepared on behalf of **LEEDARSON LIGHTING CO., LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A, and C of the Federal Communications Commission's rules and RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, March 2019 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209, 15.247 rules and RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, March 2019 of the Innovation, Science and Economic Development Canada.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 15.247 Meas Guidance v05, and RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, March 2019 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

| Parameter | Measurement Uncertainty |
|-----------------------------------|--|
| Occupied Channel Bandwidth | ±5 % |
| RF output power, conducted | ±0.61dB |
| Power Spectral Density, conducted | ±0.61 dB |
| Unwanted Emissions, radiated | 30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB |
| Unwanted Emissions, conducted | ±1.5 dB |
| Temperature | ±1 °C |
| Humidity | ±5% |
| DC and low frequency voltages | ±0.4% |
| Duty Cycle | 1% |
| AC Power Lines Conducted Emission | 3.12 dB (150 kHz to 30 MHz) |

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk "★".

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

The device supports Zigbee, 16 channels are provided for testing.

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 11 | 2405 | 19 | 2445 |
| 12 | 2410 | ... | ... |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| .. | ... | 25 | 2475 |
| 18 | 2440 | 26 | 2480 |

EUT was tested with channel 11, 18, 25 and 26.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


Test software: 'UartAssist.exe' was used for testing, which were provided by manufacturer.

| Mode | Channel | Frequency (MHz) | Power level |
|--------|------------|-----------------|-------------|
| Zigbee | Low | 2405 | 13 |
| | Middle | 2440 | 13 |
| | Additional | 2475 | 13 |
| | High | 2480 | 8 |

The maximum duty cycle as following table:

| Test mode | T _{on} (ms) | T _{on+off} (ms) | Duty Cycle (%) |
|-----------|----------------------|--------------------------|----------------|
| ZigBee | 3.210 | 21.447 | 14.97 |


Duty Cycle



Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To |
|-------------------|----------------|--------------|------------|--------------|-----|
| Power Cable | No | No | 1 | Power Source | EUT |

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| Rules | Description of Test | Result |
|--|--|------------|
| FCC §15.247 (i) & §1.1310 & §2.1091 | Maximum Permissible Exposure (MPE) | Compliance |
| RSS-102 § 2.5.2 | Exemption Limits For Routine Evaluation-RF Exposure Evaluation | Compliance |
| FCC§15.203, RSS-Gen Clause 6.8 | Antenna Requirement | Compliance |
| FCC§15.207 (a), RSS-Gen Clause 8.8 | AC Line Conducted Emissions | Compliance |
| FCC§15.205, §15.209, FCC §15.247(d), RSS-247 Clause 5.5 RSS-Gen Clause 8.10 | Spurious Emissions | Compliance |
| FCC§15.247 (a)(2), RSS-247 Clause 5.2 a) RSS-Gen Clause 6.7 | 6 dB Bandwidth | Compliance |
| FCC§15.247(b)(3), RSS-247 Clause 5.4 d) | Maximum Conducted Output Power | Compliance |
| FCC§15.247(d), RSS-247 Clause 5.5 | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| FCC§15.247(e), RSS-247 Clause 5.2 b) | Power Spectral Density | Compliance |

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | / | / | f/1500 | 30 |
| 1500–100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

| Frequency (MHz) | Antenna Gain | | Max.Target Power including Tolerance | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|-----------------|--------------|-----------|--------------------------------------|-------|--------------------------|-------------------------------------|---------------------------------|
| | (dBi) | (numeric) | (dBm) | (mW) | | | |
| 2405-2480 | -1 | 0.79 | 14 | 25.12 | 20.00 | 0.0039 | 1.0 |

Result: The device meet FCC MPE at 20 cm distance

RSS-102 § 2.5.2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION – RF EXPOSURE EVALUATION

Applicable Standard

According to RSS-102 § (2.5.2):

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

The maximum power including tune-up tolerance is 14dBm@ 2.4GHz band, the maximum antenna gain is -1 dBi, so the maximum e.i.r.p. is 13dBm (0.02W)

Exemption from Routine Evaluation Limit is:

$$1.31 \times 10^{-2} f^{0.6834} = 1.31 \times 10^{-2} \times 2405^{0.6834} = 2.68 > 0.02W$$

So the device is compliance exemption from Routine Evaluation Limits –RF exposure Evaluation.

Result: Compliance

FCC §15.203& RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC§ 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

According to RSS-Gen §6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Information And Connector Construction

The EUT has one internal antenna arrangement for Zigbee, fulfill the requirement of this section. Please refer to the EUT photos and below information:

| Antenna Type | input impedance (Ohm) | Antenna Gain /Frequency |
|--------------|--------------------------|----------------------------|
| Monopole | 50 | -1 dBi |


Result: Compliance.

FCC §15.207 (a) & RSS-GEN CLAUSE 8.8– AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a), RSS-Gen§8.8.

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 and the RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|-----------|---------------|------------------|----------------------|
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0200-01 | 2019-09-05 | 2020-09-05 |
| R&S | Test Software | EMC32 | Version8.53.0 | N/A | N/A |
| R&S | Two-line V-network | ENV 216 | 101614 | 2018-12-10 | 2019-12-10 |
| R&S | EMI Test Receiver | ESPI | 100120 | 2019-05-09 | 2020-05-09 |


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


| | |
|--------------------|------------|
| Temperature: | 21.2°C |
| Relative Humidity: | 26% |
| ATM Pressure: | 100.8kPa |
| Tester: | Sem Xiang |
| Test Date: | 2019-12-04 |

Test Mode: Transmitting (low channel was the worst case)

AC120 V, 60 Hz, Line:

| Frequency (MHz) | QuasiPeak (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|------------------------|-----------------|------|------------|-------------|--------------------|
| 0.150000 | 54.6 | 9.000 | L1 | 11.2 | 11.4 | 66.0 |
| 0.256712 | 38.9 | 9.000 | L1 | 10.3 | 22.6 | 61.5 |
| 0.434989 | 28.8 | 9.000 | L1 | 9.9 | 28.4 | 57.2 |
| 0.744445 | 18.1 | 9.000 | L1 | 9.8 | 37.9 | 56.0 |
| 1.666725 | 9.5 | 9.000 | L1 | 9.7 | 46.5 | 56.0 |
| 2.314565 | 10.1 | 9.000 | L1 | 9.8 | 45.9 | 56.0 |

| Frequency (MHz) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|----------------------|-----------------|------|------------|-------------|--------------------|
| 0.188575 | 39.3 | 9.000 | L1 | 10.7 | 14.8 | 54.1 |
| 0.283569 | 25.9 | 9.000 | L1 | 10.2 | 24.8 | 50.7 |
| 0.475741 | 13.6 | 9.000 | L1 | 9.9 | 32.8 | 46.4 |
| 0.767003 | 8.3 | 9.000 | L1 | 9.8 | 37.7 | 46.0 |
| 1.286792 | 7.9 | 9.000 | L1 | 9.8 | 38.1 | 46.0 |
| 2.456957 | 6.3 | 9.000 | L1 | 9.8 | 39.7 | 46.0 |



AC120 V, 60 Hz, Neutral:

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|
| 0.150000 | 54.7 | 9.000 | N | 11.2 | 11.3 | 66.0 |
| 0.256712 | 39.5 | 9.000 | N | 10.3 | 22.0 | 61.5 |
| 0.434989 | 30.2 | 9.000 | N | 9.9 | 27.0 | 57.2 |
| 0.737074 | 20.7 | 9.000 | N | 9.8 | 35.3 | 56.0 |
| 1.248947 | 11.6 | 9.000 | N | 9.8 | 44.4 | 56.0 |
| 16.435388 | 18.2 | 9.000 | N | 9.9 | 41.8 | 60.0 |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|
| 0.184859 | 38.3 | 9.000 | N | 10.7 | 16.0 | 54.3 |
| 0.277982 | 24.9 | 9.000 | N | 10.2 | 26.0 | 50.9 |
| 0.466367 | 14.2 | 9.000 | N | 9.9 | 32.4 | 46.6 |
| 1.119461 | 9.0 | 9.000 | N | 9.8 | 37.0 | 46.0 |
| 1.286792 | 8.1 | 9.000 | N | 9.8 | 37.9 | 46.0 |
| 16.435388 | 11.7 | 9.000 | N | 9.9 | 38.3 | 50.0 |

FCC §15.209, §15.205, §15.247(d) & RSS-247 CLAUSE 5.5, RSS-GEN CLAUSE 8.10- SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205, RSS-247 §5.5, RSS-GEN §8.10.

EUT Setup**Below 1GHz:****Above 1GHz:**

The radiated emission tests were performed in the 10 meters chamber for the range 30MHz to 1GHz and the 3 meters chamber B test site for above 1GHz, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247, the RSS-247 §5.5, RSS-Gen §8.10 limits..

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

| Measurement | RBW | Video B/W | IF B/W |
|-------------|---------|-----------|--------|
| QP | 120 kHz | 300 kHz | 120kHz |

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

1GHz- 25GHz:

| Measurement | Duty cycle | RBW | Video B/W |
|-------------|------------|------|-----------|
| PK | Any | 1MHz | 3 MHz |
| Ave. | >98% | 1MHz | 10 Hz |
| | <98% | 1MHz | 1/T |

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details


| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-------------------------------|-------------------|--------------------------|----------------------|------------------|----------------------|
| Radiated emissions Below 1GHz | | | | | |
| R&S | EMI Test Receiver | ESCI | 100035 | 2019-08-03 | 2020-08-03 |
| Farad | Test Software | EZ-EMC | V1.1.4.2 | N/A | N/A |
| Sunol Sciences | Antenna | JB3 | A060611-3 | 2017-07-21 | 2020-07-21 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-1000-01 | 2019-09-05 | 2020-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0400-02 | 2019-09-05 | 2020-09-05 |
| Unknown | Coaxial Cable | C-NJNJ-50 | C-0530-01 | 2019-09-24 | 2020-09-24 |
| Sonoma | Amplifier | 310N | 185914 | 2019-10-13 | 2020-10-13 |
| Radiated emissions Above 1GHz | | | | | |
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2019-05-09 | 2020-05-09 |
| Farad | Test Software | EZ-EMC | V1.1.4.2 | N/A | N/A |
| TDK RF | Horn Antenna | HRN-0118 | 130 084 | 2018-10-12 | 2021-10-12 |
| Ducommun Technologies | Horn Antenna | ARH-4223-02 | 1007726-01 1304 | 2017-12-06 | 2020-12-05 |
| MICRO-COAX | Coaxial Cable | UFA147-1-2362- 100100 | 64639 231029- 001 | 2019-02-24 | 2020-02-24 |
| Mini | Pre-amplifier | ZVA-183-S+ | 5969001149 | 2019-09-05 | 2020-09-05 |
| Quinstar | Amplifier | QLW-18405536-JO | 15964001001 | 2019-06-27 | 2020-06-27 |
| E-Microwave | Band-stop Filters | OBSF-2400-2483.5- S | OE01601525 | 2019-06-16 | 2020-06-16 |
| Micro-tronics | High Pass Filter | HPM50111 | S/N-G217 | 2019-06-16 | 2020-06-16 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

| Test Items | Radiation Below 1GHz | Radiation Above 1GHz |
|--------------------|----------------------|----------------------|
| Temperature: | 22.2°C | 24.2°C |
| Relative Humidity: | 37% | 40% |
| ATM Pressure: | 100.8kPa | 101.1kPa |
| Tester: | Ade Xiao | Tyler Pan |
| Test Date: | 2019-12-04 | 2019-12-03 |

Test Mode: Transmitting

1) 30MHz-1GHz (Low channel was the worst):**Horizontal:**

| Frequency (MHz) | Receiver Reading (dBuV) | Detector | Correction Factor (dB/m) | Cord. Amp. (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|-------------------------|----------|--------------------------|---------------------|----------------|-------------|
| 30.9700 | 27.99 | peak | -4.88 | 23.11 | 40.00 | 16.89 |
| 144.4600 | 31.78 | peak | -9.18 | 22.60 | 43.50 | 20.90 |
| 307.4200 | 34.83 | peak | -7.15 | 27.68 | 46.00 | 18.32 |
| 356.8900 | 34.53 | peak | -6.30 | 28.23 | 46.00 | 17.77 |
| 554.7700 | 27.80 | peak | -1.68 | 26.12 | 46.00 | 19.88 |
| 705.1200 | 27.64 | peak | 0.05 | 27.69 | 46.00 | 18.31 |

Vertical:

| Frequency (MHz) | Receiver Reading (dBuV) | Detector | Correction Factor (dB/m) | Cord. Amp. (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|-------------------------|----------|--------------------------|---------------------|----------------|-------------|
| 44.5500 | 45.67 | peak | -12.62 | 33.05 | 40.00 | 6.95 |
| 118.2700 | 38.44 | peak | -12.84 | 25.60 | 43.50 | 17.90 |
| 221.0900 | 38.17 | peak | -11.07 | 27.10 | 46.00 | 18.90 |
| 307.4200 | 34.24 | peak | -7.15 | 27.09 | 46.00 | 18.91 |
| 453.8900 | 28.91 | peak | -4.20 | 24.71 | 46.00 | 21.29 |
| 768.1700 | 26.63 | peak | 1.08 | 27.71 | 46.00 | 18.29 |




2) 1-25GHz:

| Frequency (MHz) | Receiver | | Rx Antenna | | Cable loss (dB) | Amplifier Gain (dB) | Corrected Amplitude (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|------------------------------|-------------------|--------|----------------|------------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
| | Reading (dBμV) | Remark | Polar (H/V) | Factor (dB/m) | | | | | |
| Low Channel: 2405 MHz | | | | | | | | | |
| 2405.00 | 74.93 | PK | H | 24.83 | 3.34 | 0.00 | 103.10 | N/A | N/A |
| 2405.00 | 72.31 | AV | H | 24.83 | 3.34 | 0.00 | 100.48 | N/A | N/A |
| 2405.00 | 69.89 | PK | V | 24.83 | 3.34 | 0.00 | 98.06 | N/A | N/A |
| 2405.00 | 67.35 | AV | V | 24.83 | 3.34 | 0.00 | 95.52 | N/A | N/A |
| 2390.00 | 25.41 | PK | H | 24.80 | 3.33 | 0.00 | 53.54 | 74.00 | 20.46 |
| 2390.00 | 13.01 | AV | H | 24.80 | 3.33 | 0.00 | 41.14 | 54.00 | 12.86 |
| 4810.00 | 47.55 | PK | H | 29.72 | 4.58 | 27.38 | 54.47 | 74.00 | 19.53 |
| 4810.00 | 40.29 | AV | H | 29.72 | 4.58 | 27.38 | 47.21 | 54.00 | 6.79 |
| 7215.00 | 38.98 | PK | H | 33.94 | 5.60 | 27.20 | 51.32 | 74.00 | 22.68 |
| 7215.00 | 26.65 | AV | H | 33.94 | 5.60 | 27.20 | 38.99 | 54.00 | 15.01 |
| Middle Channel: 2440 MHz | | | | | | | | | |
| 2440.00 | 73.85 | PK | H | 24.89 | 3.36 | 0.00 | 102.10 | N/A | N/A |
| 2440.00 | 71.21 | AV | H | 24.89 | 3.36 | 0.00 | 99.46 | N/A | N/A |
| 2440.00 | 68.19 | PK | V | 24.89 | 3.36 | 0.00 | 96.44 | N/A | N/A |
| 2440.00 | 65.67 | AV | V | 24.89 | 3.36 | 0.00 | 93.92 | N/A | N/A |
| 4880.00 | 45.80 | PK | H | 29.86 | 4.56 | 27.55 | 52.67 | 74.00 | 21.33 |
| 4880.00 | 38.99 | AV | H | 29.86 | 4.56 | 27.55 | 45.86 | 54.00 | 8.14 |
| 7320.00 | 39.16 | PK | H | 34.11 | 5.69 | 27.26 | 51.70 | 74.00 | 22.30 |
| 7320.00 | 26.79 | AV | H | 34.11 | 5.69 | 27.26 | 39.33 | 54.00 | 14.67 |
| Additional Channel: 2475 MHz | | | | | | | | | |
| 2475.00 | 73.22 | PK | H | 24.96 | 3.38 | 0.00 | 101.56 | N/A | N/A |
| 2475.00 | 70.65 | AV | H | 24.96 | 3.38 | 0.00 | 98.99 | N/A | N/A |
| 2475.00 | 68.19 | PK | V | 24.96 | 3.38 | 0.00 | 96.53 | N/A | N/A |
| 2475.00 | 65.76 | AV | V | 24.96 | 3.38 | 0.00 | 94.10 | N/A | N/A |
| 2483.50 | 26.53 | PK | H | 24.97 | 3.38 | 0.00 | 54.88 | 74.00 | 19.12 |
| 2483.50 | 14.62 | AV | H | 24.97 | 3.38 | 0.00 | 42.97 | 54.00 | 11.03 |
| 4950.00 | 46.21 | PK | H | 30.00 | 4.58 | 27.41 | 53.38 | 74.00 | 20.62 |
| 4950.00 | 38.78 | AV | H | 30.00 | 4.58 | 27.41 | 45.95 | 54.00 | 8.05 |
| 7425.00 | 38.64 | PK | H | 34.28 | 5.78 | 27.20 | 51.50 | 74.00 | 22.50 |
| 7425.00 | 26.10 | AV | H | 34.28 | 5.78 | 27.20 | 38.96 | 54.00 | 15.04 |
| High Channel: 2480 MHz | | | | | | | | | |
| 2480.00 | 70.20 | PK | H | 24.96 | 3.38 | 0.00 | 98.54 | N/A | N/A |
| 2480.00 | 67.16 | AV | H | 24.96 | 3.38 | 0.00 | 95.50 | N/A | N/A |
| 2480.00 | 66.19 | PK | V | 24.96 | 3.38 | 0.00 | 94.53 | N/A | N/A |
| 2480.00 | 63.76 | AV | V | 24.96 | 3.38 | 0.00 | 92.10 | N/A | N/A |
| 2483.50 | 35.54 | PK | H | 24.97 | 3.38 | 0.00 | 63.89 | 74.00 | 10.11 |
| 2483.50 | 22.89 | AV | H | 24.97 | 3.38 | 0.00 | 51.24 | 54.00 | 2.76 |
| 4960.00 | 45.36 | PK | H | 30.02 | 4.58 | 27.37 | 52.59 | 74.00 | 21.41 |
| 4960.00 | 38.34 | AV | H | 30.02 | 4.58 | 27.37 | 45.57 | 54.00 | 8.43 |
| 7440.00 | 38.03 | PK | H | 34.30 | 5.79 | 27.22 | 50.90 | 74.00 | 23.10 |
| 7440.00 | 25.78 | AV | H | 34.30 | 5.79 | 27.22 | 38.65 | 54.00 | 15.35 |

3) Worst Test plots (Low channel was the worst case)




Horizontal

Fundamental
Test with Band
Rejection Filter



Vertical

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2) & RSS-247 CLAUSE 5.2 a) & RSS-GEN CLAUSE 6.7–6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH**Applicable Standard**

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

According to RSS-247 §5.2 a)

The minimum 6 dB bandwidth shall be 500 kHz.

According to RSS-Gen §6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Test Procedure


6dB bandwidth test:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99% Occupied bandwidth test:

Use Occupied bandwidth test function, measure the 99% Occupied bandwidth.

Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|-------------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005 | 2019-09-12 | 2020-09-12 |
| Unknown | Coaxial Cable | C-SJ00-0010 | C0010/03 | Each time | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|----------------------------------|
| Temperature: | 22.9~25.1 °C |
| Relative Humidity: | 34~52% |
| ATM Pressure: | 100.6~102.7 kPa |
| Tester: | Severn Zhu |
| Test Date: | 2019-12-03~2019-12-26&2020-01-15 |

Test Mode: Transmitting



Test Result: Compliance. Please refer to the following table and plots



6dB Bandwidth:



| Mode | Channel | Frequency (MHz) | Result (MHz) | Limit (MHz) |
|--------|------------|-----------------|--------------|-------------|
| ZigBee | Low | 2405 | 1.483 | 0.5 |
| | Middle | 2440 | 1.643 | |
| | Additional | 2475 | 1.543 | |
| | High | 2480 | 1.503 | |



99% Occupied Bandwidth:

| Mode | Channel | Frequency (MHz) | Result (MHz) |
|--------|------------|-----------------|--------------|
| ZigBee | Low | 2405 | 2.224 |
| | Middle | 2440 | 2.224 |
| | Additional | 2475 | 2.224 |
| | High | 2480 | 2.244 |

6dB Bandwidth:**Low Channel****Middle Channel**

Additional Channel-2475MHz**High Channel**

99% Occupied Bandwidth:**Low Channel****Middle Channel**

Additional Channel-2475MHz**High Channel**

FCC §15.247(b) (3)& RSS-247 CLAUSE 5.4 d) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247§5.4 d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(e), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|---------------------------|-------------|---------------|------------------|----------------------|
| Unknown | Coaxial Cable | C-SJ00-0010 | C0010/03 | Each time | N/A |
| Agilent | USB Wideband Power Sensor | U2021XA | MY5425009 | 2019-05-09 | 2020-05-09 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------------------|
| Temperature: | 22.9~24.7 °C |
| Relative Humidity: | 34~47% |
| ATM Pressure: | 100.6~102.7 kPa |
| Tester: | Severn Zhu |
| Test Date: | 2019-12-03~2019-12-19 |

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

| Mode | Channel | Frequency (MHz) | Max Peak Conducted Output Power (dBm) | Limit (dBm) |
|-------------|----------------|------------------------|--|--------------------|
| ZigBee | Low | 2405 | 13.79 | 30 |
| | Middle | 2440 | 13.53 | |
| | Additional | 2475 | 13.00 | |
| | High | 2480 | 8.03 | |

Note: The maximum antenna gain is -1 dBi, so it meets the EIRP limit for ISSED.

FCC §15.247(d)& RSS-247 CLAUSE 5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|-------------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005 | 2019-09-12 | 2020-09-12 |
| Unknown | Coaxial Cable | C-SJ00-0010 | C0010/03 | Each time | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions



| | |
|--------------------|-----------------------|
| Temperature: | 22.9~24.7 °C |
| Relative Humidity: | 34~47% |
| ATM Pressure: | 100.6~102.7 kPa |
| Tester: | Severn Zhu |
| Test Date: | 2019-12-03~2019-12-19 |

Test mode: Transmitting

Test Result: Compliance. Please refer to following plots.

Band Edge, Left Side



Band Edge, Right Side-Additional Channel-2475MHz**Band Edge, Right Side-High Channel**

FCC §15.247(e) & RSS-247 CLAUSE 5.2 b - POWER SPECTRAL DENSITY**Applicable Standard**

According to FCC§15.247(e):For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 §5.2 b):

- b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|-------------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005 | 2019-09-12 | 2020-09-12 |
| Unknown | Coaxial Cable | C-SJ00-0010 | C0010/03 | Each time | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


| | |
|--------------------|-----------------------|
| Temperature: | 22.9~24.7 °C |
| Relative Humidity: | 34~47% |
| ATM Pressure: | 100.6~102.7 kPa |
| Tester: | Severn Zhu |
| Test Date: | 2019-12-03~2019-12-19 |

Test Mode: Transmitting


Test Result: Compliance. Please refer to the following table and plots

| Mode | Channel | Frequency (MHz) | Result (dBm/3kHz) | Limit (dBm/3kHz) |
|--------|------------|-----------------|-------------------|------------------|
| ZigBee | Low | 2405 | 1.32 | 8 |
| | Middle | 2440 | 1.03 | |
| | Additional | 2475 | 0.50 | |
| | High | 2480 | -4.69 | |


Power Spectral Density, Low Channel




Power Spectral Density, Middle Channel



Power Spectral Density, Additional Channel-2475MHz



Power Spectral Density, High Channel



***** END OF REPORT *****