

EDMI INTERNATIONAL TRADING (SHANGHAI) CO., LTD

Handheld Unit

Main Model: HT16

Serial Model: N/A




April 25, 2014

Report No.: 14070090-FCC-R1
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

		
David Huang Compliance Engineer	Alex Liu Technical Manager	

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

RF Test Report

To: FCC 15.249: 2013

SIEMIC, INC.
Accessing global markets



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

SIEMIC (Shenzhen-China) Laboratories Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC , RF/Wireless , Telecom
Canada	EMC, RF/Wireless , Telecom
Taiwan	EMC, RF, Telecom , Safety
Hong Kong	RF/Wireless ,Telecom
Australia	EMC, RF, Telecom , Safety
Korea	EMI, EMS, RF , Telecom, Safety
Japan	EMI, RF/Wireless, Telecom
Singapore	EMC , RF , Telecom
Europe	EMC, RF, Telecom , Safety

This page has been left blank intentionally.

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION.....	7
4	TEST SUMMARY.....	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
	ANNEX A. TEST INSTRUMENT & METHOD	22
	ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	26
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	44
	ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	48
	ANNEX E. DECLARATION OF SIMILARITY	49

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the EDM I INTERNATIONAL TRADING (SHANGHAI) CO., LTD, Handheld Unit and model: HT16 against the current Stipulated Standards. The Handheld Unit has demonstrated compliance with the FCC 15.249: 2013.

EUT Information

EUT Description : Handheld Unit


Main Model : HT16

Serial Model : N/A

Input Power :
Battery:
Model: KAYO0502001
Spec: 3.7V 3200mAh
Limited charger voltage: 4.2V
Adapter:
Model: YC-CDA2
Input: AC 100-240V; 50/60Hz
Output: 5.0V; 2.1A

Classification
Per Stipulated Test Standard : FCC 15.249: 2013

2 TECHNICAL DETAILS

Purpose	Compliance testing of Handheld Unit with stipulated standard
Applicant / Client	EDMI INTERNATIONAL TRADING (SHANGHAI) CO., LTD Room 1504-1508, Tower A, Cao He Jing High-Tech Bldg., 900 Yishan Road, Shanghai 200233, P.R.China
Manufacturer	EDMI INTERNATIONAL TRADING (SHANGHAI) CO., LTD Room 1504-1508, Tower A, Cao He Jing High-Tech Bldg., 900 Yishan Road, Shanghai 200233, P.R.China
Laboratory performing the tests	SIEMIC (Shenzhen-China) Laboratories Zone A, Floor 1, Building 2, Wan Ye Long Technology Park, South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-0755-2601 4629 / 2601 4953 Fax: +86-0755-2601 4953-810 Email: China@siemic.com.cn
Test report reference number	14070090-FCC-R1
Date EUT received	March 19, 2014
Standard applied	FCC 15.249: 2013
Dates of test (from – to)	March 26 to April 24, 2014
No of Units	#1
Equipment Category	DXX
Trade Name	 EDMI
RF Operating Frequency (ies)	915-918.6 MHz
Number of Channels	10
Modulation	GFSK
FCC ID	2AB2ZHT16

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
 All testing has been performed according to below product classification:

Spread Spectrum System/Device

Test Results Summary

Description	Pass / Fail
§15.215(c) 20 dB Bandwidth&99% Occupied Bandwidth	Pass
§15.249(a) Field Strength Measurement	Pass
§15.207(a) Conducted Emissions	Pass
§15.205(a), §15.209(a), §15.249, §15.35. Radiated Emissions(Tx)	Pass
/ Band-Edge	Pass

Channels	Frequency(MHz)
1	915
2	915.4
3	915.8
4	916.2
5	916.6
6	917.0
7	917.4
8	917.8
9	918.2
10	918.6

Note: According with FCC Part 15.31(m), we tested low and high channels.

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 20 dB Bandwidth&99% Occupied Bandwidth

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Environmental Conditions

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1008mbar
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
4. Test date : March 26, 2014
Tested By : David Huang

Standard Requirement:

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

Procedures:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel, RBW $\geq 1\%$ of the 20 dB bandwidth, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold.
4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.


Test Result: Pass

Test Mode:	Transmitting
-------------------	---------------------


Channel	Frequency (MHz)	20dB Bandwidth (KHz)	99% Occupied Bandwidth (KHz)
Low	915	82.024	77.3008
High	918.6	82.058	80.9011

The 20dB&99% bandwidth:

Low Channel



High Channel



5.2 Field Strength Measurement

1. Radiated Measurement
- EUT was set for low, mid, high channel with modulated mode and highest RF output power.
2. Radiated Emissions Measurement Uncertainty
- All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ±1.5dB.
3. Environmental Conditions
- Temperature22°C

Relative Humidity57%

Atmospheric Pressure1008mbar
4. Test date : April 24, 2014
- Tested By : David Huang

Standard Requirement:

Fundamental frequency	Field strength of fundamental (millivolts/ meter)	Field strength of harmonics (microvolts/ meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

Procedures:

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Test Result: Pass

Test Mode:	Transmitting
-------------------	---------------------

Fundamental Field Strength:

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
915	72.50	QP	H	22.5	0.9	22	73.90	94	-20.10
915	80.60	QP	V	22.5	0.9	22	82.0	94	-12.0
918.6	73.40	QP	H	22.5	0.9	22	74.80	94	-19.20
918.6	83.60	QP	V	22.5	0.9	22	85.0	94	-9.0

5.3 Conducted emissions Test Result

Standard Requirement:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Procedures:

- All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ± 3.5 dB.
- Environmental Conditions

Temperature	19°C
Relative Humidity	55%
Atmospheric Pressure	1007mbar
- Test date : April 02, 2014
Tested By : David Huang

Test Result: Pass

Test Mode: Running

Peak Detector




Quasi Peak Limit



Average Detector



Average Limit




Test Data

Phase Line Plot at 120V AC, 60Hz

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.52	48.62	56.00	-7.38	42.53	46.00	-3.47	10.56
0.15	52.51	66.00	-13.49	27.07	56.00	-28.93	12.49
0.94	41.61	56.00	-14.39	36.45	46.00	-9.55	10.33
0.84	40.89	56.00	-15.11	35.76	46.00	-10.24	10.37
1.22	37.08	56.00	-18.92	32.33	46.00	-13.67	10.30
3.74	34.24	56.00	-21.76	29.37	46.00	-16.63	10.76

Test Mode:	Running
------------	---------

Peak Detector  Quasi Peak Limit 
 Average Detector  Average Limit 



Test Data

Phase Natural Plot at 120V AC, 60Hz

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.16	55.73	65.47	-9.73	31.80	55.47	-23.66	12.43
0.51	45.85	56.00	-10.15	41.28	46.00	-4.72	10.57
0.94	39.63	56.00	-16.37	35.41	46.00	-10.59	10.33
0.84	39.24	56.00	-16.76	35.05	46.00	-10.95	10.37
1.31	36.18	56.00	-19.82	32.85	46.00	-13.15	10.31
4.94	30.49	56.00	-25.51	26.71	46.00	-19.29	10.98

5.4 Radiated Emissions (TX)

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (3m & 10m) & 1GHz above (3m) is +5.6/-4.5dB.
4. Environmental Conditions

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1009mbar
5. Test date : April 18 to April 24, 2014
Tested By : David Huang

Standard Requirement:


The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.

The spurious emission scanned frequency range is 30MHz – 25GHz.

Test Result: Pass

Test Mode: Transmitting

Below 1GHz



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H/V)	Height (cm)	Factors (dB)	Limit (dBuV)	Margin (dB)
918.61	89.18	25.00	V	126.00	5.06	46.00	43.18
149.84	42.59	195.00	V	101.00	-7.53	43.52	-0.93
205.33	39.43	85.00	H	146.00	-8.04	43.52	-4.09
172.03	39.71	250.00	V	107.00	-8.59	43.52	-3.81
138.81	37.37	178.00	V	103.00	-7.02	43.52	-6.15
271.96	41.80	191.00	V	169.00	-7.08	46.00	-4.20

Test Mode:	Transmitting
-------------------	---------------------

Above 1 GHz

Low Channel (915 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Direction (degree)	Height (m)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1830	37.89	PK	240	1	V	28.41	1.8	24	44.10	74	-29.90
1830	36.55	AV	240	1	V	28.41	1.8	24	42.76	54	-11.24
1830	48.89	PK	345	1	H	28.41	1.8	24	55.10	74	-18.90
1830	46.48	AV	345	1	H	28.41	1.8	24	52.69	54	-1.31
2745	36.55	PK	228	1	V	30.35	3.67	24	46.57	74	-27.43
2745	34.22	AV	228	1	V	30.35	3.67	24	44.24	54	-9.76
2745	38.10	PK	182	1	H	30.35	3.67	24	48.12	74	-25.88
2745	36.55	AV	182	1	H	30.35	3.67	24	46.57	54	-7.43
2282	39.07	PK	232	1	V	29.24	3.63	24	47.94	74	-26.06
2282	37.54	AV	232	1	V	29.24	3.63	24	46.41	54	-7.59
2282	40.68	PK	187	1	H	29.24	3.63	24	49.55	74	-24.45
2282	37.11	AV	187	1	H	29.24	3.63	24	45.98	54	-8.02

High Channel (918.6 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Direction (degree)	Height (m)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1837.2	41.60	PK	94.4	1	V	28.41	1.8	24	47.81	74	-26.19
1837.2	36.36	AV	94.4	1	V	28.41	1.8	24	42.57	54	-11.43
1837.2	49.18	PK	161.4	1	H	28.41	1.8	24	55.39	74	-18.61
1837.2	46.87	AV	161.4	1	H	28.41	1.8	24	53.08	54	-0.92
2755.8	39.22	PK	128	1	V	30.35	3.67	24	49.24	74	-24.76
2755.8	35.46	AV	128	1	V	30.35	3.67	24	45.48	54	-8.52
2755.8	36.99	PK	172	1	H	30.35	3.67	24	47.01	74	-26.99
2755.8	35.81	AV	172	1	H	30.35	3.67	24	45.83	54	-8.17
2282	47.92	PK	186	1	V	29.24	3.63	24	56.79	74	-17.21
2282	43.55	AV	186	1	V	29.24	3.63	24	52.42	54	-1.58
1604	40.80	PK	145	1	H	28.41	1.6	24	46.81	74	-27.19
1604	38.55	AV	145	1	H	28.41	1.6	24	44.56	54	-9.44

Spurious emissions in restricted band for FCC:

The Spurious Emission was checked in restricted band. No emissions were found and only noise floor.

5.5 Band-Edge

1. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required.
2. Environmental Conditions

Temperature	20°C
Relative Humidity	60%
Atmospheric Pressure	1008mbar
3. Test date : April 01, 2014
Tested By : David Huang


Procedures: (Radiated Method Only)

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the rotated table inside the anechoic chamber without connection to measurement instrument. Turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. Repeat above procedures until all measured frequencies were complete.
3. Set band RBW=1MHz, VBW=3MHz with a convenient frequency span from band edge.
4. Find the highest point in edge frequency, and then calculated results.
5. Repeat above procedures until all measured frequencies were complete.

Test Result: Pass


Please refer to the following tables and plots.

Band Edge, 960M-1G (Peak)




Note: Because the Pk<54 dBμV, it is not need to be test against in QP detector.

Band Edge, 1G-1.24G (Average)



Date: 1.APR.2014 14:46:30

Band Edge, 1G-1.24G (Peak)



Date: 1.APR.2014 14:47:16

Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Serial #	Calibration Date	Calibration Due Date
AC Line Conducted Emissions				
EMI test receiver	ESCS30	8471241027	05/27/2013	05/26/2014
Line Impedance Stabilization Network	LI-125A	191106	11/14/2013	11/13/2014
Line Impedance Stabilization Network	LI-125A	191107	11/14/2013	11/13/2014
LISN	ISN T800	34373	01/11/2014	01/10/2015
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	11/20/2013	11/19/2014
Transient Limiter	LIT-153	531118	09/02/2013	09/01/2014
RF conducted test				
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/17/2013	09/16/2014
Power Splitter	1#	1#	09/02/2013	09/01/2014
DC Power Supply	E3640A	MY40004013	09/17/2013	09/16/2014
Wireless Connectivity Test Set	N4010A	GB44440198	03/20/2014	03/19/2015

Annex A. ii. RADIATED EMISSIONS TEST DESCRIPTION

Limit

- Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

- In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured was complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Description of Radiated Emissions Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan on four different antenna heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 MHz to 1 GHz scan; the program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate parts of maximum hold sweeps. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees table rotation. After the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step will repeated for all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization process and pre-scan routine. The final measurement will be base on the pre-scan data reduction result.

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz, VBW} = 10\text{Hz.}$$

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph 1: EUT External Photo



Whole Package - Top View



Adapter – Front View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT – Right View

Annex B.i. Photograph 2: EUT Internal Photo




Cover Off - Front View 1




Cover Off - Front View 2




Cover Off - Front View 3




Battery -Front View




Mainboard –Front View




Mainboard –Rear View




Keyboard –Front View




Keyboard –Rear View




Connecting board –Front View




Connecting board –Rear View




Battery Connecting board –Front View




Battery Connecting board –Rear View




RF Baseboard –Front View




RF Baseboard –Rear View




RF Module –Front View




RF Module –Rear View




Antenna –Front View




Antenna –Rear View



LCD –Front View




LCD –Rear View




Shielding board –Front View



USB Cable– Front View



USB board - Front View



USB board – Rear View


Annex B.iii. Photograph 1: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz - Front View



Radiated Spurious Emissions Test Setup Above 1GHz –Front View

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
N/A	N/A	N/A

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was continuously transmitting to stimulate the worst case.

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

Annex E. DECLARATION OF SIMILARITY

NONE