



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	AIPTEK International Inc.
Applicant Address	2F, No.58, Park Avenue 2nd Rd., Science-Based Industrial Park, Hsinchu 30844, Taiwan, R.O.C
FCC ID	2AB5H-RV7001
Manufacturer's company	AIPTEK International Inc.
Manufacturer Address	2F, No.58, Park Avenue 2nd Rd., Science-Based Industrial Park, Hsinchu 30844, Taiwan, R.O.C

Product Name	PocketCinema V150W
Brand Name	AIPTEK
Model No.	RV7
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Nov. 26, 2013
Final Test Date	Dec. 26, 2013
Submission Type	Original Equipment

### Statement

**Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	5
3.5. Table for Test Modes .....	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units .....	7
3.8. Table for Parameters of Test Software Setting .....	8
3.9. EUT Operation during Test .....	8
3.10. Duty Cycle.....	9
3.11. Test Configurations .....	11
<b>4. TEST RESULT .....</b>	<b>14</b>
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. Maximum Conducted Output Power Measurement.....	18
4.3. Power Spectral Density Measurement .....	21
4.4. 6dB Spectrum Bandwidth Measurement .....	26
4.5. Radiated Emissions Measurement .....	31
4.6. Emissions Measurement .....	50
4.7. Antenna Requirements .....	68
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>69</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>71</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A5</b>


## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3N2681-01	Rev. 01	Initial issue of report	Apr. 03, 2014

## 1. CERTIFICATE OF COMPLIANCE

Product Name : PocketCinema V150W  
Brand Name : AIPTEK  
Model No. : RV7  
Applicant : AIPTEK International Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 26, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	6.69 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	10.22 dB
4.3	15.247(e)	Power Spectral Density	Complies	13.95 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.01 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.55 dB
4.7	15.203	Antenna Requirements	Complies	-

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 17.84 MHz ; MCS0 (40MHz): 36.32 MHz
Maximum Conducted Output Power	MCS0 (20MHz): 19.78 dBm ; MCS0 (40MHz): 19.65 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.04 MHz ; 11g: 16.56 MHz
Maximum Conducted Output Power	11b: 12.37 dBm ; 11g: 19.28 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

### Antenna and Band width

Antenna	Single (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

### IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	1	MCS 0-7
802.11n (HT40)	1	MCS 0-7
<p>Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.</p> <p>Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n</p>		

## 3.2. Accessories

Power	Brand	Model	Rating
Adapter	SUNNY	SYS1357-2412	INPUT:100-240V ~ 1.0A MAX, 50-60Hz OUTPUT:12V, 2.0A
Lithium Ion Polymer(LIP) battery	Power Source Energy	H604070-2S	Typical Capacity: 2000mAh Minimum Capacity: 1900mAh Nominal Voltage: 7.4V
Others			
HDMI Cable, Shield 1.2m			
HDMI Cable (HDMI to MICRO USB Cable), Shield 0.9m			
AV Cable, Non-Shield 0.3m			
USB Cable, Shield 0.9m			
Remote Controller			

### 3.3. Table for Filed Antenna

Ant.	Brand Hold	Model Name	Antenna Type	Connector	Gain (dBi)
1	Advanced Ceramic X	AT3216-B2R7HAA	Chip Antenna	N/A	0.5

Note:

For IEEE 802.11b/g/n mode (1TX/1RX):

Only Ant. 1 can be used as transmitting antenna and receiving antenna.



### 3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-



### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	802.11n 20MHz	MCS0	1/6/11	1
	802.11n 40MHz	MCS0	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	802.11n 20MHz	MCS0	1/6/11	1
	802.11n 40MHz	MCS0	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	802.11n 20MHz	MCS0	1/6/11	1
	802.11n 40MHz	MCS0	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	802.11n 20MHz	MCS0	1/6/11	1
	802.11n 40MHz	MCS0	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	802.11n 20MHz	MCS0	1/6/11	1
	802.11n 40MHz	MCS0	3/6/9	1
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Supporting Units

For Test Site No: 03CH01-CB

For Radiated Emission below 1GHz test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	DoC
Flash Disk	Silicon	D33B01	DoC
SD Card	N/A	N/A	N/A

For Radiated Emission above 1GHz test:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	DoC

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6400	DoC
Flash Disk	Silicon	D33B01	DoC
SD Card	N/A	N/A	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	QDS-BRCM1049LE

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n

Test Software Version	Realtek 11n Single Chip 92C USB WLAN MP Diagnostic Program 0.0028.1102.2011		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	55	61	62
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	53	63	63

#### Power Parameters of IEEE 802.11b/g


Test Software Version	Realtek 11n Single Chip 92C USB WLAN MP Diagnostic Program 0.0028.1102.2011		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	35	37	37
IEEE 802.11g	53	60	60

### 3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


### 3.10. Duty Cycle

#### IEEE 802.11n MCS0 20MHz




Date: 26.DEC.2013 02:07:56

#### IEEE 802.11n MCS0 40MHz




Date: 26.DEC.2013 02:07:30

# IEEE 802.11b



Date: 26.DEC.2013 02:08:56


# IEEE 802.11g



Date: 26.DEC.2013 02:08:14

### 3.11. Test Configurations


#### 3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length(m)
1	AC power Cable	No	1.4
2	USB Cable	Yes	0.9
3	VGA Cable	No	1.8
4	HDMI Cable	Yes	1.8
5	AV Cable	No	1.8
6	AC Power Cable	No	2.6


### 3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shield	Length(m)
1	AC power Cable	No	1.4
2	USB Cable	Yes	0.9
3	VGA Cable	No	1.8
4	HDMI Cable	Yes	1.8
5	AV Cable	No	1.8
6	AC Power Cable	No	2.6

## Test Configuration: above 1GHz



Item	Connection	Shield	Length(m)
1	AC power Cable	No	1.4
2	USB Cable	Yes	0.9



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



##### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	51%
Test Engineer	Justin Chiu	Phase	Line
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15240	23.68	-32.19	55.87	23.37	0.15	0.16	LINE	AVERAGE
2	0.15240	43.83	-22.04	65.87	43.52	0.15	0.16	LINE	QP
3	0.17034	33.13	-21.81	54.94	32.82	0.15	0.16	LINE	AVERAGE
4 B	0.17034	58.25	-6.69	64.94	57.94	0.15	0.16	LINE	QP
5	0.22201	48.33	-14.42	62.74	48.01	0.15	0.17	LINE	QP
6	0.22201	15.57	-37.18	52.74	15.25	0.15	0.17	LINE	AVERAGE
7	0.30834	42.51	-17.50	60.02	42.19	0.15	0.17	LINE	QP
8	0.30834	31.89	-18.12	50.02	31.57	0.15	0.17	LINE	AVERAGE
9	0.42150	39.74	-17.68	57.42	39.41	0.15	0.18	LINE	QP
10	0.42150	27.22	-20.20	47.42	26.89	0.15	0.18	LINE	AVERAGE
11	1.426	34.71	-21.29	56.00	34.31	0.17	0.23	LINE	QP
12	1.426	25.22	-20.78	46.00	24.82	0.17	0.23	LINE	AVERAGE
13	16.398	29.05	-30.95	60.00	28.06	0.52	0.47	LINE	QP
14	16.398	22.31	-27.69	50.00	21.32	0.52	0.47	LINE	AVERAGE

Temperature	25°C	Humidity	51%
Test Engineer	Justin Chiu	Phase	Neutral
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15240	42.01	-23.86	65.87	41.78	0.07	0.16	NEUTRAL	QP
2	0.15240	23.02	-32.85	55.87	22.79	0.07	0.16	NEUTRAL	AVERAGE
3	0.17678	56.99	-7.64	64.64	56.76	0.07	0.16	NEUTRAL	QP
4	0.17678	33.83	-20.80	54.64	33.60	0.07	0.16	NEUTRAL	AVERAGE
5	0.22556	48.29	-14.32	62.61	48.05	0.07	0.17	NEUTRAL	QP
6	0.22556	16.59	-36.02	52.61	16.35	0.07	0.17	NEUTRAL	AVERAGE
7	0.42373	26.11	-21.26	47.37	25.86	0.07	0.18	NEUTRAL	AVERAGE
8	0.42373	37.62	-19.75	57.37	37.37	0.07	0.18	NEUTRAL	QP
9	3.720	30.69	-25.31	56.00	30.27	0.13	0.29	NEUTRAL	QP
10	3.720	20.67	-25.33	46.00	20.25	0.13	0.29	NEUTRAL	AVERAGE
11	6.523	34.08	-25.92	60.00	33.55	0.19	0.34	NEUTRAL	QP
12	6.523	26.15	-23.85	50.00	25.62	0.19	0.34	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n
Test Date	Dec. 26, 2013		

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.46	30.00	Complies
6	2437 MHz	19.29	30.00	Complies
11	2462 MHz	19.78	30.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	15.26	30.00	Complies
6	2437 MHz	19.54	30.00	Complies
9	2452 MHz	19.65	30.00	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g
Test Date	Dec. 26, 2013		

#### Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	11.14	30.00	Complies
6	2437 MHz	12.28	30.00	Complies
11	2462 MHz	12.37	30.00	Complies

#### Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.38	30.00	Complies
6	2437 MHz	19.02	30.00	Complies
11	2462 MHz	19.28	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD).
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.3.7. Test Result of Power Spectral Density

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-8.78	8.00	Complies
6	2437 MHz	-6.55	8.00	Complies
11	2462 MHz	-6.07	8.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
3	2422 MHz	-13.11	8.00	Complies
6	2437 MHz	-6.83	8.00	Complies
9	2452 MHz	-7.78	8.00	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g

#### Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-15.39	8.00	Complies
6	2437 MHz	-15.06	8.00	Complies
11	2462 MHz	-15.39	8.00	Complies


#### Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-10.76	8.00	Complies
6	2437 MHz	-5.95	8.00	Complies
11	2462 MHz	-9.41	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 2462 MHz / Ant. 1




Date: 26.DEC.2013 02:02:21

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 2437 MHz / Ant. 1




Date: 26.DEC.2013 02:04:53

### Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Ant. 1



Date: 26.DEC.2013 01:56:55

### Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1



Date: 26.DEC.2013 01:59:21

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.84	17.84	500	Complies
6	2437 MHz	17.84	17.84	500	Complies
11	2462 MHz	17.84	17.76	500	Complies

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.48	36.32	500	Complies
6	2437 MHz	36.48	36.32	500	Complies
9	2452 MHz	36.48	36.32	500	Complies

Temperature	26°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11b/g

#### Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	14.96	500	Complies
6	2437 MHz	10.08	15.04	500	Complies
11	2462 MHz	9.52	14.88	500	Complies


#### Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	16.56	500	Complies
6	2437 MHz	16.56	16.56	500	Complies
11	2462 MHz	16.56	16.56	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 2437 MHz / Ant. 1



Date: 26.DEC.2013 02:32:35


### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 2437 MHz / Ant. 1



Date: 26.DEC.2013 02:35:01




### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Ant. 1



Date: 26.DEC.2013 02:28:09

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1



Date: 26.DEC.2013 02:30:46

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



#### **4.5.5. Test Deviation**

There is no deviation with the original standard.

#### **4.5.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	CTX
Test Date	Dec. 17, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	CTX

##### Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	183.26	37.77	43.50	-5.73	50.84	1.58	12.53	27.18	QP	178	251	HORIZONTAL
2	189.00	42.87	43.50	-0.63	57.11	1.61	11.30	27.15	QP	176	254	HORIZONTAL
3	270.03	45.36	46.00	-0.64	57.44	1.88	13.00	26.96	QP	107	231	HORIZONTAL
4	533.43	42.87	46.00	-3.13	50.22	2.74	18.01	28.10	QP	100	338	HORIZONTAL
5	600.36	44.20	46.00	-1.80	50.72	2.81	18.77	28.10	QP	157	222	HORIZONTAL
6	867.11	45.99	46.00	-0.01	49.75	3.43	20.28	27.47	QP	134	53	HORIZONTAL

## Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	88.00	36.33	40.00	-3.67	54.28	1.08	8.62	27.65	Peak	400	0 VERTICAL
2	188.99	42.56	43.50	-0.94	56.80	1.61	11.30	27.15	QP	100	314 VERTICAL
3	600.09	43.12	46.00	-2.88	49.64	2.81	18.77	28.10	QP	112	189 VERTICAL
4	785.98	39.14	46.00	-6.86	43.92	3.21	19.67	27.66	QP	100	97 VERTICAL
5	799.21	41.92	46.00	-4.08	46.55	3.22	19.76	27.61	Peak	400	0 VERTICAL
6	867.11	40.74	46.00	-5.26	44.50	3.43	20.28	27.47	Peak	400	0 VERTICAL

### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz CH 1 / Ant. 1
Test Date	Dec. 18, 2013		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.54	60.82	74.00	-13.18	56.76	5.87	33.39	35.20 Peak	181	81	HORIZONTAL
2	4824.39	46.74	54.00	-7.26	42.68	5.87	33.39	35.20 Average	181	81	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.57	66.59	74.00	-7.41	62.53	5.87	33.39	35.20 Peak	100	97	VERTICAL
2	4824.22	53.62	54.00	-0.38	49.56	5.87	33.39	35.20 Average	100	97	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz CH 6 / Ant. 1
Test Date	Dec. 18, 2013		

### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4870.76	58.95	74.00	-15.05	54.75	5.92	33.48	35.20	Peak	100	25	HORIZONTAL
2	4874.29	45.52	54.00	-8.48	41.32	5.92	33.48	35.20	Average	100	25	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4870.60	68.24	74.00	-5.76	64.07	5.92	33.45	35.20	Peak	171	354	VERTICAL
2	4872.97	53.53	54.00	-0.47	49.33	5.92	33.48	35.20	Average	171	354	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz CH 11 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4920.73	60.82	74.00	-13.18	56.51	5.97	33.54	35.20	Peak	131	25	HORIZONTAL
2	4924.45	46.51	54.00	-7.49	42.16	5.97	33.58	35.20	Average	131	25	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4920.67	66.44	74.00	-7.56	62.13	5.97	33.54	35.20	Peak	100	77	VERTICAL
2	4924.32	53.89	54.00	-0.11	49.54	5.97	33.58	35.20	Average	100	77	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz CH 3 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4844.42	46.07	54.00	-7.93	41.97	5.88	33.42	35.20	Average	180	25	HORIZONTAL
2	4844.87	58.35	74.00	-15.65	54.25	5.88	33.42	35.20	Peak	180	25	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4844.32	53.83	54.00	-0.17	49.73	5.88	33.42	35.20	Average	102	347	VERTICAL
2	4844.74	66.36	74.00	-7.64	62.26	5.88	33.42	35.20	Peak	102	347	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz CH 6 / Ant. 1
Test Date	Dec. 18, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.45	46.84	54.00	-7.16	42.64	5.92	33.48	35.20	Average	102	25	HORIZONTAL
2	4875.06	59.37	74.00	-14.63	55.17	5.92	33.48	35.20	Peak	102	25	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.45	53.21	54.00	-0.79	49.01	5.92	33.48	35.20	Average	172	347	VERTICAL
2	4874.96	65.95	74.00	-8.05	61.75	5.92	33.48	35.20	Peak	172	347	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz CH 9 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4904.45	45.86	54.00	-8.14	41.60	5.95	33.51	35.20	Average	131	26	HORIZONTAL
2	4910.73	57.58	74.00	-16.42	53.29	5.95	33.54	35.20	Peak	131	26	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4904.48	52.90	54.00	-1.10	48.64	5.95	33.51	35.20	Average	187	339	VERTICAL
2	4904.99	64.62	74.00	-9.38	60.33	5.95	33.54	35.20	Peak	187	339	VERTICAL

#### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.21	45.14	54.00	-8.86	41.08	5.87	33.39	35.20	Average	100	190	HORIZONTAL
2	4824.27	51.19	74.00	-22.81	47.13	5.87	33.39	35.20	Peak	100	190	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.17	56.39	74.00	-17.61	52.33	5.87	33.39	35.20	Peak	100	97	VERTICAL
2	4824.19	53.56	54.00	-0.44	49.50	5.87	33.39	35.20	Average	100	97	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 6 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.17	50.09	74.00	-23.91	45.89	5.92	33.48	35.20	Peak	102	234	HORIZONTAL
2	4874.20	44.85	54.00	-9.15	40.65	5.92	33.48	35.20	Average	102	234	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Limit	Level	Loss	Factor	Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.20	56.14	74.00	-17.86	51.94	5.92	33.48	35.20	Peak	188	350	VERTICAL
2	4874.21	53.67	54.00	-0.33	49.47	5.92	33.48	35.20	Average	188	350	VERTICAL



Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 11 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.17	51.70	74.00	-22.30	47.35	5.97	33.58	35.20	Peak	134	25	HORIZONTAL
2	4924.22	47.41	54.00	-6.59	43.06	5.97	33.58	35.20	Average	134	25	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.16	56.08	74.00	-17.92	51.73	5.97	33.58	35.20	Peak	205	335	VERTICAL
2	4924.20	53.77	54.00	-0.23	49.42	5.97	33.58	35.20	Average	205	335	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1 / Ant. 1
Test Date	Dec. 18, 2013		

### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4917.83	61.44	74.00	-12.56	57.15	5.95	33.54	35.20	Peak	129	26	HORIZONTAL
2	4924.16	47.26	54.00	-6.74	42.91	5.97	33.58	35.20	Average	129	26	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4922.56	68.11	74.00	-5.89	63.76	5.97	33.58	35.20	Peak	204	169	VERTICAL
2	4924.26	53.37	54.00	-0.63	49.02	5.97	33.58	35.20	Average	204	169	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 6 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.49	62.04	74.00	-11.96	57.84	5.92	33.48	35.20	Peak	174	23	HORIZONTAL
2	4874.10	47.68	54.00	-6.32	43.48	5.92	33.48	35.20	Average	174	23	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4872.59	68.92	74.00	-5.08	64.72	5.92	33.48	35.20	Peak	172	348	VERTICAL
2	4874.22	53.54	54.00	-0.46	49.34	5.92	33.48	35.20	Average	172	348	VERTICAL

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 11 / Ant. 1
Test Date	Dec. 18, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4823.65	62.72	74.00	-11.28	58.66	5.87	33.39	35.20	Peak	173	25	HORIZONTAL
2	4823.94	48.76	54.00	-5.24	44.70	5.87	33.39	35.20	Average	173	25	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4822.46	68.39	74.00	-5.61	64.33	5.87	33.39	35.20	Peak	102	351	VERTICAL
2	4824.03	53.32	54.00	-0.68	49.26	5.87	33.39	35.20	Average	102	351	VERTICAL

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.
2. The radiated emission test is performed on each TX port of operating mode without summing or adding  $10\log(N)$  since the limit is relative emission limit.  
Only worst data of each operating mode is presented.

#### **4.6.4. Test Setup Layout**

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.

#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz CH 1, 6, 11 / Ant. 1
Test Date	Dec. 17, 2013		

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	51.45	54.00	-2.55	19.31	4.09	28.05	0.00	Average	100	350	HORIZONTAL
2	2390.00	68.94	74.00	-5.06	36.80	4.09	28.05	0.00	Peak	100	350	HORIZONTAL
3	2414.60	100.52			68.32	4.11	28.09	0.00	Peak	100	350	HORIZONTAL
4	2415.40	90.87			58.67	4.11	28.09	0.00	Average	100	350	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.40	54.11	74.00	-19.89	21.97	4.09	28.05	0.00	Peak	100	349	HORIZONTAL
2	2390.00	43.21	54.00	-10.79	11.07	4.09	28.05	0.00	Average	100	349	HORIZONTAL
3	2431.60	89.12			56.87	4.12	28.13	0.00	Average	100	349	HORIZONTAL
4	2434.20	99.33			67.03	4.12	28.18	0.00	Peak	100	349	HORIZONTAL
5	2483.50	43.20	54.00	-10.80	10.78	4.16	28.26	0.00	Average	100	349	HORIZONTAL
6	2483.50	51.82	74.00	-22.18	19.40	4.16	28.26	0.00	Peak	100	349	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2465.40	98.35			65.99	4.14	28.22	0.00	Peak	100	354	HORIZONTAL
2	2467.60	88.69			56.33	4.14	28.22	0.00	Average	100	354	HORIZONTAL
3	2483.50	48.51	54.00	-5.49	16.09	4.16	28.26	0.00	Average	100	354	HORIZONTAL
4	2483.70	63.27	74.00	-10.73	30.85	4.16	28.26	0.00	Peak	100	354	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz CH 3, 6, 9 / Ant. 1
Test Date	Dec. 17, 2013		

### Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2386.40	68.64	74.00	-5.36	36.50	4.09	28.05	0.00	Peak	100	349	HORIZONTAL
2	2390.00	53.45	54.00	-0.55	21.31	4.09	28.05	0.00	Average	100	349	HORIZONTAL
3	2406.40	87.18			54.98	4.11	28.09	0.00	Average	100	349	HORIZONTAL
4	2412.80	96.44			64.24	4.11	28.09	0.00	Peak	100	349	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	49.36	54.00	-4.64	17.22	4.09	28.05	0.00	Average	100	350	HORIZONTAL
2	2390.00	62.09	74.00	-11.91	29.95	4.09	28.05	0.00	Peak	100	350	HORIZONTAL
3	2421.00	96.43			64.18	4.12	28.13	0.00	Peak	100	350	HORIZONTAL
4	2421.40	86.92			54.67	4.12	28.13	0.00	Average	100	350	HORIZONTAL
5	2483.50	46.23	54.00	-7.77	13.81	4.16	28.26	0.00	Average	100	350	HORIZONTAL
6	2483.50	58.99	74.00	-15.01	26.57	4.16	28.26	0.00	Peak	100	350	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

### Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2444.80	94.88			62.57	4.13	28.18	0.00	Peak	100	347	HORIZONTAL
2	2445.20	85.55			53.24	4.13	28.18	0.00	Average	100	347	HORIZONTAL
3	2483.50	48.35	54.00	-5.65	15.93	4.16	28.26	0.00	Average	100	347	HORIZONTAL
4	2483.50	62.84	74.00	-11.16	30.42	4.16	28.26	0.00	Peak	100	347	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1
Test Date	Dec. 18, 2013		

#### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2376.70	50.50	74.00	-23.50	18.41	4.08	28.01	0.00	Peak	100	352	HORIZONTAL
2	2390.00	39.29	54.00	-14.71	7.15	4.09	28.05	0.00	Average	100	352	HORIZONTAL
3	2413.12	93.17			60.97	4.11	28.09	0.00	Peak	100	352	HORIZONTAL
4	2413.28	89.02			56.82	4.11	28.09	0.00	Average	100	352	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.52	48.84	74.00	-25.16	16.70	4.09	28.05	0.00	Peak	100	349	HORIZONTAL
2	2390.00	39.08	54.00	-14.92	6.94	4.09	28.05	0.00	Average	100	349	HORIZONTAL
3	2436.20	92.82			60.52	4.12	28.18	0.00	Peak	100	349	HORIZONTAL
4	2436.36	89.01			56.71	4.12	28.18	0.00	Average	100	349	HORIZONTAL
5	2483.50	39.31	54.00	-14.69	6.89	4.16	28.26	0.00	Average	100	349	HORIZONTAL
6	2484.78	49.84	74.00	-24.16	17.42	4.16	28.26	0.00	Peak	100	349	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2462.80	87.09			54.73	4.14	28.22	0.00	Average	100	355	HORIZONTAL
2	2463.12	91.17			58.81	4.14	28.22	0.00	Peak	100	355	HORIZONTAL
3	2483.50	39.40	54.00	-14.60	6.98	4.16	28.26	0.00	Average	100	355	HORIZONTAL
4	2484.62	49.86	74.00	-24.14	17.44	4.16	28.26	0.00	Peak	100	355	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	66%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1
Test Date	Dec. 17, 2013		

#### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2389.80	64.63	74.00	-9.37	32.49	4.09	28.05	0.00	Peak	100	339 HORIZONTAL
2	2390.00	50.58	54.00	-3.42	18.44	4.09	28.05	0.00	Average	100	339 HORIZONTAL
3	2414.40	91.09			58.89	4.11	28.09	0.00	Average	100	339 HORIZONTAL
4	2415.60	100.86			68.66	4.11	28.09	0.00	Peak	100	339 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2390.00	43.16	54.00	-10.84	11.02	4.09	28.05	0.00	Average	100	336 HORIZONTAL
2	2390.00	53.62	74.00	-20.38	21.48	4.09	28.05	0.00	Peak	100	336 HORIZONTAL
3	2432.20	89.80			57.55	4.12	28.13	0.00	Average	100	336 HORIZONTAL
4	2433.40	99.40			67.15	4.12	28.13	0.00	Peak	100	336 HORIZONTAL
5	2483.50	43.17	54.00	-10.83	10.75	4.16	28.26	0.00	Average	100	336 HORIZONTAL
6	2484.50	53.68	74.00	-20.32	21.26	4.16	28.26	0.00	Peak	100	336 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2465.60	98.49			66.13	4.14	28.22	0.00	Peak	100	356 HORIZONTAL
2	2466.20	88.93			56.57	4.14	28.22	0.00	Average	100	356 HORIZONTAL
3	2483.50	48.35	54.00	-5.65	15.93	4.16	28.26	0.00	Average	100	356 HORIZONTAL
4	2486.30	63.15	74.00	-10.85	30.69	4.16	28.30	0.00	Peak	100	356 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 18.DEC.2013 02:53:33

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 02:55:21

### Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 02:55:52

### Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 02:57:20

# Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 02:56:44

### Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 18.DEC.2013 02:58:58

### Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 03:00:28

### Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 03:01:13

### Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 18.DEC.2013 03:02:21


# Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 18.DEC.2013 03:01:52




### Plot on Configuration IEEE 802.11b / Reference Level




Date: 18.DEC.2013 02:36:20

### Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 02:37:45

### Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 02:38:28

### Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 02:39:20

# Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 02:39:00

### Plot on Configuration IEEE 802.11g / Reference Level




Date: 18.DEC.2013 02:46:30

### Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 18.DEC.2013 02:48:19

### Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 18.DEC.2013 02:48:57

### Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 18.DEC.2013 02:51:07

# Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)



Date: 18.DEC.2013 02:50:10

## **4.7. Antenna Requirements**

### **4.7.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.7.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 12, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
Artificial Mains Network	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	9170-507	15GHz ~ 40GHz	Jan. 14, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Dec. 02, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz - 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)



Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
-------------	---------	---------	---------	--------------	---------------	------------------------

Note: Calibration Interval of instruments listed above is one year.

“\*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

## 6. MEASUREMENT UNCERTAINTY

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1 = AMN/LISN VSWR 2 =	-0.080	dB	U-shaped	0.060
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

### Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	$\pm 0.173$	dB	K=1	0.086
Cable loss	$\pm 0.174$	dB	K=2	0.087
Antenna gain	$\pm 0.169$	dB	K=2	0.084
Site imperfection	$\pm 0.433$	dB	Triangular	0.214
Pre-amplifier gain	$\pm 0.366$	dB	K=2	0.183
Transmitter antenna	$\pm 1.200$	dB	Rectangular	0.600
Signal generator	$\pm 0.461$	dB	Rectangular	0.231
Mismatch	$\pm 0.080$	dB	U-shape	0.040
Spectrum analyzer	$\pm 0.500$	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

### Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	$\pm 0.191$	dB	K=1	0.095
Cable loss	$\pm 0.169$	dB	K=2	0.084
Antenna gain	$\pm 0.191$	dB	K=2	0.096
Site imperfection	$\pm 0.582$	dB	Triangular	0.291
Pre-amplifier gain	$\pm 0.304$	dB	K=2	0.152
Transmitter antenna	$\pm 1.200$	dB	Rectangular	0.600
Signal generator	$\pm 0.461$	dB	Rectangular	0.231
Mismatch	$\pm 0.080$	dB	U-shape	0.040
Spectrum analyzer	$\pm 0.500$	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

### Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	$\pm 0.186$	dB	K=1	0.093
Cable loss	$\pm 0.167$	dB	K=2	0.083
Antenna gain	$\pm 0.190$	dB	K=2	0.095
Site imperfection	$\pm 0.488$	dB	Triangular	0.244
Pre-amplifier gain	$\pm 0.269$	dB	K=2	0.134
Transmitter antenna	$\pm 1.200$	dB	Rectangular	0.600
Signal generator	$\pm 0.461$	dB	Rectangular	0.231
Mismatch	$\pm 0.080$	dB	U-shape	0.040
Spectrum analyzer	$\pm 0.500$	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

### Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of $x_i$			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	$\pm 0.038$	dB	K=2	0.019
Attenuator	$\pm 0.047$	dB	K=2	0.024
Power Meter specification	$\pm 0.300$	dB	Triangular	0.150
Power Sensor specification	$\pm 0.300$	dB	Rectangular	0.150
Signal generator	$\pm 0.461$	dB	Rectangular	0.231
Mismatch	$\pm 0.080$	dB	U-shape	0.040
Spectrum analyzer	$\pm 0.500$	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U = 2U_c(y)$				1.726