



REPORT No. : SZ15010051S01

FCC SAR TEST REPORT

APPLICANT : HOPERUN MMAX DIGITAL PTE. LTD
PRODUCT NAME : CDMA 1x Advanced Feature Phone
MODEL NAME : MXC-545
TRADE NAME : UMX
BRAND NAME : N/A
FCC ID : 2AB5L-MXC545
STANDARD(S) : 47CFR 2.1093
IEEE 1528-2013
ISSUE DATE : 2015-02-03



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No 8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	4
1. TECHNICAL INFORMATION	5
1.1 IDENTIFICATION OF APPLICANT	5
1.2 IDENTIFICATION OF MANUFACTURER	5
1.3 EQUIPMENT UNDER TEST (EUT)	5
1.3.1 PHOTOGRAPHS OF THE EUT	5
1.3.2 IDENTIFICATION OF ALL USED EUT	6
1.4 APPLIED REFERENCE DOCUMENTS	6
1.5 DEVICE CATEGORY AND SAR LIMITS	6
2. SPECIFIC ABSORPTION RATE (SAR)	7
2.1 INTRODUCTION	7
2.2 SAR DEFINITION	7
3. SAR MEASUREMENT SETUP	8
3.1 THE MEASUREMENT SYSTEM	8
3.2 PROBE	8
3.3 PROBE CALIBRATION PROCESS	10
3.3.1 DOSIMETRIC ASSESSMENT PROCEDURE	10
3.3.2 FREE SPACE ASSESSMENT PROCEDURE	10
3.3.3 TEMPERATURE ASSESSMENT PROCEDURE	10
3.4 PHANTOM	11
3.5 DEVICE HOLDER	11
4. TISSUE SIMULATING LIQUIDS	12
5. UNCERTAINTY ASSESSMENT	14
5.1 UNCERTAINTY EVALUATION FOR EUT SAR TEST	14
5.2 UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK	15



6. SAR MEASUREMENT EVALUATION	17
6.1 SYSTEM SETUP	17
6.2 VALIDATION RESULTS	18
7. OPERATIONAL CONDITIONS DURING TEST	19
7.1 INFORMATION ON THE TESTING	19
7.2 BODY-WORN CONFIGURATIONS	20
7.3 MEASUREMENT PROCEDURE	20
7.4 DESCRIPTION OF INTERPOLATION/EXTRAPOLATION SCHEME	21
8. MEASUREMENT OF CONDUCTED OUTPUT POWER	22
9. TEST RESULTS LIST	23
ANNEX A GRAPH TEST RESULTS	26
ANNEX B GENERAL INFORMATION	98

Change History		
Issue	Date	Reason for change
1.0	2015-02-03	First edition



REPORT No. : SZ15010051S01

TEST REPORT DECLARATION

Applicant	HOPERUN MMAX DIGITAL PTE. LTD		
Applicant Address	152 BEACH ROAD #13-06 GATEWAY EAST SINGAPORE 189721		
Manufacturer	HOPERUN MMAX DIGITAL PTE. LTD		
Manufacturer Address	152 BEACH ROAD #13-06 GATEWAY EAST SINGAPORE 189721		
Product Name	CDMA 1x Advanced Feature Phone		
Model Name	MXC-545		
Brand Name	N/A		
HW Version	P1.5		
SW Version	V2.5.8		
Test Standards	47CFR 2.1093; IEEE 1528-2013		
Test Date	2014-5- 16 to 2014-5-17		
The Highest Reported 1g-SAR(W/kg)	Head	1.204W/kg	Limit(W/kg): 1.6W/kg
	Body	1.042 W/kg	

Tested by :

Liu Jun

Liu Jun

Reviewed by :

Peng Huarui

Peng Huarui

Approved by :

Zeng Dexin

Zeng Dexin



1. TECHNICAL INFORMATION

Note: the Following data is based on the information by the applicant.

1.1 Identification of Applicant

Company Name:	HOPERUN MMAX DIGITAL PTE. LTD
Address:	152 BEACH ROAD #13-06 GATEWAY EAST SINGAPORE 189721

1.2 Identification of Manufacturer

Company Name:	HOPERUN MMAX DIGITAL PTE. LTD
Address:	152 BEACH ROAD #13-06 GATEWAY EAST SINGAPORE 189721

1.3 Equipment Under Test (EUT)

Model Name:	MXC-545
Trade Name:	UMX
Brand Name:	N/A
Hardware Version:	P1.5
Software Version:	V2.5.8
Tx Frequency Bands:	CDMA BC 0: 824-849MHz; CDMA BC 1:1850-1910MHz; CDMA BC 10:806-901MHz;
Uplink Modulations:	CDMA: CDMA;
DTM:	Not support
Antenna type:	Fixed Internal Antenna
Development Stage:	Identical prototype
3GPP Version:	Release 8
Hotspot function:	Not Support

1.3.1 Photographs of the EUT

Please refer to the External Photos for the Photos of the EUT



1.3.2 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the Following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	P1.5	V2.5.8

1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
2	IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.
3	KDB 447498 D01v05r02	General RF Exposure Guidance
4	KDB 941225 D01v02	SAR test for 3G devices
5	KDB 865664 D01v01r02	SAR Measurement 100 MHz to 6 GHz
6	KDB 865664 D02v01r01	SAR Reporting

1.5 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.



2. SPECIFIC ABSORPTION RATE (SAR)

2.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are Middle than the limits for general population/uncontrolled.

2.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density. (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by,

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where C is the specific head capacity, δT is the temperature rise and δt the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where σ is the conductivity of the tissue, ρ is the mass density of the tissue and $|E|$ is the rms electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

3. SAR MEASUREMENT SETUP

3.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the Following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The Following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2 Probe


For the measurements the Specific Dosimetric E-Field Probe SN 37/08 EP80 with Following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter: 6.5 mm

- Distance between probe tip and sensor center: 2.5mm
- Distance between sensor center and the inner phantom surface: 4 mm
(repeatability better than +/- 1mm)
- Probe linearity: <0.25 dB
- Axial Isotropy: <0.25 dB
- Spherical Isotropy: <0.25 dB
- Calibration range: 835to 2500MHz for head & body simulating liquid.

Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with CENELEC EN 62209 and IEEE 1528 std, with CALISAR, Antenna proprietary calibration system. The calibration is performed with the EN 622091 annex technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) c \quad (2z/\delta)$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

l = Skin depth



Keithley configuration:

Rate = Medium; Filter =ON; RDGS=10; FILTER TYPE =MOVING AVERAGE; RANGE AUTO

After each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/Vlin(N) \quad (N=1,2,3)$$

The linearised output voltage Vlin(N) is obtained from the displayed output voltage V(N) using

$$Vlin(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

Where DCP is the diode compression point in mV.

3.3 Probe Calibration Process

3.3.1 Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm^2) using an with CALISAR, Antenna proprietary calibration system.

3.3.2 Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm^2 .

3.3.3 Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulating head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

δt = exposure time (30 seconds),

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

C = heat capacity of tissue (brain or muscle),

δT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place.

The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

Where:

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

3.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

3.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is Middle than 1°.



Device holder

System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005



4. TISSUE SIMULATING LIQUIDS

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in below table.

The following table gives the recipes for tissue simulating liquids

Frequency Band (MHz)	835		1900	
Tissue Type	Head	Body	Head	Body
Ingredients (% by weight)				
Deionised Water	50.36	50.20	54.90	40.40
Salt(NaCl)	1.25	0.90	0.18	0.50
Sugar	0.00	48.50	0.00	58.00
Tween 20	48.39	0.00	0.00	0.00
HEC	0.00	0.20	0.00	1.00
Bactericide	0.00	0.20	0.00	0.10
Triton X-100	0.00	0.00	0.00	0.00
DGBE	0.00	0.00	44.92	0.00
Measured dielectric parameters				
Diethylenglycol monohexylether	0.00	0.00	0.00	0.00
Dielectric Constant	41.50	56.10	39.90	53.30
Conductivity (S/m)	0.90	0.95	1.42	1.52

Note: Please refer to the validation results for dielectric parameters of each frequency band.

The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using an Agilent 85033E Dielectric Probe Kit and an Agilent Network Analyzer.



Table 1: Dielectric Performance of Tissue Simulating Liquid

Temperature: 22.0~23.8°C, humidity: 54~60%.						
Date	Freq.(MHz)	Liquid Parameters	Meas.	Target	Delta(%)	Limit±(%)
2014/5/16	Head 835	Relative Permittivity(ϵ_r):	41.42	41.50	-0.19	5
		Conductivity(σ):	0.92	0.90	2.22	5
	Body 835	Relative Permittivity(ϵ_r):	56.25	56.10	0.27	5
		Conductivity(σ):	0.91	0.95	-4.21	5
2014/5/17	Head 1900	Relative Permittivity(ϵ_r):	39.82	39.90	-0.20	5
		Conductivity(σ):	1.44	1.42	1.41	5
	Body 1900	Relative Permittivity(ϵ_r):	53.23	53.30	-0.13	5
		Conductivity(σ):	1.49	1.52	-1.97	5



5. UNCERTAINTY ASSESSMENT

The Following table includes the uncertainty table of the IEEE 1528. The values are determined by Antennessa.

5.1 UNCERTAINTY EVALUATION FOR EUT SAR TEST

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/ e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob . Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+- %)	Vi
Measurement System									
Probe calibration	E.2.1	4.76	N	1	1	1	4.76	4.7	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	0.7	0.7	1.01	1.0	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	0.7	0.7	1.62	1.6	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.8	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.0	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.1	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.1 5	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.8 9	∞
Test sample Related									
Test sample positioning	E.4.2. 1	0.03	N	1	1	1	0.03	0.0 3	N- 1
Device Holder Uncertainty	E.4.1.	5.00	N	1	1	1	5.00	5.0	N-



	1							0	1
Output power Power drift - SAR drift measurement	6.6.2	4.04	R	$\sqrt{3}$	1	1	2.33	2.3 3	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Liquid conductivity - deviation from target value	E.3.2	4.57	R	$\sqrt{3}$	0.64	0.43	1.69	1.1 3	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.1 5	M
Liquid permittivity - deviation from target value	E.3.2	3.69	R	$\sqrt{3}$	0.6	0.49	1.28	1.0 4	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.0 0	N	1	0.6	0.49	6.00	4.9 0	M
Combined Standard Uncertainty			RSS				11.55	10. 67	
Expanded Uncertainty (95% Confidence interval)			K=2				23.11	21. 33	

5.2 UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/ e	k
Uncertainty Component	Sec.	Tol (+-%)	Prob Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	4.76	N	1	1	1	4.76	4.7	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	0.7	0.7	1.01	1.0	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	0.7	0.7	1.62	1.6	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.8	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.0	∞




Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.1	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.1 5	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.8 9	∞
Dipole									
Dipole axis to liquid Distance	8,E.4. 2	1.00	N	$\sqrt{3}$	1	1	0.58	0.5 8	∞
Input power and SAR drift measurement	8,6.6. 2	4.04	R	$\sqrt{3}$	1	1	2.33	2.3 3	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Liquid conductivity - deviation from target value	E.3.2	4.57	R	$\sqrt{3}$	0.64	0.43	1.69	1.1 3	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	$\sqrt{3}$	0.64	0.43	1.85	1.2 4	M
Liquid permittivity - deviation from target value	E.3.2	3.69	R	$\sqrt{3}$	0.6	0.49	1.28	1.0 4	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.0 0	N	$\sqrt{3}$	0.6	0.49	3.46	2.8 3	M
Combined Standard Uncertainty			RSS				8.83	8.3 7	
Expanded Uncertainty (95% Confidence interval)			K=2				17.66	16. 73	

6. SAR MEASUREMENT EVALUATION

6.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The power meter PM1 measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to



6 GHz) at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2.

6.2 Validation Results

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

Frequency	835MHz(H)	835MHz(B)	1900MHz(H)	1900MHz(B)
Target value (1g)	9.68 W/kg	10.04 W/kg	39.36 W/kg	42.36 W/kg
Test value (1g 250 mW input)	2.451 W/kg (5.16)	2.472 W/kg (5.16)	9.672 W/kg (5.17)	9.941 W/kg (5.17)
Normalized value (1g)	9.804 W/kg	9.888 W/kg	38.688 W/kg	39.764 W/kg

Note: System checks the specific test data please see 94-97.

7. OPERATIONAL CONDITIONS DURING TEST

7.1 Information on the testing

The mobile phone antenna and battery are those specified by the manufacturer. The battery is fully charged before each measurement. The output power and frequency are controlled using a base station simulator. The mobile phone is set to transmit at its highest output peak power level.

The mobile phone is test in the “cheek” and “tilted” positions on the left and right sides of the phantom. The mobile phone is placed with the vertical centre line of the body of the mobile phone and the horizontal line crossing the centre of the earpiece in a plane parallel to the sagittal plane of the phantom.




Illustration for Cheek Position




Illustration for Tilted Position

Description of the “cheek” position:

The mobile phone is well placed in the reference plane and the earpiece is in contact with the ear. Then the mobile phone is moved until any point on the front side get in contact with the cheek of the phantom or until contact with the ear is lost.

Description of the “tilted” position:

The mobile phone is well placed in the “cheek” position as described above. Then the mobile phone is moved outward away from the mouth by an angle of 15 degrees or until contact with the ear lost.

Remark: Please refer to Appendix B for the test setup photos.

7.2 Body-worn Configurations

The body-worn configurations shall be tested with the supplied accessories (belt-clips, holsters, etc.) attached to the device in normal use configuration.

For body-worn and other configurations a flat phantom shall be used which is comprised of material with electrical properties similar to the corresponding tissues.




Illustration for Body Worn Position

7.3 Measurement procedure

The Following steps are used for each test position

1. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface.
2. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
3. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
4. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or



8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.



8. MEASUREMENT OF CONDUCTED OUTPUT POWER

1. CDMA 1xRTT power

Band	Channel	Frequency (MHz)	SO55(dBm)		SO32 (dBm)
			RC1	RC3	RC3
BC 0	1013	824.7	29.01	29.08	29.05
	384	836.52	29.15	29.15	29.13
	777	848.31	28.58	28.63	28.60
BC 1	25	1851.25	27.58	27.60	27.55
	600	1880.0	28.00	28.01	28.01
	1175	1908.75	27.46	27.49	27.41
BC 10	476	817.9	28.28	28.30	28.26
	526	819.1	28.55	28.57	28.56
	684	823.1	28.90	28.90	28.86

Note:

Maximum average output power is verified on the Low, Middle and High channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E for 1xRTT.



9. TEST RESULTS LIST

Summary of Measurement Results (CDMA BC 0 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.					
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g
Right Side Of Head	Cheek/Touch	1013	1.074	1.102	1.184
		1013	1.068 (repeated)	1.102	1.177
		384	1.011	1.084	1.096
		777	0.985	1.222	1.204
	Ear/Tilt	384	0.479	1.084	0.519
Left Side Of Head	Cheek/Touch	1013	1.020	1.102	1.124
		384	0.975	1.084	1.057
		777	0.854	1.222	1.044
	Ear/Tilt	384	0.359	1.084	0.389
Body (10mm Separation)	Back upward	384	0.354	1.089	0.386
	Front upward	384	0.664	1.089	0.723

Summary of Measurement Results (CDMA BC 1 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.					
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g
Right Side Of Head	Cheek/Touch	600	0.619	1.119	0.693
	Ear/Tilt		0.063		0.070
Left Side Of Head	Cheek/Touch		0.560		0.627
	Ear/Tilt		0.058		0.065
Body (10mm Separation)	Back upward		0.421		0.471
	Front upward		0.356		0.398



Summary of Measurement Results (CDMA BC 10 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.					
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g
Right Side Of Head	Cheek/Touch	476	0.968	1.175	1.137
		526	1.068	1.104	1.179
		684	1.173	1.023	1.200
		684	1.148 (repeated)	1.023	1.174
	Ear/Tilt	684	0.449	1.023	0.459
Left Side Of Head	Cheek/Touch	476	0.785	1.175	0.922
		526	0.846	1.104	0.934
		684	1.039	1.023	1.063
	Ear/Tilt	684	0.375	1.023	0.384
Body (10mm Separation)	Back upward	476	0.879	1.186	1.042
		526	0.904	1.107	1.001
		684	0.980	1.033	1.012
		684	0.858 (repeated)	1.033	0.886
	Front upward	684	0.645	1.033	0.666



Note:

1. When the 1-g SAR for the mid-band channel or the channel with the highest output power satisfy the following conditions, testing of the other channels in the band is not required. (Per KDB 447498 D01 General RF Exposure Guidance v05r02)
 $\leq 0.8 \text{ W/kg}$ and transmission band $\leq 100 \text{ MHz}$
 $\leq 0.6 \text{ W/kg}$ and, $100 \text{ MHz} < \text{transmission bandwidth} \leq 200 \text{ MHz}$
 $\leq 0.4 \text{ W/kg}$ and transmission band $> 200 \text{ MHz}$
2. Scaling Factor calculation

Band	Tune-up power tolerance (dBm)	SAR test channel Power (dBm)	Scaling Factor
CDMA BC 0	Max output power = 29 ± 0.5	29.08	1.102
		29.15	1.084
		28.63	1.222
		29.13	1.089
CDMA BC 1	Max output power = 28 ± 0.5	28.01	1.119
		28.01	1.119
CDMA BC 10	Max output power = 28.5 ± 0.5	28.30	1.175
		28.57	1.104
		28.90	1.023
		28.26	1.186
		28.56	1.107
		28.86	1.033

**ANNEX A GRAPH TEST RESULTS**

BAND	PARAMETERS
<u>CDMA BC 0</u>	<u>Measurement 1:</u> Right Head with Cheek device position on Low Channel in CDMA mode <u>Measurement 2:</u> Right Head with Cheek device position on Low Channel in CDMA mode <u>Measurement 3:</u> Right Head with Cheek device position on Middle Channel in CDMA mode <u>Measurement 4:</u> Right Head with Cheek device position on High Channel in CDMA mode <u>Measurement 5:</u> Right Head with Tilt device position on Middle Channel in CDMA mode <u>Measurement 6:</u> Left Head with Cheek device position on Low Channel in CDMA mode <u>Measurement 7:</u> Left Head with Cheek device position on Middle Channel in CDMA mode <u>Measurement 8:</u> Left Head with Cheek device position on High Channel in CDMA mode <u>Measurement 9:</u> Left Head with Tilt device position on Middle Channel in CDMA mode <u>Measurement 10:</u> Flat Plane with Body device position on Middle Channel in CDMA mode <u>Measurement 11:</u> Flat Plane with Body device position on Middle Channel in CDMA mode
<u>CDMA BC 1</u>	<u>Measurement 12:</u> Right Head with Cheek device position on Middle Channel in CDMA mode <u>Measurement 13:</u> Right Head with Tilt device position on Middle Channel in CDMA mode <u>Measurement 14:</u> Left Head with Cheek device position on Middle Channel in CDMA mode <u>Measurement 15:</u> Left Head with Tilt device position on Middle w Channel in CDMA mode <u>Measurement 16:</u> Flat Plane with Body device position on Middle Channel in CDMA mode <u>Measurement 17:</u> Flat Plane with Body device position on Middle Channel in CDMA mode

**CDMA BC 10**

Measurement 18: Right Head with Cheek device position on Low Channel in CDMA mode

Measurement 19: Right Head with Cheek device position on Middle Channel in CDMA mode

Measurement 20: Right Head with Cheek device position on High Channel in CDMA mode

Measurement 21: Right Head with Cheek device position on High Channel in CDMA mode

Measurement 22: Right Head with Tilt device position on High Channel in CDMA mode

Measurement 23: Left Head with Cheek device position on Low Channel in CDMA mode

Measurement 24: Left Head with Cheek device position on Middle Channel in CDMA mode

Measurement 25: Left Head with Cheek device position on High Channel in CDMA mode

Measurement 26: Left Head with Tilt device position on High Channel in CDMA mode

Measurement 27: Flat Plane with Body device position on Low Channel in CDMA mode

Measurement 28: Flat Plane with Body device position on Middle Channel in CDMA mode

Measurement 29: Flat Plane with Body device position on High Channel in CDMA mode

Measurement 30: Flat Plane with Body device position on High Channel in CDMA mode

Measurement 31: Flat Plane with Body device position on High Channel in CDMA mode

**MEASUREMENT 1**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 30 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 0
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 1013):

Frequency (MHz)	824.700000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	1.490000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.85 W/kg

SAR 10g (W/Kg)	0.806500
SAR 1g (W/Kg)	1.074361


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 2**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 45 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 0
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 1013):

Frequency (MHz)	824.700000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	3.390000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-51.00, Y=-40.00


SAR Peak: 1.50 W/kg

SAR 10g (W/Kg)	0.752340
SAR 1g (W/Kg)	1.068061


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 3**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 33 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	0.960000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.60 W/kg

SAR 10g (W/Kg)	0.711486
SAR 1g (W/Kg)	1.011043


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 4**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 30 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 0
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 777):

Frequency (MHz)	848.310000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	-3.650000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.47 W/kg

SAR 10g (W/Kg)	0.607654
SAR 1g (W/Kg)	0.985226


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 5**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 9 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Tilt
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	0.120000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-28.00, Y=-18.00


SAR Peak: 0.62 W/kg

SAR 10g (W/Kg)	0.339648
SAR 1g (W/Kg)	0.478562


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 6**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 22 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 0
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 1013):

Frequency (MHz)	824.700000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	0.920000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-16.00


SAR Peak: 1.61 W/kg

SAR 10g (W/Kg)	0.712224
SAR 1g (W/Kg)	1.020088


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 7**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 21 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	1.360000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-16.00


SAR Peak: 1.38 W/kg

SAR 10g (W/Kg)	0.625228
SAR 1g (W/Kg)	0.974805


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 8**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 22 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 0
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 777):

Frequency (MHz)	848.310000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	4.530000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-41.00, Y=-16.00


SAR Peak: 1.27 W/kg

SAR 10g (W/Kg)	0.528912
SAR 1g (W/Kg)	0.854310


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 9**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes11 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Tilt
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	0.550000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-32.00, Y=-8.00


SAR Peak: 0.48 W/kg

SAR 10g (W/Kg)	0.252721
SAR 1g (W/Kg)	0.359479


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 10**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 39 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	2.900000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=3.00, Y=10.00


SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.265650
SAR 1g (W/Kg)	0.354265


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 11**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 37 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 0
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 384):

Frequency (MHz)	836.520000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-1.220000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=5.00, Y=14.00


SAR Peak: 0.86 W/kg

SAR 10g (W/Kg)	0.477696
SAR 1g (W/Kg)	0.664023


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 12**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 9 minutes 24 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.824068
Conductivity (S/m)	1.438127
Power drift(%)	2.440000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.00
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-55.00, Y=-47.00


SAR Peak: 0.95 W/kg

SAR 10g (W/Kg)	0.324000
SAR 1g (W/Kg)	0.619493


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 13**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 7 minutes 59 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Tilt
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.824068
Conductivity (S/m)	1.438127
Power drift(%)	-3.470000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.00
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-13.00, Y=-9.00


SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.028354
SAR 1g (W/Kg)	0.063438


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 14**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 9 minutes 3 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.824068
Conductivity (S/m)	1.438127
Power drift(%)	-4.600000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.00
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-55.00, Y=-31.00


SAR Peak: 0.92 W/kg

SAR 10g (W/Kg)	0.297375
SAR 1g (W/Kg)	0.560407


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 15**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 8 minutes 3 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Tilt
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.824068
Conductivity (S/m)	1.438127
Power drift(%)	-2.980000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.00
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-24.00, Y=1.00


SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.026277
SAR 1g (W/Kg)	0.058056


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 16**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 9 minutes 36 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.231406
Conductivity (S/m)	1.486725
Power drift(%)	-0.390000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.17
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=3.00, Y=-17.00


SAR Peak: 0.71 W/kg

SAR 10g (W/Kg)	0.221830
SAR 1g (W/Kg)	0.420903


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 17**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17

Measurement duration: 9 minutes 39 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 1
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 600):

Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.231406
Conductivity (S/m)	1.486725
Power drift(%)	1.340000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.17
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-5.00, Y=-18.00


SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.183879
SAR 1g (W/Kg)	0.356300


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 18**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 36 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 10
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 476):

Frequency (MHz)	817.900000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	2.000000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.42 W/kg

SAR 10g (W/Kg)	0.613542
SAR 1g (W/Kg)	0.968168


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 19**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 33 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 10
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 526):

Frequency (MHz)	819.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	2.700000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.56 W/kg

SAR 10g (W/Kg)	0.676840
SAR 1g (W/Kg)	1.068155


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 20**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 30 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	3.290000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-40.00, Y=-31.00


SAR Peak: 1.86 W/kg

SAR 10g (W/Kg)	0.806573
SAR 1g (W/Kg)	1.173103


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 21**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 34 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	1.540000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-49.00, Y=-48.00


SAR Peak: 1.66 W/kg

SAR 10g (W/Kg)	0.819939
SAR 1g (W/Kg)	1.148275


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 22**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 27 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Tilt
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	-3.310000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-31.00, Y=-20.00


SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.322013
SAR 1g (W/Kg)	0.448894


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 23**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 36 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 10
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 476):

Frequency (MHz)	817.900000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	-3.870000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-46.00, Y=-17.00


SAR Peak: 1.12 W/kg

SAR 10g (W/Kg)	0.497967
SAR 1g (W/Kg)	0.784695


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 24**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 37 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 10
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 526):

Frequency (MHz)	819.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	1.310000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-47.00, Y=-17.00


SAR Peak: 1.18 W/kg

SAR 10g (W/Kg)	0.549131
SAR 1g (W/Kg)	0.845651


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 25**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes 34 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	4.530000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-47.00, Y=-17.00


SAR Peak: 1.48 W/kg

SAR 10g (W/Kg)	0.658516
SAR 1g (W/Kg)	1.039096


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 26**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 8 minutes11 seconds



A. Experimental conditions.

Phantom File	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Tilt
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	-0.940000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=-33.00, Y=-8.00


SAR Peak: 0.50 W/kg

SAR 10g (W/Kg)	0.267726
SAR 1g (W/Kg)	0.374632


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 27**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 38 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 10
Channels	Low
Signal	CDMA

B. SAR Measurement Results

Low Band SAR (Channel 476):

Frequency (MHz)	817.900000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-1.070000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=6.00, Y=5.00


SAR Peak: 1.09 W/kg

SAR 10g (W/Kg)	0.647788
SAR 1g (W/Kg)	0.878630


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 28**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 36 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 10
Channels	Middle
Signal	CDMA

B. SAR Measurement Results

Middle Band SAR (Channel 526):

Frequency (MHz)	819.100000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-2.380000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=6.00, Y=3.00


SAR Peak: 1.14 W/kg

SAR 10g (W/Kg)	0.657937
SAR 1g (W/Kg)	0.903759


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 29**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 37 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-0.210000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=3.00, Y=3.00


SAR Peak: 1.26 W/kg

SAR 10g (W/Kg)	0.713122
SAR 1g (W/Kg)	0.980364


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 30**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 32 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-0.930000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=7.00, Y=-16.00


SAR Peak: 1.19 W/kg

SAR 10g (W/Kg)	0.545215
SAR 1g (W/Kg)	0.858034


Z axis scan



3D screen shot



Hot spot position



**MEASUREMENT 31**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 9 minutes 41 seconds



A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	Body
Band	CDMA BC 10
Channels	High
Signal	CDMA

B. SAR Measurement Results

High Band SAR (Channel 684):

Frequency (MHz)	823.100000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	-2.760000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**




REPORT No. : SZ15010051S01

Maximum location: X=6.00, Y=10.00


SAR Peak: 0.83 W/kg

SAR 10g (W/Kg)	0.454517
SAR 1g (W/Kg)	0.644872


Z axis scan



3D screen shot



Hot spot position



**System Performance Check Data(Head)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16



Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	
Band	835MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.423815
Conductivity (S/m)	0.921853
Power drift (%)	0.420000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.73
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**



REPORT No. : SZ15010051S01


Maximum location: X=7.00, Y=-1.00

SAR 10g (W/Kg)	1.562715
SAR 1g (W/Kg)	2.451372


Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5209	1.6629	1.1437	0.8075	0.5889	0.4143


SAR, Z Axis Scan (X = 7, Y = -1)



3D scene shot



Hot spot position





System Performance Check Data(Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.16

Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.


Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	
Band	835MHz
Channels	
Signal	CW

B. SAR Measurement Results


Band SAR

Frequency (MHz)	835.000000
Relative permittivity (real part)	56.246812
Conductivity (S/m)	0.906274
Power drift (%)	0.520000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.99
Crest factor:	1:1

SURFACE SAR



VOLUME SAR





REPORT No. : SZ15010051S01


Maximum location: X=7.00, Y=-1.00

SAR 10g (W/Kg)	1.508219
SAR 1g (W/Kg)	2.472058


Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5209	1.6629	1.1437	0.8075	0.5889	0.4143


SAR, Z Axis Scan (X = 7, Y = -1)



3D scene shot



Hot spot position



**System Performance Check Data(Head)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17



Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	
Band	1900MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	1900.000000
Relative permittivity (real part)	39.824068
Conductivity (S/m)	1.438127
Power drift (%)	1.300000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.00
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**



REPORT No. : SZ15010051S01


Maximum location: X=6.00, Y=0.00

SAR 10g (W/Kg)	6.350371
SAR 1g (W/Kg)	9.671853


Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.6419	6.0043	3.7297	2.2606	1.5119	0.9792


SAR, Z Axis Scan (X = 6, Y = 0)



3D scene shot



Hot spot position



**System Performance Check Data(Body)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2014.5.17



Measurement duration: 13 minutes 26 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat Plane
Device Position	
Band	1900MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.231406
Conductivity (S/m)	1.486725
Power drift (%)	2.050000
Ambient Temperature:	22.9°C
Liquid Temperature:	22.1°C
ConvF:	6.17
Crest factor:	1:1

SURFACE SAR**VOLUME SAR**



REPORT No. : SZ15010051S01


Maximum location: X=7.00, Y=1.00

SAR 10g (W/Kg)	6.472841
SAR 1g (W/Kg)	9.940672


Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2075	7.3996	5.4654	4.1101	3.1286	2.4128


SAR, Z Axis Scan (X = 7, Y = 1)



3D scene shot



Hot spot position





REPORT No. : SZ15010051S01

ANNEX B GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

**4. List of Test Equipments**

No.	Instrument	Type	Cal. Date	Cal. Due
1	PC	Dell (Pentium IV 2.4GHz, SN:X10-23533)	(n.a)	(n.a)
2	Network Emulator	Aglient (8960, SN:10752)	2014-2-21	1year
3	Network Analyzer	Agilent(E5071B ,SN:MY42404762)	2014-9-24	1year
4	Voltmeter	Keithley (2000, SN:1000572)	2014-9-24	1year
5	Signal Generator	Rohde&Schwarz (SMP_02)	2014-9-24	1year
6	Power Amplifier	PRANA (Ap32 SV125AZ)	2014-9-24	1year
7	Power Meter	Agilent (E4416A, SN:MY45102093)	2014-5-07	1year
8	Power Sensor	Agilent (N8482A, SN:MY41091706)	2014-5-07	1year
9	Directional coupler	Giga-tronics(SN:1829112)	2014-9-24	1year
10	Probe	Satimo (SN:SN 37/08 EP80)	2014-9-22	1year
11	Dielectric Probe Kit	Agilent (85033E)	2014-9-24	1year
12	Phantom	Satimo (SN:SN_36_08_SAM62)	2014-9-24	1year
13	Liquid	Satimo(Last Calibration: 2014-5-16 to 2014-5-17)	N/A	N/A
14	Dipole 835MHz	Satimo (SN 20/08 DIPC 99)	2014-9-22	1year
15	Dipole 1900MHz	Satimo (SN 30/13 DIP1G900-261)	2014-9-22	1year

***** END OF REPORT *****