## **RF EXPOSURE TEST**

## SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

mm	25	20	15	10	5	MHz
	194	155	116	77	39	150
	137	110	82	55	27	300
	112	89	67	45	22	450
	82	66	49	33	16	835
	79	63	47	32	16	900
SAR Test Exclusion	61	49	37	24	12	1500
Threshold (mW)	54	44	33	22	11	1900
	48	38	29	19	10	2450
	40	32	24	16	8	3600
	33	26	20	13	7	5200
	32	26	19	13	6	5400
	31	25	19	12	6	5800
mm	50	45	40	35	30	MHz
	387	349	310	271	232	150
	274	246	219	192	164	300
	224	201	179	157	134	450
	164	148	131	115	98	835
		148 142	131 126	115 111	98 95	
SAR Test	164					835
Exclusion	164 158	142	126	111	95	835 900
	164 158 122	142 110	126 98	111 86	95 73	835 900 1500
Exclusion	164 158 122 109	142 110 98	126 98 87	111 86 76	95 73 65	835 900 1500 1900
Exclusion	164 158 122 109 96	142 110 98 86	126 98 87 77	111 86 76 67	95 73 65 57	835 900 1500 1900 2450
Exclusion	164 158 122 109 96 79	142 110 98 86 71	126 98 87 77 63	111 86 76 67 55	95 73 65 57 47	835 900 1500 1900 2450 3600
Exclusion	164 158 122 109 96 79 66	142 110 98 86 71 59	126 98 87 77 63 53	111 86 76 67 55 46	95 73 65 57 47 39	835 900 1500 1900 2450 3600 5200

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

$\leq$ 50 mm are determined by:
$[(max.\ power\ of\ channel,\ including\ tune-up\ tolerance,\ mW)/(min.\ test\ separation\ distance,\ mm)] \ \bullet$
[ $\sqrt{f_{\text{(GHz)}}}$ ] $\leq 3.0$ for 1-g SAR and $\leq 7.5$ for 10-g extremity SAR,16 where
$\square$ f <sub>(GHz)</sub> is the RF channel transmit frequency in GHz
$\square$ Power and distance are rounded to the nearest mW and mm before calculation 17
☐ The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is $\leq 50$ mm and
transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

for

Maximum measured transmitter power.

GFSK

frequency range	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)
2402	4.12	2.58
2440	4.82	3.03
2480	4.57	2.86

The max.output power is 2.58mW, Frequency is 2.402GHz

So (2.58/5)\* √2.402=0.7998≤ 3.0

Note:  $\sqrt{2.402} = 1.55$ 

The max.output power is 3.03mW, Frequency is 2.441GHz

So (3.03/5)\* √2.441=0.94536≤ 3.0

Note:  $\sqrt{2.441} = 1.56$ 

The max.output power is 2.86mW, Frequency is 2.48GHz

So (2.86/5)\* √2.48=0.89804≤ 3.0

Note:  $\sqrt{2.48} = 1.57$ 

Conclusion: No SAR is required.