



FCC RADIO TEST REPORT

FCC ID: 2AB7A20141140

Product : GSM MOBILE PHONE

Trade Name : N/A

Model Name : CHIC FIRE D40Z

Serial Model : CHIC FIRE D45Z,S11,R11,N11

Report No. : BZT14052159

Prepared for

HK AONYSTAR CO.,LIMITED
ROOM 1103,HANG SENG MONGKOK BUILDING,677 NATHAN
ROAD,MONGKOK,KOWLOON HONGKONG

Prepared by

BZT Testing Technology Co., Ltd
Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an
District, Shenzhen P.R. China.

TEST RESULT CERTIFICATION

Applicant's name : HK AONYSTAR CO.,LIMITED
Address : ROOM 1103,HANG SENG MONGKOK BUILDING,677 NATHAN ROAD,MONGKOK,KOWLOON HONGKONG
Manufacture's Name : HK AONYSTAR CO.,LIMITED
Address : ROOM 1103,HANG SENG MONGKOK BUILDING,677 NATHAN ROAD,MONGKOK,KOWLOON HONGKONG

Product description

Product name..... : GSM MOBILE PHONE
Model and/or type reference : CHIC FIRE D40Z
Serial Model : CHIC FIRE D45Z,S11,R11,N11
DIFF : N/A

Standards : FCC Part15.247

Test procedure ANSI C63.4-2003

This device described above has been tested by BZT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BZT, this document may be altered or revised by BZT, personal only, and shall be noted in the revision of the document.


Date of Test..... :

Date (s) of performance of tests..... : 10 April 2014 ~29 April 2014

Date of Issue : 04 May 2014

Test Result..... : **Pass**

Testing Engineer :




(Lynn Chen)

Technical Manager :



(Carlen Liu)

Authorized Signatory :



(Tommy zhang)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	36
4 . POWER SPECTRAL DENSITY TEST	52
4.1 APPLIED PROCEDURES / LIMIT	52
4.1.1 TEST PROCEDURE	52
4.1.2 DEVIATION FROM STANDARD	52
4.1.3 TEST SETUP	52
4.1.4 EUT OPERATION CONDITIONS	52
4.1.5 TEST RESULTS	53
5 . BANDWIDTH TEST	61
5.1 APPLIED PROCEDURES / LIMIT	61

Table of Contents

	Page
5.1.1 TEST PROCEDURE	61
5.1.2 DEVIATION FROM STANDARD	61
5.1.3 TEST SETUP	61
5.1.4 EUT OPERATION CONDITIONS	61
5.1.5 TEST RESULTS	62
6 . PEAK OUTPUT POWER TEST	70
6.1 APPLIED PROCEDURES / LIMIT	70
6.1.1 TEST PROCEDURE	70
6.1.2 DEVIATION FROM STANDARD	70
6.1.3 TEST SETUP	70
6.1.4 EUT OPERATION CONDITIONS	70
6.1.5 TEST RESULTS	71
7 . ANTENNA REQUIREMENT	72
7.1 STANDARD REQUIREMENT	72
7.2 EUT ANTENNA	72
8 . EUT TEST PHOTO	73
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

BZT Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.: 701733

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %** °.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	GSM MOBILE PHONE	
Trade Name	N/A	
Model Name	CHIC FIRE D40Z	
Serial Model	CHIC FIRE D45Z,S11,R11,N11	
Model Difference	All the model are the same,only different in model names.	
Product Description	The EUT is a GSM MOBILE PHONE	
	Operation Frequency:	802.11b/g/n 20:2412~2462 MHz 802.11n 40: 2422~2452MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20/40MHz):300/150/144.44/130/117/115.56/104/86.67/78/52/6.5 Mbps
	Number Of Channel	802.11b/g/n20: 11CH 802.11n 40: 7CH
	Antenna Designation:	Please see Note 3.
	Peak Output Power(Conducted):	802.11b: 9.89 dBm (Max.) 802.11g: 8.71 dBm (Max.) 802.11n(20MHz): 8.81 dBm (Max.) 802.11n(40MHz): 7.88dBm (Max.)
	Antenna Gain (dBi)	1.2 dbi
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	FHSS
	Bit Rate of Transmitter	GFSK
	Number Of Channel	79 CH
	Antenna Gain(Peak)	1.2dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Ratings	DC 3.7V from battery	
Adapter	N/A	
Battery	3.7V 2000mAh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	Integral Antenna	N/A	1.2	N/A

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n(20)CH1/ CH6/ CH11
Mode 4	802.11n(40) CH3/ CH6/ CH9
Mode 5	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n CH1/ CH6/ CH11
Mode 4	802.11n(40) CH3/ CH6/ CH9
Mode 5	Link Mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	GSM MOBILE PHONE	N/A	CHIC FIRE D40Z	N/A	EUT
E-2	Adapter	N/A	CHIC FIRE D40Z	N/A	
E-3	Earphone	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.5m	Usb cable
C-2	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2013.06.07	2014.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2013.06.07	2014.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2013.06.07	2014.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2013.06.08	2014.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2013.07.06	2014.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2013.06.07	2014.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2013.06.07	2014.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2013.06.08	2014.06.07	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	GSM MOBILE PHONE	Model Name. :	CHIC FIRE D40Z
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter with AC 120V/60Hz	Test Mode :	Mode 5

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
0.1669	22.13	9.58	31.71	55.11	-23.4	AVG
0.17	39.99	9.57	49.56	64.96	-15.4	QP
0.374	32.23	9.5	41.73	58.41	-16.68	QP
0.374	21.75	9.5	31.25	48.41	-17.16	AVG
2.03	27	9.55	36.55	56	-19.45	QP
2.03	15.81	9.55	25.36	46	-20.64	AVG
3.142	27.15	9.58	36.73	56	-19.27	QP
3.142	19.3	9.58	28.88	46	-17.12	AVG
6.5659	25.48	9.66	35.14	60	-24.86	QP
6.5659	15.41	9.66	25.07	50	-24.93	AVG
21.986	23.89	10.25	34.14	60	-25.86	QP
21.986	10.18	10.25	20.43	50	-29.57	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name. :	CHIC FIRE D40Z
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter with AC 120V/60Hz	Test Mode :	Mode 5

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
0.162	41.05	9.62	50.67	65.36	-14.69	QP
0.162	22.55	9.62	32.17	55.36	-23.19	AVG
0.382	33.89	9.52	43.41	58.23	-14.82	QP
0.382	25.68	9.52	35.2	48.23	-13.03	AVG
1.478	27.97	9.56	37.53	56	-18.47	QP
1.478	15.63	9.56	25.19	46	-20.81	AVG
2.034	26.99	9.57	36.56	56	-19.44	QP
2.034	13.53	9.57	23.1	46	-22.9	AVG
6.474	26.61	9.65	36.26	60	-23.74	QP
6.474	12.89	9.65	22.54	50	-27.46	AVG
23.222	24.37	10.26	34.63	60	-25.37	QP
23.222	11.16	10.26	21.42	50	-28.58	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	GSM MOBILE PHONE	Model Name. :	CHIC FIRE D40Z
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	Link mode	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	Link mode	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
31.0703	6.38	17.86	24.24	40	-15.76	QP
191.745	22.87	8.99	31.86	43.5	-11.64	QP
239.9874	26.75	11.65	38.4	46	-7.6	QP
336.035	23.94	16.03	39.97	46	-6.03	QP
672.8444	14.58	23.87	38.45	46	-7.55	QP
768.7481	14.11	26.2	40.31	46	-5.69	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	Link mode	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
47.9938	18.11	9.16	27.27	40	-12.73	QP
119.8555	21.03	12.09	33.12	43.5	-10.38	QP
143.8293	22.84	12.06	34.9	43.5	-8.6	QP
239.9874	27.75	11.65	39.4	46	-6.6	QP
336.035	20.26	16.03	36.29	46	-9.71	QP
866.0878	12.61	27.4	40.01	46	-5.99	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1 (802.11b Mode)/2412	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4824.15	55.29	10.44	65.73	74	-8.27	peak
4824.15	34.35	10.44	44.79	54	-9.21	AVG
7236.149	44.75	12.39	57.14	74	-16.86	peak
7236.149	33.27	12.39	45.66	54	-8.34	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1 (802.11b Mode)/2412	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.145	53.75	10.4	64.15	74	-9.85	peak
4874.145	31.27	10.4	41.67	54	-12.33	AVG
7311.163	50.27	12.75	63.02	74	-10.98	peak
7311.163	30.53	12.75	43.28	54	-10.72	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6 (802.11b Mode)/2437	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.159	48.93	10.4	59.33	74	-14.67	peak
4874.159	30.28	10.4	40.68	54	-13.32	AVG
7311.136	45.27	12.75	58.02	74	-15.98	peak
7311.136	29.23	12.75	41.98	54	-12.02	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6 (802.11b Mode)/2437	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.146	47.35	10.39	57.74	74	-16.26	peak
4934.146	35.32	10.44	45.76	54	-8.24	AVG
7386.143	44.39	12.68	57.07	74	-16.93	peak
7386.143	31.02	12.68	43.7	54	-10.3	AVG

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. No emission detected above 18GHz

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11 (802.11b Mode)/2462	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.145	48.38	10.39	58.77	74	-15.23	peak
4924.145	33.86	10.39	44.25	54	-9.75	AVG
7386.142	46.49	12.68	59.17	74	-14.83	peak
7386.142	31.91	12.68	44.59	54	-9.41	AVG

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- No emission detected above 18GHz

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11 (802.11b Mode)/2462	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.122	47.18	10.39	57.57	74	-16.43	peak
4924.122	33.28	10.39	43.67	54	-10.33	AVG
7386.143	45.21	12.68	57.89	74	-16.11	peak
7386.143	32.15	12.68	44.83	54	-9.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1 (802.11g Mode)/2412	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.17	42.15	10.44	52.59	74	-21.41	peak
4824.17	32.27	10.44	42.71	54	-11.29	AVG
7236.224	43.58	12.39	55.97	74	-18.03	peak
7236.224	34.81	12.39	47.2	54	-6.8	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1 (802.11g Mode)/2412	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.155	50.28	10.44	60.72	74	-13.28	peak
4824.155	31.27	10.44	41.71	54	-12.29	AVG
7236.142	43.16	12.39	55.55	74	-18.45	peak
7236.142	32.83	12.39	45.22	54	-8.78	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6 (802.11g Mode)/2437	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.14	43.61	10.4	54.01	74	-19.99	peak
4874.14	29.82	10.4	40.22	54	-13.78	AVG
7311.17	41.27	12.75	54.02	74	-19.98	peak
7311.17	28.39	12.75	41.14	54	-12.86	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6 (802.11g Mode)/2437	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.158	48.29	10.4	58.69	74	-15.31	peak
4874.158	33.04	10.4	43.44	54	-10.56	AVG
7311.137	43.25	12.75	56	74	-18	peak
7311.137	32.17	12.75	44.92	54	-9.08	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11 (802.11g Mode)/2462	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.138	45.14	10.39	55.53	74	-18.47	peak
4924.138	33.21	10.39	43.6	54	-10.4	AVG
7386.149	42.28	12.68	54.96	74	-19.04	peak
7386.149	29.84	12.68	42.52	54	-11.48	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11(802.11g Mode)/2462	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4924.148	43.29	10.39	53.68	74	-20.32	peak
4924.148	31.24	10.39	41.63	54	-12.37	AVG
7386.13	43.06	12.68	55.74	74	-18.26	peak
7386.13	31.27	12.68	43.95	54	-10.05	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1(802.11n Mode)/20MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.14	43.28	10.44	53.72	74	-20.28	peak
4824.14	35.84	10.44	46.28	54	-7.72	AVG
7236.122	45.58	12.39	57.97	74	-16.03	peak
7236.122	28.08	12.39	40.47	54	-13.53	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH1(802.11n Mode)/20MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824.141	47.28	10.44	57.72	74	-16.28	peak
4824.141	35.12	10.44	45.56	54	-8.44	AVG
7236.145	47.23	12.39	59.62	74	-14.38	peak
7236.145	32.11	12.39	44.5	54	-9.5	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6(802.11n Mode)/20MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.16	50.16	10.4	60.56	74	-13.44	peak
4874.16	34.27	10.4	44.67	54	-9.33	AVG
7311.128	43.65	12.75	56.4	74	-17.6	peak
7311.128	29.16	12.75	41.91	54	-12.09	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6(802.11n Mode)/20MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.161	43.11	10.4	53.51	74	-20.49	peak
4874.161	29.19	10.4	39.59	54	-14.41	AVG
7311.166	42.87	12.75	55.62	74	-18.38	peak
7311.166	27.02	12.75	39.77	54	-14.23	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11(802.11n Mode)/20MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924.14	42.17	10.39	52.56	74	-21.44	peak
4924.14	31.25	10.39	41.64	54	-12.36	AVG
7386.183	40.21	12.68	52.89	74	-21.11	peak
7386.183	31.23	12.68	43.91	54	-10.09	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH11(802.11n Mode)/20MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924.15	46.27	10.39	56.66	74	-17.34	peak
4924.15	33.09	10.39	43.48	54	-10.52	AVG
7386.167	39.18	12.68	51.86	74	-22.14	peak
7386.167	28.13	12.68	40.81	54	-13.19	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH3(802.11n Mode)/40MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4844.156	47.86	10.5	58.36	74	-15.64	peak
4844.156	33.21	10.5	43.71	54	-10.29	AVG
7266.319	42.61	12.5	55.11	74	-18.89	peak
7266.319	32.52	12.5	45.02	54	-8.98	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH3(802.11n Mode)/40MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4844.325	45.16	10.5	55.66	74	-18.34	peak
4844.325	30.11	10.5	40.61	54	-13.39	AVG
7266.258	43.17	12.5	55.67	74	-18.33	peak
7266.258	29.81	12.5	42.31	54	-11.69	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6(802.11n Mode)/40MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.238	40.29	10.4	50.69	74	-23.31	peak
4874.238	29.67	10.4	40.07	54	-13.93	AVG
7311.159	40.62	12.75	53.37	74	-20.63	peak
7311.159	29.91	12.75	42.66	54	-11.34	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH6(802.11n Mode)/40MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4874.535	43.84	10.4	54.24	74	-19.76	peak
4874.535	31.19	10.4	41.59	54	-12.41	AVG
7311.633	39.17	12.75	51.92	74	-22.08	peak
7311.633	29.22	12.75	41.97	54	-12.03	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH9(802.11n Mode)/40MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904.345	45.78	10.29	56.07	74	-17.93	peak
4904.345	35.38	10.29	45.67	54	-8.33	AVG
7356.247	43.14	12.79	55.93	74	-18.07	peak
7356.247	30.55	12.79	43.34	54	-10.66	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	CH9(802.11n Mode)/40MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904.16	45.29	10.29	55.58	74	-18.42	peak
4904.16	32.19	10.29	42.48	54	-11.52	AVG
7356.423	42.83	12.79	55.62	74	-18.38	peak
7356.423	31.28	12.79	44.07	54	-9.93	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.


3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11b Mode)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2397.1	83.21	-13.02	70.19	74	-3.81	peak
2397.1	60.12	-13.02	47.1	54	-6.9	AVG
2400	81.26	-12.99	68.27	74	-5.73	peak
2400	59.71	-12.99	46.72	54	-7.28	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2397.75	77.99	-13	64.99	74	-9.01	peak
2397.75	60.21	-13	47.21	54	-6.79	AVG
2400	74.69	-12.99	61.7	74	-12.3	peak
2400	58.15	-12.99	45.16	54	-8.84	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11b Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2483.5	75.21	-12.78	62.43	74	-11.57	peak
2483.5	60.28	-12.78	47.5	54	-6.5	AVG

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11b Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	75.61	-12.78	62.83	74	-11.17	peak
2483.5	59.21	-12.78	46.43	54	-7.57	AVG


Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2400	82.11	-12.99	69.12	74	-4.88	2400
2400	60.62	-12.99	47.63	54	-6.37	2400

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11gMode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	83.12	-12.99	70.13	74	-3.87	peak
2400	61.29	-12.99	48.3	54	-5.7	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11g Mode)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2483.5	61.71	-12.78	48.93	74	-25.07	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11g Mode)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	62.84	-12.78	50.06	74	-23.94	2483.5

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11n Mode)/20MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2400	72.18	-12.99	59.19	74	-14.81	peak
2400	59.28	-12.99	46.29	54	-7.71	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH1(802.11n Mode)/20M	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	74.71	-12.99	61.72	74	-12.28	peak
2400	60.26	-12.99	47.27	54	-6.73	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11n Mode)/20MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2483.5	74.21	-12.78	61.43	74	-12.57	peak
2483.5	61.53	-12.78	48.75	54	-5.25	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH11(802.11n Mode)/20MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	72.13	-12.78	59.35	74	-14.65	peak
2483.5	59.61	-12.78	46.83	54	-7.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH3(802.11n Mode)/40M	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	79.31	-12.99	66.32	74	-7.68	peak
2400	63.29	-12.99	50.3	54	-3.7	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH3(802.11n Mode)/40MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400	69.17	-12.99	56.18	74	-17.82	peak
2400	56.74	-12.99	43.75	54	-10.25	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH9(802.11n Mode)/40MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2483.5	61.25	-12.78	48.47	74	-25.53	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V FROM ADAPTER WITH AC 120V/60HZ
Test Mode :	CH9(802.11n Mode)/40MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.5	62.11	-12.78	49.33	74	-24.67	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-8.851	8	PASS
2437 MHz	-9.596	8	PASS
2462 MHz	-8.832	8	PASS







EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-15.1	8	PASS
2437 MHz	-13.09	8	PASS
2462 MHz	-14.34	8	PASS







EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-14.77	8	PASS
2437 MHz	-13.54	8	PASS
2462 MHz	-14.22	8	PASS







EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-20.66	8	PASS
2437 MHz	-18.06	8	PASS
2452 MHz	-21.32	8	PASS





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	9.998	12.97	>=500KHz	PASS
2437 MHz	9.584	13.12	>=500KHz	PASS
2462 MHz	9.611	13.36	>=500KHz	PASS






EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	16.33	16.35	>=500KHz	PASS
2437 MHz	16.31	16.35	>=500KHz	PASS
2462 MHz	15.41	16.36	>=500KHz	PASS






EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2412 MHz	15.34	17.54	>=500KHz	PASS
2437 MHz	17.14	17.54	>=500KHz	PASS
2462 MHz	16.97	17.54	>=500KHz	PASS






EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

Frequency	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Channel Separation (MHz)	Result
2422 MHz	35.15	35.70	>=500KHz	PASS
2437 MHz	35.33	35.72	>=500KHz	PASS
2452 MHz	35.28	35.71	>=500KHz	PASS





6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	GSM MOBILE PHONE	Model Name :	CHIC FIRE D40Z
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from Adapter with AC 120V/60Hz
Test Mode :	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	9.89	30
CH06	2437	9.48	30
CH11	2462	9.25	30
TX 802.11g Mode			
CH01	2412	8.71	30
CH06	2437	8.48	30
CH11	2462	8.51	30
TX 802.11n20 Mode			
CH01	2412	8.21	30
CH06	2437	8.81	30
CH11	2462	8.31	30
TX 802.11n40 Mode			
CH03	2422	7.88	30
CH06	2437	7.21	30
CH09	2452	7.67	30



7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The EUT antenna is integral antenna . It comply with the standard requirement.

8. EUT TEST PHOTO**Radiated Measurement Photos**

Conducted Measurement Photos

