



REPORT No.: SZ19050188S01

# RF EXPOSURE EXEMPT REPORT

**APPLICANT** : Soundmax Electronics Limited  
**PRODUCT NAME** : BT MODULE CW51P  
**MODEL NAME** : BT MODULE CW51P  
**BRAND NAME** : N/A  
**FCC ID** : 2AB7S-CW51P  
**STANDARD(S)** : 47CFR 2.1093  
KDB 447498  
**RECEIPT DATE** : 2019-05-16  
**TEST DATE** : 2019-05-29  
**ISSUE DATE** : 2019-05-29

Edited by: Chen Hao  
Chen Hao (Rapporteur)  
Approved by: Peng Huarui  
Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





## DIRECTORY

1. Technical Information.....	3
1.1 Applicant and Manufacturer Information.....	3
1.2 Equipment Under Test (EUT) Description .....	3
1.3 Photographs of the EUT.....	4
1.4 Identification of all used EUT .....	5
1.5 Applied Reference Documents .....	5
2. Device Category and RF Exposure Limit .....	6
3. Measurement of RF Output Power .....	7
4. RF Exposure Evaluation .....	8
Annex A General Information.....	9

Change History		
Version	Date	Reason for change
1.0	2019-05-29	First edition



# 1. Technical Information

**Note:** Provide by manufacturer.

## 1.1 Applicant and Manufacturer Information

<b>Applicant:</b>	Soundmax Electronics Limited
<b>Applicant Address:</b>	17/F., Eu Yan Sang Tower, 11-15 Chatham Road South, Tsim Sha Tsui, KowLoon., HongKong
<b>Manufacturer:</b>	Coordiwise Technology Corp
<b>Manufacturer Address:</b>	2F., No. 168, Sec. 1, Liujia 5th Rd., Zhubei City, Hsinchu County 302, Taiwan (R.O.C.)

## 1.2 Equipment Under Test (EUT) Description

<b>EUT Name:</b>	BT MODULE CW51P
<b>Hardware Version:</b>	V1.0
<b>Software Version:</b>	410B029
<b>Frequency Bands:</b>	Bluetooth: 2402-2480MHz
<b>Modulation Mode:</b>	GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps)
<b>Antenna Type:</b>	PCB antenna
<b>Antenna Gain:</b>	0dBi

## 1.3 Photographs of the EUT

### 1. EUT Front View



### 2. EUT Back View





## 1.4 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V1.0	410B029

## 1.5 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radio Frequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



## 2. Device Category and RF Exposure Limit

Per user manual, this device is a Wall Control for HRV unit P/N: 99-MX01. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

### **Portable Devices:**

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

### **GENERAL POPULATION / UNCONTROLLED EXPOSURE**

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.



### 3. Measurement of RF Output Power

#### 1. Bluetooth output power

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	-4.80	-6.50	-6.52
	CH 39	2441	-5.61	-7.04	-7.09
	CH 78	2480	-4.00	-7.44	-6.00
Tune-up Limit			-3.5	-6	-6

**Note:** According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

## 4. RF Exposure Evaluation

### Standalone transmission SAR evaluation:

1. According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances  $\leq 50$  mm are determined by:  
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ .
  - $f(\text{GHz})$  is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation
  - The result is rounded to one decimal place for comparison
2. The maximum source-based time-averaged including tune-up limit is 0mW @ 2.48GHz. When the BT MODULE CW51P is used on hand/head, 5mm as the most conservative minimum test separation distance was used for evaluating,

Channel	Frequency (GHz)	Max. tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 78	2.48	-3.5	0	5	0	3.0

### Simultaneous SAR evaluation:

This device only incorporates a Bluetooth module, Therefore simultaneous SAR evaluation is not required.





## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

\_\_\_\_\_ END OF REPORT \_\_\_\_\_