



26 dB RF Bandwidth & 99 % Occupied Bandwidth Measurement


Test Mode	Mode 2: IEEE 802.11a Continuous TX mode			
Frequency	26 dB Bandwidth (MHz)		•	ed Bandwidth Hz)
(MHz)	Ant-0	Ant-1	Ant-0	Ant-1
5180	19.980	19.070	16.493	16.448
5200	35.150	32.220	17.769	17.055
5240	35.140	32.820	18.050	17.265

Test Mode	Mode 3: IEEE 802.11ac 20 MHz Continuous TX mode			
Frequency		andwidth Hz)	·	ed Bandwidth Hz)
(MHz)	Ant-0	Ant-1	Ant-0	Ant-1
5180	20.520	20.470	17.623	17.635
5200	35.530	32.580	18.245	18.099
5240	35.590	32.900	18.578	18.226

Test Mode	Mode 4: IEEE 802.11ac 40 MHz Continuous TX mode			
Frequency	26 dB Bandwidth (MHz)		·	ed Bandwidth Hz)
(MHz)	Ant-0	Ant-1	Ant-0	Ant-1
5190	40.380	40.470	36.007	35.989
5230	49.450	45.240	36.151	36.077

Test Mode	Mode 5: IEEE 802.11ac 80 MHz Continuous TX mode			
Frequency	26 dB Bandwidth 99 % Occupied Bandwidth (MHz) (MHz)			
(MHz)	Ant-0	Ant-1	Ant-0	Ant-1
5210	83.520	83.290	75.729	75.643


Note: The 99 % occupied bandwidth not crossed 5250 MHz.






Test Graphs



















































6 dB RF Bandwidth Measurement

Test Mode	Mode 2: IEEE 802.11a Continuous TX mode			
Frequency (MHz)	ANT-0 ANT-1 Limit (kHz)			
5745	16310	16330	≥ 500	
5785	16080	16320	≥ 500	
5825	16330	16340	≥ 500	

Test Mode	Mode 3: IEEE 802.11ac 20 MHz Continuous TX mode			
Frequency (MHz)	ANT-0 ANT-1 Limit (kHz)			
5745	17600	17280	≥ 500	
5785	17590	17350	≥ 500	
5825	17590	17360	≥ 500	


Test Mode	Mode 4: IEEE 802.11ac 40 MHz Continuous TX mode		
Frequency (MHz)	ANT-0	Limit (kHz)	
5755	35310	35160	≥ 500
5795	35170	35180	≥ 500


Test Mode	Mode 5: IEEE 802.11ac 80 MHz Continuous TX mode			
Frequency (MHz)	ANT-0 ANT-1 Limit (kHz)			
5775	75800	75800	≥ 500	






Test Graphs












































Rev.01

Maximum Power Spectral Density Measurement

Test Mode	Mode 2: IEEE 802.11a	Mode 2: IEEE 802.11a link mode				
F	ANT-0					
Frequency (MHz)	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)		
5180	4.344	0.123	4.467			
5200	7.919	0.123	8.042	≤ 10.99		
5240	7.725	0.123	7.848			
Fraguenay		AN	T-1			
Frequency (MHz)	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)		
5180	3.392	0.123	3.515			
5200	7.381	0.123	7.504	≤ 10.99		
5240	7.293	0.123	7.416			
Fraguenay		ANT	-0+1			
Frequency (MHz)		Calculated (dBm/MHz)		Limit (dBm/MHz)		
5180	7.027					
5200	10.792			≤ 10.99		
5240		10.648				

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.



Rev.01

To all NA and a	M. J. O. IEEE 000 44.	P.Id.			
Test Mode	Mode 2: IEEE 802.11a	Mode 2: IEEE 802.11a link mode			
Frequency	ANT-0				
(MHz)	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)	
5745	0.264	0.123	7.377		
5785	-0.186	0.123	6.927	≤ 23.99	
5825	-0.202	0.123	6.911		
Fraguanay		AN	T-1		
Frequency (MHz)	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)	
5745	0.446	0.123	7.559		
5785	-0.275	0.123	6.838	≤ 23.99	
5825	-0.549	0.123	6.564		
Fraguanay		ANT	-0+1		
Frequency (MHz)	Calculated (dBm/500 kHz)			Limit (dBm/500 kHz)	
5745	10.479				
5785	9.893			≤ 23.99	
5825		9.751			

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.



Rev.01

Test Mode	Mode 3: IEEE 802.11a	Mode 3: IEEE 802.11ac 20 MHz link mode				
F	ANT-0					
Frequency (MHz)	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)		
5180	4.104	0.038	4.142			
5200	7.722	0.038	7.760	≤ 10.99		
5240	7.757	0.038	7.795			
		AN	T-1			
Frequency (MHz)	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)		
5180	3.187	0.038	3.225			
5200	7.061	0.038	7.099	≤ 10.99		
5240	7.181	0.038	7.219			
Fraguenay		ANT	-0+1			
Frequency (MHz)	Calculated (dBm/MHz)			Limit (dBm/MHz)		
5180	6.718					
5200	10.453			≤ 10.99		
5240	10.527					


Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.



Rev.01

Test Mode	Mode 3: IEEE 802.11a	c 20 MHz link mode			
Fraguenay	ANT-0				
Frequency (MHz)	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)	
5745	0.398	0.038	7.426		
5785	-0.192	0.038	6.836	≤ 23.99	
5825	-0.078	0.038	6.950		
Fraguanay		AN	T-1		
Frequency (MHz)	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)	
5745	0.367	0.038	7.395		
5785	-0.239	0.038	6.789	≤ 23.99	
5825	-0.172	0.038	6.856		
Frequency		ANT	-0+1		
(MHz)	Calculated (dBm/500 kHz)		Limit (dBm/500 kHz)		
5745	10.421				
5785	9.823			≤ 23.99	
5825		9.914			

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.





Test Mode	Mode 4: IEEE 802.11ac 40 MHz link mode				
Frequency (MHz)	ANT-0				
	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)	
5190	-4.109	0.105	-4.004	≤ 10.99	
5230	2.748	0.105	2.853		
Fraguenay	ANT-1				
Frequency (MHz)	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)	
5190	-5.353	0.105	-5.248	≤ 10.99	
5230	2.036	0.105	2.141		
Frequency (MHz)	ANT-0+1				
	Calculated (dBm/MHz)			Limit (dBm/MHz)	
5190	-1.572			≤ 10.99	
5230	5.522				

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.

Test Mode	Mode 4: IEEE 802.11ac 40 MHz link mode			
Frequency (MHz)	ANT-0			
	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)
5755	-5.081	0.105	2.013	≤ 23.99
5795	-5.612	0.105	1.482	
Frequency (MHz)	ANT-1			
	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)
5755	-4.535	0.105	2.559	≤ 23.99
5795	-5.982	0.105	1.112	
Frequency (MHz)	ANT-0+1			
	Calculated (dBm/500 kHz)			Limit (dBm/500 kHz)
5755	5.305 4.312			≤ 23.99
5795				

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.




Rev.01

Test Mode	Mode 5: IEEE 802.11ac 80 MHz link mode			
Frequency (MHz)	ANT-0			
	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)
5210	-10.900	0.237	-10.663	≤ 10.99
Frequency (MHz)	ANT-1			
	Measurement (dBm/MHz)	Duty Factor (dB)	Calculated (dBm/MHz)	Limit (dBm/MHz)
5210	-11.611	0.237	-11.374	≤ 10.99
Frequency (MHz)	ANT-0+1			
	Calculated (dBm/MHz)		Limit (dBm/MHz)	
5210	-7.994			≤ 10.99

Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.


Test Mode	Mode 5: IEEE 802.11ac 80 MHz link mode			
Frequency (MHz)	ANT-0			
	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)
5775	-14.100	0.237	-6.874	≤ 23.99
Frequency (MHz)	ANT-1			
	Measurement (dBm/100 kHz)	Duty Factor (dB)	Calculated (dBm/500 kHz)	Limit (dBm/500 kHz)
5775	-14.306	0.237	-7.080	≤ 23.99
Frequency (MHz)	ANT-0+1			
	Calculated (dBm/500 kHz)			Limit (dBm/500 kHz)
5775	-3.965			≤ 23.99


Note: Method SA-2, Power density = measured result + 10 log(1/duty cycle) + Conversion ratio = measured result + duty factor.






Test Graphs











































































































---- END----