

## **FCC RF EXPOSURE REPORT**

FCC ID:2AB9W-3F11X

Project No. : 1411074 Equipment : 3D Printer

Model : da Vince 1.1 Plus Applicant : XYZprinting, Inc.

Address: 10F., No.99, Sec. 5, Nanjing E. Rd., Songshan

Dist., Taipei City 10571, Taiwan(R.O.C.)

According: : FCC Guidelines for Human Exposure IEEE C95.1

# BTL INC.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



### MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

#### Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1	WIESON	GY136TH0131C-001	Internal	N/A	2.73	TX/RX



# **TEST RESULTS**

EUT:	3D Printer	Model Name :	da Vince 1.1 Plus	
Temperature:	<b>25</b> ℃	Relative Humidity:	55 %	
Test Voltage:	AC 120V/60Hz			
Test Mode :	TX B MODE /CH01, CH06, CH11	1		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.73	1.8750	13.52	22.4905	0.00839364	1	Complies
2.73	1.8750	13.48	22.2844	0.00831669	1	Complies
2.73	1.8750	13.23	21.0378	0.00785146	1	Complies

EUT:	3D Printer	Model Name :	da Vince 1.1 Plus	
Temperature:	<b>25</b> ℃	Relative Humidity:		
Test Voltage:	AC 120V/60Hz			
Test Mode :	TX G MODE /CH01, CH06, CH1	1		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.73	1.8750	18.63	72.9458	0.02722390	1	Complies
2.73	1.8750	18.57	71.9449	0.02685038	1	Complies
2.73	1.8750	18.54	71.4496	0.02666554	1	Complies

EUT:	3D Printer	Model Name :	da Vince 1.1 Plus			
Temperature:	mperature: 25 °C F		55 %			
Test Voltage:	AC 120V/60Hz					
Test Mode :	TX N-20M MODE /CH01, CH06, CH11					

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.73	1.8750	17.75	59.5662	0.02223056	1	Complies
2.73	1.8750	17.77	59.8412	0.02233317	1	Complies
2.73	1.8750	17.63	57.9429	0.02162471	1	Complies

Note: the calculated distance is 20 cm.