

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ABAE-BIGGIFI-001

### EUT Specification

<b>EUT</b>	Smart TV Stick
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	16.26dBm (42.27mW)
<b>Antenna gain</b>	1.2 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## Friis transmission formula: $Pd=(Pout \cdot G)/(4 \cdot \pi \cdot R^2)$

Where

$Pd$ = Power density in  $mW/cm^2$

$Pout$ =output power to antenna in Mw

$G$ = gain of antenna in linear scale ;  $Pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$Pd$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Channel	Channel Frequency (MHz)	Output Peak power (mW)	Antenna Gain (dBi)	Power density at 20cm ( $mW/cm^2$ )	Power density Limits ( $mW/cm^2$ )
<b>802.11b</b>					
Lowest	2412	19.19	1.2	0.005033	1
Middle	2437	18.71	1.2	0.004907	1
Highest	2462	19.45	1.2	0.005101	1
<b>802.11g</b>					
Lowest	2412	40.18	1.2	0.010538	1
Middle	2437	40.55	1.2	0.010635	1
Highest	2462	42.27	1.2	0.011086	1
<b>802.11n(HT20)</b>					
Lowest	2412	27.61	1.2	0.007241	1
Middle	2437	27.86	1.2	0.007307	1
Highest	2462	29.17	1.2	0.007650	1

Sincerely,



(signature)

Karl Zhao

Manager

Tel: 949-246-0528 Fax: 949-207-3298

E-mail: [karl@digilinksoftware.com](mailto:karl@digilinksoftware.com)

Address: 19 Goddard, Irvine, CA 92618