

113.00 mm

NXG
TECHNOLOGY
NX-DECO5
Powered Speaker

PCM
OPTICAL IN



SUB OUT



LINE IN



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference, including interference that may cause undesired operation.

Model number: NX-DECO5
FCC ID: 2ABB4-NXDECO5



Intertek
3114849

OUTPUT TO NX-DECO5
PASSIVE SPEAKER

+



-

NXG
TECHNOLOGY
Scottsdale, AZ
nxgtechnology.com

Designed & Engineered in U.S.A. Manufactured in China



NOT SUITABLE FOR IN-WALL MOUNTING
PAS ADAPTÉ POUR MONTAGE MURAL



WARNING: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

AVERTISSEMENT: POUR RÉDUIRE LE RISQUE DE CHOC ELECTRIQUE, NE PAS ENLEVER LE COUVERCLE (NI LE DOS). AUCUNE PIÈCE À L'INTERIEUR. ENTRETIEN DE PERSONNEL QUALIFIE.

100-240V~
50-60Hz 120W

113.00 mm

NXG
TECHNOLOGY
NX-DECO5
Passive Speaker

INPUT FROM NX-DECO5
POWERED SPEAKER

+



-

NXG
TECHNOLOGY
Scottsdale, AZ
nxgtechnology.com

Designed & Engineered in U.S.A. Manufactured in China



175.00 mm

175.00 mm