



CTK Co., Ltd.  
The First Leader of Global Regulatory Compliance

## CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea  
Tel: +82-31-339-9970 Fax: +82-31-339-9855  
www.e-ctk.com

---

# RF EXPOSURE EVALUATION

**Applicant** : Dekist Co.,Ltd

**Applicant Address** : #303 465-1 Gimryangjang-dong Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

**Kind of Product** : Multi Function 4-20mA Wireless Transmeter

**Equipment model name** : RN910

**Antenna type** : Dipole antenna    **Gain** : 1.649 dBi

**Frequency Range** : 2405 – 2475 MHz

**Number of channels** : 15



CTK Co., Ltd.  
The Prime Leader of Global Regulatory Compliance

## CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea  
Tel: +82-31-339-9970 Fax: +82-31-339-9855  
www.e-ctk.com

### \*\* MPE Calculations \*\*

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

$\begin{aligned} \text{EIRP} &= P + G \\ \text{EIRP} &= 32.43 + 1.649 \\ &= 16.759 \text{ dBm} \end{aligned}$	<p>Where,</p> <p>P = Power input to the antenna (mW)</p> <p>G = Power gain of the antenna (dBi)</p>
---	---

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

$$G = \text{Log}^{-1} (1.649 / 10)$$

$$G = 1.462$$

#### Power density at the specific separation:

$\begin{aligned} S &= PG / (4R^2\pi) \\ S &= (32.43 * 1.462) / (4 * 20^2 * \pi) \\ S &= 0.0094 \text{ mW/cm}^2 \end{aligned}$	<p>Where,</p> <p>S = Maximum power density (mW/cm<sup>2</sup>)</p> <p>P = Power input to the antenna (mW)</p> <p>G = Numeric power gain of the antenna</p> <p>R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)</p>
---	---

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm<sup>2</sup>.

The power density at 20cm does not exceed the 1 mW/cm<sup>2</sup> limit.

#### Estimated safe separation:

$\begin{aligned} R &= \sqrt{(PG / 4\pi)} \\ R &= \sqrt{(32.43 * 1.462 / 4\pi)} \\ R &= 1.94 \text{ cm} \end{aligned}$	<p>Where,</p> <p>P = Power input to the antenna (mW)</p> <p>G = Numeric power gain of the antenna</p> <p>R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)</p>
---	--