

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM140500267402

Page: 1 of 8

# **RF Exposure Evaluation Report**

**Application No.:** SZEM1405002674RF

Applicant: Shenzhen Electron Technology Co.,Ltd.

Manufacturer: Shenzhen Electron Technology Co.,Ltd.

Factory Shenzhen Electron Technology Co.,Ltd.

**Product Name:** Wifi Digital Photo Frame

Model No.(EUT): W08C-XY

**Add Model No.:** W08D-XY (The XY is client number from 01 to 50)

Trade mark: nixplay

**FCC ID:** 2ABC5-W0528

**Standards:** 47 CFR Part 1.1307(2013)

47 CFR Part 1.1310(2013)

**Date of Receipt:** 2014-06-04

**Date of Test:** 2014-06-11 to 2014-06-23

**Date of Issue:** 2014-06-25

Test Result : PASS\*

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM140500267402

Page: 2 of 8

### 2 Contents

	Page
COVER PAGE	1
CONTENTS	2
GENERAL INFORMATION	3
3.1 CLIENT INFORMATION	3
3.2 GENERAL DESCRIPTION OF EUT	3
3.4 TEST FACILITY	5
3.5 DEVIATION FROM STANDARDS	6
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 EUT RF EXPOSURE EVALUATION	8
2	CONTENTS  GENERAL INFORMATION.  3.1 CLIENT INFORMATION.  3.2 GENERAL DESCRIPTION OF EUT.  3.3 TEST LOCATION.  3.4 TEST FACILITY.  3.5 DEVIATION FROM STANDARDS.  3.6 ABNORMALITIES FROM STANDARD CONDITIONS.  3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER  RF EXPOSURE EVALUATION.  4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.  4.1.1 Limits.  4.1.2 Test Procedure.



Report No.: SZEM140500267402

Page: 3 of 8

### 3 General Information

### 3.1 Client Information

Applicant:	Shenzhen Electron Technology Co.,Ltd.	
Address of Applicant:	5/F, A bldg, Northern Junyi Park, Cuigang Sixth Industrial area, Fuyon	
	Town, Bao'an district, Shenzhen, China	
Manufacturer:	Shenzhen Electron Technology Co.,Ltd.	
Address of Manufacturer:	5/F, A bldg, Northern Junyi Park, Cuigang Sixth Industrial area, Fuyong	
	Town, Bao'an district, Shenzhen, China	
Factory:	Shenzhen Electron Technology Co.,Ltd.	
Address of Factory:	5/F, A bldg, Northern Junyi Park, Cuigang Sixth Industrial area, Fuyong	
	Town, Bao'an district, Shenzhen, China	

### 3.2 General Description of EUT

Product Name:	Wifi Digital Photo Frame	
Model No.:	W08C-XY, W08D-XY (The XY is client number from 01 to 50)	
Trade Mark:	nixplay	
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz	
	IEEE 802.11n(HT40): 2422MHz to 2452MHz	
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels	
	IEEE 802.11n HT40: 7 Channels	
Channel Separation:	5MHz	
Type of Modulation:	DSSS	
Sample Type:	Fixed production	
	IEEE 802.11b:14, IEEE 802.11g(20MHz):13,	
Test power grade:	IEEE 802.11n HT20:11.5,	
	IEEE 802.11n HT40: (40MHz):11.5 (manufacturer declare )	
Test software of EUT:	adb shell (manufacturer declare )	
Antenna Type:	Outside welds the antenna(manufacturer declare)	
Antenna Type and Gain:	nin: Type: Integral	
	Gain: 3.27dBi	
AC Adapter:	MODEL: FJ-SW0501500DU INPUT: AC 100-240V~50/60Hz 0.35A max OUTPUT: 5.0V == 1500mA	



Report No.: SZEM140500267402

Page: 4 of 8

Power Supply:	3.0V DC (3.0V x 1 "CR2025" Button cell) for remote control
Test Voltage:	230V~60Hz
AC Cable:	197cm (Unshielded)
Remark:	Only the model W08C-XY was tested, since the circuit design, PCB layout, electrical components used, internal wiring and functions were identical for the above models, with difference being the model No. and color.



Report No.: SZEM140500267402

Page: 5 of 8

### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.



Report No.: SZEM140500267402

Page: 6 of 8

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.





Report No.: SZEM140500267402

Page: 7 of 8

# 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### **4.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6		
(B) Limits	for General Populati	on/Uncontrolled Exp	oosure			
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30 30		

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout\*G)/(4\* Pi \* R 2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140500267402

Page: 8 of 8

### 4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 3.27dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.1232 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm <sup>2</sup> )		
Highest	2462	14.70	29.5121	0.0125	1.0	PASS

Note: Refer to report No. SZEM140500267401for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.