

ACCREDIT CERT #3816.0

Report No.: SZEM190701695002

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1907016950CR

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Address of Applicant: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan,

Shenzhen, China

Manufacturer: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Address of Manufacturer: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan,

Shenzhen, China

Factory: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Address of Factory: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan,

Shenzhen, China

Equipment Under Test (EUT):

Product Name: Wifi Digital Photo Frame

Model No.: W10E

FCC ID: 2ABC5-W0535

Standards: 47 CFR Part 1.1307

47 CFR Part 1.1310

Date of Receipt: 2019-07-31

Date of Test: 2019-08-18 to 2019-10-12

Date of Issue: 2019-10-15

Test Result : PASS*

Keny Xu EMC Laboratory Manager

Ceny. Ku



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.sepy.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.sepy.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein, Any holder of this document is advised that information contained hereon reflects the Company's indings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excend and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 3D days only.

Attention: To check the authenticity of testing /inspection report & certificate (see refered to the state of the substance).

No.1 Workshop, M-10, Mode Section, Science & Technology Park, Sherizhen, China 518057 t (86-755) 2601:2053 t (86-755) 26710594 www.sps.group.com.
中国 - 梁圳 - 科技园中区M-10练—号厂房 邮票: 518057 t (86-755) 2601:2053 t (86-755) 26710594 sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM190701695002

Page: 2 of 8

2 Version

Revision Record						
Version Chapter		Date	Modifier	Remark		
01		2019-10-15		Original		

Authorized for issue by:		
	leo. 61	
	Leo Li /Project Engineer	-
	EvicFu	
	Eric Fu /Reviewer	-



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.scs.com/en/Terms-and-Conditions.ascx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.scs.com/en/Terms-and-Conditions/Terms-and-Cond

or e-mail: CN. Doccheck@sgs.com
No.1 Workshop, M-10, Midde Section, Science & Technology Park, Shemzhen, China 518/057 t (86-755) 2601/2053 f (86-755) 26710594 www.sgsgroup.com.cn
中国 - 采圳 - 科技図中区M-10核—号厂房 邮籍: 518/057 t (86-755) 2601/2053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: SZEM190701695002

Page: 3 of 8

3 Contents

	Page
COVER PAGE	1
VERSION	2
CONTENTS	3
GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION	5
4.3 TEST FACILITY	5
4.4 DEVIATION FROM STANDARDS	6
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
RF EXPOSURE EVALUATION	7
5.1 RF Exposure Compliance Requirement	7
5.1.1 Limits	
5.1.2 Test Procedure	<i>7</i>
4.1.3 EUT RF EXPOSURE EVALUATION	
	4.1 GENERAL DESCRIPTION OF EUT



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeef, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-en/d-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of Hability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and its document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forsety-or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) bested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing firespection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: \$CN.Doccheck-Resas.com

No.1 Workshop, M-10, Midde Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (88-755) 26710594 www.sgsgroup.com.cn 中国 - 采划 - 科技园中区M-10核—号厂房 邮籍: 518057 t (86-755) 26012053 f (88-755) 26710594 sgs.china@sgs.com



Report No.: SZEM190701695002

Page: 4 of 8

4 General Information

4.1 General Description of EUT

Power supply:	DC 5V	
	Adapter Model:S018-1A050250VU	
	Input: AC120V 60Hz 0.6A	
	Output:DC 5.0V 2.5A	
Cable:	DC cable: 200cm shielded	
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz	
	802.11n(HT40): 2422MHz to 2452MHz	
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK)	
	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)	
Number of Channels:	802.11b/g/n(HT20):11	
	802.11n(HT40):7	
Channel Spacing:	5MHz	
Antenna Type:	FPC Antenna	
Antenna Gain:	1.5dBi	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available or request or accessible at https://www.sgs.com/en/Terms-and-Conditions.sags and, for electronic format documents, subject to Terms-and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Pocument-ags-Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alreadion, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s). Para retained for 3D days only.

Attention: To check the authenticity of testing fins pection report & certificate, please contact us at telephone: (85-755) 8307 1443.

or email: CN.Doccheck-Roses.com.

or e-mail: CN. Doccheck@sgs.com
No.1 Workshop, M-10, Midde Section, Science & Technology Park, Shemzhen, China 518/057 t (86-755) 2601/2053 f (86-755) 26710594 www.sgsgroup.com.cn
中国 - 采圳 - 科技図中区M-10核—号厂房 邮籍: 518/057 t (86-755) 2601/2053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: SZEM190701695002

Page: 5 of 8

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.sspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-And-Conditions-And-Con

No.1 Workshop, M-10, Midde Section, Science & Technology Park, Shemzhen, China 518057 t (86-755) 2601:2053 f (86-755) 26710594 www.sgsgroup.com. 中国 · 采圳 · 科技园中区M-10栋一号厂房 邮箱: 518057 t (86-755) 2601:2053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: SZEM190701695002

Page: 6 of 8

4.4 Deviation from Standards

None

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.asgx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-



Report No.: SZEM190701695002

Page: 7 of 8

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Coument.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or e mail: CN. Deccheck@sgs. Com
No.1 Workshop, M-10, Midde Section, Science & Technology Park, Sherizhen, Chlina 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.



Report No.: SZEM190701695002

Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 1.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.41 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducte d Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm²)	Result
Highest	2452	14.42	27.67	0.0078	1.0	PASS

Note: Refer to report No. SZEM190701695001 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

- End of the Report -

