

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM160400289303

Email: ee.shenzhen@sgs.com Page: 1 of 7

## **RF Exposure Evaluation Report**

Application No.: SZEM1604002893CR

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Manufacturer: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Factory SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Product Name: Wifi Digital Photo Frame

Model No.(EUT): W08E
Add Model No.: W08F

**FCC ID:** 2ABC5-W0806

**Standards:** 47 CFR Part 1.1307 (2015)

47 CFR Part 1.1310 (2015)

**Date of Receipt:** 2016-04-29

**Date of Test:** 2016-05-07 to 2016-05-12

**Date of Issue:** 2016-05-17

Test Result : PASS\*

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM160400289303

Page: 2 of 7

## 2 Version

Revision Record						
Version	Chapter	Date	Modifier	Remark		
00		2016-05-17		Original		

Authorized for issue by:			
Tested By	(Bill Chen) /Project Engineer	2016-05-12  Date	
Prepared By	Iris Zhou	2016-05-17	
	(Iris Zhou) /Clerk	Date	
Checked By	Eric Fu	2016-05-17	
	(Eric Fu) /Reviewer	Date	



Report No.: SZEM160400289303

Page: 3 of 7

### 3 Contents

1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	
4.3 TEST LOCATION	5
4.4 TEST FACILITY	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 RF EXPOSURE EVALUATION	6
5.1 RF Exposure Compliance Requirement	6
5.1.1 Limits	
5.1.2 Test Procedure	
4.1.3 EUT RF EXPOSURE EVALUATION	



Report No.: SZEM160400289303

Page: 4 of 7

### 4 General Information

### 4.1 Client Information

Applicant:	SHENZHEN ELECTRON TECHNOLOGY CO., LTD.			
Address of Applicant:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen			
Manufacturer:	SHENZHEN ELECTRON TECHNOLOGY CO., LTD.			
Address of Manufacturer:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen			
Factory: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.				
Address of Factory:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen			

### 4.2 General Description of EUT

Product Name:	Wifi Digital Photo Frame
Model No.:	W08E
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM, QPSK,BPSK) QPSK,BPSK)
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Antenna Type:	PCB
Antenna Gain:	-0.6dBi
Power Supply:	MODEL:K-E30502000U1 INPUT:100-240V 50/60Hz 0.35A MAX OUTPUT:5V 2000mA
Cable:	USB cable:160cm shield

Remark:

Model No.: W08E, W08F

Only the model W08E was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, only different on model No. and color.



Report No.: SZEM160400289303

Page: 5 of 7

#### 4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### • Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

### 4.5 Deviation from Standards

None.

#### 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.



Report No.: SZEM160400289303

Page: 6 of 7

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### **5.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614 1842/f 61.4	1.63 *(100) 4.89/f *(900/f²) 0.163 1.0 f/300		6 6 6 6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout\*G)/(4\*Pi\*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM160400289303

Page: 7 of 7

### 4.1.3 EUT RF Exposure Evaluation

Antenna Gain: -0.6dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 0.871in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output	Output Power to Antenna	Power Density at R = 20 cm	Limit	Result
	(	Power (dBm)	(mW)	(mW/cm²)		
Highest	2462	14.09	25.64	0.004	1.0	PASS

Note: Refer to report No. SZEM160400289302 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.