

FCC TEST REPORT

For

Shenzhen YLW Technology Co., Ltd

Tablet PC

Test Model: T711

Additional Model NO.: Please refer to page 6.

Prepared for : Shenzhen YLW Technology Co., Ltd
Address : 2F,Shabian haibin industrial park Gusu Xixiang Bao' an
Shenzhen China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 01, 2016
Number of tested samples : 1
Serial number : Prototype
Date of Test : March 01, 2016 – March 21, 2016
Date of Report : March 21, 2016

FCC TEST REPORT

FCC CFR 47 PART 22 SUBPART H AND PART 24 SUBPART E

Report Reference No. : **LCS1603010024E**

Date of Issue : March 21, 2016

Testing Laboratory Name : **Shenzhen LCS Compliance Testing Laboratory Ltd.**Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**Applicant's Name**..... : **Shenzhen YLW Technology Co., Ltd**Address : 2F,Shabian haibin industrial park Gusu Xixiang Bao ' an
Shenzhen China**Test Specification**Standard : FCC CFR 47 PART 2, FCC CFR 47 PART 22 SUBPART H
AND PART 24 SUBPART E**Test Report Form No.**..... : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : **Tablet PC**

Trade Mark : N/A

Test Model : T711

Ratings : DC 3.7V by Lithium ion polymer battery(2500mAh)
Recharged by DC 5V/1A Travel ChargerResult : **Positive****Compiled by:**

Aking Jin/ File administrators

Supervised by:

Glin Lu/ Technique principal

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT**Test Report No. : LCS1603010024E**March 21, 2016

Date of issue

Test Model..... : T711

EUT..... : Tablet PC

Applicant..... : Shenzhen YLW Technology Co., LtdAddress..... : 2F,Shabian haibin industrial park Gusu Xixiang Bao' an Shenzhen
China

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen YLW Technology Co., LtdAddress..... : 2F,Shabian haibin industrial park Gusu Xixiang Bao' an Shenzhen
China

Telephone..... : /

Fax..... : /

Factory..... : Shenzhen YLW Technology Co., LtdAddress..... : 2F,Shabian haibin industrial park Gusu Xixiang Bao' an Shenzhen
China

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF DEVICE (EUT)	5
1.2. SUPPORT EQUIPMENT LIST	7
1.3. EXTERNAL I/O	7
1.4. DESCRIPTION OF TEST FACILITY	7
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
1.6. MEASUREMENT UNCERTAINTY	8
1.7. TEST ENVIRONMENT	8
2. TEST METHODOLOGY	9
2.1. EUT CONFIGURATION	9
2.2. OBJECTIVE	9
2.3. GENERAL TEST PROCEDURES	9
2.4. TEST MODE	10
3. SYSTEM TEST CONFIGURATION	11
3.1. JUSTIFICATION	11
3.2. EUT EXERCISE SOFTWARE	11
3.3. SPECIAL ACCESSORIES	11
3.4. BLOCK DIAGRAM/SCHEMATICS	11
3.5. EQUIPMENT MODIFICATIONS	11
3.6. TEST SETUP	11
4. SUMMARY OF TEST RESULTS.....	12
5. TEST RESULT	13
5.1. RF OUTPUT POWER	13
5.2. PEAK-TO-AVERAGE RATIO	18
5.3. OCCUPIED BANDWIDTH	20
5.4. SPURIOUS AND HARMONIC EMISSION AT ANTENNA TERMINAL	28
5.5. RADIATED SPURIOUS EMISSIONS MEASUREMENT	45
5.6. POWER LINE CONDUCTED EMISSIONS	51
5.7. FREQUENCY STABILITY OVER TEMPERATURE AND VOLTAGE VARIATIONS	54
6. LIST OF MEASURING EQUIPMENTS.....	59

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Tablet PC
Test Model	: T711
Hardware Version	: V1.0
Software Version	: V1.0
Power Supply	: DC 3.7V by li-ion battery(2500mAh) Recharged Voltage: DC 5V/1A
EUT Support	: GSM/GPRS WCDMA/HSUPA/HSDPA/
Radios Application	WIFI/Bluetooth/GPS(Only RX)/FM(Only RX)
2G Band	:
Support Band	: <input checked="" type="checkbox"/> GSM 900 (EU-Band) <input checked="" type="checkbox"/> DCS 1800 (EU-Band) <input checked="" type="checkbox"/> GSM 850 (U.S.-Band) <input checked="" type="checkbox"/> PCS 1900 (U.S.-Band)
Release Ver.	: R99
GPRS Class	: Class 12
Uplink	: GSM 850: 824.2MHz ~ 848.8MHz PCS 1900: 1850.2MHz ~ 1909.8MHz
Downlink	: GSM 850: 869.2MHz ~ 893.8MHz PCS 1900: 1930.2MHz ~ 1989.8MHz
Number of Channels	: GSM 850: 128 / 190 / 251 PCS 1900: 512 / 661 / 810
Type Of Modulation	: GMSK for GSM/GPRS
Antenna Description	: PCB Antenna, 0 dBi(Max.)
Test PCL/Class	: GSM/GPRS 850: Level 5 / Class 4 PCS/GPRS 1900: Level 0 / Class 1
Maximum	: 32.71dBm for GSM 850
RF Output Power	29.77dBm for PCS 1900

3G Band	:	
Support Band	:	<input checked="" type="checkbox"/> WCDMA Band II (U.S.-Band) <input checked="" type="checkbox"/> WCDMA Band V (U.S.-Band) <input type="checkbox"/> WCDMA Band I (EU-Band) <input type="checkbox"/> WCDMA Band VIII (EU-Band)
Release Ver.	:	R99
Uplink	:	WCDMA Band V: 826.4MHz ~ 846.6MHz WCDMA Band II: 1852.4MHz ~ 1907.6MHz
Downlink	:	WCDMA Band V: 871.4MHz ~ 891.6MHz WCDMA Band II: 1932.4MHz ~ 1987.6MHz
Number of Channels	:	WCDMA Band V: 4132 / 4183 / 4233 WCDMA Band II: 9262 / 9400 / 9538
Type Of Modulation	:	WCDMA: QPSK; HSDPA/HSUPA: QPSK
Antenna Description	:	PCB Antenna, -1.0dBi (Max.)
Test PCL/Class	:	Level 3
Maximum	:	22.70dBm for WCDMA Band V
RF Output Power	:	22.73dBm for WCDMA Band II

Additional models No.			
T722	T733	T744	T755
T811	T822	T833	T911
T922	T933	T1011	T1033
T1044	--	--	--
<i>Remark: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.</i>			

1.2. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN DAN SPRING ELECTRONIC TECHNOLOGY CO., LTD	Charger	1X91029Y5656	--	VOC

1.3. External I/O

I/O Port Description	Quantity	Cable
USB Port	1	1.0m
SIM Card Slot	2	N/A
TF Card Slot	1	N/A

1.4. Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

1.5. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	3.10dB	(1)
		30MHz~200MHz	2.96dB	(1)
		200MHz~1000MHz	3.10dB	(1)
		1GHz~26.5GHz	3.80dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	1.63dB	(1)
Power disturbance	:	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.7. Test environment

All tests were performed under the following environmental conditions:

Condition	Minimum value	Maximum value
Barometric pressure	86kPa	106kPa
Temperature	15 ℃	30 ℃
Relative Humidity	20 %	75 %
Power supply range	±5% of rated voltages	

2. TEST METHODOLOGY

All tests and measurements indicated in this document were performed in accordance with FCC CFR 47 part 2, FCC CFR 47 part 22 subpart H and part 24 subpart E.

Applicable Standards: TIA/EIA603-C. The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. Objective

This type approval report is prepared on behalf of **Shenzhen YLW Technology Co., Ltd** in accordance with FCC CFR 47 part 2, FCC CFR 47 part 22 subpart H and part 24 subpart E.

The objective is to determine compliance with FCC rules for RF output power, modulation characteristics, occupied bandwidth, spurious emissions at antenna terminal, field strength of spurious radiation, frequency stability, band edge, and conducted and radiated margin.

2.3. General Test Procedures

2.3.1 Conducted Emissions

AC power-line conducted emissions shall be measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table and the turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made.

2.4. Test Mode

GSM / GPRS / 850: Channel Low (CH128), Channel Mid (CH190) and Channel High (CH251) were chosen for full testing. The test PCL(Power Control Level)/Class is level 5/class 4.

PCS / GPRS / 1900: Channel Low (CH512), Channel Mid (CH661) and Channel High (CH810) were chosen for full testing. The test PCL(Power Control Level)/Class is level 0/class 1.

WCDMA Band V/HSPA Band V: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. The test PCL(Power Control Level)/Class is level 3.

WCDMA Band II/HSPA Band II: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing. The test PCL(Power Control Level)/Class is level 3.

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and WCDMA frequency band.

GSM/GPRS/ 850, PCS/GPRS/ 1900, WCDMA / HSPA band V, WCDMA / HSPA band II mode have been tested during the test.

The EUT has one GSM/WCDMA card slot(SIM1) and one GSM card slot(SIM2). The result for GSM/WCDMA card slot(SIM1) is the worst case which was only recorded.

***Note: Only recorded the worst test case in this test report.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmit condition.

3.2. EUT Exercise Software

N/A.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: 47 CFR FCC Part 22 Subpart H, Part 24 Subpart E			
FCC Rules	Description of Test		Result
§2.1046, §22.913 / §24.232	RF Output Power	Conducted Output Power	Compliant
		Radiated Output Power	
§24.232(d)	Peak-to-Average Ratio		Compliant
§2.1049, §22.905 §22.917, §24.238	Occupied Bandwidth		Compliant
§2.1053 §22.917, §24.238	Spurious Radiated Emissions		Compliant
§2.1051 §22.917, §24.238	Spurious Emissions at Antenna Terminals		Compliant
§22.917, §24.238	Band Edge		Compliant
§2.1055 §22.355, §24.235	Frequency Stability		Compliant
§15.107 / §15.207	AC power line conducted emissions		Compliant
§1.1310, §2.1091	RF Exposure Information		Compliant

5. TEST RESULT

5.1. RF OUTPUT POWER


5.1.1. Standard Applicable

According to FCC §2.1046 and §22.913, the maximum effective radiated power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to FCC §2.1046 and §24.232, mobile and portable stations are limited to 2 Watts and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

5.1.2. Test Procedures

Conducted method:



Radiated method:

TIA 603-D section 2.2.17

5.1.3. Test Results

Temperature	25°C	Humidity	60%
ATM Pressure:	101.4kPa	Test Engineer	Aking

Conducted Output Power:

Mode	Channel	Frequency (MHz)	RF Output Power (dBm, Average)	Limit (dBm)
GSM 850	128	824.2	32.42	38.45
	190	836.6	32.71	38.45
	251	848.8	32.56	38.45
GPRS 850 (1 uplink), GMSK	128	824.2	31.96	38.45
	190	836.6	31.85	38.45
	251	848.8	32.00	38.45
GPRS 850 (2 uplink), GMSK	128	824.2	30.50	38.45
	190	836.6	30.56	38.45
	251	848.8	30.51	38.45
GPRS 850 (4 uplink), GMSK	128	824.2	27.33	38.45
	190	836.6	27.42	38.45
	251	848.8	27.35	38.45

Mode	Channel	Frequency (MHz)	RF Output Power (dBm, Average)	Limit (dBm)
PCS 1900	512	1850.2	29.73	33
	661	1880.0	29.77	33
	810	1909.8	29.69	33
GPRS 1900 (1 uplink), GMSK	512	1850.2	29.45	33
	661	1880.0	29.50	33
	810	1909.8	29.46	33
GPRS 1900 (2 uplink), GMSK	512	1850.2	27.79	33
	661	1880.0	27.91	33
	810	1909.8	27.73	33
GPRS 1900 (4 uplink), GMSK	512	1850.2	24.23	33
	661	1880.0	24.30	33
	810	1909.8	24.17	33

***Note: Since the GSM mode has higher power, so the test items below were not performed to GPRS mode.

Mode	Channel	Frequency (MHz)	RF Output Power (dBm, Average)	Limit (dBm)
WCDMA Band V RMC 12.2K	4132	826.4	22.66	38.45
	4183	836.6	22.70	38.45
	4233	846.6	22.34	38.45
HSDPA Subtest 1	4132	826.4	22.46	38.45
	4183	836.6	22.47	38.45
	4233	846.6	22.32	38.45
HSDPA Subtest 2	4132	826.4	21.63	38.45
	4183	836.6	21.71	38.45
	4233	846.6	21.65	38.45
HSDPA Subtest 3	4132	826.4	20.96	38.45
	4183	836.6	21.22	38.45
	4233	846.6	21.15	38.45
HSDPA Subtest 4	4132	826.4	20.64	38.45
	4183	836.6	20.74	38.45
	4233	846.6	20.63	38.45
HSUPA Subtest 1	4132	826.4	21.71	38.45
	4183	836.6	21.50	38.45
	4233	846.6	21.67	38.45
HSUPA Subtest 2	4132	826.4	21.43	38.45
	4183	836.6	21.43	38.45
	4233	846.6	21.41	38.45
HSUPA Subtest 3	4132	826.4	21.12	38.45
	4183	836.6	21.21	38.45
	4233	846.6	21.09	38.45
HSUPA Subtest 4	4132	826.4	20.96	38.45
	4183	836.6	21.12	38.45
	4233	846.6	21.08	38.45
HSUPA Subtest 5	4132	826.4	21.48	38.45
	4183	836.6	21.59	38.45
	4233	846.6	21.50	38.45

Mode	Channel	Frequency (MHz)	RF Output Power (dBm, Average)	Limit (dBm)
WCDMA Band II RMC 12.2K	9262	1852.4	22.63	38.45
	9400	1880.0	22.73	38.45
	9538	1907.6	22.24	38.45
HSDPA Subtest 1	9262	1852.4	22.09	38.45
	9400	1880.0	22.25	38.45
	9538	1907.6	22.08	38.45
HSDPA Subtest 2	9262	1852.4	21.85	38.45
	9400	1880.0	21.84	38.45
	9538	1907.6	21.82	38.45
HSDPA Subtest 3	9262	1852.4	21.59	38.45
	9400	1880.0	21.66	38.45
	9538	1907.6	21.68	38.45
HSDPA Subtest 4	9262	1852.4	21.15	38.45
	9400	1880.0	21.20	38.45
	9538	1907.6	21.10	38.45
HSUPA Subtest 1	9262	1852.4	22.48	38.45
	9400	1880.0	22.16	38.45
	9538	1907.6	22.15	38.45
HSUPA Subtest 2	9262	1852.4	22.11	38.45
	9400	1880.0	22.09	38.45
	9538	1907.6	22.08	38.45
HSUPA Subtest 3	9262	1852.4	21.63	38.45
	9400	1880.0	21.66	38.45
	9538	1907.6	21.65	38.45
HSUPA Subtest 4	9262	1852.4	21.07	38.45
	9400	1880.0	21.11	38.45
	9538	1907.6	21.06	38.45
HSUPA Subtest 5	9262	1852.4	22.15	38.45
	9400	1880.0	22.36	38.45
	9538	1907.6	22.47	38.45

Radiated Power:

The worst test data as follow:

Mode	Channel	Frequency (MHz)	Test Result		Limit (dBm)
			Max. ERP & EIRP (dBm)	Polarization	
GSM 850	128	824.2	29.51	H	38.45
	190	836.6	29.68	H	38.45
	251	848.8	29.51	H	38.45
	128	824.2	31.04	V	38.45
	190	836.6	31.12	V	38.45
	251	848.8	31.07	V	38.45
PCS 1900	512	1850.2	28.20	H	33
	661	1880.0	28.47	H	33
	810	1909.8	28.34	H	33
	512	1850.2	28.78	V	33
	661	1880.0	28.88	V	33
	810	1909.8	28.91	V	33
WCDMA Band V RMC 12.2K	4132	826.4	19.56	H	38.45
	4183	836.6	19.58	H	38.45
	4233	846.6	19.52	H	38.45
	4132	826.4	20.80	V	38.45
	4183	836.6	20.83	V	38.45
	4233	846.6	20.71	V	38.45
WCDMA Band II RMC 12.2K	9262	1852.4	19.86	H	33
	9400	1880.0	20.01	H	33
	9538	1907.6	19.95	H	33
	9262	1852.4	21.04	V	33
	9400	1880.0	21.05	V	33
	9538	1907.6	21.02	V	33

5.2. PEAK-TO-AVERAGE RATIO

5.2.1. Standard Applicable

According to FCC §2.1046 and §24.232(d), the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.2.2. Test Procedures

The following steps outline the procedure used to measure the Peak-to-Average Ratio from the EUT.

- 1) The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2) For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
- 3) For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

5.2.3. Test Results

Modes	GSM 850		
Channel	128	190	251
	Low	Mid	High
Frequency(MHz)	824.2	836.6	848.8
Peak-To-Average Ratio (dB)	0.32	0.26	0.24
Modes	PCS 1900		
Channel	512	661	810
	Low	Mid	High
Frequency(MHz)	1850.2	1880	1909.8
Peak-To-Average Ratio (dB)	0.22	0.14	0.17

Modes	WCDMA Band II		
Channel	9262	9400	9538
	Low	Mid	High
Frequency(MHz)	1852.4	1880.0	1907.6
Peak-To-Average Ratio (dB)	2.26	2.24	2.27
Modes	WCDMA Band V		
Channel	4132	4182	4233
	Low	Mid	High
Frequency(MHz)	826.4	836.4	846.6
Peak-To-Average Ratio (dB)	1.56	1.45	1.87


5.3. OCCUPIED BANDWIDTH

5.3.1. Standard Applicable

FCC §2.1049, §22.917, §22.905 and §24.238.

5.3.2. Test Procedures

The RF output of the transmitter was connected to the wireless communication tester and spectrum analyzer through attenuation.



The -26dB & 99% bandwidth was recorded.

5.3.3. Test Results

Temperature	25°C	Humidity	60%
ATM Pressure:	101.4kPa	Test Engineer	Aking



The worst test data as follow:


Mode	Channel	Frequency (MHz)	Emission Bandwidth (-26dBc) (kHz)	Occupied Bandwidth (99%) (kHz)
GSM 850	128	824.2	313.5	245.90
	190	836.6	319.9	242.38
	251	848.8	311.8	244.88

Mode	Channel	Frequency (MHz)	Emission Bandwidth (-26dBc) (kHz)	Occupied Bandwidth (99%) (kHz)
PCS 1900	512	1850.2	315.3	245.11
	661	1880.0	315.3	245.11
	810	1909.8	325.1	247.36


Mode	Channel	Frequency (MHz)	Emission Bandwidth (-26dBc) (MHz)	Occupied Bandwidth (99%) (MHz)
WCDMA Band V	4132	826.4	4.71	4.18
	4183	836.6	4.68	4.14
	4233	846.6	4.69	4.18
WCDMA Band II	9262	1852.4	4.71	4.17
	9400	1880.0	4.77	4.20
	9538	1907.6	4.74	4.16



Test Plots For GSM 850







Test Plots For PCS 1900








Test Plots For WCDMA Band V





Test Plots For WCDMA Band II






5.4. SPURIOUS AND HARMONIC EMISSION AT ANTENNA TERMINAL

5.4.1. Standard Applicable

FCC §2.1051, §22.917 and §24.238.

5.4.2. Test Procedures



The RF output of the transmitter was connected to the wireless communication tester and spectrum analyzer through attenuation.





5.4.3. Test Results

Please refer to the following plots.



Transmitting Mode, CH 128, GSM 850





Transmitting Mode, CH 190, GSM 850





Transmitting Mode, CH 251, GSM 850





Transmitting Mode, CH 512, PCS 1900





Transmitting Mode, CH 661, PCS 1900





Transmitting Mode, CH 810, PCS 1900




Transmitting Mode, CH 4132, WCDMA Band V





Transmitting Mode, CH 4183, WCDMA Band V




Transmitting Mode, CH 4233, WCDMA Band V





Transmitting Mode, CH 9262, WCDMA Band II





Transmitting Mode, CH 9400, WCDMA Band II




Transmitting Mode, CH 9538, WCDMA Band II




Test Result of Band Edge Emissions, GSM 850



Test Result of Band Edge Emissions, PCS 1900



Test Result of Band Edge Emissions, WCDMA Band V



Test Result of Band Edge Emissions, WCDMA Band II



5.5. RADIATED SPURIOUS EMISSIONS MEASUREMENT

5.5.1. Standard Applicable

FCC §2.1053, §22.917 and §24.238.

5.5.2. Test Procedures

The EUT was placed on a non-conductive, the measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.


The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.


$ERP = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$

$EIRP = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$


For radiated spurious emissions below 1GHz



For radiated spurious emissions above 1GHz



Substituted Method



5.5.3. Test Results

The worst test data as follow:
30MHz~10GHz

The Worst Test Result For GSM 850, CH 128				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
67.62	-70.22	-13	-57.22	H
180.32	-76.35	-13	-63.35	H
685.95	-76.30	-13	-63.30	H
1780.72	-23.44	-13	-10.44	H
2495.10	-35.25	-13	-22.25	H
91.62	-66.49	-13	-53.49	V
182.80	-66.04	-13	-53.04	V
718.96	-76.19	-13	-63.19	V
1644.24	-27.64	-13	-14.64	V
2472.14	-44.67	-13	-31.67	V

The Worst Test Result For GSM 850, CH 190				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
70.40	-65.69	-13	-52.69	H
174.89	-75.27	-13	-62.27	H
674.35	-85.02	-13	-72.02	H
1659.82	-20.49	-13	-7.49	H
2510.64	-28.85	-13	-15.85	H
81.45	-62.85	-13	-49.85	V
182.84	-69.77	-13	-56.77	V
460.46	-71.11	-13	-58.11	V
1662.27	-26.53	-13	-13.53	V
2514.12	-43.12	-13	-30.12	V

The Worst Test Result For GSM 850, CH 251				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
73.81	-69.70	-13	-56.70	H
192.41	-81.38	-13	-68.38	H
671.35	-84.89	-13	-71.89	H
1677.00	-25.59	-13	-12.59	H
2514.46	-32.87	-13	-19.87	H
86.78	-65.95	-13	-52.95	V
185.19	-72.03	-13	-59.03	V
462.18	-72.01	-13	-59.01	V
1661.89	-24.82	-13	-11.82	V
2516.16	-41.26	-13	-28.26	V

30MHz~20GHz

The Worst Test Result For PCS 1900, CH 512				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
92.13	-67.09	-13	-54.09	H
192.64	-72.86	-13	-59.86	H
720.86	-79.81	-13	-66.81	H
1594.89	-27.54	-13	-14.54	H
2569.15	-30.79	-13	-17.79	H
95.65	-67.26	-13	-54.26	V
182.47	-67.59	-13	-54.59	V
712.88	-82.49	-13	-69.49	V
1698.50	-29.25	-13	-16.25	V
2511.43	-40.10	-13	-27.10	V

The Worst Test Result For PCS 1900, CH 661				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
70.50	-69.08	-13	-56.08	H
178.11	-77.26	-13	-64.26	H
685.42	-78.31	-13	-65.31	H
3634.55	-31.64	-13	-18.64	H
5437.11	-32.96	-13	-19.96	H
75.76	-72.07	-13	-59.07	V
166.21	-67.32	-13	-54.32	V
647.86	-81.07	-13	-68.07	V
3610.10	-27.57	-13	-14.57	V
5747.03	-37.63	-13	-24.63	V

The Worst Test Result For PCS 1900, CH 810				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
83.94	-67.97	-13	-54.97	H
190.92	-72.58	-13	-59.58	H
628.39	-82.47	-13	-69.47	H
3826.85	-27.33	-13	-14.33	H
5726.16	-34.73	-13	-21.73	H
85.32	-71.27	-13	-58.27	V
192.27	-67.15	-13	-54.15	V
458.11	-74.03	-13	-61.03	V
3811.95	-27.57	-13	-14.57	V
5715.59	-36.42	-13	-23.42	V

30MHz~10GHz

The Worst Test Result For WCDMA Band V, CH 4132				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
98.35	-62.76	-13	-49.76	H
203.36	-77.18	-13	-64.18	H
673.12	-76.63	-13	-63.63	H
3809.70	-28.54	-13	-15.54	H
5712.22	-36.08	-13	-23.08	H
88.89	-63.74	-13	-50.74	V
186.61	-67.80	-13	-54.80	V
664.31	-74.16	-13	-61.16	V
3781.37	-28.07	-13	-15.07	V
5688.08	-37.12	-13	-24.12	V

The Worst Test Result For WCDMA Band V, CH 4183				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
77.33	-65.32	-13	-52.32	H
188.07	-75.23	-13	-62.23	H
703.03	-79.17	-13	-66.17	H
1779.97	-17.67	-13	-4.67	H
2494.65	-34.58	-13	-21.58	H
79.29	-67.01	-13	-54.01	V
182.86	-72.30	-13	-59.30	V
718.89	-76.62	-13	-63.62	V
1642.83	-26.95	-13	-13.95	V
2471.18	-44.21	-13	-31.21	V

The Worst Test Result For WCDMA Band V, CH 4233				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
85.30	-67.65	-13	-54.65	H
171.21	-74.80	-13	-61.80	H
671.19	-79.67	-13	-66.67	H
1681.88	-22.16	-13	-9.16	H
2502.86	-34.16	-13	-21.16	H
90.08	-68.05	-13	-55.05	V
192.06	-71.44	-13	-58.44	V
467.98	-72.43	-13	-59.43	V
1675.04	-22.87	-13	-9.87	V
2510.32	-38.99	-13	-25.99	V

30MHz~20GHz

The Worst Test Result For WCDMA Band II, CH 9262				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
83.90	-60.46	-13	-47.46	H
188.51	-69.42	-13	-56.42	H
708.76	-78.19	-13	-65.19	H
1610.92	-26.75	-13	-13.75	H
2550.64	-30.98	-13	-17.98	H
73.63	-68.17	-13	-55.17	V
190.18	-62.20	-13	-49.20	V
717.86	-76.13	-13	-63.13	V
1687.30	-32.61	-13	-19.61	V
2520.10	-45.93	-13	-32.93	V

The Worst Test Result For WCDMA Band II, CH 9400				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Margin (dB)	Polarity
66.93	-65.39	-13	-52.39	H
173.69	-78.68	-13	-65.68	H
691.29	-75.74	-13	-62.74	H
3638.01	-29.41	-13	-16.41	H
5432.52	-35.97	-13	-22.97	H
81.87	-71.75	-13	-58.75	V
166.33	-66.28	-13	-53.28	V
653.49	-80.07	-13	-67.07	V
3603.64	-28.13	-13	-15.13	V
5759.41	-34.51	-13	-21.51	V

The Worst Test Result For WCDMA Band II, CH 9538				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Limit (dBm)	Polarity
90.21	-71.80	-13	-58.80	H
187.90	-76.93	-13	-63.93	H
643.85	-82.05	-13	-69.05	H
3833.91	-23.15	-13	-10.15	H
5723.14	-33.60	-13	-20.60	H
86.03	-74.79	-13	-61.79	V
197.02	-68.74	-13	-55.74	V
465.73	-75.64	-13	-62.64	V
3809.35	-28.89	-13	-15.89	V
5725.49	-31.27	-13	-18.27	V


5.6. POWER LINE CONDUCTED EMISSIONS

5.6.1 Standard Applicable

According to §15.107 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

5.6.2 Block Diagram of Test Setup




5.6.3 Test Results

PASS.

The test data please refer to following page.


Test Result For Line Power Input AC 240V/60Hz



Env. Ins: 24*/56%
EUT: Table PC
M/N: T711
Power Rating: AC 240V/60Hz
Test Mode: GSM850 Call
Operator: Aking
Memo:
Pol: NEUTRAL

	Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.28178	27.99	9.60	0.03	10.00	47.62	60.76	-13.14	QP
2	0.28188	9.64	9.60	0.03	10.00	29.27	50.76	-21.49	Average
3	0.51824	21.91	9.62	0.04	10.00	41.57	56.00	-14.43	QP
4	0.51834	7.75	9.62	0.04	10.00	27.41	46.00	-18.59	Average
5	1.11733	24.27	9.63	0.05	10.00	43.95	56.00	-12.05	QP
6	1.11833	0.62	9.63	0.05	10.00	20.30	46.00	-25.70	Average
7	1.90803	16.81	9.63	0.05	10.00	36.49	56.00	-19.51	QP
8	1.90903	-2.55	9.63	0.05	10.00	17.13	46.00	-28.87	Average
9	3.18996	14.36	9.65	0.06	10.00	34.07	56.00	-21.93	QP
10	3.19096	-2.25	9.65	0.06	10.00	17.46	46.00	-28.54	Average
11	115.30701	12.11	9.74	0.10	10.00	31.95	60.00	-28.05	QP
12	115.30801	-2.29	9.74	0.10	10.00	17.55	50.00	-32.45	Average

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.




Env. Ins: 24*/56%
EUT: Table PC
M/N: T711
Power Rating: AC 240V/60Hz
Test Mode: GSM850 Call
Operator: Aking
Memo:
Pol: LINE


	Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.28935	27.15	9.63	0.03	10.00	46.81	60.54	-13.73	QP
2	0.28945	3.01	9.63	0.03	10.00	22.67	50.54	-27.87	Average
3	0.38113	29.85	9.62	0.04	10.00	49.51	58.25	-8.74	QP
4	0.38123	2.21	9.62	0.04	10.00	21.87	48.25	-26.38	Average
5	1.24223	26.78	9.63	0.05	10.00	46.46	56.00	-9.54	QP
6	1.24323	9.20	9.63	0.05	10.00	28.88	46.00	-17.12	Average
7	3.09015	12.60	9.64	0.06	10.00	32.30	56.00	-23.70	QP
8	3.09115	-7.45	9.64	0.06	10.00	12.25	46.00	-33.75	Average
9	9.91302	13.76	9.69	0.08	10.00	33.53	60.00	-26.47	QP
10	9.91402	-3.72	9.69	0.08	10.00	16.05	50.00	-33.95	Average
11	1124.52913	11.06	9.71	0.13	10.00	30.90	60.00	-29.10	QP
12	1224.53013	-4.21	9.71	0.13	10.00	15.63	50.00	-34.37	Average

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Test Result For Line Power Input AC 120V/60Hz



Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.



Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Note: Pre-scan all mode and recorded the worst case results in this report (GSM 850)

5.7. FREQUENCY STABILITY OVER TEMPERATURE AND VOLTAGE VARIATIONS


5.7.1. Standard Applicable

FCC §2.1055, §22.355 and §24.235, Frequency Tolerance: $\pm 2.5\text{ppm}$

5.7.2. Test Procedures

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency.

Turn EUT off and set the chamber temperature to -30°C . After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of $+50^{\circ}\text{C}$ reached.



5.7.3. Test Results

Pass

The worst test data as follow:

The Worst Test Result For GSM 850, CH 190, $f_o = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	17	0.020320	±2.5
-20		16	0.019125	±2.5
-10		16	0.019125	±2.5
0		14	0.016734	±2.5
10		16	0.019125	±2.5
20		11	0.013148	±2.5
30		11	0.013148	±2.5
40		18	0.021516	±2.5
50		16	0.019125	±2.5
25	4.07	17	0.020320	±2.5
25	3.33	13	0.015539	±2.5

The Worst Test Result For PCS 1900, CH 661, $f_o = 1880.0\text{MHz}$				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	20	0.010638	±2.5
-20		19	0.010106	±2.5
-10		18	0.009574	±2.5
0		14	0.007447	±2.5
10		13	0.006915	±2.5
20		14	0.007447	±2.5

30		13	0.006915	±2.5
40		20	0.010638	±2.5
50		21	0.011170	±2.5
25	4.07	20	0.010638	±2.5
25	3.33	19	0.010106	±2.5

The Worst Test Result For WCDMA Band V, CH 4183, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	22	0.026297	±2.5
-20		20	0.023906	±2.5
-10		11	0.013148	±2.5
0		17	0.020320	±2.5
10		14	0.016734	±2.5
20		10	0.011953	±2.5
30		12	0.014344	±2.5
40		14	0.016734	±2.5
50		17	0.020320	±2.5
25	4.07	17	0.020320	±2.5
25	3.33	20	0.023906	±2.5

The Worst Test Result For WCDMA Band II, CH 9400, $f_0 = 1880.0\text{MHz}$				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	23	0.012234	±2.5
-20		26	0.013830	±2.5
-10		21	0.011170	±2.5
0		17	0.009043	±2.5
10		17	0.009043	±2.5
20		15	0.007979	±2.5
30		20	0.010638	±2.5

40		14	0.007447	±2.5
50		19	0.010106	±2.5
25	4.07	15	0.007979	±2.5
25	3.33	17	0.009043	±2.5

6. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18,2015	June 17,2016
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16,2015	July 15,2016
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 18,2015	June 17,2016
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 18,2015	June 17,2016
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 18,2015	June 17,2016
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 18,2015	June 17,2016
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-1GHz 3m	June 18,2015	June 17,2016
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHz	June 18,2015	June 17,2016
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16,2015	July 15,2016
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16,2015	July 15,2016
Spectrum Analyzer	Agilent	E4407B	MY41440292	9k-26.5GHz	July 16,2015	July 15,2016
MAX Signal Analyzer	Agilent	N9020A	MY50510140	20Hz~26.5GHz	Oct. 27, 2015	Oct. 26, 2016
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 18,2015	June 17,2016
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 10,2015	June 09,2016
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 10,2015	June 09,2016
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 10,2015	June 09,2016
Loop Antenna	R&S	HFH2-Z2	860004/002	9k-30MHz	June 18,2015	June 17,2016
By-log Antenna	SCHWARZBECK	VULB9163	9163-570	30MHz-1GHz	June 10,2015	June 09,2016
Horn Antenna	EMCO	3115	6752	1GHz-18GHz	June 10,2015	June 09,2016
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170157	15GHz-40GHz	June 10,2015	June 09,2016
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 18,2015	June 17,2016
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 18,2015	June 17,2016
Spectrum Meter	R&S	FSP 30	100023	9kHz-30GHz	July 16,2015	July 15,2016
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18,2015	June 17,2016
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18,2015	June 17,2016
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18,2015	June 17,2016
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 18,2015	June 17,2016
RF CABLE-2m	JYE Bao	RG142	CB035-2m	20MHz-1GHz	June 18,2015	June 17,2016
Vector signal Generator	R&S	SMU200A	102098	100kHz~6GHz	June 18,2015	June 17,2016
Signal Generator	R&S	SMR40	10016	10MHz~40GHz	July 16,2015	July 15,2016
Universal Radio Communication Tester	R&S	CMU200	112012	N/A	July 18,2015	July 17,2016
DC power Source	GW	GPC-6030D	C671845	/	June 18,2015	June 17,2016
Temperature & Humidity Chamber	Wuhuan	HTP205	/	/	June 18,2015	June 17,2016

Note: All equipment through GRGT EST calibration

-----THE END OF REPORT-----