

# FCC Part 22H & 24E

## Measurement and Test Report

### For

**PCSmart S.A.**

**Carrera 116 no. 15 - 25 Bogota - Colombia**

**FCC ID: 2ABFV-S3GI**

**FCC Rules:** FCC Part 22H, FCC Part 24E

**Product Description:** Entertainment Tablet

**Tested Model:** Touch Smart Slim 3Gi

**Report No.:** STR14068118I-1

**Tested Date:** 2014-05-07 to 2014-06-23

**Issued Date:** 2014-06-23

**Tested By:** Silin Chen / Engineer

**Reviewed By:** Lahm Peng / EMC Manager

**Approved & Authorized By:** Jandy so / PSQ Manager

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>3. RF EXPOSURE .....</b>	<b>8</b>
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
<b>4. RF OUTPUT POWER.....</b>	<b>9</b>
4.1 STANDARD APPLICABLE.....	9
4.2 TEST EQUIPMENT LIST AND DETAILS .....	9
4.3 TEST PROCEDURE.....	9
4.4 ENVIRONMENTAL CONDITIONS .....	10
4.5 SUMMARY OF TEST RESULTS/PLOTS .....	10
<b>5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....</b>	<b>18</b>
5.1 STANDARD APPLICABLE.....	18
5.2 TEST EQUIPMENT LIST AND DETAILS .....	18
5.3 TEST PROCEDURE.....	18
5.4 ENVIRONMENTAL CONDITIONS .....	18
5.5 SUMMARY OF TEST RESULTS .....	19
<b>6. EMISSION BANDWIDTH.....</b>	<b>21</b>
6.1 STANDARD APPLICABLE.....	21
6.2 TEST EQUIPMENT LIST AND DETAILS .....	21
6.3 TEST PROCEDURE.....	21
6.4 ENVIRONMENTAL CONDITIONS .....	21
6.5 SUMMARY OF TEST RESULTS/PLOTS .....	22
<b>7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....</b>	<b>36</b>
7.1 STANDARD APPLICABLE.....	36
7.2 TEST EQUIPMENT LIST AND DETAILS .....	36
7.3 TEST PROCEDURE.....	36
7.4 ENVIRONMENTAL CONDITIONS .....	36
7.5 SUMMARY OF TEST RESULTS/PLOTS .....	37
<b>8. SPURIOUS RADIATED EMISSIONS.....</b>	<b>85</b>
8.1 MEASUREMENT UNCERTAINTY .....	85
8.2 STANDARD APPLICABLE.....	85
8.3 TEST EQUIPMENT LIST AND DETAILS .....	85
8.4 TEST PROCEDURE.....	85
8.5 ENVIRONMENTAL CONDITIONS .....	86
8.6 SUMMARY OF TEST RESULTS/PLOTS .....	86
<b>9. FREQUENCY STABILITY .....</b>	<b>96</b>
9.1 STANDARD APPLICABLE.....	96
9.2 TEST EQUIPMENT LIST AND DETAILS .....	96
9.3 TEST PROCEDURE.....	96
9.4 ENVIRONMENTAL CONDITIONS .....	97
9.5 SUMMARY OF TEST RESULTS/PLOTS .....	97

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: PCSmart S.A.  
Address of applicant: Carrera 116 no. 25 - 25 Bogota - Colombia

Manufacturer: Shenzhen Wisky Technology Co., LTD  
Address of manufacturer: 5th Floor, W2-A Building, Hi-Tech Park South 1st Road, Nanshan District, Shenzhen

General Description of EUT	
Product Name:	Entertainment Tablet
Brand Name:	PCSMART
Model No.:	Touch Smart Slim 3Gi
Adding Mode:	Touch Smart Slim 3Gi Black Touch Smart Slim 3Gi white
Software Version:	V1.00_20140411
Hardware Version:	TV1.0_140107
IMEI:	863059020047561
Rated Voltage:	DC 3.7V
Battery:	4000mAh
Power Adaptor:	FY0502000/SAPA05010US
	Input 100-240V, 50/60Hz, Output DC 5V
Device Category:	Portable Device
<p><i>The EUT is GSM850/900/DCS1800/PCS1900, WCDMA Band I, Band II, Band V, Band VIII, Entertainment Tablet. the Entertainment Tablet is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850 and GSM1900 and Bluetooth, Wi-Fi, and camera functions. For more information see the following datasheet</i></p> <p><i>The test data is gathered from a production sample, provided by the manufacturer. The other model listed in the report has different appearance only of Touch Smart Slim 3Gi without circuit and electronic construction changed, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
<b>2G</b>	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
RF Output Power:	GSM850: 32.66dBm, GSM1900: 29.39dBm
Type of Modulation:	GMSK, 8PSK
Antenna Type:	Internal Antenna
Antenna Gain:	GSM850: 2.0dBi GSM1900: 2.0dBi
GPRS/EDGE Class:	Class 12
<b>3G</b>	
Support Networks:	WCDMA
Support Band:	WCDMA Band II, WCDMA Band V
Uplink Frequency:	WCDMA Band II: 1850~1980MHz WCDMA Band V: 824~849MHz
Downlink Frequency:	WCDMA Band II: 1930~1990MHz WCDMA Band V: 869~894MHz
RF Output Power:	WCDMA850: 22.91dBm, WCDMA1900: 21.52dBm
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	2.0dBi

## 1.2 Test Standards

The following report is prepared on behalf of the PCSmart S.A. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603-C: 2004 and ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	GSM 1900	Low, Middle, High Channels
TM4	GPRS 1900	Low, Middle, High Channels
TM5	WCDMA Band V	Low, Middle, High Channels
TM6	HSPA Band V	Low, Middle, High Channels
TM7	WCDMA Band II	Low, Middle, High Channels
TM8	HSPA Band II	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band V	WCDMA/HSPA	826.4 MHz	4132
		836.4 MHz	4182
		846.6 MHz	4233
WCDMA Band II	WCDMA/HSPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
Note: the transmitter has been tested on the communications mode of GSM, GPRS,WCDMA, HSPA compliance test and record the worst case.			

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.8	Unshielded	Without Core

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a),	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the SAR report.



## 4. RF Output Power

### 4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

### 4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-334	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086198	2014-05-24	2015-05-23
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-28	2015-05-27
Signal Generator	R&S	SMR20	100047	2014-05-28	2015-05-27

### 4.3 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.

4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

#### 4.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### 4.5 Summary of Test Results/Plots

Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	28.65	1.5	0	H	1.5	0	27.15	38.45
824.2	30.44	1.5	0	V	1.5	0	28.94	38.45
Middle Channel								
836.6	28.51	1.5	0	H	1.5	0	27.01	38.45
836.6	30.51	1.5	0	V	1.5	0	29.01	38.45
High Channel								
848.8	28.61	1.5	0	H	1.5	0	27.11	38.45
848.8	30.43	1.5	0	V	1.5	0	28.93	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	21.25	1.5	0	H	1.9	7.7	27.05	33
1850.2	22.96	1.5	0	V	1.9	7.7	28.76	33
Middle Channel								
1880.0	21.09	1.5	0	H	1.9	7.7	26.89	33
1880.0	23.07	1.5	0	V	1.9	7.7	28.87	33
High Channel								
1909.8	21.21	1.5	0	H	1.9	7.7	27.01	33
1909.8	23.10	1.5	0	V	1.9	7.7	28.90	33

## ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	27.12	1.5	0	H	1.5	0	25.62	38.45
824.2	28.61	1.5	0	V	1.5	0	27.11	38.45
Middle Channel								
836.6	26.51	1.5	0	H	1.5	0	25.01	38.45
836.6	28.50	1.5	0	V	1.5	0	27.00	38.45
High Channel								
848.8	26.84	1.5	0	H	1.5	0	25.34	38.45
848.8	28.66	1.5	0	V	1.5	0	27.16	38.45

## EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	19.83	1.5	0	H	1.9	7.7	25.63	33
1850.2	21.88	1.5	0	V	1.9	7.7	27.68	33
Middle Channel								
1880.0	20.33	1.5	0	H	1.9	7.7	26.13	33
1880.0	22.21	1.5	0	V	1.9	7.7	28.01	33
High Channel								
1909.8	19.87	1.5	0	H	1.9	7.7	25.67	33
1909.8	21.73	1.5	0	V	1.9	7.7	27.53	33

## ERP For EDGE Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	23.86	1.5	0	H	1.5	0	22.36	38.45
824.2	25.75	1.5	0	V	1.5	0	24.25	38.45
Middle Channel								
836.6	23.62	1.5	0	H	1.5	0	22.12	38.45
836.6	25.75	1.5	0	V	1.5	0	24.25	38.45
High Channel								
848.8	23.19	1.5	0	H	1.5	0	21.69	38.45
848.8	25.59	1.5	0	V	1.5	0	24.09	38.45

## EIRP For EDGE Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	15.83	1.5	0	H	1.9	7.7	21.63	33
1850.2	18.25	1.5	0	V	1.9	7.7	24.05	33
Middle Channel								
1880.0	15.56	1.5	0	H	1.9	7.7	21.36	33
1880.0	19.12	1.5	0	V	1.9	7.7	24.92	33
High Channel								
1909.8	15.42	1.5	0	H	1.9	7.7	21.22	33
1909.8	18.33	1.5	0	V	1.9	7.7	24.13	33

## ERP For WCDMA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.75	1.5	0	H	1.5	0	18.25	38.45
826.4	20.86	1.5	0	V	1.5	0	19.36	38.45
Middle Channel								
836.4	19.84	1.5	0	H	1.5	0	18.34	38.45
836.4	20.92	1.5	0	V	1.5	0	19.42	38.45
High Channel								
846.6	19.74	1.5	0	H	1.5	0	18.24	38.45
846.6	20.66	1.5	0	V	1.5	0	19.16	38.45

## ERP For HSDPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.85	1.5	0	H	1.5	0	18.35	38.45
826.4	20.86	1.5	0	V	1.5	0	19.36	38.45
Middle Channel								
836.4	19.92	1.5	0	H	1.5	0	18.42	38.45
836.4	21.51	1.5	0	V	1.5	0	20.01	38.45
High Channel								
846.6	18.78	1.5	0	H	1.5	0	17.28	38.45
846.6	20.55	1.5	0	V	1.5	0	19.05	38.45

## ERP For HSUPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.84	1.5	0	H	1.5	0	18.34	38.45
826.4	21.14	1.5	0	V	1.5	0	19.64	38.45
Middle Channel								
836.4	19.50	1.5	0	H	1.5	0	18.00	38.45
836.4	20.74	1.5	0	V	1.5	0	19.24	38.45
High Channel								
846.6	19.48	1.5	0	H	1.5	0	17.98	38.45
846.6	20.62	1.5	0	V	1.5	0	19.12	38.45

## EIRP For WCDMA Mode Band II

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	11.44	1.5	0	H	1.9	7.7	17.24	33
1852.4	13.46	1.5	0	V	1.9	7.7	19.26	33
Middle Channel								
1880.0	11.15	1.5	0	H	1.9	7.7	16.95	33
1880.0	13.54	1.5	0	V	1.9	7.7	19.34	33
High Channel								
1907.6	11.05	1.5	0	H	1.9	7.7	16.85	33
1907.6	14.20	1.5	0	V	1.9	7.7	20.00	33

## EIRP For HSDPA Mode Band II

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	11.88	1.5	0	H	1.9	7.7	17.68	33
1852.4	13.44	1.5	0	V	1.9	7.7	19.24	33
Middle Channel								
1880.0	11.54	1.5	0	H	1.9	7.7	17.34	33
1880.0	13.14	1.5	0	V	1.9	7.7	18.94	33
High Channel								
1907.6	11.53	1.5	0	H	1.9	7.7	17.33	33
1907.6	13.56	1.5	0	V	1.9	7.7	19.36	33

## EIRP For HSUPA Mode Band II

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	11.59	1.5	0	H	1.9	7.7	17.39	33
1852.4	13.56	1.5	0	V	1.9	7.7	19.36	33
Middle Channel								
1880.0	11.89	1.5	0	H	1.9	7.7	17.69	33
1880.0	13.14	1.5	0	V	1.9	7.7	18.94	33
High Channel								
1907.6	12.19	1.5	0	H	1.9	7.7	17.99	33
1907.6	13.62	1.5	0	V	1.9	7.7	19.42	33

Note: Result = Substitute - Cable loss + Antenna Gain

Max. Conducted Output Power

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	32.66	38.45
	Middle Channel	836.6	32.63	38.45
	High Channel	848.8	32.54	38.45
GPRS(1 Slot)	Low Channel	824.2	32.48	38.45
	Middle Channel	836.6	32.53	38.45
	High Channel	848.8	32.44	38.45
EDGE(1 Slot)	Low Channel	824.2	27.04	38.45
	Middle Channel	836.6	27.42	38.45
	High Channel	848.8	27.29	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	29.39	33.0
	Middle Channel	1880.0	29.30	33.0
	High Channel	1909.8	28.69	33.0
GPRS(1 Slot)	Low Channel	1850.2	29.39	33.0
	Middle Channel	1880.0	29.27	33.0
	High Channel	1909.8	28.67	33.0
EDGE(1 Slot)	Low Channel	1850.2	25.55	33.0
	Middle Channel	1880.0	25.69	33.0
	High Channel	1909.8	25.08	33.0



For WCDMA Band V

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.81	38.45
	Middle Channel	836.4	22.61	38.45
	High Channel	846.6	22.91	38.45
HSDPA	Low Channel	826.4	22.11	38.45
	Middle Channel	836.4	22.01	38.45
	High Channel	846.6	22.23	38.45
HSUPA	Low Channel	826.4	21.95	38.45
	Middle Channel	836.4	22.05	38.45
	High Channel	846.6	22.04	38.45

For WCDMA Band II

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	1852.4	21.52	30.0
	Middle Channel	1880.0	21.50	30.0
	High Channel	1907.6	21.23	30.0
HSDPA	Low Channel	1852.4	21.12	30.0
	Middle Channel	1880.0	21.28	30.0
	High Channel	1907.6	21.03	30.0
HSUPA	Low Channel	1852.4	21.03	30.0
	Middle Channel	1880.0	21.12	30.0
	High Channel	1907.6	21.00	30.0

## 5. Peak-to-average Radio (PAR) of Transmitter

### 5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 5.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

### 5.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



### 5.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 5.5 Summary of Test Results

For Cellular Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	128	824.2	32.80	32.66	0.14	13
	190	836.6	32.79	32.63	0.16	13
	251	848.8	32.70	32.54	0.16	13
GPRS (1 Slot)	128	824.2	32.63	32.48	0.15	13
	190	836.6	32.68	32.53	0.15	13
	251	848.8	32.58	32.44	0.14	13
EDGE (1 Slot)	128	824.2	27.19	27.04	0.15	13
	190	836.6	27.57	27.42	0.15	13
	251	848.8	27.44	27.29	0.15	13

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
GSM	512	1850.2	29.54	29.39	0.15	13
	661	1880.0	29.43	29.30	0.13	13
	810	1909.8	28.82	28.69	0.13	13
GPRS (1 Slot)	512	1850.2	29.53	29.39	0.14	13
	661	1880.0	29.41	29.27	0.14	13
	810	1909.8	28.80	28.67	0.13	13
EDGE (1 Slot)	512	1850.2	25.66	25.55	0.11	13
	661	1880.0	25.82	25.69	0.13	13
	810	1909.8	25.22	25.08	0.14	13

## For WCDMA Band V

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
WCDMA	4132	826.4	25.46	22.81	2.65	13
	4183	836.4	25.31	22.61	2.7	13
	4233	846.6	25.56	22.91	2.65	13
HSDA	4132	826.4	24.67	22.11	2.56	13
	4183	836.4	24.18	22.01	2.17	13
	4233	846.6	24.63	22.23	2.4	13
HSUPA	4132	826.4	24.34	21.95	2.39	13
	4183	836.4	24.12	22.05	2.07	13
	4233	846.6	24.30	22.04	2.26	13

## For WCDMA Band II

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
WCDMA	9262	1852.4	24.46	21.52	2.94	13
	9400	1880.0	24.38	21.50	2.88	13
	9538	1907.6	24.16	21.23	2.93	13
HSDPA	9262	1852.4	23.62	21.12	2.5	13
	9400	1880.0	23.82	21.28	2.54	13
	9538	1907.6	23.76	21.03	2.73	13
HSUPA	9262	1852.4	23.36	21.03	2.33	13
	9400	1880.0	23.43	21.12	2.31	13
	9538	1907.6	23.15	21.00	2.15	13

## 6. Emission Bandwidth

### 6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 6.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

### 6.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



### 6.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 6.5 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	254.1382	340.856
	190	836.6	250.3227	336.693
	251	848.8	249.0922	335.494
GPRS	128	824.2	252.6220	335.244
	190	836.6	255.7320	338.238
	251	848.8	253.7362	333.297
EDGE	128	824.2	264.5944	332.392
	190	836.6	262.9310	330.287
	251	848.8	265.6439	339.570

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	257.3912	337.490
	661	1880.0	254.5394	331.698
	810	1909.8	256.8128	338.836
GPRS	512	1850.2	253.6274	339.650
	661	1880.0	257.0134	340.886
	810	1909.8	254.8679	341.604
EDGE	512	1850.2	254.3009	335.744
	661	1880.0	262.0201	343.375
	810	1909.8	260.9917	330.788

## For Band II


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9400	1880.0	4.1331	4.633
HSUPA	9400	1880.0	4.1477	4.647
HSDPA	9400	1880.0	4.1484	4.642

## For Band V


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4182	836.4	4.1452	4.634
HSUPA	4182	836.4	4.1614	4.639
HSDPA	4182	836.4	4.1513	4.646

*Please refer to the following test plots:*

For Cellular Band  
GSM Low Channel




GSM Middle Channel







GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




EDGE Low Channel




EDGE Middle Channel




EDGE High channel




For PCS Band  
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




EDGE Low Channel



EDGE Middle Channel




EDGE High channel






For Band II


WCDMA Middle Channel




HSDPA Middle Channel




For Band V  
WCDMA Middle Channel



HSUPA Middle Channel



HSDPA Middle Channel



## 7. Out of Band Emissions at Antenna Terminal

### 7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


### 7.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Spectrum Analyzer	FSP	836079/035	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

### 7.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:




### 7.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


## 7.5 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band


GSM Low Channel 30MHz to 1GHz




Above 1GHz




GSM Middle Channel  
30MHz to 1GHz




Above 1GHz




GSM High Channel  
30MHz to 1GHz




Above 1GHz



GSM Low Band Emission




GSM High Band Emission







GPRS Low Channel  
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel  
30MHz to 1GHz




Above 1GHz




GPRS High Channel  
30MHz to 1GHz




Above 1GHz




GPRS Low Band Emission




GPRS High Band Emission




EDGE Low Channel  
30MHz to 1GHz




Above 1GHz




EDGE Middle Channel  
30MHz to 1GHz




Above 1GHz



EDGE High Channel  
30MHz to 1GHz




Above 1GHz



EDGE Low Band Emission




EDGE High Band Emission






For PCS Band  
GSM Low Channel  
30MHz to 1GHz




Above 1GHz




GSM Middle Channel


30MHz to 1GHz




Above 1GHz




GSM High Channel  
30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission



GPRS Low Channel  
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel

30MHz to 1GHz




Above 1GHz




GPRS High Channel


30MHz to 1GHz




Above 1GHz



GPRS Low Band Emission




GPRS High Band Emission






EDGE Low Channel  
30MHz to 1GHz




Above 1GHz




EDGE Middle Channel


30MHz to 1GHz




Above 1GHz




EDGE High Channel  
30MHz to 1GHz




Above 1GHz



EDGE Low Band Emission




EDGE High Band Emission




For Band II


WCDMA Low Channel  
30MHz to 1GHz




Above 1GHz




WCDMA Middle Channel  
30MHz to 1GHz




Above 1GHz




WCDMA High Channel  
30MHz to 1GHz




Above 1GHz



## WCDMA Low Band Spurious Emission




## WCDMA High Band Spurious Emission







HSUPA Low Channel  
30MHz to 1GHz




Above 1GHz




HSUPA Middle Channel  
30MHz to 1GHz




Above 1GHz




HSUPA High Channel  
30MHz to 1GHz




Above 1GHz




## HSUPA Low Band Spurious Emission




## HSUPA High Band Spurious Emission




HSDPA Low Channel  
30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel  
30MHz to 1GHz




Above 1GHz




HSDPA High Channel  
30MHz to 1GHz




Above 1GHz



## HSDPA Low Band Spurious Emission



## HSDPA High Band Spurious Emission







**For Band V**

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz




WCDMA Middle Channel  
30MHz to 1GHz




Above 1GHz




WCDMA High Channel  
30MHz to 1GHz




Above 1GHz




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSUPA Low Channel  
30MHz to 1GHz




Above 1GHz




HSUPA Middle Channel  
30MHz to 1GHz




Above 1GHz




HSUPA High Channel  
30MHz to 1GHz




Above 1GHz



## HSUPA Low Band Spurious Emission




## HSUPA High Band Spurious Emission







HSDPA Low Channel  
30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel  
30MHz to 1GHz




Above 1GHz




### HSDPA High Channel 30MHz to 1GHz




### Above 1GHz



## HSDPA Low Band Spurious Emission



## HSDPA High Band Spurious Emission



## 8. Spurious Radiated Emissions

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.20$  dB.

### 8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### 8.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-334	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086198	2014-05-24	2015-05-23
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-28	2015-05-27
Signal Generator	R&S	SMR20	100047	2014-05-28	2015-05-27

### 8.4 Test Procedure

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB  $= 43 + 10 \log_{10}(\text{power out in Watts})$

## 8.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 8.6 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:


**-27.14 at 945.4399 MHz in the Vertical polarization for HSDPA Band II Mode Middle channel,  
9 kHz to 18 GHz.**

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

*Spurious Emission From 30MHz to 1GHz*


*For Cellular Band\_GSM850 Mode*

*Horizontal:*



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	40.5591	-70.51	20.41	-50.10	-13.00	-37.10	ERP
2	100.2286	-70.61	17.60	-53.01	-13.00	-40.01	ERP
3	321.0608	-69.77	20.80	-48.97	-13.00	-35.97	ERP
4	739.6605	-69.98	27.51	-42.47	-13.00	-29.47	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.9942	-70.32	20.66	-49.66	-13.00	-36.66	ERP
2	100.2286	-69.95	17.92	-52.03	-13.00	-39.03	ERP
3	293.0842	-69.95	20.66	-49.29	-13.00	-36.29	ERP
4	744.8661	-69.34	27.10	-42.24	-13.00	-29.24	ERP
5	1000.0000	-69.49	29.05	-40.44	-13.00	-27.44	ERP

For PCS Band\_GSM1900 Mode


Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	744.8661	-76.59	29.74	-46.85	-13.00	-33.85	ERP
2	900.1474	-77.91	31.18	-46.73	-13.00	-33.73	ERP




Vertical:




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	36.2541	-77.52	20.89	-56.63	-13.00	-43.63	ERP
2	750.1082	-77.94	29.58	-48.36	-13.00	-35.36	ERP
3	887.6099	-78.51	30.95	-47.56	-13.00	-34.56	ERP

Spurious Emission From 30MHz to 1GHz  
For band V Mode  
Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	46.0163	-79.05	19.65	-59.40	-13.00	-46.40	ERP
2	582.7423	-77.80	26.07	-51.73	-13.00	-38.73	ERP
3	932.2713	-76.49	30.11	-46.38	-13.00	-33.38	ERP

Vertical:




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	36.2541	-77.52	20.89	-56.63	-13.00	-43.63	ERP
2	599.3211	-78.06	26.56	-51.50	-13.00	-38.50	ERP
3	938.8324	-76.22	29.91	-46.31	-13.00	-33.31	ERP

Spurious Emission From 30MHz to 1GHz


For band II Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.7147	-69.80	20.62	-49.18	-13.00	-36.18	ERP
2	98.8326	-70.14	17.65	-52.49	-13.00	-39.49	ERP
3	318.8170	-69.67	21.07	-48.60	-13.00	-35.60	ERP
4	739.6605	-69.99	27.29	-42.70	-13.00	-29.70	ERP
5	993.0114	-69.15	28.80	-40.35	-13.00	-27.35	ERP

Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	108.2667	-69.84	17.08	-52.76	-13.00	-39.76	ERP
2	230.9068	-67.66	17.52	-50.14	-13.00	-37.14	ERP
3	744.8661	-69.06	27.10	-41.96	-13.00	-28.96	ERP
4	839.1818	-68.75	27.27	-41.48	-13.00	-28.48	ERP
5	932.2715	-69.03	28.01	-41.02	-13.00	-28.02	ERP

*Spurious Emissions Above 1GHz**For Cellular Band\_GSM850 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-60.69	10.25	-50.44	-13.00	-37.44	H
2472.6	-59.79	14.02	-45.77	-13.00	-32.77	H
1648.4	-60.04	13.38	-46.66	-13.00	-33.66	V
2472.6	-58.95	15.25	-43.70	-13.00	-30.70	V
Middle Channel (836.6MHz)						
1673.2	-60.02	10.12	-49.90	-13.00	-36.90	H
2509.8	-59.72	13.84	-45.88	-13.00	-32.88	H
1673.2	-59.98	10.14	-49.84	-13.00	-36.84	V
2509.8	-60.38	13.86	-46.52	-13.00	-33.52	V
High Channel (848.8MHz)						
1697.6	-60.38	14.05	-46.33	-13.00	-33.33	H
2546.4	-59.64	14.41	-45.23	-13.00	-32.23	H
1697.6	-60.36	13.96	-46.40	-13.00	-33.40	V
2546.4	-59.56	15.11	-44.45	-13.00	-31.45	V

*For PCS Band\_GSM1900 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-59.90	13.67	-46.23	-13.00	-33.23	H
5550.6	-58.38	14.54	-43.84	-13.00	-30.84	H
3700.4	-59.25	10.21	-49.04	-13.00	-36.04	V
5550.6	-60.60	14.05	-46.55	-13.00	-33.55	V
Middle Channel (1880MHz)						
3700.4	-59.51	13.77	-45.74	-13.00	-32.74	H
5550.6	-58.69	14.35	-44.34	-13.00	-31.34	H
3700.4	-59.16	10.27	-48.89	-13.00	-35.89	V
5550.6	-58.87	12.22	-46.65	-13.00	-33.65	V
High Channel (1909.8MHz)						
3700.4	-60.28	13.77	-46.51	-13.00	-33.51	H
5550.6	-60.08	14.28	-45.80	-13.00	-32.80	H
3700.4	-59.84	10.27	-49.57	-13.00	-36.57	V
5550.6	-59.72	13.47	-46.25	-13.00	-33.25	V

*For Band V Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-59.45	14.98	-44.47	-13.00	-31.47	H
2479.2	-59.97	17.02	-42.95	-13.00	-29.95	H
1652.8	-53.42	-0.50	-53.92	-13.00	-40.92	V
2479.2	-59.65	13.77	-45.88	-13.00	-32.88	V
Middle Channel (836.4MHz)						
1652.8	-58.68	6.86	-51.82	-13.00	-38.82	H
2479.2	-59.17	14.62	-44.55	-13.00	-31.55	H
1652.8	-59.63	15.67	-43.96	-13.00	-30.96	V
2479.2	-60.66	17.01	-43.65	-13.00	-30.65	V
High Channel (846.6MHz)						
1652.8	-57.79	6.86	-50.93	-13.00	-37.93	H
2479.2	-60.81	15.03	-45.78	-13.00	-32.78	H
1652.8	-58.29	6.86	-51.43	-13.00	-38.43	V
2479.2	-59.73	13.66	-46.07	-13.00	-33.07	V

*For Band II Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1852.4MHz)						
3704.8	-58.81	5.88	-52.93	-13.00	-39.93	H
5557.2	-59.37	15.37	-44.00	-13.00	-31.00	H
3704.8	-59.87	8.18	-51.69	-13.00	-38.69	V
5557.2	-60.10	15.98	-44.12	-13.00	-31.12	V
Middle Channel (1880MHz)						
3704.8	-59.29	10.17	-49.12	-13.00	-36.12	H
5557.2	-59.14	14.69	-44.45	-13.00	-31.45	H
3704.8	-58.86	14.67	-44.19	-13.00	-31.19	V
5557.2	-59.41	16.50	-42.91	-13.00	-29.91	V
High Channel (1907.6MHz)						
3704.8	-59.33	6.91	-52.42	-13.00	-39.42	H
5557.2	-59.37	15.33	-44.04	-13.00	-31.04	H
3704.8	-59.63	15.67	-43.96	-13.00	-30.96	V
5557.2	-58.96	10.06	-48.90	-13.00	-35.90	H

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

## 9. Frequency Stability

### 9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 9.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B-ESA	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication	CMU200	112012	2014-05-28	2015-05-27
GONGWEN	Moisture Test Chamber	GDS-150	SEMT-0013	2014-05-28	2015-05-27

### 9.3 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal



## 9.4 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 9.5 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	46	0.0550
40	3.7	30	0.0359
30	3.7	21	0.0251
20	3.7	25	0.0299
10	3.7	32	0.0383
0	3.7	38	0.0454
-10	3.7	46	0.0550
-20	3.7	40	0.0478
-30	3.7	48	0.0574

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-73	-0.0388
40	3.7	-69	-0.0367
30	3.7	-51	-0.0271
20	3.7	-67	-0.0356
10	3.7	-48	-0.0255
0	3.7	-37	-0.0197
-10	3.7	-43	-0.0229
-20	3.7	-57	-0.0303
-30	3.7	-53	-0.0282

## For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	63	0.0753
40	3.7	57	0.0681
30	3.7	46	0.0550
20	3.7	36	0.0430
10	3.7	28	0.0335
0	3.7	37	0.0442
-10	3.7	42	0.0502
-20	3.7	45	0.0538
-30	3.7	48	0.0574

## For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-30	-0.0160
40	3.7	-19	-0.0101
30	3.7	-21	-0.0112
20	3.7	-27	-0.0144
10	3.7	-30	-0.0160
0	3.7	-38	-0.0202
-10	3.7	-46	-0.0245
-20	3.7	-43	-0.0229
-30	3.7	-50	-0.0266

## For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-48	-0.0574
40	3.7	-57	-0.0681
30	3.7	-35	-0.0418
20	3.7	-46	-0.0550
10	3.7	-52	-0.0622
0	3.7	-46	-0.0550
-10	3.7	-55	-0.0657
-20	3.7	-60	-0.0717
-30	3.7	-63	-0.0753

## For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	62	0.0330
40	3.7	53	0.0282
30	3.7	48	0.0255
20	3.7	45	0.0239
10	3.7	48	0.0255
0	3.7	52	0.0277
-10	3.7	58	0.0309
-20	3.7	63	0.0335
-30	3.7	70	0.0372

## For WCDMA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-50	-0.0598
40	3.7	-45	-0.0538
30	3.7	-38	-0.0454
20	3.7	-33	-0.0394
10	3.7	-38	-0.0454
0	3.7	-40	-0.0478
-10	3.7	-45	-0.0538
-20	3.7	-56	-0.0669
-30	3.7	-63	-0.0753

## For WCDMA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	65	0.0346
40	3.7	62	0.0330
30	3.7	47	0.0250
20	3.7	35	0.0186
10	3.7	40	0.0213
0	3.7	36	0.0191
-10	3.7	44	0.0234
-20	3.7	58	0.0309
-30	3.7	60	0.0319

## For HSUPA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-55	-0.0658
40	3.7	-43	-0.0514
30	3.7	-38	-0.0454
20	3.7	-40	-0.0478
10	3.7	-46	-0.0550
0	3.7	-53	-0.0634
-10	3.7	-47	-0.0562
-20	3.7	-55	-0.0658
-30	3.7	-63	-0.0753

## For HSUPA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-44	-0.0234
40	3.7	-37	-0.0197
30	3.7	-52	-0.0277
20	3.7	-33	-0.0176
10	3.7	-40	-0.0213
0	3.7	-37	-0.0197
-10	3.7	-45	-0.0239
-20	3.7	-53	-0.0282
-30	3.7	-49	-0.0261

## For HSDPA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-64	-0.0765
40	3.7	-58	-0.0693
30	3.7	-47	-0.0562
20	3.7	-52	-0.0622
10	3.7	-66	-0.0789
0	3.7	-70	-0.0837
-10	3.7	-73	-0.0873
-20	3.7	-82	-0.0980
-30	3.7	-78	-0.0933

## For HSDPA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-70	-0.0372
40	3.7	-64	-0.0340
30	3.7	-56	-0.0298
20	3.7	-48	-0.0255
10	3.7	-45	-0.0239
0	3.7	-52	-0.0277
-10	3.7	-58	-0.0309
-20	3.7	-63	-0.0335
-30	3.7	-60	-0.0319

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	34	0.0406
	3.7	25	0.0299
	4.2	38	0.0454
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-72	-0.0383
	3.7	-67	-0.0356
	4.2	-70	-0.0372
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	44	0.0526
	3.7	36	0.0430
	4.2	42	0.0502
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-33	-0.0176
	3.7	-27	-0.0144
	4.2	-38	-0.0202

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-55	-0.0657
	3.7	-46	-0.0550
	4.2	-43	-0.0514
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	43	0.0229
	3.7	45	0.0239
	4.2	52	0.0277
Reference Frequency(Middle Channel): WCDMA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-38	-0.0454
	3.7	-33	-0.0395
	4.2	-30	-0.0359
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	42	0.0223
	3.7	35	0.0186
	4.2	38	0.0202
Reference Frequency(Middle Channel): HSUPA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-46	-0.0245
	3.7	-40	-0.0213
	4.2	-38	-0.0202



Reference Frequency(Middle Channel): HSUPA1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-38	-0.0202
	3.7	-33	-0.0176
	4.2	-42	-0.0223
Reference Frequency(Middle Channel): HSDPA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-48	-0.0574
	3.7	-52	-0.0622
	4.2	-55	-0.0658
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-52	-0.0277
	3.7	-48	-0.0255
	4.2	-50	-0.0266

\*\*\*\*\* END OF REPORT \*\*\*\*\*