Appendix D

RF Test Data for 5.8G WLAN (Conducted Measurement)


Product Name: PCSGOB1018M-Series Trade Mark: PC SMART Test Model: PCSGOB1018M-A


Environmental Conditions

Temperature:	23.2 ° C
Relative Humidity:	52.5%
ATM Pressure:	100.0 kPa
Test Engineer:	Wilson.Hong
Supervised by:	Jayden.Zhuo

D.1 Duty Cycle

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
IEEE 802.11a	5785	100	0.00	0.01
IEEE 802.11n HT20	5785	100	0.00	0.01
IEEE 802.11n HT40	5755	100	0.00	0.01
IEEE 802.11ac VHT20	5785	100	0.00	0.01
IEEE 802.11ac VHT40	5755	100	0.00	0.01
IEEE 802.11ac VHT80	5775	100	0.00	0.01







D.2 Maximum Conduct Peak Output Power

Test Mode	Channel	Frequency (MHz)	Burst Average Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)
	149	5745	7.29	0	9.29	
IEEE 802.11a	157	5785	7.02	0	9.02	30
	165	5825	7.32	0	9.32	
IEEE 802.11n HT20	149	5745	7.05	0	8.05	
	157	5785	7.14	0	8.64	30
	165	5825	7.25	0	8.95	
IEEE 802.11n HT40	151	5755	6.04	0	8.04	30
	159	5795	6.91	0	8.91	30
	149	5745	7.12	0	8.62	
IEEE 802.11ac VHT20	157	5785	7.41	0	8.41	30
	165	5825	7.16	0	8.16	
IEEE 802.11ac VHT40	151	5755	6.88	0	8.88	30
	159	5795	6.52	0	8.52	30
IEEE 802.11ac VHT80	155	5775	6.27	0	8.27	30


D.3 Power Spectral Density

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/300KHz)	Duty Cycle Factor (dB)	RBW Factor (dB)	Report Power Density (dBm/500KHz)	Limit (dBm/500KHz)
	149	5745	-3.335	0	2.218	-1.117	
IEEE 802.11a	157	5785	-2.669	0	2.218	-0.451	30
	165	5825	-2.135	0	2.218	0.083	
	149	5745	-3.778	0	2.218	-1.560	30
IEEE 802.11n HT20	157	5785	-2.805	0	2.218	-0.587	
	165	5825	-2.927	0	2.218	-0.709	
IEEE 802.11n HT40	151	5755	-6.178	0	2.218	-3.960	30
1002.11110140	159	5795	-5.002	0	2.218	-2.784	
IEEE 802.11ac VHT20	149	5745	-3.968	0	2.218	-1.750	30
	157	5785	-3.162	0	2.218	-0.944	
	165	5825	-2.270	0	2.218	-0.052	
IEEE 802.11ac VHT40	151	5755	-5.828	0	2.218	-3.610	30
	159	5795	-5.021	0	2.218	-2.803	30
IEEE 802.11ac VHT80	155	5775	-10.238	0	2.218	-8.020	30








IEEE 802.11a / Channel 157 / 5785 MHz



IEEE 802.11a / Channel 165 / 5825 MHz









IEEE 802.11n HT20 / Channel 157 / 5785 MHz








CF Step 3.000000 MHz <u>Auto</u> Freq Offset 0 Hz Center 5.74500 GHz #Res BW 300 kHz Span 30.00 MHz Sweep 1.000 ms (1001 pts) **#VBW** 910 kHz* STATUS IEEE 802.11ac VHT20 / Channel 149 / 5745 MHz

-40.0


-50 O

-60.0


-70.0




IEEE 802.11ac VHT20 / Channel 157 / 5785 MHz



IEEE 802.11ac VHT 20 / Channel 165 / 5825 MHz



IEEE 802.11ac VHT40 / Channel 151 / 5755 MHz



IEEE 802.11ac VHT40 / Channel 159 / 5795 MHz

#VBW 910 kHz*


Span 120.0 MHz Sweep 1.667 ms (1001 pts)


STATUS

Center 5.77500 GHz #Res BW 300 kHz


D.4 Emission Bandwidth

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
	149	5745	17.610	
IEEE 802.11a	157	5785	17.630	>=0.5
	165	5825	17.620	
	149	5745	17.520	
IEEE 802.11n HT20	157	5785	17.690	>=0.5
	165	5825	17.590	
IEEE 802.11n HT40	151	5755	35.880	>=0.5
1EEE 802.1111 H140	159	5795	36.030	/=0.5
	149	5745	17.350	>=0.5
IEEE 802.11ac VHT20	157	5785	16.900	>=0.5
	165	5825	17.590	
IEEE 802.11ac VHT40	151	5755	36.340	>=0.5
	159	5795	35.860	
IEEE 802.11ac VHT80	155	5775	75.660	>=0.5







IEEE 802.11n HT20 / Channel 149 / 5745 MHz



IEEE 802.11n HT20 / Channel 157 / 5785 MHz



IEEE 802.11n HT20 / Channel 165 / 5825 MHz



-6.00 dB

STATUS

x dB

17.35 MHz

x dB Bandwidth

STATUS

Total Power

OBW Power

x dB

12.8 dBm

99.00 %

-6.00 dB

STATUS

Freq Offset

Occupied Bandwidth

Transmit Freq Error

x dB Bandwidth


50.437 MHz


1.2886 MHz


35.86 MHz

D.5 Undesirable Emissions Measurement


Test Mode	Channel	Frequency	Conducted Power	Antenna Gain	EIRP	Detector	Limit
	Chamber	(MHz)	(dBm)	(dBi)	(dBm/MHz)	Detector	(dBm/MHz)
JEEE 000 44a	149	5650.000	-49.658	2.000	-47.658	Peak	-27.00
		5700.000	-49.680	2.000	-47.680	Peak	10.00
	149	5720.000	-44.194	2.000	-42.194	Peak	15.60
		5725.000	-33.127	2.000	-31.127	Peak	27.00
IEEE 802.11a		5850.000	-33.063	2.000	-31.063	Peak	27.00
	165	5855.000	-40.222	2.000	-38.222	Peak	15.60
	165	5875.000	-48.639	2.000	-46.639	Peak	10.00
		5925.000	-48.190	2.000	-46.190	Peak	-27.00
		5650.000	-49.124	2.000	-47.124	Peak	-27.00
	149	5700.000	-50.124	2.000	-48.124	Peak	10.00
	149	5720.000	-44.627	2.000	-42.627	Peak	15.60
IEEE 802.11n HT20		5725.000	-35.029	2.000	-33.029	Peak	27.00
IEEE 002.1111 1120		5850.000	-35.142	2.000	-33.142	Peak	27.00
	165	5855.000	-39.190	2.000	-37.190	Peak	15.60
	165	5875.000	-49.281	2.000	-47.281	Peak	10.00
		5925.000	-48.974	2.000	-46.974	Peak	-27.00
		5650.000	-50.142	2.000	-48.142	Peak	-27.00
	151	5700.000	-48.250	2.000	-46.250	Peak	10.00
	151	5720.000	-36.340	2.000	-34.340	Peak	15.60
IEEE 000 44 = LIT40		5725.000	-31.390	2.000	-29.390	Peak	27.00
IEEE 802.11n HT40		5850.000	-32.493	2.000	-30.493	Peak	27.00
	150	5855.000	-34.860	2.000	-32.860	Peak	15.60
	159	5875.000	-45.176	2.000	-43.176	Peak	10.00
		5925.000	-48.544	2.000	-46.544	Peak	-27.00
		5650.000	-48.870	2.000	-46.870	Peak	-27.00
	149	5700.000	-50.115	2.000	-48.115	Peak	10.00
	149	5720.000	-45.180	2.000	-43.180	Peak	15.60
IEEE 802.11ac VHT20		5725.000	-36.808	2.000	-34.808	Peak	27.00
IEEE 002.11ac VH120		5850.000	-37.152	2.000	-35.152	Peak	27.00
	165	5855.000	-41.018	2.000	-39.018	Peak	15.60
	165	5875.000	-48.791	2.000	-46.791	Peak	10.00
		5925.000	-38.335	2.000	-36.335	Peak	-27.00
		5650.000	-49.733	2.000	-47.733	Peak	-27.00
	149	5700.000	-49.563	2.000	-47.563	Peak	10.00
		5720.000	-38.195	2.000	-36.195	Peak	15.60
IEEE 802.11ac VHT40		5725.000	-34.396	2.000	-32.396	Peak	27.00
ILLE 802.11ac VIII40		5850.000	-32.089	2.000	-30.089	Peak	27.00
	165	5855.000	-35.062	2.000	-33.062	Peak	15.60
	100	5875.000	-44.284	2.000	-42.284	Peak	10.00
		5925.000	-48.231	2.000	-46.231	Peak	-27.00
		5650.000	-51.827	2.000	-49.827	Peak	-27.00
	155	5700.000	-43.407	2.000	-41.407	Peak	10.00
		5720.000	-34.744	2.000	-32.744	Peak	15.60
IEEE 802.11ac VHT80		5725.000	-34.953	2.000	-32.953	Peak	27.00
ILEE OUZ. HAC VITIOU	155	5850.000	-35.255	2.000	-33.255	Peak	27.00
		5855.000	-37.857	2.000	-35.857	Peak	15.60
		5875.000	-45.811	2.000	-43.811	Peak	10.00
		5925.000	-49.782	2.000	-47.782	Peak	-27.00










FCC ID: XXXXX-YYYYY




IEEE 802.11n HT20 / Channel 165 / 5825 MHz / Peak









Page 26 of 28

IEEE 802.11ac VHT20 / Channel 165 / 5825 MHz / Peak

-48.231 dBn

5.925 00 GHz


FUNCTION

FUNCTION WIDTH


STATUS

<u>Auto</u>

Freq Offset



IEEE 802.11ac VHT80 / Channel 155 / 5775 MHz / Peak



IEEE 802.11ac VHT80 / Channel 155/ 5775 MHz / Peak