

FCC PART 15 B
TEST REPORT

For

PC Smart S.A.

Carrera 116 no.15-25

FCC ID: 2ABFV-P45K15

| | |
|---|---|
| Report Type: Original Report | Product Type: Touch Smart Phone Krone 4.5 |
| Test Engineer: Dean Liu |  |
| Report Number: RSZ150925010-00D | |
| Report Date: 2015-10-30 | |
| Reviewed By: Sula Huang RF Leader |  |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| DESCRIPTION OF TEST CONFIGURATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| LOCAL SUPPORT EQUIPMENT LIST AND DETAILS | 5 |
| SUPPORT CABLE LIST AND DETAILS | 5 |
| CONFIGURATION OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS..... | 7 |
| FCC§15.107 - CONDUCTED EMISSIONS..... | 8 |
| MEASUREMENT UNCERTAINTY | 8 |
| EUT SETUP..... | 8 |
| EMI TEST RECEIVER SETUP..... | 9 |
| TEST EQUIPMENT LIST AND DETAILS..... | 9 |
| TEST PROCEDURE | 9 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 9 |
| TEST RESULTS SUMMARY | 10 |
| TEST DATA | 10 |
| FCC §15.109 - RADIATED SPURIOUS EMISSIONS | 13 |
| MEASUREMENT UNCERTAINTY | 13 |
| EUT SETUP | 13 |
| EMI TEST RECEIVER SETUP..... | 14 |
| TEST PROCEDURE | 14 |
| TEST EQUIPMENT LIST AND DETAILS..... | 15 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 15 |
| TEST RESULTS SUMMARY | 15 |
| TEST DATA | 15 |
| ENVIRONMENTAL CONDITIONS..... | 15 |

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *PC Smart S.A.*'s product, model number: *XF4502 (FCC ID: 2ABFV-P45K15)* (the "EUT") in this report was a *Touch Smart Phone Krone 4.5*, which was measured approximately: 13.21 cm (L) x 6.62 cm (W) x 0.96 cm (H), rated input voltage: DC3.8V rechargeable Li-ion battery or DC5.0V charging from adapter. The highest operating frequency is 1.3 GHz.

Adapter information:

Model: TUJP050100-A00

Input: AC100-240V, 50/60 Hz, 0.2A

Output: DC 5V, 1A

All measurement and test data in this report was gathered from production sample serial number: 150925010 (Assigned byBACL, Dongguan). The EUT was received on 2015-09-30.

Objective

This test report is prepared on behalf of *PC Smart S.A.* in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2ABFV-P45K15.

FCC Part 15C DSS submissions with FCC ID: 2ABFV-P45K15.

FCC Part 22H, 24E, 27 PCE submissions with FCC ID: 2ABFV-P45K15.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

The software “winthrax.exe” was used during test.

Equipment Modifications

No modification was made to the EUT tested.


Local Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|---------------|----------|----------------------|
| DELL | Laptop | PP11L | QDS-BRCM1017 |
| HP | Printer | C3941A | JPTVOB2337 |
| DELL | Keyboard | L100 | CNORH656658907BL05DC |
| SAST | Modem | AEM-2100 | 0293 |
| Kingston | Micro SD card | 4GB | / |

Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To |
|-------------------|----------------|--------------|------------|-------------------------|----------|
| Serial Cable | yes | no | 1.2 | Serial Port of Laptop | Modem |
| Parallel Cable | yes | no | 1.2 | Parallel Port of Laptop | Printer |
| Keyboard Cable | yes | no | 1.8 | USB Port of Laptop | Keyboard |
| USB Cable | yes | no | 1.2 | USB Port of Laptop | EUT |
| Earphone Cable | no | no | 1.2 | Audio Port of EUT | Earphone |

Configuration of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Results |
|-----------|---------------------|------------|
| §15.107 | Conducted Emissions | Compliance |
| §15.109 | Radiated Emissions | Compliance |

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

| Measurement | U_{cisp} |
|---|------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB |

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter of laptop was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|---------|---------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCS 30 | 830245/006 | 2014-10-20 | 2015-10-20 |
| R&S | L.I.S.N | ESH2-Z5 | 892107/021 | 2015-07-16 | 2016-07-15 |
| R&S | Two-line V-network | ENV 216 | 3560.6550.12 | 2014-12-11 | 2015-12-11 |
| R&S | Test Software | EMC32 | Version8.53.0 | N/A | N/A |

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

7.90 dB at 0.317235 MHz in the **Line** conducted mode

Test Data


Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 26.5°C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 100.1 kPa |

The testing was performed by Dean Liu on 2015-10-30.


Test Mode: Downloading

AC120V, 60Hz, Line:



| Frequency (MHz) | QuasiPeak (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) | Comment |
|-----------------|------------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.181612 | 50.1 | 9.000 | L1 | 9.8 | 14.3 | 64.4 | Compliance |
| 0.314718 | 44.4 | 9.000 | L1 | 9.8 | 15.4 | 59.8 | Compliance |
| 0.378019 | 45.3 | 9.000 | L1 | 9.8 | 13.0 | 58.3 | Compliance |
| 0.384091 | 44.6 | 9.000 | L1 | 9.8 | 13.6 | 58.2 | Compliance |
| 0.396530 | 42.8 | 9.000 | L1 | 9.8 | 15.1 | 57.9 | Compliance |
| 0.402900 | 41.8 | 9.000 | L1 | 9.8 | 16.0 | 57.8 | Compliance |

| Frequency (MHz) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) | Comment |
|-----------------|----------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.181612 | 38.1 | 9.000 | L1 | 9.8 | 16.3 | 54.4 | Compliance |
| 0.262017 | 37.7 | 9.000 | L1 | 9.8 | 13.7 | 51.4 | Compliance |
| 0.288307 | 36.9 | 9.000 | L1 | 9.8 | 13.7 | 50.6 | Compliance |
| 0.317235 | 41.9 | 9.000 | L1 | 9.8 | 7.9 | 49.8 | Compliance |
| 0.576662 | 34.0 | 9.000 | L1 | 9.8 | 12.0 | 46.0 | Compliance |
| 0.634524 | 31.8 | 9.000 | L1 | 9.8 | 14.2 | 46.0 | Compliance |

AC120V, 60Hz, Neutral:

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.169044 | 51.7 | 9.000 | N | 9.8 | 13.3 | 65.0 | Compliance |
| 0.387164 | 42.6 | 9.000 | N | 9.8 | 15.5 | 58.1 | Compliance |
| 0.503608 | 39.9 | 9.000 | N | 9.8 | 16.1 | 56.0 | Compliance |
| 0.732382 | 37.2 | 9.000 | N | 9.8 | 18.8 | 56.0 | Compliance |
| 0.768247 | 36.8 | 9.000 | N | 9.8 | 19.2 | 56.0 | Compliance |
| 0.952654 | 35.4 | 9.000 | N | 9.8 | 20.6 | 56.0 | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.174519 | 35.4 | 9.000 | N | 9.8 | 19.4 | 54.7 | Compliance |
| 0.259937 | 37.7 | 9.000 | N | 9.8 | 13.7 | 51.4 | Compliance |
| 0.290613 | 37.9 | 9.000 | N | 9.8 | 12.6 | 50.5 | Compliance |
| 0.314718 | 41.7 | 9.000 | N | 9.8 | 8.1 | 49.8 | Compliance |
| 0.576662 | 34.3 | 9.000 | N | 9.8 | 11.7 | 46.0 | Compliance |
| 0.634524 | 31.1 | 9.000 | N | 9.8 | 14.9 | 46.0 | Compliance |

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30MHz~200MHz: 5.0 dB; 200MHz~1GHz: 6.2 dB; 1GHz~6GHz: 4.45 dB, 6GHz~18GHz: 5.23 dB

Table 1 – Values of U_{cisp}


| Measurement | | U_{cisp} |
|---|----------------------|------------|
| Radiated disturbance (electric field strength at an OATS or in a SAC) | (30 MHz to 1000 MHz) | 6.3 dB |
| Radiated disturbance (electric field strength in a FAR) | (1 GHz to 6 GHz) | 5.2 dB |
| Radiated disturbance (electric field strength in a FAR) | (6 GHz to 18 GHz) | 5.5 dB |

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 6.5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1 MHz | 3 MHz | / | Peak |
| | 1 MHz | 10 Hz | / | Ave. |

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|----------------|-------------------|------------|---------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCI | 100224 | 2015-08-03 | 2016-08-02 |
| Sunol Sciences | Antenna | JB3 | A060611-3 | 2014-11-06 | 2017-11-05 |
| HP | Amplifier | 8447E | 2434A02181 | 2015-09-01 | 2016-09-01 |
| Agilent | Spectrum Analyzer | E4440A | SG43360054 | 2014-12-04 | 2015-12-04 |
| ETS-Lindgren | Horn Antenna | 3115 | 9808-5557 | 2015-09-06 | 2018-09-06 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 054201245 | 2015-02-19 | 2016-02-19 |
| Farad | Test Software | EZ-EMC | V1.1.4.2 | N/A | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

7.20 dB at 398.6000 MHz in the Line polarization

Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 26.9 °C |
| Relative Humidity: | 49 % |
| ATM Pressure: | 101.1 kPa |


The testing was performed by Dean Liu on 2015-10-14.

Test Result: Compliance


Test Mode: Downloading

1) Below 1GHz:

Horizontal




| Frequency (MHz) | Receiver Reading (dBμV) | Detector (PK/QP/Avg) | Correction Factor (dB/m) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------------------|----------------------|--------------------------|---------------------|----------------|-------------|
| 30.0000 | 27.94 | QP | 0.76 | 28.70 | 40.00 | 11.30 |
| 63.9500 | 37.16 | QP | -12.66 | 24.50 | 40.00 | 15.50 |
| 103.7200 | 31.49 | QP | -8.69 | 22.80 | 43.50 | 20.70 |
| 239.5200 | 35.86 | QP | -7.66 | 28.20 | 46.00 | 17.80 |
| 284.1400 | 32.13 | QP | -5.93 | 26.20 | 46.00 | 19.80 |
| 398.6000 | 42.34 | QP | -3.54 | 38.80 | 46.00 | 7.20 |

Vertical


| Frequency (MHz) | Receiver Reading (dBμV) | Detector (PK/QP/Avg) | Correction Factor (dB/m) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------------------|----------------------|--------------------------|---------------------|----------------|-------------|
| 30.0000 | 27.94 | QP | 0.76 | 28.70 | 40.00 | 11.30 |
| 63.9500 | 37.16 | QP | -12.66 | 24.50 | 40.00 | 15.50 |
| 103.7200 | 31.49 | QP | -8.69 | 22.80 | 43.50 | 20.70 |
| 239.5200 | 35.86 | QP | -7.66 | 28.20 | 46.00 | 17.80 |
| 284.1400 | 32.13 | QP | -5.93 | 26.20 | 46.00 | 19.80 |
| 398.6000 | 42.34 | QP | -3.54 | 38.80 | 46.00 | 7.20 |

2) Above 1GHz:



| Frequency (MHz) | Receiver Reading (dBμV) | Detector (PK/QP/Avg) | Correction Factor (dB/m) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------------------|----------------------|--------------------------|---------------------|----------------|-------------|
| 1082.500 | 43.91 | peak | 1.44 | 45.35 | 74.00 | 28.65 |
| 1082.500 | 31.58 | AVG | 1.44 | 33.02 | 54.00 | 20.98 |
| 1417.500 | 41.26 | peak | 1.84 | 43.10 | 74.00 | 30.90 |
| 1417.500 | 28.75 | AVG | 1.84 | 30.59 | 54.00 | 23.41 |
| 1507.500 | 41.81 | peak | 1.27 | 43.08 | 74.00 | 30.92 |
| 1507.500 | 29.20 | AVG | 1.27 | 30.47 | 54.00 | 23.53 |

Note: For above 6 GHz, all spurious emissions are 20dB below the limit or are on the system noise floor.

Vertical

| Frequency (MHz) | Receiver Reading (dBμV) | Detector (PK/QP/Avg) | Correction Factor (dB/m) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------------------|----------------------|--------------------------|---------------------|----------------|-------------|
| 1080.000 | 41.91 | peak | 1.44 | 43.35 | 74.00 | 30.65 |
| 1080.000 | 29.67 | AVG | 1.44 | 31.11 | 54.00 | 22.89 |
| 1495.000 | 41.84 | peak | 1.33 | 43.17 | 74.00 | 30.83 |
| 1495.000 | 29.29 | AVG | 1.33 | 30.62 | 54.00 | 23.38 |
| 2492.500 | 41.14 | peak | 4.95 | 46.09 | 74.00 | 27.91 |
| 2492.500 | 28.62 | AVG | 4.95 | 33.57 | 54.00 | 20.43 |

Note: For above 6 GHz, all spurious emissions are 20dB below the limit or are on the system noise floor.

*******END OF REPORT*******