#01_GSM850_GPRS (4 Tx slots)_Left Cheek_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: HSL850_140809 Medium parameters used: f = 849 MHz; σ = 0.921 S/m; ε_r = 43.064; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.63, 8.63, 8.63); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch251/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.346 W/kg

Configuration/Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.724 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.372 W/kg
SAR(1 g) = 0.300 W/kg; SAR(10 g) = 0.228 W/kg
Maximum value of SAR (measured) = 0.344 W/kg

0 dB = 0.344 W/kg = -4.63 dBW/kg

#02_GSM1900_GPRS (4 Tx slots)_Left Cheek_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: HSL1900_140809 Medium parameters used: f = 1880 MHz; σ = 1.442 S/m; ε_r = 39.566; ρ = 1000 kg/m^3
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.76, 7.76, 7.76); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch661/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.886 W/kg

Configuration/Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.391 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.08 W/kg
SAR(1 g) = 0.691 W/kg; SAR(10 g) = 0.407 W/kg
Maximum value of SAR (measured) = 0.886 W/kg

0 dB = 0.886 W/kg = -0.53 dBW/kg

#03_WCDMA II_RMC 12.2Kbps_Left Cheek_Ch9400

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: HSL1900_140809 Medium parameters used: f = 1880 MHz; σ = 1.442 S/m; ε$_r$ = 39.566; ρ = 1000 kg/m^3
Ambient Temperature：23.1 ℃；Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.76, 7.76, 7.76); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch9400/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.880 W/kg

Configuration/Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.277 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 1.13 W/kg
SAR(1 g) = 0.698 W/kg; SAR(10 g) = 0.404 W/kg
Maximum value of SAR (measured) = 0.921 W/kg

0 dB = 0.921 W/kg = -0.36 dBW/kg

#04_WLAN2.4GHz_802.11b 1Mbps_Left Cheek_Ch1

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.021

Medium: HSL_2450_140918 Medium parameters used: f = 2412 MHz; σ = 1.772 S/m; ε_r = 37.581; ρ = 1000 kg/m^3

Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3954; ConvF(7.26, 7.26, 7.26); Calibrated: 2013/11/4;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2014/5/15
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Ch1/Area Scan (71x121x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0892 W/kg

Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.114 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.128 W/kg
SAR(1 g) = 0.057 W/kg; SAR(10 g) = 0.029 W/kg
Maximum value of SAR (measured) = 0.0880 W/kg

0 dB = 0.0880 W/kg = -10.56 dBW/kg

#05_GSM850_GPRS (4 Tx slots)_Back_1cm_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: MSL850_140809 Medium parameters used: f = 849 MHz; σ = 0.999 S/m; ε_r = 54.212; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.62, 8.62, 8.62); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch251/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.00 W/kg

Configuration/Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.368 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 1.09 W/kg
SAR(1 g) = 0.855 W/kg; SAR(10 g) = 0.640 W/kg
Maximum value of SAR (measured) = 0.982 W/kg

0 dB = 0.982 W/kg = -0.08 dBW/kg

#06_GSM1900_GPRS (4 Tx slots)_Back_1cm_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: MSL1900_140810 Medium parameters used: f = 1880 MHz; σ = 1.529 S/m; ε_r = 52.502; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.19, 7.19, 7.19); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch661/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.884 W/kg

Configuration/Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.984 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.394 W/kg
Maximum value of SAR (measured) = 0.839 W/kg

0 dB = 0.839 W/kg = -0.76 dBW/kg

#07_WCDMA II_RMC 12.2Kbps_Back_1cm_Ch9400

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL1900_140810 Medium parameters used: f = 1880 MHz; σ = 1.529 S/m; ε$_r$ = 52.502; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.19, 7.19, 7.19); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch9400/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.834 W/kg

Configuration/Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.313 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.987 W/kg
SAR(1 g) = 0.619 W/kg; SAR(10 g) = 0.372 W/kg
Maximum value of SAR (measured) = 0.800 W/kg

0 dB = 0.800 W/kg = -0.97 dBW/kg

#08_WLAN2.4GHz_802.11b 1Mbps_Back_1cm_Ch1

Communication System: 802.11b; Frequency: 2412 MHz;Duty Cycle: 1:1.021
Medium: MSL_2450_140918 Medium parameters used: f = 2412 MHz; σ = 1.881 S/m; ε_r = 53.369; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3954; ConvF(7.34, 7.34, 7.34); Calibrated: 2013/11/4;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2014/5/15
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1446
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Ch1/Area Scan (71x121x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0804 W/kg

Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.568 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.105 W/kg
SAR(1 g) = 0.060 W/kg; SAR(10 g) = 0.035 W/kg
Maximum value of SAR (measured) = 0.0808 W/kg

0 dB = 0.0808 W/kg = -10.93 dBW/kg

#09_GSM850_GPRS (4 Tx slots)_Back_1cm_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: MSL850_140809 Medium parameters used: f = 849 MHz; σ = 0.999 S/m; ε_r = 54.212; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.62, 8.62, 8.62); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch251/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.00 W/kg

Configuration/Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.368 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 1.09 W/kg
SAR(1 g) = 0.855 W/kg; SAR(10 g) = 0.640 W/kg
Maximum value of SAR (measured) = 0.982 W/kg

0 dB = 0.982 W/kg = -0.08 dBW/kg

#10_GSM1900_GPRS (4 Tx slots)_Back_1cm_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: MSL1900_140810 Medium parameters used: f = 1880 MHz; σ = 1.529 S/m; ε_r = 52.502; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.19, 7.19, 7.19); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch661/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.884 W/kg

Configuration/Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.984 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.394 W/kg
Maximum value of SAR (measured) = 0.839 W/kg

0 dB = 0.839 W/kg = -0.76 dBW/kg

#11_WCDMA II_RMC 12.2Kbps_Back_1cm_Ch9400

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL1900_140810 Medium parameters used: f = 1880 MHz; σ = 1.529 S/m; ε_r = 52.502; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.19, 7.19, 7.19); Calibrated: 2013/10/15;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1388; Calibrated: 2013/10/30
- Phantom: SAM-R; Type: SAM; Serial: 1795
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Configuration/Ch9400/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.834 W/kg

Configuration/Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.313 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.987 W/kg
SAR(1 g) = 0.619 W/kg; SAR(10 g) = 0.372 W/kg
Maximum value of SAR (measured) = 0.800 W/kg

0 dB = 0.800 W/kg = -0.97 dBW/kg

#12_WLAN2.4GHz_802.11b 1Mbps_Back_1cm_Ch1

Communication System: 802.11b; Frequency: 2412 MHz;Duty Cycle: 1:1.021
Medium: MSL_2450_140918 Medium parameters used: f = 2412 MHz; σ = 1.881 S/m; ε_r = 53.369; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3954; ConvF(7.34, 7.34, 7.34); Calibrated: 2013/11/4;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2014/5/15
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1446
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Ch1/Area Scan (71x121x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0804 W/kg

Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.568 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.105 W/kg
SAR(1 g) = 0.060 W/kg; SAR(10 g) = 0.035 W/kg
Maximum value of SAR (measured) = 0.0808 W/kg

0 dB = 0.0808 W/kg = -10.93 dBW/kg