

# FCC Radio Test Report

## ***FCC ID: 2ABGP-SYMRX***

**Report No.** : TB-FCC138948  
**Applicant** : Symstar Technology(Shenzhen)Co., Ltd.  
**Equipment Under Test (EUT)**  
**EUT Name** : USB Dongle  
**Model No.** : SYM13015  
**Serial No.** : N/A  
**Brand Name** : GAMEPOP  
**Receipt Date** : 2013-11-25  
**Test Date** : 2013-11-26 to 2013-12-06  
**Issue Date** : 2013-12-09  
**Standards** : FCC Part 15, Subpart C  
**Test Method** : ANSI C63.4:2003  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** : *Wan Su*

**Approved& Authorized** : *Roy Lai*

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	4
1.4 Description of Support Units .....	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting .....	7
1.7 Test Facility.....	8
<b>2. TEST SUMMARY.....</b>	<b>9</b>
<b>3. CONDUCTED EMISSION TEST .....</b>	<b>10</b>
3.1 Test Standard and Limit.....	10
3.2 Test Setup.....	10
3.3 Test Procedure.....	10
3.4 Test Equipment Used.....	11
3.5 EUT Operating Mode .....	11
3.6 Test Data.....	11
<b>4. RADIATED EMISSION TEST .....</b>	<b>14</b>
4.1 Test Standard and Limit.....	14
4.2 Test Setup.....	15
4.3 Test Procedure.....	16
4.4 EUT Operating Condition .....	16
4.5 Test Equipment .....	17
4.6 Test Data.....	17
<b>5. RESTRICTED BANDS REQUIREMENT .....</b>	<b>26</b>
5.1 Test Standard and Limit.....	26
5.2 Test Setup.....	26
5.3 Test Procedure.....	26
5.4 EUT Operating Condition .....	27
5.5 Test Equipment .....	27
5.6 Test Data.....	28
<b>6. BANDWIDTH TEST.....</b>	<b>29</b>
6.1 Test Setup.....	29
6.2 Test Procedure.....	29
6.3 EUT Operating Condition .....	29
6.4 Test Equipment .....	29
6.5 Test Data.....	29
<b>7. ANTENNA REQUIREMENT.....</b>	<b>33</b>

7.1 Standard Requirement.....	33
7.2 Antenna Connected Construction .....	33
7.3 Result.....	33

# 1. General Information About EUT

## 1.1 Client Information

<b>Applicant</b>	:	Symstar Technology(Shenzhen)Co., Ltd.
<b>Address</b>	:	Room 204, Block C, Tsinghua Unis Inforport, Langshan RD, Hi-Tech Industrial Park(North), Nanshan District, Shenzhen, P.R.China
<b>Manufacturer</b>	:	Symstar Technology(Shenzhen)Co., Ltd.
<b>Address</b>	:	Room 204, Block C, Tsinghua Unis Inforport, Langshan RD, Hi-Tech Industrial Park(North), Nanshan District, Shenzhen, P.R.China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	USB Dongle	
<b>Models No.</b>	:	SYM13015	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:2402~2480 MHz	
	:	Number of Channels:	79 channels
	:	Out Power:	96.50 dBuV/m@3m Peak 76.40 dBuV/m@3m Avg
	:	Antenna Gain:	0 dBi
	:	Modulation Type:	GFSK
<b>Power Supply</b>	:	DC power from PC system.	
<b>Power Rating</b>	:	DC 5.0V by USB port.	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

### Note:


(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) Channel List:

Channel List		
Low Channel (MHz)	MID Channel (MHz)	HIGH Channel (MHz)
2402	2441	2480


## 1.3 Block Diagram Showing the Configuration of System Tested

## Mode 1: Normal Link



Note: During Testing the EUT was in receiving mode.

## Mode 2: TX Mode



## 1.4 Description of Support Units

Equipment Information				
Name	Model	S/N	Manufacturer	Used "√"
Printer	HP1505n	VNF3G06957	HP	√
LCD Monitor	E170Sc	----	DELL	√
PC	OPTIPLEX380	----	DELL	√

Keyboard	L100	U01C	DELL	√
Mouse	M-UARDEL7	----	DELL	√
TF Card	1GB	----	Kingston	
U Disk	1GB	----	SSK	
TV	LC24F566DC	----	KONKA	
Notebook	M490sA	----	Lenovo	√
Smart Remote Control	iM-LM-036	FCC ID: 2ABGP-SYMTX	Symstar Technology (Shenzhen) Co., Ltd.	Provide by applicant.
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	YES(2)	1.8M	
Cable 2	YES	YES(1)	2.0M	
Cable 3	YES	NO	1.5M	
Cable 4	YES	NO	1.5M	
Cable 5	YES	NO	10M	

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Link

For Radiated Test	
Final Test Mode	Description
Mode 1	Normal Link
Mode 2	TX Mode

### Note:

For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

(1)According to ANSI C63.4 standards, the measurements are performed at the highest,

middle, lowest available channels.

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered as mobile equipment; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF mode.

## 1.7 Test Facility

The tests were performed at:

Shenzhen Certification Technology Service Co., Ltd

2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road, Bao'an District, Shenzhen, 518126, China

Tel: 86-755-86375552 Fax: 86-755-26736857

At the time of testing, the Laboratory is accredited. It is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 197647.

The test report was fulfilled by Shenzhen Toby Technology Co., Ltd. Shenzhen Toby Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements results.



## 2. Test Summary

FCC Part 15 Subpart C(15.249)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.205	Restricted Bands	PASS	N/A
15.207	AC Power Conducted Emission	PASS	N/A
15.249 & 15.209	Radiated Spurious Emission	PASS	N/A
15.215(C)	20dB Bandwidth	PASS	N/A
<b>Note:</b> N/A is an abbreviation for Not Applicable.			

### 3. Conducted Emission Test

#### 3.1 Test Standard and Limit

##### 3.1.1 Test Standard

FCC Part 15.207

##### 3.1.2 Test Limit

**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 3.2 Test Setup



#### 3.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN is at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 3.4 Test Equipment Used

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	2013-08-10	2014-08-09
50ΩCoaxial Switch	Anritsu	MP59B	X10321	2013-08-10	2014-08-09
L.I.S.N	Rohde & Schwarz	ENV216	101131	2013-08-10	2014-08-09
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	2013-08-10	2014-08-09


### 3.5 EUT Operating Mode

Please refer to the description of test mode.

### 3.6 Test Data


Please refer following page.

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55 %
Terminal	Line		
Test Voltage :	AC 120 V / 60Hz		
Test Mode :	Mode 1		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1700	38.84	9.96	48.80	64.96	-16.16	QP	
2		0.1700	36.38	9.96	46.34	54.96	-8.62	AVG	
3		0.2060	38.34	10.02	48.36	63.36	-15.00	QP	
4	*	0.2060	35.37	10.02	45.39	53.36	-7.97	AVG	
5		0.5780	32.88	10.06	42.94	56.00	-13.06	QP	
6		0.5780	25.65	10.06	35.71	46.00	-10.29	AVG	
7		1.5859	27.33	10.06	37.39	56.00	-18.61	QP	
8		1.5859	22.28	10.06	32.34	46.00	-13.66	AVG	
9		2.1380	26.59	10.06	36.65	56.00	-19.35	QP	
10		2.1380	21.65	10.06	31.71	46.00	-14.29	AVG	

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55 %
Terminal	Neutral		
Test Voltage :	AC 120 V / 60Hz		
Test Mode :	Mode 1		



No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1700	36.22	9.96	46.18	64.96	-18.78	QP	
2	0.1700	33.50	9.96	43.46	54.96	-11.50	AVG	
3	0.2060	34.91	10.02	44.93	63.36	-18.43	QP	
4	0.2060	32.72	10.02	42.74	53.36	-10.62	AVG	
5	0.5700	34.73	10.05	44.78	56.00	-11.22	QP	
6 *	0.5700	27.14	10.05	37.19	46.00	-8.81	AVG	
7	1.5859	27.55	10.06	37.61	56.00	-18.39	QP	
8	1.5859	22.44	10.06	32.50	46.00	-13.50	AVG	
9	2.1420	26.85	10.06	36.91	56.00	-19.09	QP	
10	2.1420	21.99	10.06	32.05	46.00	-13.95	AVG	

## 4. Radiated Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.209

#### 4.1.2 Test Limit

**Radiated Emission Limit ( 9kHz~1000MHz)**

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**Radiated Emission Limit (Above 1000MHz)**

Frequency (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54

**Note:**


(1) The tighter limit applies at the band edges.

(2) Emission Level(dBuV/m)=20log Emission Level(Uv/m)


**Limits of radiated emission measurement (15.249)**

FCC Part 15 (15.249), Subpart C	
Limit	Frequency Range (MHz)
Field strength of fundamental 50000 $\mu$ V/m (94 dB $\mu$ V/m) @ 3 m	2400~2483.5
Field strength of fundamental 500 $\mu$ V/m (94 dB $\mu$ V/m) @ 3 m	Above 2483.5


## 4.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

#### 4.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) For the actual test configuration, please see the test setup photo.

#### 4.4 EUT Operating Condition

The EUT was set to Continual Transmitting in maximum power, and new batteries are used during testing.



## 4.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Date
Spectrum Analyzer	ROHDE& SCHWARZ	FSP30	DE25181	2012-12-31	2013-12-30
Spectrum Analyzer	Agilent	E4407B	MY49510055	2012-12-31	2013-12-30
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	101165	2012-12-31	2013-12-30
Bilog Antenna	SCHWARZBECK	VULB9168	9168-438	2013-02-12	2014-02-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA9120D	2013-02-12	2014-02-11
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170D	2013-02-12	2014-02-11
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2013-02-12	2014-02-11
Pre-amplifier	SCHWARZBECK	BBV9743	9743-019	2013-10-28	2014-10-27
Pre-amplifier	Quietek	AP-180C	CHM-0602012	2013-10-28	2014-10-27

## 4.6 Test Data

Please see the next page.


### 4.6.1 Duty Cycle

(1) During transmitting mode, one cycle time  $T_1=10.02\text{ms}$



Date: 7.DEC.2013 10:01:22

(2) One pulse time  $T_2= 0.33\text{ ms}$



Date: 7.DEC.2013 10:02:21

(3) Duty Cycle=  $T2^3/T1 \cdot 100\% = 9.88\%$

(4) Avg=Peak+20log(Duty Cycle)=Peak-20.10

#### 4.6.2 Field Strength of the Fundamental

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Test Voltage :	DC 3.0 V		
Test Mode :	TX Mode		

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBUV/m)		Limit3m (dBUV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
2402.060	V	92.47	72.37	114.00	94.00	21.53	21.63
2438.930	V	93.18	73.08	114.00	94.00	20.82	20.92
2478.950	V	93.36	73.76	114.00	94.00	20.14	20.24
--	V	--	--	114.00	94.00	--	--
--	V	--	--	114.00	94.00	--	--
2402.060	H	95.61	75.51	114.00	94.00	18.39	18.49
2438.930	H	96.34	76.24	114.00	94.00	17.66	17.76
2478.950	H	96.50	76.40	114.00	94.00	17.50	17.60
--	H	--	--	114.00	94.00	--	--
--	H	--	--	114.00	94.00	--	--


Note:

(1) Peak measuring use spectrum setting: RBW/VBW 3 MHz/3 MHz

(2) Average=Peak-20.10

### 4.6.3 Radiated Spurious Emission (Below 1 GHz)


E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Polarization	Horizontal		
Test Voltage :	DC 3.0 V		
Test Mode :	TX 2480 Mode		



Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	67.20	40.06	11.21	26.98	0.28	24.57	40.00	-15.43	Peak
2	71.83	37.76	10.51	26.77	0.19	21.69	40.00	-18.31	Peak
3	166.07	33.67	13.56	26.92	0.39	20.70	43.50	-22.80	Peak
4	199.29	39.92	9.90	26.97	0.43	23.28	43.50	-20.22	Peak
5	317.70	41.06	13.24	27.22	0.61	27.69	46.00	-18.31	Peak
6	375.94	43.01	14.35	27.35	0.96	30.97	46.00	-15.03	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Polarization	Vertical		
Test Voltage :	DC 3.0 V		
Test Mode :	TX 2480 Mode		



Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	63.76	45.68	11.98	27.43	0.24	30.47	40.00	-9.53	Peak
2	71.83	45.60	10.51	26.77	0.19	29.53	40.00	-10.47	Peak
3	166.07	36.92	13.56	26.92	0.39	23.95	43.50	-19.55	Peak
4	197.89	40.05	10.01	26.97	0.48	23.57	43.50	-19.93	Peak
5	499.42	37.51	16.51	27.62	0.81	27.21	46.00	-18.79	Peak
6	965.54	33.37	22.19	27.60	1.97	29.93	54.00	-24.07	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

#### 4.6.4 Radiated Spurious Emission (Above 1 GHz)

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Test Voltage :	DC 5.0 V		
Test Mode :	TX 2402 MHz		

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBUV/m)		Limit3m (dBUV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4804.110	V	49.77	29.67	74.00	54.00	24.23	24.33
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
4804.110	H	52.63	32.53	74.00	54.00	21.37	21.47
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--

**Note:**

(1) Peak measuring use spectrum setting: RBW/VBW 1 MHz/1 MHz

(2) Average=Peak-20.10

(3) The emission levels of other frequencies are very lower than the limit and not show in the test report.

E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Test Voltage :	DC 5.0 V		
Test Mode :	TX 2441 MHz		

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBUV/m)		Limit3m (dBUV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4882.070	V	48.75	28.65	74.00	54.00	25.25	25.35
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
4882.070	H	52.79	32.69	74.00	54.00	21.21	21.31
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--

**Note:**

(1) Peak measuring use spectrum setting: RBW/VBW 1 MHz/1 MHz

(2) Average=Peak-20.10

(3) The emission levels of other frequencies are very lower than the limit and not show in the test report.



E.U.T :	USB Dongle	Model Name :	SYM13015
Temperature :	23°C	Relative Humidity :	55%
Test Voltage :	DC 5.0 V		
Test Mode :	TX 2480 MHz		

Freq. (MHz)	Ant. Pol. H/V	Emission Level (dBUV/m)		Limit3m (dBUV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4960.090	V	51.68	31.58	74.00	54.00	22.32	22.42
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
--	V	--	--	74.00	54.00	--	--
4960.090	H	53.75	33.65	74.00	54.00	20.25	20.35
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--
--	H	--	--	74.00	54.00	--	--

**Note:**

(1) Peak measuring use spectrum setting: RBW/VBW 1 MHz/1 MHz

(2) Average=Peak-20.10

(3) The emission levels of other frequencies are very lower than the limit and not show in the test report.

## 5. Restricted Bands Requirement

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard


FCC Part 15.209

FCC Part 15.205

#### 5.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3 M)
2310~2390	Attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation
2483.5~2500	

### 5.2 Test Setup



### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector

mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) For the actual test configuration, please see the test setup photo.

## 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 5.5 Test Equipment

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Date
Spectrum Analyzer	ROHDE& SCHWARZ	FSP30	DE25181	2012-12-31	2013-12-30
Spectrum Analyzer	Agilent	E4407B	MY49510055	2012-12-31	2013-12-30
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	101165	2012-12-31	2013-12-30
Bilog Antenna	SCHWARZBECK	VULB9168	9168-438	2013-02-12	2014-02-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA9120D	2013-02-12	2014-02-11
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170D	2013-02-12	2014-02-11
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2013-02-12	2014-02-11
Pre-amplifier	SCHWARZBECK	BBV9743	9743-019	2013-10-28	2014-10-27
Pre-amplifier	Quietek	AP-180C	CHM-0602012	2013-10-28	2014-10-27

## 5.6 Test Data

### Band Edge (Radiated Emissions)

Spectrum Detector: PK & AVG      Test Date : December 07, 2013  
Temperature : 28 °C      Humidity : 55 %

TX 2402 MHz					
Frequency MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PEAK	AV	PEAK	AV
2390.0	H	50.31	30.21	74.00	54.00
2390.0	V	48.40	28.30	74.00	54.00


TX 2480 MHz					
Frequency MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PEAK	AV	PEAK	AV
2483.5	H	53.56	33.46	74.00	54.00
2483.5	V	51.72	31.62	74.00	54.00

**Note:**

- (1) Peak measuring use spectrum setting: RBW/VBW 1 MHz/1 MHz
- (2) Average=Peak-20.10

## 6. Bandwidth Test

### 6.1 Test Setup



### 6.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Bandwidth: RBW=100 kHz, VBW=300kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.

### 6.3 EUT Operating Condition

The EUT was set to continuously transmitting for the Bandwidth Test.


### 6.4 Test Equipment

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Date
Spectrum Analyzer	ROHDE& SCHWARZ	FSP30	DE25181	2012-12-31	2013-12-30

### 6.5 Test Data

Low Channel Frequency (MHz)	20dB Bandwidth (MHz)
2402	2.280


## 2402 MHz



Date: 7.DEC.2013 09:41:58

MID Channel Frequency (MHz)	20dB Bandwidth (MHz)
2441	2.460


## 2441 MHz



Date: 7.DEC.2013 09:24:08

HIGH Channel Frequency (MHz)	20dB Bandwidth (MHz)
2480	2.920

## 2480 MHz



Date: 7.DEC.2013 09:34:20



## 7. Antenna Requirement

### 7.1 Standard Requirement

#### 7.1.1 Standard

FCC Part 15.203

#### 7.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 7.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 7.3 Result

The EUT antenna is a Printed Antenna. It complies with the standard requirement.