


AppendixA: DTS Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_BT4.0	Ant1	2402	0.728	2401.688	2402.416	0.5	PASS
		2440	0.760	2439.664	2440.424	0.5	PASS
		2480	0.736	2479.684	2480.420	0.5	PASS








Ke Mei Ou Lab Corp.

AppendixB: Occupied Channel Bandwidth

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_BT4.0	Ant1	2402	1.096	0.000	0.000		PASS
		2440	1.088	0.000	0.000		PASS
		2480	1.084	0.000	0.000		PASS








AppendixC: Maximum conducted output power

TestMode	Antenna	Channel	Result	Limit	Verdict
		2402	-3.96	<=30	PASS
BLE_BT4.0	Ant1	2440	-2.76	<=30	PASS
		2480	-1.45	<=30	PASS








Ke Mei Ou Lab Corp.

AppendixD: Maximum power spectral density

TestMode	Antenna	Channel	Result	Limit	Verdict
BLE_BT4.0		2402	-14.1	<=8	PASS
	Ant1	2440	-13	<=8	PASS
		2480	-11.4	<=8	PASS








AppendixE:Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel	Result	Limit	Verdict
BLE_BT4.0	Ant1	Low	2402	-5.44	-43.02	<=-25.44	PASS
		High	2480	-2.44	-46.08	<=-22.44	PASS








Ke Mei Ou Lab Corp.


AppendixF:Conducted SpuriousEmission

TestMode	Antenna	Channel	FreqRange	RefLevel	Result	Limit	Verdict
		2402	Reference	-5.34	-5.34		PASS
			2402 30~1000		-47.77	<=-25.34	PASS
	Ant1		1000~26500	1000~26500	-30.57	<=-25.34	PASS
		2440	Reference		-4.01		PASS
BLE_BT4.0			30~1000	30~1000	-48.14	<=-24.01	PASS
			1000~26500	1000~26500	-30.12	<=-24.01	PASS
		2480	Reference	-2.43	-2.43		PASS
			30~1000	30~1000	-47.41	<=-22.43	PASS
			1000~26500	1000~26500	-31	<=-22.43	PASS
















TestMode	Antenna	Channel	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_BT4.0	Ant1	2402	0.35	0.50	70.88
		2440	0.35	0.50	70.75
		2480	0.35	0.50	70.75



