

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Bluetooth portable speaker

MODEL No.:

**NB520, NB530, NB550, NB560, NB570, NB580, NB590, NB11, NB12, NB13,
NB15, NB16, NB17, NB18, NB19, NB20, NB21, NB22, NB23, NB25,
AIRYBOX-NB16**

FCC ID: 2ABLQ-NOGO

Trademark: 

REPORT NO: ES131114104E2

ISSUE DATE: December 16, 2013

Prepared for

NOGO INTERNATIONAL CO., LTD.

**The 4th F.of Bldg.1, Huangtian industrial zone, Xixiang town, Bao'an district,
Shenzhen, China**

Prepared by

SHENZHEN EMTEK CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,

Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE


Applicant:	NOGO INTERNATIONAL CO.,LTD. The 4th F.of Bldg.1, Huangtian industrial zone, Xixiang town, Bao'an district, Shenzhen, China
Manufacturer:	NOGO INTERNATIONAL CO.,LTD. The 4th F.of Bldg.1, Huangtian industrial zone, Xixiang town, Bao'an district, Shenzhen, China
Product Description:	Bluetooth portable speaker
Model Number:	NB520, NB530, NB550, NB560, NB570, NB580, NB590, NB11, NB12, NB13, NB15, NB16, NB17, NB18, NB19, NB20, NB21, NB22, NB23, NB25, AIRYBOX-NB16 (Note: These models are identical in circuitry and electrical, mechanical and physical construction; the only differences are the appearance and model no. for trading purpose. We prepare NB520 for test. and the worst result recorded in the report.)
File Number:	ES131114104E2


We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : December 10, 2013 to December 15, 2013

Prepared by : 
Joe Xia/Editor

Reviewer : 
June Xie/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager

Table of Contents

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION.....	5
1.2 RELATED SUBMITTAL(S) / GRANT(S).....	5
1.3 TEST METHODOLOGY	6
1.4 SPECIAL ACCESSORIES	6
1.5 EQUIPMENT MODIFICATIONS.....	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE.....	7
2.3 TEST PROCEDURE.....	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES.....	9
4. SUMMARY OF TEST RESULTS	10
5. CONDUCTED EMISSIONS TEST.....	11
5.1 MEASUREMENT PROCEDURE.....	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	11
5.3 MEASUREMENT EQUIPMENT USED.....	11
5.4 CONDUCTED EMISSION LIMIT	11
5.5 MEASUREMENT RESULT	11
6. RADIATED EMISSION TEST.....	14
6.1 MEASUREMENT PROCEDURE.....	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3 MEASUREMENT EQUIPMENT USED.....	15
6.4 RADIATED EMISSION LIMIT	15
6.5 MEASUREMENT RESULT	17
7. 6DB BANDWIDTH TEST	23
7.1 MEASUREMENT PROCEDURE.....	23
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	23
7.3 MEASUREMENT EQUIPMENT USED.....	23
7.4 MEASUREMENT RESULTS	23
8. MAXIMUM PEAK OUTPUT POWER TEST	26
8.1 MEASUREMENT PROCEDURE.....	26
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	26
8.3 MEASUREMENT EQUIPMENT USED.....	26
8.4 PEAK POWER OUTPUT LIMIT.....	26
8.5 MEASUREMENT RESULTS	26
9. BAND EDGE TEST.....	27
9.1 MEASUREMENT PROCEDURE.....	27
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	27

9.3	MEASUREMENT EQUIPMENT USED.....	27
9.4	MEASUREMENT RESULTS	27
10.	POWER DENSITY	29
10.1	TEST EQUIPMENT	29
10.2	MEASURING INSTRUMENTS AND SETTING	29
10.3	TEST PROCEDURES	29
10.4	BLOCK DIAGRAM OF TEST SETUP	29
10.5	LIMIT	29
10.6	TEST RESULT.....	30
11	ANTENNA PORT EMISSION	32
11.1	TEST EQUIPMENT	32
11.2	MEASURING INSTRUMENTS AND SETTING	32
11.3	TEST PROCEDURES.....	32
11.4	BLOCK DIAGRAM OF TEST SETUP.....	32
11.5	TEST RESULT.....	32
12.	ANTENNA APPLICATION	36
12.1	ANTENNA REQUIREMENT	36
12.2	RESULT	36

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 2402-2480MHz
- B). Modulation: BT4.0 DSS: GFSK, 1/4 Π -DQPSK, 8DPSK; BT4.0 DTS: GFSK
- C). Number of Channel: BT4.0 DSS: 79 channels; BT4.0 DTS: 40 channels
- D). Channel space: BT4.0 DSS: 1MHz; BT4.0 DTS: 2MHz
- E). RF Output Power: BT4.0 DSS: 8.37dBm ; BT4.0 DTS:8.84dBm
- F). BIT Rate of Transmission: 1Mbps, 2Mbps, 3Mbps
- G). Antenna Type: PCB antenna
- H). Antenna GAIN: 1.20dBi
- I). Power Supply: 3.7V (Internal rechargeable lithium battery) or DC 5V from USB

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	15	2430	29	2458
2	2404	16	2432	30	2460
3	2406	17	2434	31	2462
4	2408	18	2436	32	2464
5	2410	19	2438	33	2466
6	2412	20	2440	34	2468
7	2414	21	2442	35	2470
8	2416	22	2444	36	2472
9	2418	23	2446	37	2474
10	2420	24	2448	38	2476
11	2422	25	2450	39	2478
12	2424	26	2452	40	2480
13	2426	27	2454		
14	2428	28	2456		

Note:

1. This device is Bluetooth portable speaker included BT4.0 transceiver function.
2. Test of channel was included the lowest middle and highest frequency in lowest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: 2ABLQ-NOGO filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.3 Test Methodology

All the test program has follow FCC new test procedure KDB558074 D01 v03r01, Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2009). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29
 The certificate is valid until 2016.10.28
 The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
 The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
 The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, April 17, 2013
 The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
 The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD.
 Site Location : Bldg 69, Majialong Industry Zone,
 Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions


The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Bluetooth portable speaker		NB520	2ABLQ-NOGO	N/A	<i>EUT</i>
2.	Adapter	archos	HNEB050150UX	N/A	N/A	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is an Internet Tablet and powered by host equipment; these is Digital Transmission system (DTS) and with modulation GFSK.

The mode is used: **Transmitting mode**

1. For lowest channel : 2402MHz (Channel 01)
2. For middle channel : 2440MHz (Channel 20)
3. For highest channel: 2480MHz (Channel 40)

4. Summary of Test Results


FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2013	05/28/2014
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2013	05/28/2014
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2013	05/28/2014
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2013	05/28/2014
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2013	05/28/2014

5.4 Conducted Emission Limit

Conducted Emission

Frequency(MHz)

Quasi-peak

Average

0.15-0.5

66-56

56-46

0.5-5.0

56

46

5.0-30.0

60


50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

PASS



Site Conduction #1

Phase: **L1**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz


Humidity: 53 %

Mode: BT ON

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1650	53.86	0.00	53.86	65.21	-11.35	QP	
2		0.1650	32.16	0.00	32.16	55.21	-23.05	AVG	
3		0.2700	51.04	0.00	51.04	61.12	-10.08	QP	
4		0.2700	38.46	0.00	38.46	51.12	-12.66	AVG	
5	*	0.5400	49.38	0.00	49.38	56.00	-6.62	QP	
6		0.5400	35.99	0.00	35.99	46.00	-10.01	AVG	
7		2.1400	48.18	0.00	48.18	56.00	-7.82	QP	
8		2.1400	37.39	0.00	37.39	46.00	-8.61	AVG	
9		4.6700	43.76	0.00	43.76	56.00	-12.24	QP	
10		4.6700	25.33	0.00	25.33	46.00	-20.67	AVG	
11		12.5500	34.64	0.00	34.64	60.00	-25.36	QP	
12		12.5500	27.92	0.00	27.92	50.00	-22.08	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: HE



Site Conduction #1

Phase: **N**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 53 %

Mode: BT ON

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1758	48.59	0.00	48.59	64.68	-16.09	QP	
2		0.1758	29.47	0.00	29.47	54.68	-25.21	AVG	
3		0.2700	48.39	0.00	48.39	61.12	-12.73	QP	
4		0.2700	37.02	0.00	37.02	51.12	-14.10	AVG	
5		0.5400	48.62	0.00	48.62	56.00	-7.38	QP	
6		0.5400	37.36	0.00	37.36	46.00	-8.64	AVG	
7	*	2.1400	51.52	0.00	51.52	56.00	-4.48	QP	
8		2.1400	39.97	0.00	39.97	46.00	-6.03	AVG	
9		4.4700	38.30	0.00	38.30	56.00	-17.70	QP	
10		4.4700	31.21	0.00	31.21	46.00	-14.79	AVG	
11		21.0500	38.93	0.00	38.93	60.00	-21.07	QP	
12		21.0500	33.45	0.00	33.45	50.00	-16.55	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: HE

6. Radiated Emission Test


6.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.


For emissions measurement set the bandwidth of the Spectrum's RBW at 1MHz above 1GHz and RBW 100 KHz below 1GHz.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/29/2013	05/28/2014
Pre-Amplifier	HP	8447D	2944A07999	05/29/2013	05/28/2014
Bilog Antenna	Schwarzbeck	VULB9163	142	05/14/2013	05/13/2014
Loop Antenna	ARA	PLA-1030/B	1029	05/14/2013	05/13/2014
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/14/2013	05/13/2014
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/14/2013	05/13/2014
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2013	05/28/2014
Cable	Rosenberger	N/A	FP2RX2	05/29/2013	05/28/2014
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2013	05/28/2014
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2013	05/28/2014

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result

Operation Mode: TX Mode Test Date : December 10, 2013
Frequency Range: 0.009~30MHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Operation Mode: TX Channel 01 Test Date : December 10, 2013
Frequency Range: 30~1000MHz Temperature : 26℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
336.23	V	33.61	46.00	-12.39	QP
359.55	V	37.65	46.00	-8.35	QP
455.93	V	42.35	46.00	-3.65	QP
552.31	V	35.73	46.00	-10.27	QP
648.69	V	35.56	46.00	-10.44	QP
696.88	V	34.43	46.00	-11.57	QP
311.36	H	40.16	46.00	-5.84	QP
336.23	H	42.21	46.00	-3.79	QP
359.55	H	39.47	46.00	-6.53	QP
407.74	H	40.22	46.00	-5.78	QP
455.93	H	42.66	46.00	-3.34	QP
600.50	H	39.15	46.00	-6.85	QP

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode:	TX Channel 20	Test Date :	December 10, 2013
Frequency Range:	30~1000MHz	Temperature :	26°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
336.23	V	32.45	46.00	-13.55	QP
359.55	V	38.92	46.00	-7.08	QP
455.93	V	41.21	46.00	-4.79	QP
552.31	V	34.56	46.00	-11.44	QP
648.69	V	36.80	46.00	-9.20	QP
696.88	V	33.28	46.00	-12.72	QP
311.36	H	39.05	46.00	-6.95	QP
336.23	H	42.33	46.00	-3.67	QP
359.55	H	38.31	46.00	-7.69	QP
407.74	H	41.36	46.00	-4.64	QP
455.93	H	41.51	46.00	-4.49	QP
600.50	H	38.03	46.00	-7.97	QP

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode:	TX Channel 40	Test Date :	December 10, 2013
Frequency Range:	30~1000MHz	Temperature :	26℃
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
336.23	V	31.28	46.00	-14.72	QP
359.55	V	40.16	46.00	-5.84	QP
455.93	V	40.06	46.00	-5.94	QP
552.31	V	33.45	46.00	-12.55	QP
648.69	V	37.92	46.00	-8.08	QP
696.88	V	32.12	46.00	-13.88	QP
311.36	H	40.19	46.00	-5.81	QP
336.23	H	42.18	46.00	-3.82	QP
359.55	H	37.19	46.00	-8.81	QP
407.74	H	42.39	46.00	-3.61	QP
455.93	H	40.35	46.00	-5.65	QP
600.50	H	39.13	46.00	-6.87	QP

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT stood on the table position is the worst case result in the report.

Operation Mode: TX Channel 01 Test Date : December 10, 2013
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4881.51	V	61.56	47.71	74.00	54.00	-12.44	-6.29
7322.16	V	54.12	43.74	74.00	54.00	-19.88	-10.26
10836.00	V	53.43	35.52	74.00	54.00	-20.57	-18.48
13996.29	V	53.57	35.44	74.00	54.00	-20.43	-18.56
15165.23	V	52.57	34.44	74.00	54.00	-21.43	-19.56
15794.24	V	52.42	34.31	74.00	54.00	-21.58	-19.69
4881.42	H	65.29	45.70	74.00	54.00	-8.71	-8.30
7322.02	H	62.93	47.77	74.00	54.00	-11.07	-6.23
10917.67	H	53.13	34.69	74.00	54.00	-20.87	-19.31
12958.42	H	50.93	33.45	74.00	54.00	-23.07	-20.55
14484.11	H	50.42	32.46	74.00	54.00	-23.58	-21.54
15331.10	H	49.65	32.29	74.00	54.00	-24.35	-21.71

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:** (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: TX Channel 20 Test Date : December 10, 2013
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4880.90	V	61.56	47.81	74.00	54.00	-12.44	-6.19
7320.59	V	58.14	45.79	74.00	54.00	-15.86	-8.21
9760.59	V	53.41	35.68	74.00	54.00	-20.59	-18.32
13996.25	V	53.59	35.46	74.00	54.00	-20.41	-18.54
15165.31	V	52.47	34.47	74.00	54.00	-21.53	-19.53
15791.88	V	52.32	34.33	74.00	54.00	-21.68	-19.67
4880.93	H	65.21	49.66	74.00	54.00	-8.79	-4.34
7320.64	H	62.81	47.76	74.00	54.00	-11.19	-6.24
9760.23	H	53.17	34.70	74.00	54.00	-20.83	-19.30
12960.91	H	50.98	33.44	74.00	54.00	-23.02	-20.56
14484.13	H	50.37	32.49	74.00	54.00	-23.63	-21.51
15328.60	H	49.68	32.31	74.00	54.00	-24.32	-21.69

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:** (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: TX Channel 40 Test Date : December 10, 2013
Frequency Range: 1GHz~25GHz Temperature : 26°C
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4959.43	V	61.92	47.98	74.00	54.00	-12.08	-6.02
7441.52	V	58.72	45.02	74.00	54.00	-15.28	-8.98
8572.28	V	51.69	33.31	74.00	54.00	-22.31	-20.69
10642.71	V	49.14	31.61	74.00	54.00	-24.86	-22.39
14432.10	V	52.69	35.00	74.00	54.00	-21.31	-19.00
15819.00	V	50.48	32.81	74.00	54.00	-23.52	-21.19
4959.40	H	59.57	45.27	74.00	54.00	-14.43	-8.73
7441.52	H	58.02	42.98	74.00	54.00	-15.98	-11.02
8708.50	H	51.56	33.57	74.00	54.00	-22.44	-20.43
10996.90	H	47.28	33.98	74.00	54.00	-26.72	-20.02
12476.83	H	51.71	37.53	74.00	54.00	-22.29	-16.47
15312.89	H	51.27	39.40	74.00	54.00	-22.73	-14.60

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


7. 6dB Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in BLE mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014



7.4 Measurement Results

6 Bandwidth Test Data Chart:
Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	December 12, 2013
Test By:	Jack	Temperature :	26℃
Test Result:	PASS	Humidity :	60 %

Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (kHz)
01	2402	725.172	>500
20	2440	715.913	>500
40	2480	717.395	>500





8. Maximum Peak Output Power Test

8.1 Measurement Procedure

The maximum peak conducted output power can be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast, average-responding diode type sensor.

- a. The Transmitter output (antenna port) was connected to the power meter.
- b. Turn on the EUT and power meter and then record the peak power value.
- c. Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/29/2013	05/28/2014
Power sensor	MA2411B	0738172	05/29/2013	05/28/2014

8.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

8.5 Measurement Results

Spectrum Detector:	PK	Test Date :	December 12, 2013
Test By:	Jack	Temperature :	26°C
Test Result:	PASS	Humidity :	60 %

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
01	2402	8.04	1W(30dBm)	PASS
20	2440	8.84	1W(30dBm)	PASS
40	2480	8.76	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Spectrum Detector:	PK/AV	Test Date :	December 12, 2013
Test By:	Jack	Temperature :	26°C
Test channel:	01	Humidity :	60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2322	H	55.00	39.90	74	54
2357	V	55.22	40.02	74	54

Spectrum Detector:	PK/AV	Test Date :	December 12, 2013
Test By:	Jack	Temperature :	26°C
Test channel:	40	Humidity :	60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2484.91	H	54.86	40.70	74	54
2491.27	V	55.05	40.41	74	54

Spectrum Detector: PK/AV Test Date : December 12, 2013
Test By: Jack Temperature : 26°C
test mode: Hopping mode Humidity : 60 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.0	H	55.10	40.05	74	54
2390.0	V	55.05	40.40	74	54
2483.5	H	55.16	39.99	74	54
2483.5	V	54.37	40.69	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	$3\text{kHz} \leq \text{RBW} \leq 100\text{KHz}$
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

10.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the $\text{RBW} \geq 3 \text{ kHz}$. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

10.4 Block Diagram of Test Setup




10.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

10.6 Test Result

Spectrum Detector: PK Test Date : December 15, 2013
 Test By: Jack Temperature : 26°C
 Test Result: PASS Humidity : 60 %
 Operation Mode: BLE

Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
01	-6.67	<8dBm	PASS
20	-5.76	<8dBm	PASS
40	-5.91	<8dBm	PASS





11 Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2013	05/28/2014

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.



11.4 Block Diagram of Test setup





11.5 Test Result

PASS.



Low Channel 01



Mid Channel 20



High Channel 40



12. Antenna Application

12.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna is PCB Antenna. The antenna's gain is 1.20 dBi and meets the requirement.