BSC-401N

Page1. MCU

Page2. MEMORY

Page3. ETHERNET

Page4. AUDIO

Page5. CAMERA

Page6. UART


Page7. IN/OUT


Page8. POWER


저항, 콘덴서 기본 Size : 1608 저항, 콘덴서 별도 표기 Size 참조.




NO C	HANGE	DATE	SIGN			
1 Br	ian 2	2013 02 0)4			
MODEL	_ BS(C-401(IS	SC-401)			
PART	0.	INFO				
DATE	2012	2/03/12				
DESIG	SN .					
EXAMI	NE					
APPRO	VAL					
DRAWI	NG NO	IHD-A4C	C-120312-00			
File	BSC-	401	DSN			
IDT INC						












0 CHAN	IGE	D	ATE		SIGN
Brian					
MODEL				SC-	401)
PART	4.	AUD	010		
DATE	201	2/03	/ 12		
DESIGN					
FXAMINE					


APPROVAL


DRAWING NO IHD-A4C-120312-00
File BSC-401____.DSN


IDT INC




CAM CONNECTOR











NO	CHANGE	DATE	SIGN
1	Brian	2013 02	04

MODEL BSC-401(ISC-401)

PART 8. POWER

DATE 2012/03/12

DESIGN

EXAMINE

APPROVAL

TTTOVAL

DRAWING NO IHD-A4C-120312-00

File BSC-401____.DSN

IDT INC

