

## FCC PART 15.247



## TEST REPORT

For

### Posh Mobile Limited

1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

**FCC ID: 2ABN6L500**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Ultra 5.0 LTE
<b>Test Engineer:</b>	Lion Xiao 
<b>Report Number:</b>	RDG150525002-00B
<b>Report Date:</b>	2015-06-10
<b>Reviewed By:</b>	Sula Huang  RF Leader
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EQUIPMENT MODIFICATIONS .....	5
EUT EXERCISE SOFTWARE .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093- RF EXPOSURE .....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY .....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE .....	12
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY .....	13
TEST DATA .....	13
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>18</b>
APPLICABLE STANDARD .....	18
MEASUREMENT UNCERTAINTY .....	18
EUT SETUP .....	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	19
TEST PROCEDURE .....	19
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST RESULTS SUMMARY .....	20
TEST DATA .....	20
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA .....	31
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>39</b>

APPLICABLE STANDARD .....	39
TEST PROCEDURE .....	39
TEST EQUIPMENT LIST AND DETAILS.....	39
TEST DATA .....	39
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>41</b>
APPLICABLE STANDARD .....	41
TEST PROCEDURE .....	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA .....	41
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>46</b>
APPLICABLE STANDARD .....	46
TEST PROCEDURE .....	46
TEST EQUIPMENT LIST AND DETAILS.....	46
TEST DATA .....	46
<b>DECLARATION LETTER .....</b>	<b>54</b>

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

The *Posh Mobile Limited*'s product, model number: *L500A (FCC ID: 2ABN6L500)* (the "EUT") in this report was a *Ultra 5.0 LTE*, which was measured approximately: 14.2 cm (L) x 7.3 cm (W) x 1.0 cm (H), rated input voltage: DC 3.8V rechargeable Li-ion battery or DC5V charging from adapter.

*Note: The series product, model L500A, L500B are electrically identical, the difference between them is just the model name, we selected L500A for fully testing, the detail was explained in the attached declaration letter.*

*All measurement and test data in this report was gathered from production sample serial number: 150525002 (Assigned by BACL, Dongguan). The EUT was received on 2015-05-26.*

### Objective

This report is prepared on behalf of *Posh Mobile Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABN6L500.  
FCC Part 15C DSS submissions with FCC ID: 2ABN6L500.  
FCC Part 22H, 24E, 27 PCE submissions with FCC ID: 2ABN6L500.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.  
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### Equipment Modifications

No modification was made to the EUT tested.

## EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting as following table:

Test Mode	Test Software Version	Engineering Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	11	10	9
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	12	11	10
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	12	11	10
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	BLE	N/A	N/A	N/A


## Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

## External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	yes	no	1.0	USB Port of Laptop	EUT
Earphone Cable	no	no	1.2	Audio Port of EUT	Earphone

## Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance



---

## **FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**

---

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

The SAR data please refer to the SAR report, report No.:RDG150525002-20.

FINAL

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has one integral antenna arrangement for WiFi, which was permanently attached and the antenna gain is 1.6 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cispr}$

Measurement	$U_{cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2014-06-09	2015-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**0.8 dB at 0.499611 MHz** in the **Line** conducted mode for BLE.


**Test Data****Environmental Conditions**

<b>Temperature:</b>	26.8°C
<b>Relative Humidity:</b>	56%
<b>ATM Pressure:</b>	99.7 kPa

*The testing was performed by Lion Xiao on 2015-05-27*

Test Mode: Transmitting (Wi-Fi)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.507637	54.7	9.000	L1	10.1	1.3*	56.0	Compliance
0.536756	55.1	9.000	L1	10.1	0.9*	56.0	Compliance
0.619536	54.9	9.000	L1	10.3	1.1*	56.0	Compliance
0.930151	52.9	9.000	L1	10.4	3.1*	56.0	Compliance
1.056628	53.2	9.000	L1	10.4	2.8*	56.0	Compliance
1.117238	54.7	9.000	L1	10.4	1.3*	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.499611	44.0	9.000	L1	10.1	2.0*	46.0	Compliance
0.554139	44.6	9.000	L1	10.1	1.4*	46.0	Compliance
0.604902	44.9	9.000	L1	10.3	2.1*	46.0	Compliance
0.930151	39.3	9.000	L1	10.4	6.7	46.0	Compliance
1.117238	38.9	9.000	L1	10.4	7.1	46.0	Compliance
1.171949	38.1	9.000	L1	10.4	7.9	46.0	Compliance

\*within measurement uncertainty!

**AC120 V, 60 Hz, Neutral:**


Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.499611	55.0	9.000	N	10.1	1.0*	56.0	Compliance
0.558572	54.7	9.000	N	10.1	1.3*	56.0	Compliance
0.590613	54.8	9.000	N	10.2	1.2*	56.0	Compliance
1.144267	54.6	9.000	N	10.4	1.4*	56.0	Compliance
1.269154	50.2	9.000	N	10.4	5.8	56.0	Compliance
2.307034	47.8	9.000	N	10.4	8.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.503608	43.7	9.000	N	10.1	2.3*	46.0	Compliance
0.545378	44.9	9.000	N	10.1	1.1*	46.0	Compliance
0.604902	44.4	9.000	N	10.3	1.6*	46.0	Compliance
0.967957	43.5	9.000	N	10.4	2.5*	46.0	Compliance
1.239175	39.0	9.000	N	10.4	7.0	46.0	Compliance
1.310256	40.4	9.000	N	10.4	5.6	46.0	Compliance

\*within measurement uncertainty!

Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.402900	54.5	9.000	L1	10.2	3.2*	57.8	Compliance
0.499611	54.7	9.000	L1	10.1	1.3*	56.0	Compliance
0.536756	54.5	9.000	L1	10.1	1.5*	56.0	Compliance
0.619536	53.9	9.000	L1	10.3	2.1*	56.0	Compliance
1.117238	54.9	9.000	L1	10.4	1.1*	56.0	Compliance
1.299858	48.5	9.000	L1	10.4	7.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.499611	45.2	9.000	L1	10.1	0.8*	46.0	Compliance
0.554139	44.6	9.000	L1	10.1	1.4*	46.0	Compliance
0.609741	44.9	9.000	L1	10.3	1.1*	46.0	Compliance
0.930151	41.5	9.000	L1	10.4	4.5	46.0	Compliance
1.117238	40.1	9.000	L1	10.4	5.9	46.0	Compliance
1.171949	36.8	9.000	L1	10.4	9.2	46.0	Compliance

\*within measurement uncertainty!



**AC120 V, 60 Hz, Neutral:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.567545	54.9	9.000	N	10.2	1.1*	56.0	Compliance
0.595338	54.5	9.000	N	10.2	1.5*	56.0	Compliance
0.805868	52.1	9.000	N	10.4	3.9	56.0	Compliance
0.991374	51.4	9.000	N	10.4	4.6	56.0	Compliance
1.126176	54.7	9.000	N	10.4	1.3*	56.0	Compliance
1.331304	49.8	9.000	N	10.4	6.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.381043	39.6	9.000	N	10.3	8.6	48.3	Compliance
0.511698	41.6	9.000	N	10.1	4.4	46.0	Compliance
0.549741	44.5	9.000	N	10.1	1.5*	46.0	Compliance
0.604902	45.0	9.000	N	10.3	1.0*	46.0	Compliance
0.805868	42.7	9.000	N	10.4	3.3	46.0	Compliance
1.310256	40.5	9.000	N	10.4	5.5	46.0	Compliance

*\*within measurement uncertainty!*

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

### Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cisp}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cisp}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cisp})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cisp})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of  $U_{cisp}$

Measurement	$U_{cisp}$
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

### EUT Setup

Below 1GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

**Test Procedure**

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	E4440A	SG43360054	2014-12-04	2015-12-04
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2014-09-06	2015-09-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**4.17 dB at 2483.5 MHz in the Vertical polarization for WiFi Mode (802.11g)**

## Test Data

### Environmental Conditions

Temperature:	24.1 °C
Relative Humidity:	60 %
ATM Pressure:	99.8 kPa

\* The testing was performed by Lion Xiao on 2015-05-28.

Test Mode: Transmitting

## 802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	69.93	PK	H	25.67	3.68	0.00	99.28	N/A	N/A
2412	63.16	AV	H	25.67	3.68	0.00	92.51	N/A	N/A
2412	71.14	PK	V	25.67	3.68	0.00	100.49	N/A	N/A
2412	65.93	AV	V	25.67	3.68	0.00	95.28	N/A	N/A
2390	30.45	PK	V	25.61	3.63	0.00	59.69	74.00	14.31
2390	15.36	AV	V	25.61	3.63	0.00	44.60	54.00	9.40
4824	35.25	PK	V	30.64	5.03	27.41	43.51	74.00	30.49
4824	23.14	AV	V	30.64	5.03	27.41	31.40	54.00	22.60
7236	32.25	PK	V	34.17	6.65	25.90	47.17	74.00	26.83
7236	19.63	AV	V	34.17	6.65	25.90	34.55	54.00	19.45
9648	31.88	PK	V	36.06	8.55	27.46	49.03	74.00	24.97
9648	18.62	AV	V	36.06	8.55	27.46	35.77	54.00	18.23
2929	36.34	PK	V	27.02	6.32	27.54	42.14	74.00	31.86
2929	23.24	AV	V	27.02	6.32	27.54	29.04	54.00	24.96
240.1	41.4	QP	V	12.22	1.86	21.48	34.00	46.00	12.00
Middle Channel: 2437 MHz									
2437	69.98	PK	H	25.74	3.75	0.00	99.47	N/A	N/A
2437	63.21	AV	H	25.74	3.75	0.00	92.70	N/A	N/A
2437	71.16	PK	V	25.74	3.75	0.00	100.65	N/A	N/A
2437	66.05	AV	V	25.74	3.75	0.00	95.54	N/A	N/A
4874	35.38	PK	V	30.77	5.14	27.42	43.87	74.00	30.13
4874	23.27	AV	V	30.77	5.14	27.42	31.76	54.00	22.24
7311	32.3	PK	V	34.35	6.74	25.88	47.51	74.00	26.49
7311	19.71	AV	V	34.35	6.74	25.88	34.92	54.00	19.08
9748	31.95	PK	V	36.30	8.61	27.24	49.62	74.00	24.38
9748	18.8	AV	V	36.30	8.61	27.24	36.47	54.00	17.53
3131	36.41	PK	V	27.62	6.93	27.43	43.53	74.00	30.47
3131	23.46	AV	V	27.62	6.93	27.43	30.58	54.00	23.42
3190	35.27	PK	V	27.81	6.26	27.38	41.96	74.00	32.04
3190	22.13	AV	V	27.81	6.26	27.38	28.82	54.00	25.18
240.1	41.56	QP	V	12.22	1.86	21.48	34.16	46.00	11.84
High Channel: 2462 MHz									
2462	69.21	PK	H	25.80	3.75	0.00	98.76	N/A	N/A
2462	64.32	AV	H	25.80	3.75	0.00	93.87	N/A	N/A
2462	71.32	PK	V	25.80	3.75	0.00	100.87	N/A	N/A
2462	66.1	AV	V	25.80	3.75	0.00	95.65	N/A	N/A
2483.5	30.14	PK	V	25.86	3.67	0.00	59.67	74.00	14.33
2483.5	15.14	AV	V	25.86	3.67	0.00	44.67	54.00	9.33
4924	35.5	PK	V	30.90	5.34	27.43	44.31	74.00	29.69
4924	23.28	AV	V	30.90	5.34	27.43	32.09	54.00	21.91
7386	32.47	PK	V	34.53	6.83	25.86	47.97	74.00	26.03
7386	19.89	AV	V	34.53	6.83	25.86	35.39	54.00	18.61
9848	32.18	PK	V	36.54	8.66	26.94	50.44	74.00	23.56
9848	18.96	AV	V	36.54	8.66	26.94	37.22	54.00	16.78
3131	36.66	PK	V	27.62	6.93	27.43	43.78	74.00	30.22
3131	23.6	AV	V	27.62	6.93	27.43	30.72	54.00	23.28
240.1	41.35	QP	V	12.22	1.86	21.48	33.95	46.00	12.05

## 802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	67.88	PK	H	25.67	3.68	0.00	97.23	N/A	N/A
2412	56.52	AV	H	25.67	3.68	0.00	85.87	N/A	N/A
2412	70.13	PK	V	25.67	3.68	0.00	99.48	N/A	N/A
2412	57.75	AV	V	25.67	3.68	0.00	87.10	N/A	N/A
2390	37.36	PK	V	25.61	3.63	0.00	66.60	74.00	7.40
2390	19.24	AV	V	25.61	3.63	0.00	48.48	54.00	5.52
4824	35.01	PK	V	30.64	5.03	27.41	43.27	74.00	30.73
4824	23.13	AV	V	30.64	5.03	27.41	31.39	54.00	22.61
7236	32.07	PK	V	34.17	6.65	25.90	46.99	74.00	27.01
7236	19.42	AV	V	34.17	6.65	25.90	34.34	54.00	19.66
9648	31.67	PK	V	36.06	8.55	27.46	48.82	74.00	25.18
9648	18.44	AV	V	36.06	8.55	27.46	35.59	54.00	18.41
2929	36.02	PK	V	27.02	6.32	27.54	41.82	74.00	32.18
2929	22.99	AV	V	27.02	6.32	27.54	28.79	54.00	25.21
240.1	41.08	QP	V	12.22	1.86	21.48	33.68	46.00	12.32
Middle Channel: 2437 MHz									
2437	67.99	PK	H	25.74	3.75	0.00	97.48	N/A	N/A
2437	56.57	AV	H	25.74	3.75	0.00	86.06	N/A	N/A
2437	70.25	PK	V	25.74	3.75	0.00	99.74	N/A	N/A
2437	57.78	AV	V	25.74	3.75	0.00	87.27	N/A	N/A
4874	35.14	PK	V	30.77	5.14	27.42	43.63	74.00	30.37
4874	23.25	AV	V	30.77	5.14	27.42	31.74	54.00	22.26
7311	32.12	PK	V	34.35	6.74	25.88	47.33	74.00	26.67
7311	19.71	AV	V	34.35	6.74	25.88	34.92	54.00	19.08
9748	31.9	PK	V	36.30	8.61	27.24	49.57	74.00	24.43
9748	18.54	AV	V	36.30	8.61	27.24	36.21	54.00	17.79
2950	36.2	PK	V	27.07	6.61	27.54	42.34	74.00	31.66
2950	23.26	AV	V	27.07	6.61	27.54	29.40	54.00	24.60
3610	35.01	PK	V	29.04	4.61	27.28	41.38	74.00	32.62
3610	21.97	AV	V	29.04	4.61	27.28	28.34	54.00	25.66
240.1	41.11	QP	V	12.22	1.86	21.48	33.71	46.00	12.29
High Channel: 2462 MHz									
2462	68.25	PK	H	25.80	3.75	0.00	97.80	N/A	N/A
2462	56.69	AV	H	25.80	3.75	0.00	86.24	N/A	N/A
2462	70.45	PK	V	25.80	3.75	0.00	100.00	N/A	N/A
2462	57.99	AV	V	25.80	3.75	0.00	87.54	N/A	N/A
2483.5	39.36	PK	V	25.86	3.67	0.00	68.89	74.00	5.11
2483.5	20.3	AV	V	25.86	3.67	0.00	49.83	54.00	4.17*
4924	35.21	PK	V	30.90	5.34	27.43	44.02	74.00	29.98
4924	23.39	AV	V	30.90	5.34	27.43	32.20	54.00	21.80
7386	32.25	PK	V	34.53	6.83	25.86	47.75	74.00	26.25
7386	19.85	AV	V	34.53	6.83	25.86	35.35	54.00	18.65
9848	32.18	PK	V	36.54	8.66	26.94	50.44	74.00	23.56
9848	18.58	AV	V	36.54	8.66	26.94	36.84	54.00	17.16
2950	36.3	PK	V	27.07	6.61	27.54	42.44	74.00	31.56
2950	23.31	AV	V	27.07	6.61	27.54	29.45	54.00	24.55
240.1	41.02	QP	V	12.22	1.86	21.48	33.62	46.00	12.38

\*within measurement uncertainty!

## 802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	66.03	PK	H	25.67	3.68	0.00	95.38	N/A	N/A
2412	54.89	AV	H	25.67	3.68	0.00	84.24	N/A	N/A
2412	68.83	PK	V	25.67	3.68	0.00	98.18	N/A	N/A
2412	57.24	AV	V	25.67	3.68	0.00	86.59	N/A	N/A
2390	40.11	PK	V	25.61	3.63	0.00	69.35	74.00	4.65
2390	18.34	AV	V	25.61	3.63	0.00	47.58	54.00	6.42
4824	34.88	PK	V	30.64	5.03	27.41	43.14	74.00	30.86
4824	22.96	AV	V	30.64	5.03	27.41	31.22	54.00	22.78
7236	31.98	PK	V	34.17	6.65	25.90	46.90	74.00	27.10
7236	19.54	AV	V	34.17	6.65	25.90	34.46	54.00	19.54
9648	31.37	PK	V	36.06	8.55	27.46	48.52	74.00	25.48
9648	18.24	AV	V	36.06	8.55	27.46	35.39	54.00	18.61
2929	35.84	PK	V	27.02	6.32	27.54	41.64	74.00	32.36
2929	22.99	AV	V	27.02	6.32	27.54	28.79	54.00	25.21
240.1	41.79	QP	V	12.22	1.86	21.48	34.39	46.00	11.61
Middle Channel: 2437 MHz									
2437	66.17	PK	H	25.74	3.75	0.00	95.66	N/A	N/A
2437	55.19	AV	H	25.74	3.75	0.00	84.68	N/A	N/A
2437	68.83	PK	V	25.74	3.75	0.00	98.32	N/A	N/A
2437	57.73	AV	V	25.74	3.75	0.00	87.22	N/A	N/A
4874	34.99	PK	V	30.77	5.14	27.42	43.48	74.00	30.52
4874	23.23	AV	V	30.77	5.14	27.42	31.72	54.00	22.28
7311	32.1	PK	V	34.35	6.74	25.88	47.31	74.00	26.69
7311	19.65	AV	V	34.35	6.74	25.88	34.86	54.00	19.14
9748	31.63	PK	V	36.30	8.61	27.24	49.30	74.00	24.70
9748	18.49	AV	V	36.30	8.61	27.24	36.16	54.00	17.84
2950	36.09	PK	V	27.07	6.61	27.54	42.23	74.00	31.77
2950	23.05	AV	V	27.07	6.61	27.54	29.19	54.00	24.81
3610	34.86	PK	V	29.04	4.61	27.28	41.23	74.00	32.77
3610	21.88	AV	V	29.04	4.61	27.28	28.25	54.00	25.75
240.1	41.36	QP	V	12.22	1.86	21.48	33.96	46.00	12.04
High Channel: 2462 MHz									
2462	66.34	PK	H	25.80	3.75	0.00	95.89	N/A	N/A
2462	55.42	AV	H	25.80	3.75	0.00	84.97	N/A	N/A
2462	68.94	PK	V	25.80	3.75	0.00	98.49	N/A	N/A
2462	57.78	AV	V	25.80	3.75	0.00	87.33	N/A	N/A
2483.5	40.21	PK	V	25.86	3.67	0.00	69.74	74.00	4.26*
2483.5	19.36	AV	V	25.86	3.67	0.00	48.89	54.00	5.11
4924	35.12	PK	V	30.90	5.34	27.43	43.93	74.00	30.07
4924	23.29	AV	V	30.90	5.34	27.43	32.10	54.00	21.90
7386	32.35	PK	V	34.53	6.83	25.86	47.85	74.00	26.15
7386	19.86	AV	V	34.53	6.83	25.86	35.36	54.00	18.64
9848	31.78	PK	V	36.54	8.66	26.94	50.04	74.00	23.96
9848	18.64	AV	V	36.54	8.66	26.94	36.90	54.00	17.10
2950	36.33	PK	V	27.07	6.61	27.54	42.47	74.00	31.53
2950	23.11	AV	V	27.07	6.61	27.54	29.25	54.00	24.75
240.1	41.5	QP	V	12.22	1.86	21.48	34.10	46.00	11.90

\*within measurement uncertainty!




## BLE Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	62.85	PK	H	25.65	3.66	0.00	92.16	N/A	N/A
2402	50.44	AV	H	25.65	3.66	0.00	79.75	N/A	N/A
2402	59.62	PK	V	25.65	3.66	0.00	88.93	N/A	N/A
2402	47.08	AV	V	25.65	3.66	0.00	76.39	N/A	N/A
2390	26.37	PK	H	25.61	3.63	0.00	55.61	74.00	18.39
2390	14.02	AV	H	25.61	3.63	0.00	43.26	54.00	10.74
4804	32.28	PK	H	30.59	5.06	27.41	40.52	74.00	33.48
4804	19.42	AV	H	30.59	5.06	27.41	27.66	54.00	26.34
7206	30.95	PK	H	34.09	6.61	25.91	45.74	74.00	28.26
7206	18.51	AV	H	34.09	6.61	25.91	33.30	54.00	20.70
9608	35.41	PK	H	35.96	8.53	27.55	52.35	74.00	21.65
9608	21.44	AV	H	35.96	8.53	27.55	38.38	54.00	15.62
1364	34.47	PK	H	23.25	3.16	26.97	33.91	74.00	40.09
1364	21.73	AV	H	23.25	3.16	26.97	21.17	54.00	32.83
241.1	42.3	QP	H	12.23	1.86	21.48	34.91	46.00	11.09
Middle Channel: 2440 MHz									
2440	63.31	PK	H	25.74	3.76	0.00	92.81	N/A	N/A
2440	51.1	AV	H	25.74	3.76	0.00	80.60	N/A	N/A
2440	60.12	PK	V	25.74	3.76	0.00	89.62	N/A	N/A
2440	48.72	AV	V	25.74	3.76	0.00	78.22	N/A	N/A
4880	32.42	PK	H	30.79	5.18	27.42	40.97	74.00	33.03
4880	19.69	AV	H	30.79	5.18	27.42	28.24	54.00	25.76
7320	31.2	PK	H	34.37	6.75	25.88	46.44	74.00	27.56
7320	18.66	AV	H	34.37	6.75	25.88	33.90	54.00	20.10
9760	35.56	PK	H	36.32	8.62	27.21	53.29	74.00	20.71
9760	21.53	AV	H	36.32	8.62	27.21	39.26	54.00	14.74
4365	34.62	PK	H	29.83	5.00	26.92	42.53	74.00	31.47
4365	21.93	AV	H	29.83	5.00	26.92	29.84	54.00	24.16
1364	34.26	PK	H	23.25	3.16	26.97	33.70	74.00	40.30
1364	22.17	AV	H	23.25	3.16	26.97	21.61	54.00	32.39
241.1	42.36	QP	H	12.23	1.86	21.48	34.97	46.00	11.03
High Channel: 2480 MHz									
2480	62.93	PK	H	25.85	3.68	0.00	92.46	N/A	N/A
2480	50.69	AV	H	25.85	3.68	0.00	80.22	N/A	N/A
2480	60.7	PK	V	25.85	3.68	0.00	90.23	N/A	N/A
2480	48.16	AV	V	25.85	3.68	0.00	77.69	N/A	N/A
2483.5	26.26	PK	H	25.86	3.67	0.00	55.79	74.00	18.21
2483.5	14.23	AV	H	25.86	3.67	0.00	43.76	54.00	10.24
4960	32.64	PK	H	31.00	5.34	27.43	41.55	74.00	32.45
4960	19.78	AV	H	31.00	5.34	27.43	28.69	54.00	25.31
7440	31.21	PK	H	34.66	6.89	25.97	46.79	74.00	27.21
7440	18.88	AV	H	34.66	6.89	25.97	34.46	54.00	19.54
9920	35.82	PK	H	36.71	8.71	26.66	54.58	74.00	19.42
9920	21.74	AV	H	36.71	8.71	26.66	40.50	54.00	13.50
2312	34.63	PK	H	25.41	3.43	27.31	36.16	74.00	37.84
2312	22.12	AV	H	25.41	3.43	27.31	23.65	54.00	30.35
241.1	42.21	QP	H	12.23	1.86	21.48	34.82	46.00	11.18




# Conducted Spurious Emissions at Antenna Port


## 802.11b Low Channel




## 802.11b Middle Channel




### 802.11b High Channel




### 802.11g Low Channel



### 802.11g Middle Channel




### 802.11g High Channel




### 802.11n ht20 Low Channel

Fundamental




### 802.11n ht20 Middle Channel


Fundamental




### 802.11n ht20 High Channel




### BLE Low Channel



### BLE Middle Channel



### BLE High Channel



## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause8.1 Option 1:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	59 %
ATM Pressure:	99.8 kPa


\* The testing was performed by Lion Xiao on 2015-05-28.

Test Mode: Transmitting



Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	7.695	$\geq 0.5$
	Middle	2437	7.776	$\geq 0.5$
	High	2462	7.776	$\geq 0.5$
802.11g	Low	2412	16.353	$\geq 0.5$
	Middle	2437	15.593	$\geq 0.5$
	High	2462	16.513	$\geq 0.5$
802.11n20	Low	2412	17.585	$\geq 0.5$
	Middle	2437	17.715	$\geq 0.5$
	High	2462	17.635	$\geq 0.5$
BLE	Low	2402	0.739	$\geq 0.5$
	Middle	2440	0.739	$\geq 0.5$
	High	2480	0.745	$\geq 0.5$


### 802.11b Low Channel






**802.11b Middle Channel****802.11b High Channel**


### 802.11g Low Channel




### 802.11g Middle Channel




### 802.11g High Channel




### 802.11n ht20 Low Channel




## 802.11n ht20 Middle Channel




## 802.11n ht20 High Channel




### BLE Low Channel



### BLE Middle Channel



### BLE High Channel



## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2014-11-03	2015-11-03

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	59 %
ATM Pressure:	99.8 kPa

\* The testing was performed by Lion Xiao on 2015-05-28.

*Test Mode: Transmitting (Wi-Fi)*

*Test Result: Compliant. Please refer to the following table.*

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	13.69	30	PASS
	Middle	2437	13.33	30	PASS
	High	2462	13.76	30	PASS
802.11g	Low	2412	17.93	30	PASS
	Middle	2437	17.78	30	PASS
	High	2462	17.62	30	PASS
802.11n20	Low	2412	17.83	30	PASS
	Middle	2437	18.11	30	PASS
	High	2462	17.90	30	PASS

Test mode	Channel	Frequency	Max Conducted Average Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	12.65	30	PASS
	Middle	2437	12.49	30	PASS
	High	2462	12.69	30	PASS
802.11g	Low	2412	12.62	30	PASS
	Middle	2437	12.49	30	PASS
	High	2462	12.31	30	PASS
802.11n20	Low	2412	12.42	30	PASS
	Middle	2437	12.67	30	PASS
	High	2462	12.46	30	PASS

*Test Mode: Transmitting (BLE)*

*Test Result: Compliant. Please refer to the following table.*

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
BLE	Low	2402	-5.70	30	PASS
	Middle	2440	-4.62	30	PASS
	High	2480	-4.61	30	PASS



## FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


Temperature:	25.7°C
Relative Humidity:	59 %
ATM Pressure:	99.8 kPa

\* The testing was performed by Lion Xiao on 2015-05-28.


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


### 802.11b: Band Edge, Left Side




### 802.11b: Band Edge, Right Side




### 802.11g: Band Edge, Left Side




### 802.11g: Band Edge, Right Side





### 802.11n ht20 Band Edge, Left Side



### 802.11n ht20 Band Edge, Right Side





## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause10.2:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	25.7 °C
Relative Humidity:	59 %
ATM Pressure:	99.8 kPa


\* The testing was performed by Lion Xiao on 2015-05-28.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-11.13	$\leq 8$
	Middle	2437	-11.58	$\leq 8$
	High	2462	-11.21	$\leq 8$
802.11g	Low	2412	-15.13	$\leq 8$
	Middle	2437	-15.32	$\leq 8$
	High	2462	-15.57	$\leq 8$
802.11n20	Low	2412	-16.48	$\leq 8$
	Middle	2437	-16.19	$\leq 8$
	High	2462	-16.43	$\leq 8$
BLE	Low	2402	-20.97	$\leq 8$
	Middle	2440	-19.98	$\leq 8$
	High	2480	-19.94	$\leq 8$


### Power Spectral Density, 802.11b Low Channel



### Power Spectral Density, 802.11b Middle Channel




### Power Spectral Density, 802.11b High Channel







### Power Spectral Density, 802.11g Low Channel




### Power Spectral Density, 802.11g Middle Channel




### Power Spectral Density, 802.11g High Channel




### Power Spectral Density, 802.11n ht20 Low Channel




### Power Spectral Density, 802.11n ht20 Middle Channel




### Power Spectral Density, 802.11n ht20 High Channel




### Power Spectral Density, BLE Low Channel



### Power Spectral Density, BLE Middle Channel



### Power Spectral Density, BLE High Channel



## DECLARATION LETTER

### Declaration of Alteration

To Whom It May Concern,

We, Posh Mobile Limited, hereby declare that there are some differences between our Multiple Models and testing products. Details as below:

(This is for your reference only.)

Products Description	Name	Ultra 5.0 LTE		
	Brand	POSH		
	Manufacturer	Shenzhen Posh Mobile Limited		
	Project No.	RDG150525002, RDG150525002-20		
Differences Description				
Testing Products	Multiple Models		Differences Items	Details
L500A	L500B		Model name	They are same motherboard, and just have the different model name.

Notes: Testing products-the products tested by BACL

Multiple Model- have the same or similar appearance, structure, PCB, Material and function to the testing products, and only are different for little parameters.

Besides the differences in the table above, we declare the products are identical. We guarantee all the information provided above is true, and notice that we'll bear all the consequences caused by any false information or concealing.

Best Regards,

Signature:

Print Name: K.N. Chong

Title: Manager

