

FCC PART 22H, PART 24E
FCC PART 27
MEASUREMENT AND TEST REPORT

For

Posh Mobile Limited

1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

FCC ID: 2ABN6S410

Report Type: Original Report	Product Type: Kick Lite
Test Engineer: Lion Xiao	<i>Lion Xiao</i>
Report Number: RDG150715004-00C	
Report Date: 2015-07-24	
Reviewed By: Sula Huang RF Leader	<i>Sula Huang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) & § 27.50 - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH.....	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26
FCC §2.1051, §22.917(A) & §24.238(A) & §27.53- SPURIOUS EMISSIONS AT ANTENNA TERMINALS...33	
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §2.1053, §22.917 & §24.238 & §27.53- SPURIOUS RADIATED EMISSIONS	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST EQUIPMENT LIST AND DETAILS.....	50
TEST DATA	51
FCC §22.917(A) & §24.238(A) & §27.53(H)- BAND EDGES.....	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA	54
FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY.....	66
APPLICABLE STANDARD	66

TEST PROCEDURE66

TEST EQUIPMENT LIST AND DETAILS.....67

TEST DATA67

DECLARATHION LETTER.....74

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Posh Mobile Limited*'s product, model number: *S410A (FCC ID: 2ABN6S410)* (the "EUT") in this report was a *Kick Lite*, which was measured approximately: 12.35 cm (L) x 6.3 cm (W) x 1.25 cm (H), rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information:

Part No.: C01-S410

Input: AC 100-240V 50/60Hz 0.15A

Output: DC5V, 0.75A

Note: The series product, model S410A, S410B are electrically identical, the difference between them is just the model name, we selected S410A for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 150715004 (Assigned by BACL, Dongguan). The EUT was received on 2015-07-16.

Objective

This report is prepared on behalf of *Posh Mobile Limited* in accordance with: Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules. Part 2, Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABN6S410

FCC Part 15C DSS submissions with FCC ID: 2ABN6S410

FCC Part 15C DTS submissions with FCC ID: 2ABN6S410

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	109038
N/A	ANTENNA	N/A	N/A

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c); §27.50	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a); §27.53	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a); §27.53	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235; §27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG150715004-20.

FINAL

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E, Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) & § 27.50 - RF OUTPUT POWER**Applicable Standard**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

According to FCC §2.1046 and §27.50 (d), (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test Procedure**GSM**

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + only

MS Signal

> 33 dBm for GSM 850

> 30 dBm for GSM 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

TCH > choose desired test channel

Hopping > Off

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDM A General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	Ahs= β_{hs}/β_c	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI's	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.											

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

Radiated method:

ANSI/TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
Giga	Signal Generator	1026	320408	2015-05-09	2016-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2012-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.5 °C
Relative Humidity:	57%
ATM Pressure:	100kPa

The testing was performed by Lion Xiao on 2015-07-21.

Conducted Power**Cellular Band (Part 22H) & PCS Band (Part 24E)**

Band	Channel No.	Peak Output Power (dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	32.40	32.15	31.09	30.14	29.05
	190	32.60	32.41	31.30	30.22	29.14
	251	32.70	32.54	31.43	30.37	29.31
PCS	512	30.00	29.89	28.75	27.70	26.67
	661	29.60	29.56	28.33	27.30	26.21
	810	29.20	29.11	28.02	26.97	25.93

WCDMA Band II (PART 24E)

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99	1	22.53	2.48	22.68	2.56	22.52	2.24
HSDPA	1	21.49	2.45	21.62	2.51	21.44	2.29
	2	21.43	2.49	21.58	2.57	21.40	2.25
	3	21.40	2.46	21.66	2.50	21.48	2.31
	4	21.44	2.41	21.61	2.59	21.41	2.27
HSUPA	1	21.47	2.43	21.67	2.53	21.5	2.21
	2	21.42	2.40	21.63	2.58	21.47	2.28
	3	21.48	2.37	21.68	2.52	21.42	2.20
	4	21.45	2.44	21.62	2.48	21.49	2.29
DC-HSDPA	5	21.39	2.42	21.60	2.55	21.43	2.23
	1	21.32	2.49	21.55	2.59	21.39	2.26
	2	21.34	2.52	21.59	2.51	21.34	2.32
	3	21.37	2.50	21.52	2.57	21.30	2.30
	4	21.30	2.48	21.54	2.50	21.35	2.25
HSPA+	1	21.22	2.43	21.48	2.54	21.25	2.21

WCDMA Band IV (PART 27)

Mode	3GPP Sub Test	Conducted Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99	1	22.83	2.64	22.96	2.52	22.90	2.48
HSDPA	1	21.81	2.67	21.92	2.56	21.87	2.49
	2	21.79	2.61	21.95	2.53	21.84	2.43
	3	21.83	2.65	21.90	2.55	21.81	2.47
	4	21.80	2.69	21.94	2.58	21.88	2.51
HSUPA	1	21.78	2.62	21.85	2.61	21.85	2.54
	2	21.74	2.68	21.88	2.59	21.8	2.50
	3	21.79	2.64	21.83	2.63	21.83	2.53
	4	21.72	2.70	21.87	2.60	21.79	2.46
	5	21.75	2.66	21.82	2.54	21.82	2.52
DC-HSDPA	1	21.66	2.63	21.75	2.57	21.77	2.48
	2	21.61	2.69	21.70	2.51	21.73	2.42
	3	21.68	2.73	21.76	2.54	21.78	2.45
	4	21.65	2.70	21.72	2.50	21.70	2.40
HSPA+	1	21.53	2.64	21.61	2.55	21.64	2.43


WCDMA Band V (PART 22H)

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99	1	22.58	2.80	22.67	2.64	22.29	2.72
HSDPA	1	21.62	2.84	21.5	2.60	21.24	2.7
	2	21.59	2.87	21.52	2.65	21.20	2.79
	3	21.61	2.85	21.57	2.69	21.27	2.74
	4	21.57	2.89	21.53	2.63	21.25	2.78
DC-HSDPA	1	21.44	2.93	21.41	2.65	21.13	2.85
	2	21.49	2.89	21.35	2.58	21.10	2.80
	3	21.46	2.92	21.31	2.61	21.16	2.83
	4	21.41	2.87	21.34	2.67	21.11	2.81
HSUPA	1	21.54	2.81	21.46	2.61	21.22	2.75
	2	21.59	2.84	21.43	2.68	21.20	2.71
	3	21.52	2.86	21.48	2.62	21.17	2.76
	4	21.58	2.90	21.42	2.66	21.14	2.73
	5	21.50	2.97	21.47	2.71	21.19	2.79
HSPA+	1	21.39	2.83	21.26	2.65	21.02	2.78

Note: peak-to-average ratio (PAR) <13 dB.


Peak-to-average ratio (PAR)
WCDMA Band II (PART 24E)

Low Channel




Date: 21.JUL.2015 11:37:28

Middle Channel



Date: 21.JUL.2015 11:37:55


High Channel



Date: 21.JUL.2015 11:38:13


WCDMA Band IV (PART 27)

Low Channel




Date: 21.JUL.2015 11:40:23

Middle Channel



Date: 21.JUL.2015 11:40:10


High Channel



Date: 21.JUL.2015 11:40:36


WCDMA Band V (PART 22H)

Low Channel




Date: 21.JUL.2015 11:41:29

Middle Channel



Date: 21.JUL.2015 11:42:26

High Channel



Date: 21.JUL.2015 11:43:02

ERP & EIRP

PART 22H

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Middle Channel								
836.600	H	100.78	25.9	0.0	1.0	24.9	38.5	13.6
836.600	V	104.70	32.9	0.0	1.0	31.9	38.5	6.6
WCDMA Band V Middle Channel								
836.600	H	90.92	16.0	0.0	1.0	15.0	38.5	23.5
836.600	V	94.07	22.3	0.0	1.0	21.3	38.5	17.2

PART 24E

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
PCS 1900 Middle Channel								
1880.000	H	87.34	15.7	11.7	1.4	26.0	33.0	7.0
1880.000	V	90.07	18.6	11.7	1.4	28.9	33.0	4.1
WCDMA Band II Middle Channel								
1880.000	H	81.13	9.5	11.7	1.4	19.8	33.0	13.2
1880.000	V	83.26	11.8	11.7	1.4	22.1	33.0	10.9

PART 27

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band IV Middle Channel								
1732.600	H	82.88	9.9	10.9	1.4	19.4	30.0	10.6
1732.600	V	85.56	12.2	10.9	1.4	21.7	30.0	8.3

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level


FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH**Applicable Standard**

FCC §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	59%
ATM Pressure:	99.5 kPa



The testing was performed by Lion Xiao on 2015-07-20.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Band	Channel No.	Mode	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
Cellular	190	GSM	246	317
PCS	661	PCS	244	315
WCDMA Band II	9400	Rel 99	4188	4770
	9400	HSDPA	4208	4790
	9400	HSUPA	4208	4770
WCDMA Band V	4183	Rel 99	4168	4790
	4183	HSDPA	4188	4810
	4183	HSUPA	4188	4770
WCDMA Band IV	1413	Rel 99	4188	4770
	1413	HSDPA	4188	4790
	1413	HSUPA	4188	4790


[illegible]

GMSK PCS Band**REL99 Band II**


HSDPA Band II




HSUPA Band II





REL99 Band V



HSDPA Band V





Ref Lvl 35 dBm Delta 1 [T1] 1.21 dB RBW 100 kHz RF Att 30 dB
 35 dBm 4.78957916 MHz VBW 300 kHz SWT 5 ms Unit dBm

15 dB Offset

D1 17.28 dBm

D2 -8.62 dBm

1MAX

1MA

Center 1.7326 GHz 1 MHz/ Span 10 MHz

Date: 20.JUL.2015 15:33:11

Ref Lvl 35 dBm Delta 1 [T1] 1.78 dB RBW 100 kHz RF Att 30 dB
 35 dBm 4.78957916 MHz SWT 5 ms Unit dBm

15 dB Offset

D1 17.93 dBm

1MAX

D2 -8.07 dBm

▼1 [T1] -10.51 dBm

▲1 [T1] 1.73020521 GHz 1.78 dB

OPB 4.78957916 MHz 4.18837675 MHz

▼2 [T1] 8.49 dBm

▼T2 [T1] 1.73050581 GHz 8.80 dBm

1MA

Center 1.7326 GHz 1 MHz/ Span 10 MHz

Date: 20.JUL.2015 15:34:05

FCC §2.1051, §22.917(a) & §24.238(a) & §27.53- SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) , §24.238(a) and §27.53.

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data



Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	59 %
ATM Pressure:	99.5 kPa



The testing was performed by Lion Xiao on 2015-07-20.


Please refer to the following plots.

GSM850_Middle Channel





PCS 1900_ Middle Channel








REL99 Band II_ Middle Channel




Fundamental






HSDPA Band II _Middle Channel







HSUPA Band II_Middle Channel









REL99 Band V_ Middle Channel



HSDPA Band V_ Middle Channel






HSUPA Band V_ Middle Channel




WCDMA Band IV



REL99 Band IV_ Middle Channel








HSDPA Band IV _Middle Channel





HSUPA Band IV _ Middle Channel





FCC §2.1053, §22.917 & §24.238 & §27.53- SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917, § 24.238 and § 27.53.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
Giga	Signal Generator	1026	320408	2015-05-09	2016-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2012-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.8 °C
Relative Humidity:	49%
ATM Pressure:	99.5 kPa

The testing was performed by Lion Xiao on 2015-07-20.

EUT Operation Mode: Transmitting

Cellular Band (PART 22H)**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:836.600 MHz								
1673.200	H	48.29	-52.8	10.6	1.5	-43.7	-13.0	30.7
1673.200	V	50.81	-50.6	10.6	1.5	-41.5	-13.0	28.5
2509.800	H	56.80	-41.2	13.1	2.8	-30.9	-13.0	17.9
2509.800	V	58.64	-38.5	13.1	2.8	-28.2	-13.0	15.2

For below 1GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

WCDMA Band V

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:836.600 MHz								
1673.200	H	41.09	-60	10.6	1.5	-50.9	-13.0	37.9
1673.200	V	44.23	-57.1	10.6	1.5	-48.0	-13.0	35.0

For below 1GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

PCS Band(PART 24E)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:1880.000 MHz								
3760.000	H	47.82	-46.5	13.8	2.9	-35.6	-13.0	22.6
3760.000	V	50.58	-42.5	13.8	2.9	-31.6	-13.0	18.6

For below 1GHz, all spurious emissions are 20dB below the limit or are on the system noise floor level.

WCDMA Band II

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:1880.000 MHz								
3760.000	H	44.28	-50	13.8	2.9	-39.1	-13.0	26.1
3760.000	V	47.18	-45.9	13.8	2.9	-35.0	-13.0	22.0

WCDMA Band IV(PART 27)

WCDMA Band IV (FDD)								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:1732.600 MHz								
3465.200	H	41.36	-55.6	13.9	1.9	-43.6	-13.0	30.6
3465.200	V	43.92	-52.2	13.9	1.9	-40.2	-13.0	27.2

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §22.917(a) & §24.238(a) & §27.53(h)- BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), AWS emission limits—(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**



Temperature:	27.1 °C
Relative Humidity:	59 %
ATM Pressure:	99.5 kPa

The testing was performed by Lion Xiao on 2015-7-20.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following plots.


ENV

GSM 850, Left Band Edge**GSM 850, Right Band Edge**


GSM 1900, Left Band Edge




GSM 1900, Right Band Edge





REL99 Band II, Left Band Edge




REL99 Band II, Right Band Edge



HSDPA Band II, Left Band Edge**HSDPA Band II, Right Band Edge**


HSUPA Band II, Left Band Edge




HSUPA Band II, Right Band Edge




REL99 Band V, Left Band Edge




REL99 Band V Right Band Edge




HSDPA Band V, Left Band Edge




HSDPA Band V, Right Band Edge




HSUPA Band V, Left Band Edge




HSUPA Band V, Right Band Edge





REL99 Band IV, Left Band Edge




REL99 Band IV Right Band Edge




HSDPA Band IV, Left Band Edge**HSDPA Band IV, Right Band Edge**

HSUPA Band IV, Left Band Edge



HSUPA Band IV, Right Band Edge



FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235, §27.54

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-3	2014-08-01	2015-08-01
R&S	Universal Radio Communication Tester	CMU200	109 038	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	59%
ATM Pressure:	99.5 kPa

The testing was performed by Lion Xiao on 2015-7-20.

Cellular Band (Part 22H)

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	31	0.037	2.5
-20	3.7	34	0.041	2.5
-10	3.7	39	0.047	2.5
0	3.7	30	0.036	2.5
10	3.7	37	0.044	2.5
20	3.7	35	0.042	2.5
30	3.7	32	0.038	2.5
40	3.7	38	0.045	2.5
50	3.7	30	0.036	2.5
20	3.5	36	0.043	2.5
20	4.2	33	0.039	2.5

WCDMA Band V: Re199

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	56	0.067	2.5
-20	3.7	51	0.061	2.5
-10	3.7	58	0.069	2.5
0	3.7	53	0.063	2.5
10	3.7	50	0.060	2.5
20	3.7	58	0.069	2.5
30	3.7	52	0.062	2.5
40	3.7	55	0.066	2.5
50	3.7	57	0.068	2.5
20	3.5	22	0.026	2.5
20	4.2	56	0.067	2.5

WCDMA Band V: HSDPA

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-46	-0.055	2.5
-20	3.7	-49	-0.059	2.5
-10	3.7	-42	-0.050	2.5
0	3.7	-47	-0.056	2.5
10	3.7	-45	-0.054	2.5
20	3.7	-41	-0.049	2.5
30	3.7	-48	-0.057	2.5
40	3.7	-43	-0.051	2.5
50	3.7	-40	-0.048	2.5
20	3.5	-46	-0.055	2.5
20	4.2	-42	-0.050	2.5

WCDMA Band V: HSUPA

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-51	-0.061	2.5
-20	3.7	-55	-0.066	2.5
-10	3.7	-53	-0.063	2.5
0	3.7	56	0.067	2.5
10	3.7	-59	-0.071	2.5
20	3.7	-52	-0.062	2.5
30	3.7	-57	-0.068	2.5
40	3.7	-53	-0.063	2.5
50	3.7	-58	-0.069	2.5
20	3.5	-50	-0.060	2.5
20	4.2	-54	-0.065	2.5

PCS Band (Part 24E)

GMSK, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	64	0.034	Pass
-20	3.7	69	0.037	Pass
-10	3.7	62	0.033	Pass
0	3.7	67	0.036	Pass
10	3.7	60	0.032	Pass
20	3.7	65	0.035	Pass
30	3.7	69	0.037	Pass
40	3.7	63	0.034	Pass
50	3.7	68	0.036	Pass
20	3.5	64	0.034	Pass
20	4.2	60	0.032	Pass

WCDMA Band II: Re199

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-27	-0.014	Pass
-20	3.7	-22	-0.012	Pass
-10	3.7	-29	-0.015	Pass
0	3.7	-20	-0.011	Pass
10	3.7	-25	-0.013	Pass
20	3.7	-28	-0.015	Pass
30	3.7	-21	-0.011	Pass
40	3.7	-24	-0.013	Pass
50	3.7	-28	-0.015	Pass
20	3.5	-26	-0.014	Pass
20	4.2	-23	-0.012	Pass

WCDMA Band II: HSDPA

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	24	0.013	Pass
-20	3.7	29	0.015	Pass
-10	3.7	21	0.011	Pass
0	3.7	25	0.013	Pass
10	3.7	28	0.015	Pass
20	3.7	23	0.012	Pass
30	3.7	26	0.014	Pass
40	3.7	20	0.011	Pass
50	3.7	27	0.014	Pass
20	3.5	29	0.015	Pass
20	4.2	22	0.012	Pass

WCDMA Band II: HSUPA

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-37	-0.020	Pass
-20	3.7	-33	-0.018	Pass
-10	3.7	-30	-0.016	Pass
0	3.7	-35	-0.019	Pass
10	3.7	-38	-0.020	Pass
20	3.7	-32	-0.017	Pass
30	3.7	-39	-0.021	Pass
40	3.7	-36	-0.019	Pass
50	3.7	-34	-0.018	Pass
20	3.5	-37	-0.020	Pass
20	4.2	-33	-0.018	Pass

PART 27:**WCDMA Band IV: Re199**

Middle Channel, $f_c = 1732.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-22	-0.013	Pass
-20	3.7	-29	-0.017	Pass
-10	3.7	-24	-0.014	Pass
0	3.7	-21	-0.012	Pass
10	3.7	-28	-0.016	Pass
20	3.7	-23	-0.013	Pass
30	3.7	-27	-0.016	Pass
40	3.7	20	0.012	Pass
50	3.7	-26	-0.015	Pass
20	3.5	-24	-0.014	Pass
20	4.2	-28	-0.016	Pass

WCDMA Band IV: HSDPA

Middle Channel, $f_c = 1732.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	31	0.018	Pass
-20	3.7	35	0.020	Pass
-10	3.7	37	0.021	Pass
0	3.7	33	0.019	Pass
10	3.7	38	0.022	Pass
20	3.7	30	0.017	Pass
30	3.7	34	0.020	Pass
40	3.7	37	0.021	Pass
50	3.7	32	0.018	Pass
20	3.5	39	0.023	Pass
20	4.2	35	0.020	Pass

WCDMA Band IV: HSUPA

Middle Channel, $f_c = 1732.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-41	-0.024	Pass
-20	3.7	-40	-0.023	Pass
-10	3.7	-37	-0.021	Pass
0	3.7	-45	-0.026	Pass
10	3.7	-41	-0.024	Pass
20	3.7	-48	-0.028	Pass
30	3.7	-43	-0.025	Pass
40	3.7	-47	-0.027	Pass
50	3.7	-42	-0.024	Pass
20	3.5	-49	-0.028	Pass
20	4.2	-44	-0.025	Pass

DECLARATION LETTER**Declaration of Alteration**

To Whom It May Concern,

We, Posh Mobile Limited, hereby declare that there are some differences between our Multiple Models and testing products. Details as below:

(This is for your reference only.)

(This is for your reference only.)

Products Description	Name	Kick Lite		
	Brand	POSH		
	Manufacturer	Shenzhen Posh Mobile Limited		
	Project No.	RDG150715004, RDG150715004-20		
Differences Description				
Testing Products	Multiple Models		Differences Items	Details
S410A	S410B		Model name.	They are same motherboard, and just have the different model name .

Notes: Testing products-the products tested by BACL

Multiple Model- have the same or similar appearance, structure, PCB, Material and function to the testing products.

Besides the differences in the table above, we declare the products are identical
We guarantee all the information provided above is true, and notice that we'll bear all the consequences caused by any false information or concealing

Best Regards,

Signature:
Print Name: K.N. Chong
Title: Manager



ADD: 1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong Tel:
0085221229685 Fax: 0085239044979 Email: poshmobileltd@yahoo.com

QPDG004R32 Version1.0 (20140717)

***** END OF REPORT *****