





FCC PART 15.247 TEST REPORT

For

Posh Mobile Limited

1011A, 10/F., Harbour Centre Tower 1, No. 1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

FCC ID: 2ABN6X700

Report Type: Original Report	Product Name: Equal Plus
Test Engineer:	<u>Lorin Bian</u> 
Report Number:	<u>RDG160913001D</u>
Report Date:	<u>2016-11-29</u>
Reviewed By:	<u>Henry Ding</u>  EMC Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
EXTERNAL CABLE	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	13
APPLICABLE STANDARD	13
FCC §15.203 - ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER SETUP	16
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	22
APPLICABLE STANDARD	22
MEASUREMENT UNCERTAINTY	22
EUT SETUP	23
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	24
TEST PROCEDURE	24
CORRECTED AMPLITUDE & MARGIN CALCULATION	24
TEST EQUIPMENT LIST AND DETAILS	25
TEST DATA	25
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS	31
TEST DATA	31
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS	40

TEST DATA.....	40
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS	42
TEST DATA.....	42
FCC §15.247(e) - POWER SPECTRAL DENSITY	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST EQUIPMENT LIST AND DETAILS	48
TEST DATA.....	48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Posh Mobile Limited** 's product, model number: **X700 (FCC ID: 2ABN6X700)** (the "EUT") in this report was a **Equal Plus**, which was measured approximately: 19.2 cm (L) × 10.2 cm (W) × 0.8 cm (H), rated input voltage: DC3.8V rechargeable Li-ion battery or DC5V from adapter.

Adapter information:

Model: A31-501000

C/N: C01-L700

Input: 100-240V~50/60Hz 0.2A

Output: DC 5.0V, 1A

Note: The series product, model X700, X700A, X700B, X700C are electrically identical, the difference between them just have the different model name and appearance(colour) , we selected X700 for fully testing, the details was explained in the declaration letter.

**All measurement and test data in this report was gathered from final production sample, serial number: 160913001 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-09-13, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Posh Mobile Limited** in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABN6X700.

FCC Part 15C DSS submissions with FCC ID: 2ABN6X700.

FCC Part 22H, 24E PCE submissions with FCC ID: 2ABN6X700.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The uncertainty of any RF tests which use conducted method measurement is ± 3.17 dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz: ± 4.7 dB;

200M~1GHz: ± 6.0 dB;

1G~6GHz: ± 5.13 dB;

6G~25GHz: ± 5.47 dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11. For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power) was setting by the software as following table:

Test Mode	Test Software Version	EngineerMode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	15	14	15
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	14	13	13.5
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	13.5	13	13.5
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	15.5	15	15.5


Note: BLE mode configured as maximum power by the system default setting.

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	2	2	100%
802.11g	2	2	100%
802.11n ht20	2	2	100%
802.11n ht40	2	2	100%
BLE	0.45	1.25	36%

The minimum transmission duration(T) is 0.45ms for BLE mode.


802.11b




802.11g




802.11n ht20



802.11n ht40




BLE



External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	1.2	USB Port of Adater	EUT
Earphone Cable	No	No	1.3	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For WiFi mode

The max tune-up conducted power is 9.7 dBm (9.33 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.33/5 \cdot (\sqrt{2.462}) = 2.9 \leq 3.0$

For bluetooth LE mode

The max tune-up conducted power is -8.6 dBm (0.14 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.14/5 \cdot (\sqrt{2.48}) = 0.04 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for Wifi/BT, and the antenna gain is 0.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisprr} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 –non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisprr} of Table 1, then:


–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit;
 –non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ± 3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisprr}

Measurement	U_{cisprr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2015-12-02	2016-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	3560.6550.06	2015-12-02	2016-12-01
N/A	Conducted Cable	NO.5	N/A	2015-11-10	2016-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	26.7 °C
Relative Humidity:	43 %
ATM Pressure:	101.2 kPa

The testing was performed by Lorin Bian on 2016-11-03.

Test Mode: Transmitting (Wi-Fi)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.446873	49.7	9.000	L1	9.7	7.2	56.9	Compliance
0.545378	48.1	9.000	L1	9.7	7.9	56.0	Compliance
0.644717	47.8	9.000	L1	9.7	8.2	56.0	Compliance
0.744147	48.8	9.000	L1	9.7	7.2	56.0	Compliance
0.793127	47.1	9.000	L1	9.7	8.9	56.0	Compliance
0.845331	48.1	9.000	L1	9.7	7.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.446873	44.0	9.000	L1	9.7	3.0	47.0	Compliance
0.549741	42.0	9.000	L1	9.7	4.0	46.0	Compliance
0.595338	42.5	9.000	L1	9.7	3.5	46.0	Compliance
0.644717	40.9	9.000	L1	9.7	5.1	46.0	Compliance
0.698191	43.2	9.000	L1	9.7	2.8	46.0	Compliance
0.849330	43.7	9.000	L1	9.7	2.3	46.0	Compliance

AC120 V, 60 Hz, Neutral:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.545378	46.2	9.000	N	9.6	9.8	56.0	Compliance
0.692650	45.9	9.000	N	9.6	10.1	56.0	Compliance
0.744147	47.8	9.000	N	9.6	8.2	56.0	Compliance
0.838622	45.9	9.000	N	9.6	10.1	56.0	Compliance
0.886728	45.0	9.000	N	9.6	11.0	56.0	Compliance
1.385415	45.5	9.000	N	9.7	10.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.443327	42.2	9.000	N	9.6	4.8	47.0	Compliance
0.595338	40.8	9.000	N	9.6	5.2	46.0	Compliance
0.644717	42.2	9.000	N	9.6	3.8	46.0	Compliance
0.692650	39.8	9.000	N	9.6	6.2	46.0	Compliance
0.795630	44.6	9.000	N	9.6	1.4	46.0	Compliance
0.838622	42.7	9.000	N	9.6	3.3	46.0	Compliance

Test Mode: Transmitting (BLE)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.549741	49.2	9.000	L1	9.7	6.8	56.0	Compliance
0.600101	48.6	9.000	L1	9.7	7.4	56.0	Compliance
0.649874	49.5	9.000	L1	9.7	6.5	56.0	Compliance
0.698191	49.0	9.000	L1	9.7	7.0	56.0	Compliance
0.799472	49.7	9.000	L1	9.7	6.3	56.0	Compliance
0.900972	49.1	9.000	L1	9.7	6.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.450448	45.0	9.000	L1	9.7	1.9	46.9	Compliance
0.549741	43.0	9.000	L1	9.7	3.0	46.0	Compliance
0.600101	43.8	9.000	L1	9.7	2.2	46.0	Compliance
0.649874	44.6	9.000	L1	9.7	1.4	46.0	Compliance
0.750100	42.7	9.000	L1	9.7	3.3	46.0	Compliance
0.799472	43.6	9.000	L1	9.7	2.4	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.554139	40.7	9.000	N	9.6	15.3	56.0	Compliance
0.698191	48.5	9.000	N	9.6	7.5	56.0	Compliance
0.750100	48.6	9.000	N	9.6	7.4	56.0	Compliance
0.799472	48.4	9.000	N	9.6	7.6	56.0	Compliance
1.548915	49.5	9.000	N	9.7	6.5	56.0	Compliance
1.599078	49.9	9.000	N	9.7	6.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.600101	42.9	9.000	N	9.6	3.1	46.0	Compliance
0.649874	44.6	9.000	N	9.6	1.4	46.0	Compliance
0.750100	40.8	9.000	N	9.6	5.2	46.0	Compliance
0.799472	43.6	9.000	N	9.6	2.4	46.0	Compliance
1.548915	41.6	9.000	N	9.7	4.4	46.0	Compliance
1.599078	43.7	9.000	N	9.7	2.3	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ±4.7 dB ;

200M~1GHz: ±6.0 dB ;

1G~6GHz: ±5.13dB;


6G~25GHz: ±5.47 dB;

Table 2 – Values of U_{cisp}


Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2015-12-02	2016-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Sunol Sciences	Broadband Antenna	JB3	A101808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2015-12-02	2016-12-01
ETS	Horn Antenna	3115	003-6076	2015-12-02	2016-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2015-12-02	2016-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2015-11-10	2016-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2015-11-10	2016-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2015-11-10	2016-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.7 °C
Relative Humidity:	43 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-11-03.

Test Mode: Transmitting

30MHz-25GHz:

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	71.01	PK	H	23.50	3.00	0.00	97.51	N/A	N/A
2412	67.23	AV	H	23.50	3.00	0.00	93.73	N/A	N/A
2412	67.22	PK	V	23.50	3.00	0.00	93.72	N/A	N/A
2412	63.84	AV	V	23.50	3.00	0.00	90.34	N/A	N/A
2390	24.61	PK	H	23.57	3.00	0.00	51.18	74.00	22.82
2390	13.05	AV	H	23.57	3.00	0.00	39.62	54.00	14.38
4824	34.86	PK	H	30.84	5.11	26.87	43.94	74.00	30.06
4824	23.87	AV	H	30.84	5.11	26.87	32.95	54.00	21.05
7236	34.03	PK	H	34.77	6.18	26.36	48.62	74.00	25.38
7236	22.87	AV	H	34.77	6.18	26.36	37.46	54.00	16.54
3618	41.66	PK	H	27.47	4.35	26.58	46.90	74.00	27.10
3618	31.87	AV	H	27.47	4.35	26.58	37.11	54.00	16.89
717.73	40.95	QP	V	21.05	2.04	28.66	35.38	46.00	10.62
893.3	42.02	QP	V	22.72	2.38	28.14	38.98	46.00	7.02
Middle Channel: 2437 MHz									
2437	70.63	PK	H	23.41	3.00	0.00	97.04	N/A	N/A
2437	67.73	AV	H	23.41	3.00	0.00	94.14	N/A	N/A
2437	65.38	PK	V	23.41	3.00	0.00	91.79	N/A	N/A
2437	61.89	AV	V	23.41	3.00	0.00	88.30	N/A	N/A
4874	34.96	PK	H	31.00	5.09	26.87	44.18	74.00	29.82
4874	24.23	AV	H	31.00	5.09	26.87	33.45	54.00	20.55
7311	33.85	PK	H	34.92	6.21	26.40	48.58	74.00	25.42
7311	23.25	AV	H	34.92	6.21	26.40	37.98	54.00	16.02
3045	33.23	PK	H	24.45	3.50	26.43	34.75	74.00	39.25
3045	22.58	AV	H	24.45	3.50	26.43	24.10	54.00	29.90
3618	42.39	PK	H	27.47	4.35	26.58	47.63	74.00	26.37
3618	32.51	AV	H	27.47	4.35	26.58	37.75	54.00	16.25
717.73	41.02	QP	V	21.05	2.04	28.66	35.45	46.00	10.55
893.3	42.69	QP	V	22.72	2.38	28.14	39.65	46.00	6.35
High Channel: 2462 MHz									
2462	71.24	PK	H	23.33	2.99	0.00	97.56	N/A	N/A
2462	68.04	AV	H	23.33	2.99	0.00	94.36	N/A	N/A
2462	67.18	PK	V	23.33	2.99	0.00	93.50	N/A	N/A
2462	64.54	AV	V	23.33	2.99	0.00	90.86	N/A	N/A
2483.5	25.74	PK	H	23.26	2.99	0.00	51.99	74.00	22.01
2483.5	13.82	AV	H	23.26	2.99	0.00	40.07	54.00	13.93
4924	34.19	PK	H	31.16	5.07	26.88	43.54	74.00	30.46
4924	23.92	AV	H	31.16	5.07	26.88	33.27	54.00	20.73
7386	33.91	PK	H	35.07	6.25	26.43	48.80	74.00	25.20
7386	23.24	AV	H	35.07	6.25	26.43	38.13	54.00	15.87
3163	38.05	PK	H	25.11	3.67	26.47	40.36	74.00	33.64
3163	27.47	AV	H	25.11	3.67	26.47	29.78	54.00	24.22
717.73	40.66	QP	V	21.05	2.04	28.66	35.09	46.00	10.91
893.3	42.75	QP	V	22.72	2.38	28.14	39.71	46.00	6.29

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	74.31	PK	H	23.50	3.00	0.00	100.81	N/A	N/A
2412	64.91	AV	H	23.50	3.00	0.00	91.41	N/A	N/A
2412	68.71	PK	V	23.50	3.00	0.00	95.21	N/A	N/A
2412	58.34	AV	V	23.50	3.00	0.00	84.84	N/A	N/A
2390	34.92	PK	H	23.57	3.00	0.00	61.49	74.00	12.51
2390	18.46	AV	H	23.57	3.00	0.00	45.03	54.00	8.97
4824	34.47	PK	H	30.84	5.11	26.87	43.55	74.00	30.45
4824	23.54	AV	H	30.84	5.11	26.87	32.62	54.00	21.38
7236	34.09	PK	H	34.77	6.18	26.36	48.68	74.00	25.32
7236	23.48	AV	H	34.77	6.18	26.36	38.07	54.00	15.93
3618	42.12	PK	H	27.47	4.35	26.58	47.36	74.00	26.64
3618	31.54	AV	H	27.47	4.35	26.58	36.78	54.00	17.22
717.73	41.22	QP	V	21.05	2.04	28.66	35.65	46.00	10.35
893.3	43.78	QP	V	22.72	2.38	28.14	40.74	46.00	5.26
Middle Channel: 2437 MHz									
2437	72.15	PK	H	23.41	3.00	0.00	98.56	N/A	N/A
2437	62.97	AV	H	23.41	3.00	0.00	89.38	N/A	N/A
2437	66.31	PK	V	23.41	3.00	0.00	92.72	N/A	N/A
2437	57.64	AV	V	23.41	3.00	0.00	84.05	N/A	N/A
4874	34.67	PK	H	31.00	5.09	26.87	43.89	74.00	30.11
4874	23.84	AV	H	31.00	5.09	26.87	33.06	54.00	20.94
7311	33.42	PK	H	34.92	6.21	26.40	48.15	74.00	25.85
7311	23.44	AV	H	34.92	6.21	26.40	38.17	54.00	15.83
2745	33.56	PK	H	23.69	3.21	26.65	33.81	74.00	40.19
2745	22.74	AV	H	23.69	3.21	26.65	22.99	54.00	31.01
3618	41.91	PK	H	27.47	4.35	26.58	47.15	74.00	26.85
3618	32.2	AV	H	27.47	4.35	26.58	37.44	54.00	16.56
717.73	42.39	QP	V	21.05	2.04	28.66	36.82	46.00	9.18
893.3	42.88	QP	V	22.72	2.38	28.14	39.84	46.00	6.16
High Channel: 2462 MHz									
2462	72.39	PK	H	23.33	2.99	0.00	98.71	N/A	N/A
2462	64.33	AV	H	23.33	2.99	0.00	90.65	N/A	N/A
2462	67.34	PK	V	23.33	2.99	0.00	93.66	N/A	N/A
2462	58.95	AV	V	23.33	2.99	0.00	85.27	N/A	N/A
2483.5	30.84	PK	H	23.26	2.99	0.00	57.09	74.00	16.91
2483.5	18.15	AV	H	23.26	2.99	0.00	44.40	54.00	9.60
4924	34.1	PK	H	31.16	5.07	26.88	43.45	74.00	30.55
4924	22.88	AV	H	31.16	5.07	26.88	32.23	54.00	21.77
7386	34.21	PK	H	35.07	6.25	26.43	49.10	74.00	24.90
7386	23.1	AV	H	35.07	6.25	26.43	37.99	54.00	16.01
3163	38.57	PK	H	25.11	3.67	26.47	40.88	74.00	33.12
3163	27.39	AV	H	25.11	3.67	26.47	29.70	54.00	24.30
717.73	43.66	QP	V	21.05	2.04	28.66	38.09	46.00	7.91
893.3	41.81	QP	V	22.72	2.38	28.14	38.77	46.00	7.23

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	71.77	PK	H	23.50	3.00	0.00	98.27	N/A	N/A
2412	63.42	AV	H	23.50	3.00	0.00	89.92	N/A	N/A
2412	67.02	PK	V	23.50	3.00	0.00	93.52	N/A	N/A
2412	58.62	AV	V	23.50	3.00	0.00	85.12	N/A	N/A
2390	33.43	PK	H	23.57	3.00	0.00	60.00	74.00	14.00
2390	17.93	AV	H	23.57	3.00	0.00	44.50	54.00	9.50
4824	34.98	PK	H	30.84	5.11	26.87	44.06	74.00	29.94
4824	23.12	AV	H	30.84	5.11	26.87	32.20	54.00	21.80
7236	34.11	PK	H	34.77	6.18	26.36	48.70	74.00	25.30
7236	23.53	AV	H	34.77	6.18	26.36	38.12	54.00	15.88
3618	42.17	PK	H	27.47	4.35	26.58	47.41	74.00	26.59
3618	31.12	AV	H	27.47	4.35	26.58	36.36	54.00	17.64
717.73	44.28	QP	V	21.05	2.04	28.66	38.71	46.00	7.29
893.3	42.71	QP	V	22.72	2.38	28.14	39.67	46.00	6.33
Middle Channel: 2437 MHz									
2437	71.25	PK	H	23.41	3.00	0.00	97.66	N/A	N/A
2437	62.67	AV	H	23.41	3.00	0.00	89.08	N/A	N/A
2437	66.69	PK	V	23.41	3.00	0.00	93.10	N/A	N/A
2437	57.31	AV	V	23.41	3.00	0.00	83.72	N/A	N/A
4874	34.99	PK	H	31.00	5.09	26.87	44.21	74.00	29.79
4874	24.38	AV	H	31.00	5.09	26.87	33.60	54.00	20.40
7311	32.84	PK	H	34.92	6.21	26.40	47.57	74.00	26.43
7311	23.54	AV	H	34.92	6.21	26.40	38.27	54.00	15.73
2580	33.06	PK	H	23.36	3.06	26.81	32.67	74.00	41.33
2580	22.67	AV	H	23.36	3.06	26.81	22.28	54.00	31.72
3618	42.58	PK	H	27.47	4.35	26.58	47.82	74.00	26.18
3618	32.4	AV	H	27.47	4.35	26.58	37.64	54.00	16.36
717.73	43.27	QP	V	21.05	2.04	28.66	37.70	46.00	8.30
893.3	41.02	QP	V	22.72	2.38	28.14	37.98	46.00	8.02
High Channel: 2462 MHz									
2462	70.99	PK	H	23.33	2.99	0.00	97.31	N/A	N/A
2462	62.54	AV	H	23.33	2.99	0.00	88.86	N/A	N/A
2462	66.38	PK	V	23.33	2.99	0.00	92.70	N/A	N/A
2462	58.67	AV	V	23.33	2.99	0.00	84.99	N/A	N/A
2483.5	34.51	PK	H	23.26	2.99	0.00	60.76	74.00	13.24
2483.5	19.43	AV	H	23.26	2.99	0.00	45.68	54.00	8.32
4924	34.69	PK	H	31.16	5.07	26.88	44.04	74.00	29.96
4924	23.73	AV	H	31.16	5.07	26.88	33.08	54.00	20.92
7386	33.52	PK	H	35.07	6.25	26.43	48.41	74.00	25.59
7386	23.64	AV	H	35.07	6.25	26.43	38.53	54.00	15.47
3163	38.3	PK	H	25.11	3.67	26.47	40.61	74.00	33.39
3163	26.88	AV	H	25.11	3.67	26.47	29.19	54.00	24.81
717.73	42.25	QP	V	21.05	2.04	28.66	36.68	46.00	9.32
893.3	42.96	QP	V	22.72	2.38	28.14	39.92	46.00	6.08

802.11 n ht40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	68.61	PK	H	23.47	3.00	0.00	95.08	N/A	N/A
2422	60.11	AV	H	23.47	3.00	0.00	86.58	N/A	N/A
2422	64.53	PK	V	23.47	3.00	0.00	91.00	N/A	N/A
2422	56.34	AV	V	23.47	3.00	0.00	82.81	N/A	N/A
2390	33.3	PK	H	23.57	3.00	0.00	59.87	74.00	14.13
2390	21.01	AV	H	23.57	3.00	0.00	47.58	54.00	6.42
4844	35.14	PK	H	30.90	5.10	26.87	44.27	74.00	29.73
4844	23.02	AV	H	30.90	5.10	26.87	32.15	54.00	21.85
7266	34.46	PK	H	34.83	6.19	26.38	49.10	74.00	24.90
7266	23.25	AV	H	34.83	6.19	26.38	37.89	54.00	16.11
3618	41.5	PK	H	27.47	4.35	26.58	46.74	74.00	27.26
3618	31.58	AV	H	27.47	4.35	26.58	36.82	54.00	17.18
717.73	43.66	QP	V	21.05	2.04	28.66	38.09	46.00	7.91
893.3	41.27	QP	V	22.72	2.38	28.14	38.23	46.00	7.77
Middle Channel: 2437 MHz									
2437	67.88	PK	H	23.41	3.00	0.00	94.29	N/A	N/A
2437	59.34	AV	H	23.41	3.00	0.00	85.75	N/A	N/A
2437	63.72	PK	V	23.41	3.00	0.00	90.13	N/A	N/A
2437	55.49	AV	V	23.41	3.00	0.00	81.90	N/A	N/A
4874	34.86	PK	H	31.00	5.09	26.87	44.08	74.00	29.92
4874	24.35	AV	H	31.00	5.09	26.87	33.57	54.00	20.43
7311	34.09	PK	H	34.92	6.21	26.40	48.82	74.00	25.18
7311	22.82	AV	H	34.92	6.21	26.40	37.55	54.00	16.45
2954	33.81	PK	H	24.11	3.39	26.45	34.86	74.00	39.14
2954	22.51	AV	H	24.11	3.39	26.45	23.56	54.00	30.44
3618	41.69	PK	H	27.47	4.35	26.58	46.93	74.00	27.07
3618	32.36	AV	H	27.47	4.35	26.58	37.60	54.00	16.40
717.73	42.14	QP	V	21.05	2.04	28.66	36.57	46.00	9.43
893.3	40.09	QP	V	22.72	2.38	28.14	37.05	46.00	8.95
High Channel: 2452 MHz									
2452	67.59	PK	H	23.36	3.00	0.00	93.95	N/A	N/A
2452	59.32	AV	H	23.36	3.00	0.00	85.68	N/A	N/A
2452	63.47	PK	V	23.36	3.00	0.00	89.83	N/A	N/A
2452	54.36	AV	V	23.36	3.00	0.00	80.72	N/A	N/A
2483.5	31.51	PK	H	23.26	2.99	0.00	57.76	74.00	16.24
2483.5	18.84	AV	H	23.26	2.99	0.00	45.09	54.00	8.91
4904	34.68	PK	H	31.09	5.08	26.87	43.98	74.00	30.02
4904	23.06	AV	H	31.09	5.08	26.87	32.36	54.00	21.64
7356	33.74	PK	H	35.01	6.23	26.42	48.56	74.00	25.44
7356	22.86	AV	H	35.01	6.23	26.42	37.68	54.00	16.32
3163	38.69	PK	H	25.11	3.67	26.47	41.00	74.00	33.00
3163	28.58	AV	H	25.11	3.67	26.47	30.89	54.00	23.11
717.73	41.05	QP	V	21.05	2.04	28.66	35.48	46.00	10.52
893.3	42.05	QP	V	22.72	2.38	28.14	39.01	46.00	6.99

BLE Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	61.58	PK	H	23.53	3.00	0.00	88.11	N/A	N/A
2402	50.24	AV	H	23.53	3.00	0.00	76.77	N/A	N/A
2402	56.06	PK	V	23.53	3.00	0.00	82.59	N/A	N/A
2402	45.68	AV	V	23.53	3.00	0.00	72.21	N/A	N/A
2390	25.53	PK	H	23.57	3.00	0.00	52.10	74.00	21.90
2390	14.39	AV	H	23.57	3.00	0.00	40.96	54.00	13.04
4804	33.24	PK	H	30.77	5.12	26.87	42.26	74.00	31.74
4804	24.44	AV	H	30.77	5.12	26.87	33.46	54.00	20.54
7206	34.07	PK	H	34.71	6.16	26.35	48.59	74.00	25.41
7206	23.46	AV	H	34.71	6.16	26.35	37.98	54.00	16.02
2745	31.02	PK	H	23.69	3.21	26.65	31.27	74.00	42.73
2745	21.8	AV	H	23.69	3.21	26.65	22.05	54.00	31.95
717.73	42.05	QP	V	21.05	2.04	28.66	36.48	46.00	9.52
893.3	41.22	QP	V	22.72	2.38	28.14	38.18	46.00	7.82
Middle Channel: 2440 MHz									
2440	60.44	PK	H	23.40	3.00	0.00	86.84	N/A	N/A
2440	49.73	AV	H	23.40	3.00	0.00	76.13	N/A	N/A
2440	55.86	PK	V	23.40	3.00	0.00	82.26	N/A	N/A
2440	44.38	AV	V	23.40	3.00	0.00	70.78	N/A	N/A
4880	32.93	PK	H	31.02	5.09	26.87	42.17	74.00	31.83
4880	24.52	AV	H	31.02	5.09	26.87	33.76	54.00	20.24
7320	34.08	PK	H	34.94	6.22	26.40	48.84	74.00	25.16
7320	23.91	AV	H	34.94	6.22	26.40	38.67	54.00	15.33
2745	34.59	PK	H	23.69	3.21	26.65	34.84	74.00	39.16
2745	23.17	AV	H	23.69	3.21	26.65	23.42	54.00	30.58
3450	30.36	PK	H	26.72	4.11	26.57	34.62	74.00	39.38
3450	21.85	AV	H	26.72	4.11	26.57	26.11	54.00	27.89
717.73	40.22	QP	V	21.05	2.04	28.66	34.65	46.00	11.35
893.3	41.65	QP	V	22.72	2.38	28.14	38.61	46.00	7.39
High Channel: 2480 MHz									
2480	59.68	PK	H	23.27	2.99	0.00	85.94	N/A	N/A
2480	48.53	AV	H	23.27	2.99	0.00	74.79	N/A	N/A
2480	55.37	PK	V	23.27	2.99	0.00	81.63	N/A	N/A
2480	44.91	AV	V	23.27	2.99	0.00	71.17	N/A	N/A
2483.5	26.89	PK	H	23.26	2.99	0.00	53.14	74.00	20.86
2483.5	15.32	AV	H	23.26	2.99	0.00	41.57	54.00	12.43
4960	33.42	PK	H	31.27	5.05	26.88	42.86	74.00	31.14
4960	23.79	AV	H	31.27	5.05	26.88	33.23	54.00	20.77
7440	34.25	PK	H	35.18	6.27	26.45	49.25	74.00	24.75
7440	24.12	AV	H	35.18	6.27	26.45	39.12	54.00	14.88
2745	30.84	PK	H	23.69	3.21	26.65	31.09	74.00	42.91
2745	21.86	AV	H	23.69	3.21	26.65	22.11	54.00	31.89
717.73	40.28	QP	V	21.05	2.04	28.66	34.71	46.00	11.29
893.3	42.36	QP	V	22.72	2.38	28.14	39.32	46.00	6.68


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3~29.6 °C
Relative Humidity:	50~52%
ATM Pressure:	100.8~100.9 kPa


* The testing was performed by Lorin Bian from 2016-11-04 to 2016-11-05.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.62	≥0.5
	Middle	2437	9.22	≥0.5
	High	2462	9.22	≥0.5
802.11g	Low	2412	16.43	≥0.5
	Middle	2437	16.43	≥0.5
	High	2462	16.43	≥0.5
802.11n20	Low	2412	17.39	≥0.5
	Middle	2437	17.64	≥0.5
	High	2462	17.64	≥0.5
802.11n40	Low	2422	36.23	≥0.5
	Middle	2437	36.23	≥0.5
	High	2452	36.23	≥0.5
BLE	Low	2402	0.72	≥0.5
	Middle	2440	0.73	≥0.5
	High	2480	0.73	≥0.5


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n ht20 Low Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel




802.11n ht40 Low Channel




802.11n ht40 Middle Channel



BLE Middle Channel



BLE High Channel




FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54170074	2016-01-03	2017-01-03
Agilent	P-Series Power Meter	N1912A	MY5000798	2016-01-03	2017-01-03
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3 °C
Relative Humidity:	50 %
ATM Pressure:	100.9 kPa

* The testing was performed by Lorin Bian on 2016-11-04.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Max Conducted Average Output Power	Limit
		(MHz)	(dBm)	(dBm)	(dBm)
802.11b	Low	2412	11.25	9.63	30
	Middle	2437	11.02	9.44	30
	High	2462	10.89	9.33	30
802.11g	Low	2412	14.01	9.22	30
	Middle	2437	13.83	9.04	30
	High	2462	14.41	9.65	30
802.11n20	Low	2412	14.36	9.6	30
	Middle	2437	13.55	8.84	30
	High	2462	13.82	9.1	30
802.11n40	Low	2422	15.76	8.88	30
	Middle	2437	16.64	9.63	30
	High	2452	16.56	9.52	30
BLE	Low	2402	-9.53	/	30
	Middle	2440	-8.91	/	30
	High	2480	-8.67	/	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3~29.6 °C
Relative Humidity:	50~52%
ATM Pressure:	100.8~100.9 kPa

* The testing was performed by Lorin Bian from 2016-11-04 to 2016-11-05.


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n ht20 Band Edge, Left Side




802.11n ht20 Band Edge, Right Side




802.11n ht40 Band Edge, Left Side




802.11n ht40 Band Edge, Right Side



BLE Band Edge , Left Side



BLE Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.3~29.6 °C
Relative Humidity:	50~52%
ATM Pressure:	100.8~100.9 kPa


* The testing was performed by Lorin Bian from 2016-11-04 to 2016-11-05.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-15.12	≤8
	Middle	2437	-16.05	≤8
	High	2462	-15.71	≤8
802.11g	Low	2412	-20.27	≤8
	Middle	2437	-20.48	≤8
	High	2462	-19.94	≤8
802.11n20	Low	2412	-19.61	≤8
	Middle	2437	-20.34	≤8
	High	2462	-20	≤8
802.11n40	Low	2422	-20.01	≤8
	Middle	2437	-20.55	≤8
	High	2452	-19.86	≤8
BLE	Low	2402	-25.71	≤8
	Middle	2440	-24.93	≤8
	High	2480	-24.67	≤8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n ht20 Low Channel




Power Spectral Density, 802.11n ht20 Middle Channel




Power Spectral Density, 802.11n ht20 High Channel




Power Spectral Density, 802.11n ht40 Low Channel




Power Spectral Density, 802.11n ht40 Middle Channel




Page 55 of 56



Power Spectral Density, BLE Middle Channel



Power Spectral Density, BLE High Channel



***** **END OF REPORT** *****