FCC RF Test Report

APPLICANT : Nyle Oswind Parry Limited Liability Company

EQUIPMENT : Tablet PC MODEL NAME : GRT67VY

FCC ID : 2ABO6-0610

STANDARD : 47 CFR Part 2, 27

CLASSIFICATION : PCS Licensed Transmitter (PCB)

The testing completed on Apr. 26, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager





SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 1 of 128

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMA	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Product Feature of Equipment Under Test	5
	1.3	Product Specification subjective to this standard	5
	1.4	Modification of EUT	5
	1.5	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
	1.6	Testing Location	7
	1.7	Applicable Standards	7
2	TES	Γ CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	8
	2.2	Connection Diagram of Test System	9
	2.3	Support Unit used in test configuration and system	9
	2.4	Measurement Results Explanation Example	9
3	TES	Γ RESULT	10
	3.1	Conducted Output Power Measurement and ERP/EIRP Measurement	10
	3.2	Peak-to-Average Ratio	19
	3.3	Occupied Bandwidth	25
	3.4	Conducted Band Edge Measurement	70
	3.5	Conducted Spurious Emission Measurement	104
	3.6	Radiated Spurious Emission Measurement	114
	3.7	Frequency Stability Measurement	124
4	LIST	OF MEASURING EQUIPMENT	127
5	UNC	ERTAINTY OF EVALUATION	128

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 2 of 128

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG432436-10B	Rev. 01	Initial issue of report	Jul. 29, 2014
FG432436-10B	Rev. 02	Add maximum RSE results of 1559MHz-1610MHz at page 122-123.	Sep. 01, 2014

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 3 of 128

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.1	§27.50(b)(10)	Effective Radiated Power (Band 13)	ERP < 3 Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt	PASS	-
3.2	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§2.1049 §27.53(h)(3)	Occupied Bandwidth	Reporting Only	PASS	-
3.4	\$2.1051 \$27.53(c)(2) \$27.53(c)(4) \$27.53(h)	Conducted Band Edge Measurement (Band 4) (Band 13)	< 43+10log10(P[Watt])	PASS	-
3.5	§2.1051 §27.53(c)(2) §27.53(h)	Conducted Spurious Emission (Band 4) (Band 13)	< 43+10log ₁₀ (P[Watts])	PASS	-
\$2.1053 \$27.53(c)(2) \$27.53(f) \$27.53(h)		Radiated Spurious Emission (Band 4) (Band 13)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 12.91 dB at 1559.000 MHz
3.7	§2.1055 Frequency Stability		< 2.5 ppm	PASS	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 4 of 128

1 General Description

1.1 Applicant

Nyle Oswind Parry Limited Liability Company

7027 Old Madison Pike, Suite 108, Huntsville, Alabama 35806

1.2 Product Feature of Equipment Under Test

	Product Feature
Equipment	Tablet PC
Model Name	GRT67VY
FCC ID	2ABO6-0610
	GSM/EGPRS/WCDMA/HSPA/LTE
	<2.4GHz band>
	WLAN 11b/g/n HT20
EUT supports Radios application	WLAN 11ac VHT20
EOT Supports Radios application	Bluetooth v4.0 EDR/LE
	<5GHz band>
	WLAN 11a/n HT20/HT40
	WLAN 11ac VHT20/VHT40/VHT80

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification subjective to this standard

Product Specification subjective to this standard									
Tx Frequency	LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz								
Rx Frequency	LTE Band 4: 2110.7 MHz ~ 2154.3 MHz LTE Band 13: 748.5 MHz ~ 753.5 MHz								
Bandwidth	LTE Band 4: 1.4MHz/3MHz/5MHz/10MHz/15MHz/20MHz LTE Band 13: 5MHz/10MHz								
Maximum Output Power to Antenna	LTE Band 4: 23.80 dBm LTE Band 13: 22.90 dBm								
Antenna Type	Fixed Internal Antenna								
Antenna Gain	LTE Band 4: 1.70 dBi LTE Band 13: -0.40 dBi								
Type of Modulation	QPSK / 16QAM								

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 5 of 128
Report Template No.: BU5-FGLTE Version 1.1

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	BW	Emission Designator	Frequency Tolerance (ppm)	Maximum ERP/EIRP
Part 27	LTE Band 4	QPSK	1.4 MHz	1M10G7D	-	0.35 W
Part 27	LTE Band 4	16QAM	1.4 MHz	1M10D7W	-	0.28 W
Part 27	LTE Band 4	QPSK	3 MHz	2M73G7D	-	0.35 W
Part 27	LTE Band 4	16QAM	3 MHz	2M74D7W	-	0.28 W
Part 27	LTE Band 4	QPSK	5MHz	4M50G7D	-	0.34 W
Part 27	LTE Band 4	16QAM	5MHz	4M51D7W	-	0.27 W
Part 27	LTE Band 4	QPSK	10MHz	9M06G7D	0.0118 ppm	0.34 W
Part 27	LTE Band 4	16QAM	10MHz	9M04D7W	-	0.28 W
Part 27	LTE Band 4	QPSK	15MHz	13M5G7D	-	0.34 W
Part 27	LTE Band 4	16QAM	15MHz	13M5D7W	-	0.27 W
Part 27	LTE Band 4	QPSK	20MHz	18M5G7D	-	0.36 W
Part 27	LTE Band 4	16QAM	20MHz	18M5D7W	-	0.27 W
Part 27	LTE Band 13	QPSK	5MHz	4M51G7D	-	0.11 W
Part 27	LTE Band 13	16QAM	5MHz	4M50D7W	-	0.09 W
Part 27	LTE Band 13	QPSK	10MHz	9M08G7D	0.0102 ppm	0.11 W
Part 27	LTE Band 13	16QAM	10MHz	9M02D7W	-	0.09 W

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 6 of 128
Report Template No.: BU5-FGLTE Version 1.1

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.					
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Techn	ology Park,				
Test Site Location	Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.					
rest site Location	TEL: +886-3-327-3456					
	FAX: +886-3-328-4978					
Took Site No	Sporton	Site No.				
Test Site No.	TH02-HY	03CH07-HY				

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 27
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 7 of 128

2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Total Manage	Ban		В	andwid	lth (MH	z)		Modu	Modulation RB #			Test Channel			
Test Items	d	1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	М	Н
Max. Output Power	4	V	V	V	V	y	V	v	V	٧	V	v	V	V	v
Max. Output Fower	13	-	-	V	V	-	-	v	V	V	y	v	V	V	V
Peak-to-Average	4						V	v	v	٧		v	V	V	v
Ratio	13	-	-		V	-	-	v	v	V		v	V	v	V
26dB and 99%	4	V	V	V	V	V	V	v	v			v	V	V	V
Bandwidth	13	-	-	V	V	-	-	v	v			v	V	V	V
Conducted	4	V	V	v	V	y	y	v	v	V		v	V		v
Band Edge	13	-	-	V	V	-	-	v	V	٧		v	V		V
Conducted	4	v	v	v	v	v	v	v	v	V				v	
Spurious Emission	13	-	-	v	v	-	-	v	v	V				v	
Frequency	4				y			v				v		V	
Stability	13	•	•		٧	•	•	v				v		V	
E.R.P./ E.I.R.P.	4	V	V	V	v	v	V	v	v	٧			V	٧	v
E.K.F.J E.I.K.F.	13	-	-	v	v	-	-	v	v	V			v	v	v
Radiated Spurious	4	V	V	V	V	v	V	v		٧				V	
Emission	13	-	-	v	v	-	-	v		v				v	
	1. 7	The m	ark "γ	" mea	ns tha	t this	config	uration is	chosen fo	r testi	ng			I	
	2. The mark "-" means that this bandwidth is not supported.														
Note	3.	Γhe de	evice i	s inve	stigate	ed froi	n 30N	/IHz to 10 t	times of fu	ndam	ental :	signal	for ra	diated	
					-			nt RB size				•			
								emissions					•		

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 8 of 128

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	N/A	Unshielded, 1.0 m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 4.2 + 10 = 14.2 (dB)

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 9 of 128

3 Test Result

3.1 Conducted Output Power Measurement and ERP/EIRP Measurement

3.1.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 13. (FCC Only)

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4.

According to KDB 412172 D01 Power Approach,

 $EIRP = P_T + G_T - L_C$, ERP = EIRP - 2.15, where

 P_T = transmitter output power in dBm

 G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 10 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.1.5 Test Result of Conducted Output Power

<LTE Band 4 Conducted Power>

BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Cha	nnel	20050	20175	20300	
	Frequen	cy (MHz)	1720	1732.5	1745	
20	QPSK	1	0	<mark>23.80</mark>	23.50	23.50
20	QPSK	1	49	23.70	23.40	23.50
20	QPSK	1	99	23.50	23.40	23.50
20	QPSK	50	0	22.50	22.20	22.30
20	QPSK	50	24	22.40	22.10	22.30
20	QPSK	50	49	22.30	22.00	22.30
20	QPSK	100	0	22.30	22.20	22.20
20	16QAM	1	0	22.60	22.60	22.60
20	16QAM	1	49	22.50	22.50	22.60
20	16QAM	1	99	22.40	22.50	22.50
20	16QAM	50	0	21.20	21.20	21.20
20	16QAM	50	24	21.20	21.10	21.30
20	16QAM	50	49	21.20	21.10	21.30
20	16QAM	100	0	21.30	21.20	21.30
	Cha	nnel		20025	20175	20325
	Frequen	cy (MHz)		1717.5	1732.5	1747.5
15	QPSK	1	0	23.60	23.50	23.60
15	QPSK	1	37	23.60	23.50	23.60
15	QPSK	1	74	23.40	23.40	23.40
15	QPSK	36	0	22.30	22.30	22.30
15	QPSK	36	18	22.30	22.20	22.40
15	QPSK	36	37	22.30	22.10	22.30
15	QPSK	75	0	22.20	22.20	22.30
15	16QAM	1	0	22.60	22.50	22.50
15	16QAM	1	37	22.60	22.40	22.50
15	16QAM	1	74	22.40	22.40	22.50
15	16QAM	36	0	21.30	21.30	21.40
15	16QAM	36	18	21.30	21.20	21.30
15	16QAM	36	37	21.30	21.20	21.30
15	16QAM	75	0	21.20	21.20	21.30

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 11 of 128
Report Template No.: BU5-FGLTE Version 1.1

BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Cha	nnel		20000	20175	20350
	Frequen	cy (MHz)		1715	1732.5	1750
10	QPSK	1	0	23.50	23.50	23.60
10	QPSK	1	24	23.50	23.40	23.50
10	QPSK	1	49	23.40	23.30	23.40
10	QPSK	25	0	22.40	22.30	22.40
10	QPSK	25	12	22.40	22.20	22.40
10	QPSK	25	24	22.40	22.30	22.40
10	QPSK	50	0	22.20	22.20	22.30
10	16QAM	1	0	22.50	22.50	22.70
10	16QAM	1	24	22.50	22.40	22.50
10	16QAM	1	49	22.50	22.40	22.60
10	16QAM	25	0	21.40	21.30	21.40
10	16QAM	25	12	21.40	21.30	21.50
10	16QAM	25	24	21.40	21.30	21.40
10	16QAM	50	0	21.20	21.20	21.30
	Cha	nnel	•	19975	20175	20375
	Frequen	cy (MHz)		1712.5	1732.5	1752.5
5	QPSK	1	0	23.60	23.40	23.60
5	QPSK	1	12	23.60	23.40	23.50
5	QPSK	1	24	23.50	23.30	23.50
5	QPSK	12	0	22.60	22.50	22.60
5	QPSK	12	6	22.60	22.40	22.50
5	QPSK	12	11	22.60	22.50	22.60
5	QPSK	25	0	22.40	22.30	22.40
5	16QAM	1	0	22.60	22.50	22.60
5	16QAM	1	12	22.50	22.50	22.60
5	16QAM	1	24	22.50	22.40	22.50
5	16QAM	12	0	21.60	21.50	21.70
5	16QAM	12	6	21.70	21.50	21.60
5	16QAM	12	11	21.70	21.50	21.70
5	16QAM	25	0	21.40	21.30	21.40

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 12 of 128
Report Template No.: BU5-FGLTE Version 1.1

BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Cha	nnel	19965	20175	20385	
	Frequen	cy (MHz)	1711.5	1732.5	1753.5	
3	QPSK	1	0	23.70	23.60	23.70
3	QPSK	1	7	23.70	23.50	23.60
3	QPSK	1	14	23.70	23.50	23.60
3	QPSK	8	0	22.70	22.70	22.80
3	QPSK	8	4	22.70	22.60	22.70
3	QPSK	8	7	22.70	22.60	22.70
3	QPSK	15	0	22.70	22.50	22.60
3	16QAM	1	0	22.70	22.60	22.70
3	16QAM	1	7	22.70	22.60	22.70
3	16QAM	1	14	22.60	22.50	22.70
3	16QAM	8	0	21.70	21.60	21.70
3	16QAM	8	4	21.70	21.60	21.70
3	16QAM	8	7	21.70	21.60	21.70
3	16QAM	15	0	21.70	21.60	21.70
	Cha	nnel		19957	20175	20393
	Frequen	cy (MHz)		1710.7	1732.5	1754.3
1.4	QPSK	1	0	23.60	23.50	23.70
1.4	QPSK	1	2	23.60	23.50	23.70
1.4	QPSK	1	5	23.50	23.40	23.60
1.4	QPSK	3	0	23.50	23.40	23.60
1.4	QPSK	3	1	23.50	23.50	23.70
1.4	QPSK	3	2	23.60	23.40	23.70
1.4	QPSK	6	0	22.60	22.50	22.80
1.4	16QAM	1	0	22.60	22.60	22.80
1.4	16QAM	1	2	22.50	22.50	22.70
1.4	16QAM	1	5	22.50	22.50	22.70
1.4	16QAM	3	0	22.60	22.60	22.70
1.4	16QAM	3	1	22.60	22.60	22.70
1.4	16QAM	3	2	22.60	22.60	22.60
1.4	16QAM	6	0	21.70	21.60	21.80

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 13 of 128
Report Template No.: BU5-FGLTE Version 1.1

<LTE Band 13 Conducted Power>

BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Cha	nnel			23230	
	Frequen	cy (MHz)			782	
10	QPSK	1	0		<mark>22.90</mark>	
10	QPSK	1	24		22.60	
10	QPSK	1	49		22.80	
10	QPSK	25	0		21.50	
10	QPSK	25	12		21.50	
10	QPSK	25	24		21.70	
10	QPSK	50	0		21.40	
10	16QAM	1	0		21.80	
10	16QAM	1	24		21.60	
10	16QAM	1	49		21.90	
10	16QAM	25	0		20.40	
10	16QAM	25	12		20.50	
10	16QAM	25	24		20.60	
10	16QAM	50	0		20.40	
	Cha	nnel		23205	23230	23255
	Frequen	cy (MHz)		779.5	782	784.5
5	QPSK	1	0	22.70	22.50	22.88
5	QPSK	1	12	22.60	22.50	22.80
5	QPSK	1	24	22.50	22.80	22.85
5	QPSK	12	0	21.60	21.70	21.70
5	QPSK	12	6	21.60	21.60	21.70
5	QPSK	12	11	21.50	21.70	21.90
5	QPSK	25	0	21.50	21.50	21.60
5	16QAM	1	0	21.70	21.60	21.60
5	16QAM	1	12	21.60	21.50	21.80
5	16QAM	1	24	21.60	21.80	21.90
5	16QAM	12	0	20.70	20.70	20.70
5	16QAM	12	6	20.70	20.60	20.80
5	16QAM	12	11	20.60	20.70	20.90
5	16QAM	25	0	20.40	20.50	20.60

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 14 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.1.6 Test Result of Conducted Output Power and ERP/EIRP

	LTE Band 4 (GT - LC = 1.70 dB)						
Modes	LTE B	and 4 (QPSK,BW=	=1.4M)	LTE Ba	LTE Band 4 (16QAM,BW=1.4M)		
Channel	19957 (Low)	20175 (Mid)	20393 (High)	19957 (Low)	20175 (Mid)	20393 (High)	
Frequency (MHz)	1710.7	1732.5	1754.3	1710.7	1732.5	1754.3	
Conducted Power P _T (dBm)	23.6	23.5	23.7	22.6	22.6	22.8	
Conducted Power P _T (Watts)	0.23	0.22	0.23	0.18	0.18	0.19	
EIRP(dBm)	25.30	25.20	25.40	24.30	24.30	24.50	
EIRP(Watts)	0.34	0.33	0.35	0.27	0.27	0.28	

	LTE Band 4 (G _T - L _C = 1.70 dB)						
Modes	LTE E	Band 4 (QPSK,BW	/=3M)	LTE Band 4 (16QAM,BW=3M)			
Channel	19965(Low)	20175 (Mid)	20385 (High)	19965(Low)	20175 (Mid)	20385 (High)	
Frequency (MHz)	1711.5	1732.5	1753.5	1711.5	1732.5	1753.5	
Conducted Power P _T (dBm)	23.7	23.6	23.7	22.7	22.6	22.7	
Conducted Power P _T (Watts)	0.23	0.23	0.23	0.19	0.18	0.19	
EIRP(dBm)	25.40	25.30	25.40	24.40	24.30	24.40	
EIRP(Watts)	0.35	0.34	0.35	0.28	0.27	0.28	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 15 of 128
Report Template No.: BU5-FGLTE Version 1.1

	LTE Band 4 (G_T - L_C = 1.70 dB)						
Modes	LTE E	Band 4 (QPSK,BW	/=5M)	LTE B	LTE Band 4 (16QAM,BW=5M)		
Channel	19975(Low)	20175 (Mid)	20375 (High)	19975(Low)	20175 (Mid)	20375 (High)	
Frequency (MHz)	1712.5	1732.5	1752.5	1712.5	1732.5	1752.5	
Conducted Power P _T (dBm)	23.6	23.4	23.6	22.6	22.5	22.6	
Conducted Power P _T (Watts)	0.23	0.22	0.23	0.18	0.18	0.18	
EIRP(dBm)	25.30	25.10	25.30	24.30	24.20	24.30	
EIRP(Watts)	0.34	0.32	0.34	0.27	0.27	0.27	

	LTE Band 4 ($G_T - L_C = 1.70 \text{ dB}$)							
Modes	LTE B	and 4 (QPSK,BW	=10M)	LTE B	and 4 (16QAM,BW	/=10M)		
Channel	20000 (Low)	20175 (Mid)	20350 (High)	20000 (Low)	20175 (Mid)	20350 (High)		
Frequency (MHz)	1715	1732.5	1750	1715	1732.5	1750		
Conducted Power P _T (dBm)	23.5	23.5	23.6	22.5	22.5	22.7		
Conducted Power P _T (Watts)	0.22	0.22	0.23	0.18	0.18	0.19		
EIRP(dBm)	25.20	25.20	25.30	24.20	24.20	24.40		
EIRP(Watts)	0.33	0.33	0.34	0.26	0.26	0.28		

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 16 of 128
Report Template No.: BU5-FGLTE Version 1.1

	LTE Band 4 (GT - L _C = 1.70 dB)						
Modes	LTE B	and 4 (QPSK,BW:	=15M)	LTE Band 4 (16QAM,BW=15M)			
Channel	20025 (Low)	20175 (Mid)	20325 (High)	20025 (Low)	20175 (Mid)	20325 (High)	
Frequency (MHz)	1717.5	1732.5	1747.5	1717.5	1732.5	1747.5	
Conducted Power P _T (dBm)	23.6	23.5	23.6	22.6	22.5	22.5	
Conducted Power P _T (Watts)	0.23	0.22	0.23	0.18	0.18	0.18	
EIRP(dBm)	25.30	25.20	25.30	24.30	24.20	24.20	
EIRP(Watts)	0.34	0.33	0.34	0.27	0.27	0.27	

	LTE Band 4 (GT - L _C = 1.70 dB)						
Modes	LTE B	and 4 (QPSK,BW	=20M)	LTE B	and 4 (16QAM,BW	/=20M)	
Channel	20050 (Low)	20175 (Mid)	20300 (High)	20050 (Low)	20175 (Mid)	20300 (High)	
Frequency (MHz)	1720	1732.5	1745	1720	1732.5	1745	
Conducted Power P _T (dBm)	23.8	23.5	23.5	22.6	22.6	22.6	
Conducted Power P _T (Watts)	0.24	0.22	0.22	0.18	0.18	0.18	
EIRP(dBm)	25.50	25.20	25.20	24.30	24.30	24.30	
EIRP(Watts)	0.36	0.33	0.33	0.27	0.27	0.27	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 17 of 128
Report Template No.: BU5-FGLTE Version 1.1

	LTE Band 13 (GT - L _C = -0.40 dB)						
Modes	LTE B	and 13 (QPSK,BV	V=5M)	LTE B	LTE Band 13 (16QAM,BW=5M)		
Channel	23205 (Low)	23230 (Mid)	23255 (High)	23205 (Low)	23230 (Mid)	23255 (High)	
Frequency (MHz)	779.5	782	784.5	779.5	782	784.5	
Conducted Power P _T (dBm)	22.7	22.8	22.9	21.7	21.8	21.9	
Conducted Power P _T (Watts)	0.19	0.19	0.19	0.15	0.15	0.15	
ERP(dBm)	20.15	20.25	20.33	19.15	19.25	19.35	
ERP(Watts)	0.10	0.11	0.11	0.08	0.08	0.09	

	LTE Band 13 (GT - LC = -0.40 dB)						
Modes	LTE Band 13 (QPSK,BW=10M)	LTE Band 13 (16QAM,BW=10M)					
Channel	23230 (Mid)	23230 (Mid)					
Frequency (MHz)	782	782					
Conducted Power P _T (dBm)	22.9	21.9					
Conducted Power P _T (Watts)	0.19	0.15					
ERP(dBm)	20.35	19.35					
ERP(Watts)	0.11	0.09					

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 18 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum and system simulator via a power divider.
- Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- 3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
- 4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 19 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.2.5 Test Result of Peak-to-Average Ratio


	LTE Band 4					
BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Channel			20050	20175	20300
	Frequency (I	ИHz)		1720	1732.5	1745
20	16QAM	1	0	5.87	6.15	6.12
20	16QAM	100	0	6.41	6.44	6.41

			LTE E	Band 13		
BW [MHz]	Modulation	RB Size	RB Offset	Power (dBm) Low Ch. / Freq.	Power (dBm) Middle Ch. / Freq.	Power (dBm) High Ch. / Freq.
	Channel				23230	
	Frequency (ИHz)			782	
10	16QAM	1	0		6.25	
10	16QAM	50	0		6.31	

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 20 of 128


3.2.6 Peak to Average Power Ratio

Peak-to-Average Ratio on LTE Band 4 20MHz / 16QAM in Ch. 20050 (1RB Size)



Date: 24.APR.2014 22:38:54

Peak-to-Average Ratio on LTE Band 4 20MHz / 16QAM in Ch. 20175 (1RB Size)




Date: 24.APR.2014 22:36:21

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 21 of 128
Report Template No.: BU5-FGLTE Version 1.1

Peak-to-Average Ratio on LTE Band 4

20MHz / 16QAM in Ch. 20300 (1RB Size)



Date: 24.APR.2014 22:37:15

Peak-to-Average Ratio on LTE Band 4

20MHz / 16QAM in Ch. 20050 (100RB Size)



Complementary Cumulative Distribution Fur NOF samples: 100000, Usable BW: 23.7MHz


Mean Peak Crest	Trace 21.38 29.27 7.89	dBm dBm
10 %	3.01	dB
1 %	5.13	dB
.1 %	6.41	dB
.01 %	7.18	dB

Date: 24.APR.2014 22:35:41

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 22 of 128

Peak-to-Average Ratio on LTE Band 4


20MHz / 16QAM in Ch. 20175 (100RB Size)



Date: 24.APR.2014 22:36:47

Peak-to-Average Ratio on LTE Band 4

20MHz / 16QAM in Ch. 20300 (100RB Size)



Complementary Cumulative Distribution Fur NOF samples: 100000, Usable BW: 23.7MHz

Mean Peak Crest	Trace 21.31 28.71 7.40	$^{\tt dBm}_{\tt dBm}$
10 %	2.92	dB
1 %	5.13	dB
.1 %	6.41	dB
.01 %	7.08	dB

Date: 24.APR.2014 22:37:51

Report No. : FG432436-10B Report Version : Rev. 02 : 23 of 128 Page Number

Peak-to-Average Ratio on LTE Band 13

10MHz / 16QAM in Ch. 23230 (1RB Size)




Trace 1 22.12 dBm 28.77 dBm 6.65 dB Crest 2.95 dB 5.32 dB 6.25 dB 6.60 dB 10 % 1 % .1 % .01 %

Date: 25.APR.2014 00:21:24

Peak-to-Average Ratio on LTE Band 13

10MHz / 16QAM in Ch. 23230 (50RB Size)



Complementary Cumulative Distribution Function NOF samples: 100000, Usable BW: 11.2MHz

Trace 1 20.85 dBm 28.55 dBm 7.71 dB Mean Peak Crest 10 % 1 % .1 % 2.98 dB 5.10 dB 6.31 dB 7.12 dB

Date: 25.APR.2014 00:43:12

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 24 of 128

3.3 Occupied Bandwidth

3.3.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.3.4 Test Setup




Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 25 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.3.5 Test Result (Plots) of Occupied Bandwidth


Band: LTE Band 4 BW / Mod.: 1.4MHz / QPSK

99% Occupied Bandwidth Plot on Channel 19957



Date: 24.APR.2014 22:40:50


26dB Bandwidth Plot on Channel 19957



Date: 24.APR.2014 20:15:53


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 26 of 128
Report Template No.: BU5-FGLTE Version 1.1

99% Occupied Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:21:31


26dB Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:22:05


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 27 of 128

99% Occupied Bandwidth Plot on Channel 20393



Date: 24.APR.2014 20:24:37

26dB Bandwidth Plot on Channel 20393




Date: 24.APR.2014 20:25:11

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 28 of 128


Band: LTE Band 4 BW / Mod.: 1.4MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 19957



Date: 24.APR.2014 20:15:35


26dB Bandwidth Plot on Channel 19957



Date: 24.APR.2014 20:16:10


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 29 of 128

99% Occupied Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:21:47


26dB Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:22:22


Report No. : FG432436-10B Report Version : Rev. 02 : 30 of 128 Page Number

99% Occupied Bandwidth Plot on Channel 20393



Date: 24.APR.2014 20:24:53

26dB Bandwidth Plot on Channel 20393




Date: 24.APR.2014 20:25:28

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 31 of 128


Band: LTE Band 4 BW / Mod.: 3MHz / QPSK

99% Occupied Bandwidth Plot on Channel 19965



Date: 24.APR.2014 20:30:50


26dB Bandwidth Plot on Channel 19965



Date: 24.APR.2014 20:31:23


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 32 of 128

99% Occupied Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:37:03


26dB Bandwidth Plot on Channel 20175



Date: 24.APR.2014 20:37:36


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 33 of 128

99% Occupied Bandwidth Plot on Channel 20385



Date: 24.APR.2014 20:40:09

26dB Bandwidth Plot on Channel 20385




Date: 24.APR.2014 20:40:42

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 34 of 128


Band: LTE Band 4 BW / Mod.: 3MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 19965



Date: 24.APR.2014 20:31:06


26dB Bandwidth Plot on Channel 19965



Date: 24.APR.2014 20:31:41


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 35 of 128

99% Occupied Bandwidth Plot on Channel 20175




Date: 24.APR.2014 20:37:18

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 20:37:54

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 36 of 128



Date: 24.APR.2014 20:40:24

26dB Bandwidth Plot on Channel 20385




Date: 24.APR.2014 20:40:59

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 37 of 128


Band: LTE Band 4 BW / Mod.: 5MHz / QPSK

99% Occupied Bandwidth Plot on Channel 19975




Date: 24.APR.2014 20:46:20

26dB Bandwidth Plot on Channel 19975




Date: 24.APR.2014 20:46:53

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 38 of 128




Date: 24.APR.2014 20:52:34

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 20:53:07

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 39 of 128



Date: 24.APR.2014 20:55:40

26dB Bandwidth Plot on Channel 20375




Date: 24.APR.2014 20:56:13

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 40 of 128


Band: LTE Band 4 BW / Mod.: 5MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 19975




Date: 24.APR.2014 20:46:35

26dB Bandwidth Plot on Channel 19975




Date: 24.APR.2014 20:47:11

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 41 of 128




Date: 24.APR.2014 20:52:50

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 20:53:25

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 42 of 128



Date: 24.APR.2014 20:55:55

26dB Bandwidth Plot on Channel 20375




Date: 24.APR.2014 20:56:31

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 43 of 128


Band: LTE Band 4 BW / Mod.: 10MHz / QPSK

99% Occupied Bandwidth Plot on Channel 20000




Date: 24.APR.2014 21:01:52

26dB Bandwidth Plot on Channel 20000




Date: 24.APR.2014 21:02:25

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 44 of 128




Date: 24.APR.2014 21:08:03

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:08:36

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 45 of 128



Date: 24.APR.2014 21:11:08

26dB Bandwidth Plot on Channel 20350




Date: 24.APR.2014 21:11:41

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 46 of 128


Band: LTE Band 4 BW / Mod.: 10MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 20000




Date: 24.APR.2014 21:02:08

26dB Bandwidth Plot on Channel 20000




Date: 24.APR.2014 21:02:43

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 47 of 128




Date: 24.APR.2014 21:08:18

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:08:54

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 48 of 128



Date: 24.APR.2014 21:11:24

26dB Bandwidth Plot on Channel 20350




Date: 24.APR.2014 21:11:59

Report No. : FG432436-10B : Rev. 02 Report Version Page Number : 49 of 128


Band: LTE Band 4 BW / Mod.: 15MHz / QPSK

99% Occupied Bandwidth Plot on Channel 20025




Date: 24.APR.2014 21:17:20

26dB Bandwidth Plot on Channel 20025




Date: 24.APR.2014 21:17:53

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 50 of 128




Date: 24.APR.2014 21:23:31

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:24:05

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 51 of 128



Date: 24.APR.2014 21:26:37

26dB Bandwidth Plot on Channel 20325




Date: 24.APR.2014 21:27:11

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 52 of 128


Band: LTE Band 4 BW / Mod.: 15MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 20025




Date: 24.APR.2014 21:17:36

26dB Bandwidth Plot on Channel 20025




Date: 24.APR.2014 21:18:11

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 53 of 128




Date: 24.APR.2014 21:23:47

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:24:22

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 54 of 128



Date: 24.APR.2014 21:26:53

26dB Bandwidth Plot on Channel 20325




Date: 24.APR.2014 21:27:28

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 55 of 128


Band: LTE Band 4 BW / Mod.: 20MHz / QPSK

99% Occupied Bandwidth Plot on Channel 20050




Date: 24.APR.2014 21:32:50

26dB Bandwidth Plot on Channel 20050




Date: 24.APR.2014 21:33:23

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 56 of 128




Date: 24.APR.2014 21:39:01

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:39:34

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 57 of 128



Date: 24.APR.2014 21:42:07

26dB Bandwidth Plot on Channel 20300




Date: 24.APR.2014 21:42:40

Report No. : FG432436-10B Report Version : Rev. 02 : 58 of 128 Page Number


Band: LTE Band 4 BW / Mod.: 20MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 20050




Date: 24.APR.2014 21:33:06

26dB Bandwidth Plot on Channel 20050




Date: 24.APR.2014 21:33:41

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 59 of 128




Date: 24.APR.2014 21:39:16

26dB Bandwidth Plot on Channel 20175




Date: 24.APR.2014 21:39:52

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 60 of 128



Date: 24.APR.2014 21:42:23

26dB Bandwidth Plot on Channel 20300




Date: 24.APR.2014 21:42:58

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 61 of 128


Band: LTE Band 13 BW / Mod.: 5MHz / QPSK

99% Occupied Bandwidth Plot on Channel 23205




Date: 24.APR.2014 22:54:49

26dB Bandwidth Plot on Channel 23205




Date: 24.APR.2014 22:55:08

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 62 of 128




Date: 24.APR.2014 22:55:57

26dB Bandwidth Plot on Channel 23230




Date: 24.APR.2014 22:56:14

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 63 of 128



Date: 24.APR.2014 22:57:03

26dB Bandwidth Plot on Channel 23255




Date: 24.APR.2014 22:57:21

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 64 of 128


Band: LTE Band 13 BW / Mod.: 5MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 23205




Date: 24.APR.2014 22:55:24

26dB Bandwidth Plot on Channel 23205




Date: 24.APR.2014 22:55:41

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 65 of 128




Date: 24.APR.2014 22:56:30

26dB Bandwidth Plot on Channel 23230




Date: 24.APR.2014 22:56:48

Report No. : FG432436-10B Report Version : Rev. 02 : 66 of 128 Page Number



Date: 24.APR.2014 22:57:37

26dB Bandwidth Plot on Channel 23255




Date: 24.APR.2014 22:57:54

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 67 of 128


Band: LTE Band 13 BW / Mod.: 10MHz / QPSK

99% Occupied Bandwidth Plot on Channel 23230



Date: 24.APR.2014 22:58:10

26dB Bandwidth Plot on Channel 23230




Date: 24.APR.2014 22:58:28

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 68 of 128


Band: LTE Band 13 BW / Mod.: 10MHz / 16QAM

99% Occupied Bandwidth Plot on Channel 23230



Date: 24.APR.2014 22:58:43

26dB Bandwidth Plot on Channel 23230



Date: 24.APR.2014 22:59:01

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 69 of 128

3.4 Conducted Band Edge Measurement

3.4.1 Description of Conducted Band Edge Measurement

27.53 (c) for Band 13

For operations in the 776-788 MHz band, the FCC limit is 43 + $10\log_{10}(P[Watts])$ dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least 65 + 10 log10 p(watts), dB, for mobile and portable equipment.

27.53 (h) for Band 4

For operations in the 1710 - 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[Watts])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The band edges of low and high channels for the highest RF powers were measured. Set RBW
 = 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
- 3. Set spectrum analyzer with RMS detector.
- 4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 5. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)


```
= P(W)- [43 + 10log(P)] (dB)
```

= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

= -13dBm.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 70 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.4.4 Test Setup




Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 71 of 128

Test Result (Plots) of Conducted Band Edge 3.4.5

Band :	LTE Band 4	Band Width:	1.4MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 20:16:56


Lower Band Edge Plot for QPSK-RB Size 6, RB Offset 0



Date: 24.APR.2014 20:18:30


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 72 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 5



Date: 24.APR.2014 20:26:15

Higher Band Edge Plot for QPSK-RB Size 6, RB Offset 0



Date: 24.APR.2014 20:27:48

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 73 of 128

Band: LTE Band 4 **Band Width:** 1.4MHz / 16QAM

Lower Band Edge Plot for 16QAM -RB Size 1, RB Offset 0



Date: 24.APR.2014 20:17:43

Lower Band Edge Plot for 16QAM-RB Size 6, RB Offset 0



Date: 24.APR.2014 20:19:16


: FG432436-10B Report No. Report Version : Rev. 02 Page Number : 74 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 5



Date: 24.APR.2014 20:27:01

Higher Band Edge Plot for 16QAM-RB Size 6, RB Offset 0




Date: 24.APR.2014 20:28:34

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 75 of 128

Band: LTE Band 4 Band Width: 3MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 20:32:27

Lower Band Edge Plot for QPSK-RB Size 15, RB Offset 0



Date: 24.APR.2014 20:34:01


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 76 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 14



Date: 24.APR.2014 20:41:46

Higher Band Edge Plot for QPSK-RB Size 15, RB Offset 0



Date: 24.APR.2014 20:43:19

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 77 of 128


Band: LTE Band 4 Band Width: 3MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 24.APR.2014 20:33:14


Lower Band Edge Plot for 16QAM-RB Size 15, RB Offset 0



Date: 24.APR.2014 20:34:47


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 78 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 14



Date: 24.APR.2014 20:42:32

Higher Band Edge Plot for 16QAM-RB Size 15, RB Offset 0




Date: 24.APR.2014 20:44:05

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 79 of 128


Band: LTE Band 4 **Band Width:** 5MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 20:47:58

Lower Band Edge Plot for QPSK-RB Size 25, RB Offset 0



Date: 24.APR.2014 20:49:31

: FG432436-10B Report No. Report Version : Rev. 02 Page Number : 80 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 24



Date: 24.APR.2014 20:57:17

Higher Band Edge Plot for QPSK-RB Size 25, RB Offset 0




Date: 24.APR.2014 20:58:50

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 81 of 128


Band: LTE Band 4 Band Width: 5MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 24.APR.2014 20:48:45

Lower Band Edge Plot for 16QAM-RB Size 25, RB Offset 0



Date: 24.APR.2014 20:50:18

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 82 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 24



Date: 24.APR.2014 20:58:04

Higher Band Edge Plot for 16QAM-RB Size 25, RB Offset 0




Date: 24.APR.2014 20:59:37

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 83 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band: LTE Band 4 **Band Width:** 10MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:03:29


Lower Band Edge Plot for QPSK-RB Size 50, RB Offset 0



Date: 24.APR.2014 21:05:02


: FG432436-10B Report No. Report Version : Rev. 02 Page Number : 84 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 49



Date: 24.APR.2014 21:12:45

Higher Band Edge Plot for QPSK-RB Size 50, RB Offset 0




Date: 24.APR.2014 21:14:18

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 85 of 128


Band: LTE Band 4 Band Width: 10MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:04:15


Lower Band Edge Plot for 16QAM-RB Size 50, RB Offset 0



Date: 24.APR.2014 21:05:48


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 86 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 49



Date: 24.APR.2014 21:13:32

Higher Band Edge Plot for 16QAM-RB Size 50, RB Offset 0




Date: 24.APR.2014 21:15:05

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 87 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band: LTE Band 4 Band Width: 15MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:18:57


Lower Band Edge Plot for QPSK-RB Size 75, RB Offset 0



Date: 24.APR.2014 21:20:30

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 88 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 74



Date: 24.APR.2014 21:28:15

Higher Band Edge Plot for QPSK-RB Size 75, RB Offset 0




Date: 24.APR.2014 21:29:48

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 89 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band: LTE Band 4 Band Width: 15MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:19:43


Lower Band Edge Plot for 16QAM-RB Size 75, RB Offset 0



Date: 24.APR.2014 21:21:16


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 90 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 74



Date: 24.APR.2014 21:29:01

Higher Band Edge Plot for 16QAM-RB Size 75, RB Offset 0




Date: 24.APR.2014 21:30:34

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 91 of 128


Band: LTE Band 4 **Band Width:** 20MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:34:27


Lower Band Edge Plot for QPSK-RB Size 100, RB Offset 0



Date: 24.APR.2014 21:36:00


: FG432436-10B Report No. Report Version : Rev. 02 Page Number : 92 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 99



Date: 24.APR.2014 21:43:44

Higher Band Edge Plot for QPSK-RB Size 100, RB Offset 0




Date: 24.APR.2014 21:45:17

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 93 of 128


Band: LTE Band 4 Band Width: 20MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 24.APR.2014 21:35:13


Lower Band Edge Plot for 16QAM-RB Size 100, RB Offset 0



Date: 24.APR.2014 21:36:46


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 94 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 99



Date: 24.APR.2014 21:44:31

Higher Band Edge Plot for 16QAM-RB Size 100, RB Offset 0




Date: 24.APR.2014 21:46:04

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 95 of 128


Band: LTE Band 13 **Band Width:** 5MHz / QPSK

Lower Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 26.APR.2014 18:09:06


Lower Band Edge Plot for QPSK-RB Size 25, RB Offset 0



Date: 26.APR.2014 18:11:27


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 96 of 128

Higher Band Edge Plot for QPSK-RB Size 1, RB Offset 24



Date: 26.APR.2014 18:24:04

Higher Band Edge Plot for QPSK-RB Size 25, RB Offset 0




Date: 26.APR.2014 18:19:57

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 97 of 128


Band: LTE Band 13 **Band Width:** 5MHz / 16QAM

Lower Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 26.APR.2014 18:07:04


Lower Band Edge Plot for 16QAM-RB Size 25, RB Offset 0



Date: 26.APR.2014 18:13:46


Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 98 of 128

Higher Band Edge Plot for 16QAM-RB Size 1, RB Offset 24



Date: 26.APR.2014 18:26:34

Higher Band Edge Plot for 16QAM-RB Size 25, RB Offset 0




Date: 26.APR.2014 18:16:10

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 99 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band: LTE Band 13 Band Width: 10MHz / QPSK

Middle Band Edge Plot for QPSK-RB Size 1, RB Offset 0



Date: 26.APR.2014 17:51:56


Middle Band Edge Plot for QPSK-RB Size 50, RB Offset 0



Date: 26.APR.2014 18:00:59

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 100 of 128
Report Template No.: BU5-FGLTE Version 1.1

Middle Band Edge Plot for QPSK-RB Size 1, RB Offset 49




Date: 26.APR.2014 17:54:03

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 101 of 128


Band: LTE Band 13 Band Width: 10MHz / 16QAM

Middle Band Edge Plot for 16QAM-RB Size 1, RB Offset 0



Date: 26.APR.2014 17:49:30


Middle Band Edge Plot for 16QAM-RB Size 50, RB Offset 0



Date: 26.APR.2014 17:58:59

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 102 of 128
Report Template No.: BU5-FGLTE Version 1.1

Middle Band Edge Plot for 16QAM-RB Size 1, RB Offset 49



Date: 26.APR.2014 17:56:26

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 103 of 128

3.5 Conducted Spurious Emission Measurement

3.5.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)


```
= P(W) - [43 + 10log(P)] (dB)
```

= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

= -13dBm.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 104 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.5.4 Test Setup




Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 105 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.5.5 Test Result (Plots) of Conducted Spurious Emission


Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	1.4MHz		

QPSK (RB Size 1, RB Offset 0)



Date: 24.APR.2014 20:23:22

16QAM (RB Size 1, RB Offset 0)




Date: 24.APR.2014 20:24:21

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 106 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	3MHz		

QPSK (RB Size 1, RB Offset 0)



Date: 24.APR.2014 20:38:53

16QAM (RB Size 1, RB Offset 0)




Date: 24.APR.2014 20:39:53

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 107 of 128
Report Template No.: BU5-FGLTE Version 1.1


Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	5MHz		

QPSK (RB Size 1, RB Offset 0)



Date: 24.APR.2014 20:54:24


16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 20:55:24


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 108 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	10MHz		



Date: 24.APR.2014 21:09:53


16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 21:10:53


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 109 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	15MHz		



Date: 24.APR.2014 21:25:22


16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 21:26:22


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 110 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :	LTE Band 4	Channel:	CH20175 (Middle)
Band Width:	20MHz		



Date: 24.APR.2014 21:40:51


16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 21:41:51


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 111 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :	LTE Band 13	Channel:	CH23230 (Middle)
Band Width:	5MHz		



Date: 24.APR.2014 23:40:32


16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 23:41:22


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 112 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :	LTE Band 13	Channel:	CH23230 (Middle)
Band Width:	10MHz		



Date: 24.APR.2014 23:46:10

16QAM (RB Size 1, RB Offset 0)



Date: 24.APR.2014 23:47:10

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 113 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.6 Radiated Spurious Emission Measurement

3.6.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

- 1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

- = P(W)- [43 + 10log(P)] (dB)
- = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
- = -13dBm.
- 11. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 12. ERP (dBm) = EIRP 2.15


Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 114 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.6.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 115 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.6.5 Test Result of Field Strength of Spurious Radiated

Band :		LTE Band 4 Temperature : 21~24°C								
Test Mode	:	1.4MHz QPSK RB Size 1 Offset 0 Relative Humidity: 44~48%								
Test Engin	eer:	Stan Hsieh and Ken Wu Polarization : Horizontal								
Remark :	ark: Spurious emissions within 30-10th harmonic were found more than 20dB below limit line.								limit line.	
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result
			Limit	Reading	Powe	er loss	Gai	n		
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dB	i)	(H/V)	
3463	-45.5	7 -13	-32.57	-60.34	-49.4	4.48	8.3	1	Н	Pass
5195	-47.80	6 -13	-34.86	-67.18	-52.5	5.332	9.98	3	Н	Pass
6927	-41.90	6 -13	-28.96	-68.28	-47.2	6.1	11.3	4	Н	Pass

Band :		LTE Band 4	4			Temperature :		21~24°C	
Test Mode	:	1.4MHz QF	PSK RB	Size 1 Offs	et 0	Relative Humi	dity:	44~48%	
Test Engir	neer :	Stan Hsieh	and Ke	n Wu	ı	Polarization :		Vertical	
Remark :		Spurious e	missions	s within 30-	10th har	monic were for	und more	e than 20dB belo	w limit line.
Frequency	EIRE	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna Polarization	n Result
			Limit	Reading	Powe	r loss	Gair	า	
(MHz)	(dBn	n) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi) (H/V)	
3463	-44.2	7 -13	-31.27	-60.17	-48.1	4.48	8.31	V	Pass
5195	-48.5	6 -13	-35.56	-68.05	-53.2	5.332	9.98	3 V	Pass
6927	-42.9	6 -13	-29.96	-68.63	-48.2	6.1	11.3	4 V	Pass

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 116 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	4		1	Temperature :		21~24°C		
Test Mode	:	3MHz QPSK RB Size 1 Offset 0 Relative Humic						44~48%		
Test Engin	eer:	Stan Hsieh and Ken Wu Polarization : Horizontal								
Remark:		Spurious e	missions	within 30-	rmonic were fou	and more	e than 20dB be	low limit line.		
Frequency	EIRF	P Limit	Over	SPA	S.G.			enna Polarizati	on Result	
/ MILI- \	/ alDss) (dDm)	Limit	Reading	Powe		Gai			
(MHz)	(dBn	, , , ,	(dB)	(dBm)	(dBm	, ,	(dB	, , ,	ъ	
3462	-44.4	7 -13	-31.47	-59.29	-48.3	3 4.48	8.3	1 H	Pass	
5193	-49.4	6 -13	-36.46	-68.55	-54.1	1 5.332	9.98	3 H	Pass	
6924	-41.8	6 -13	-28.86	-68.25	-47.1	1 6.1	11.3	4 H	Pass	

Band :		LTE Band	4		l	Temperature :			21~24°C		
Test Mode	:	3MHz QPS	K RB Si	ze 1 Offset	0	Relative Humidity :			48%		
Test Engir	neer :	Stan Hsieh	and Kei	n Wu		Polarization :		Vert	ical		
Remark: Spurious emissions within 30-10th harmonic were found more than 20dB below limit							limit line.				
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	r loss	Gai	า			
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi)	(H/V)		
3462	-47.2	7 -13	-34.27	-63.13	-51.1	4.48	8.3		V	Pass	
5193	-51.0	6 -13	-38.06	-69.48	-55.7	5.332	9.98	3	V	Pass	
6924	-43.9	6 -13	-30.96	-69.14	-49.2	. 6.1	11.3	4	V	Pass	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 117 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	4			Temperature :	21~24°C			
Test Mode	:	5MHz QPS	SK RB Si	ze 1 Offset	0	Relative Humi	44~4	8%		
Test Engin	eer :	Stan Hsieh and Ken Wu Polarization : Horizontal								
Remark:		Spurious e	Spurious emissions within 30-10th harmonic were fo						20dB below	limit line.
Frequency	EIR	P Limit	Over	SPA	S.G				Polarization	Result
(MI I =)	/ alD as	·	Limit	Reading	Powe		Gai	-	(1100)	
(MHz)	(dBn	1) (dBm)	(dB)	(dBm)	(dBn	n) (dB)	(dB	l)	(H/V)	
3460	-45.4	7 -13	-32.47	-60.35	-49.3	3 4.48	8.3	1	Н	Pass
5190	-49.8	6 -13	-36.86	-68.58	-54.	5 5.332	9.98	3	Н	Pass
6920	-43.6	6 -13	-30.66	-69.08	-48.9	9 6.1	11.3	4	Н	Pass

Band :		LTE Band	4		ŀ	Temperature :		21~24°C		
Test Mode	:	5MHz QPS	K RB Si	ze 1 Offset	0	Relative Humi	dity :	44~48	3%	
Test Engir	neer :	Stan Hsieh	and Ke	n Wu		Polarization : Vertical			al	
Remark :		Spurious e	missions	within 30-	10th hai	rmonic were fo	und more	e than 2	20dB below	limit line.
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna P	olarization	Result
			Limit	Reading	Powe	r loss	Gaiı	n		
(MHz)	(dBn	n) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi	i)	(H/V)	
3460	-48.6	7 -13	-35.67	-64.12	-52.5	4.48	8.31	1	V	Pass
5190	-48.8	6 -13	-35.86	-68.28	-53.5	5.332	9.98	3	V	Pass
6920	-43.2	6 -13	-30.26	-67.9	-48.5	6.1	11.3	4	V	Pass

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 118 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	4			Temperature :		21~24°C		
Test Mode	:	10MHz QPSK RB Size 1 Offset 0 Relative Humidity: 44~48%								
Test Engin	eer :	Stan Hsieh and Ken Wu Polarization : Horizontal								
Remark :		Spurious e	missions	within 30-	10th hai	rmonic were fou	und more	e than	20dB below	limit line.
Frequency	EIR	P Limit	Over	SPA	S.G.				Polarization	Result
/ ** **	/ ID	·	Limit	Reading	Powe		Gai	-	4100	
(MHz)	(dBn	1) (dBm)	(dB)	(dBm)	(dBm	n) (dB)	(dBi)	(H/V)	
3455	-48.0	7 -13	-35.07	-62.38	-51.9	9 4.48	8.3	1	Н	Pass
5183	-49.9	6 -13	-36.96	-68.71	-54.6	5.332	9.98	3	Н	Pass
6910	-42.8	6 -13	-29.86	-68.32	-48.1	1 6.1	11.3	4	Н	Pass

Band :		LTE Band	4		1	Temperature :		21~24°C	
Test Mode	·:	10MHz QP	SK RB	Size 1 Offse	et 0	Relative Humi	dity:	44~48%	
Test Engir	neer :	Stan Hsieh	and Ke	n Wu	F	Polarization :		Vertical	
Remark:		Spurious e	missions	s within 30-	10th har	monic were for	und more	e than 20dB be	low limit line.
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna Polarizatio	on Result
			Limit	Reading	Powe	r loss	Gair	า	
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi) (H/V)	
3455	-48.3	7 -13	-35.37	-64.2	-52.2	4.48	8.31	V	Pass
5183	-50.4	6 -13	-37.46	-69.14	-55.1	5.332	9.98	8 V	Pass
6910	-43.8	6 -13	-30.86	-68.76	-49.1	6.1	11.3	4 V	Pass

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 119 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	4			Temperature :			21~24°C		
Test Mode	:	15MHz QP	SK RB S	Size 1 Offse	et O	Relative Humidity :			44~48%		
Test Engin	eer:	Stan Hsieh	and Ker	n Wu		Polarization : Horizontal					
Remark :		Spurious e	purious emissions within 30-10th harmonic were found mor						n 20dB below	limit line.	
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	er loss	Gai	n			
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm	n) (dB)	(dBi	i)	(H/V)		
3450	-47.3	7 -13	-34.37	-62.17	-51.2	2 4.48	8.3	1	Н	Pass	
5175	-50.1	6 -13	-37.16	-68.9	-54.8	5.332	9.98	3	Н	Pass	
6900	-42.9	6 -13	-29.96	-68.72	-48.2	2 6.1	11.3	4	Н	Pass	

Band :		LTE Band	4			Temperature :			21~24°C		
Test Mode	:	15MHz QF	SK RB	Size 1 Offse	et 0	Relative Humidity: 44			14~48%		
Test Engir	neer :	Stan Hsieh	and Ke	n Wu	ı	Polarization : Ve			cal		
Remark :		Spurious e	missions	s within 30-	10th hai	monic were for	und more	e thar	20dB below	limit line.	
Frequency	EIRF	P Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	r loss	Gair	n			
(MHz)	(dBm	n) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi	i)	(H/V)		
3450	-46.2	7 -13	-33.27	-65.84	-50.1	4.48	8.31	ĺ	V	Pass	
5175	-49.4	6 -13	-36.46	-68.17	-54.1	5.332	9.98	3	V	Pass	
6900	-44.3	6 -13	-31.36	-69.16	-49.6	6.1	11.3	4	V	Pass	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 120 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	4			Temperature :			21~24°C	
Test Mode	:	20MHz QP	SK RB S	Size 1 Offse	et O	Relative Humic	44~48%			
Test Engin	eer:	Stan Hsieh	and Ker	n Wu		Polarization : Horizontal			zontal	
Remark :		purious emissions within 30-10th harmonic were found mo						e thar	n 20dB below	limit line.
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result
			Limit	Reading	Powe	er loss	Gai	n		
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm	n) (dB)	(dBi	i)	(H/V)	
3445	-46.4	7 -13	-33.47	-61.23	-50.3	3 4.48	8.3	1	Н	Pass
5168	-49.5	6 -13	-36.56	-68.55	-54.2	5.332	9.98	3	Н	Pass
6890	-42.5	6 -13	-29.56	-68.2	-47.8	6.1	11.3	4	Н	Pass

Band :		LTE Band	4		ŀ	Temperature :			21~24°C		
Test Mode	:	20MHz QP	SK RB S	Size 1 Offse	et 0	Relative Humidity :			44~48%		
Test Engir	neer :	Stan Hsieh	and Ke	n Wu		Polarization : Vert			ical		
Remark :		Spurious e	missions	s within 30-	10th hai	rmonic were fo	und more	e tha	n 20dB below	limit line.	
Frequency	EIRF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	r loss	Gaiı	า			
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi)	(H/V)		
3445	-49.3	7 -13	-36.37	-65.35	-53.2	4.48	8.31		V	Pass	
5168	-50.1	6 -13	-37.16	-68.91	-54.8	5.332	9.98	3	V	Pass	
6890	-43.2	6 -13	-30.26	-68.8	-48.5	6.1	11.3	4	V	Pass	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 121 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	13			Temperature :			21~24°C		
Test Mode	:	5MHz QPS	K RB Si	ze 1 Offset	0	Relative Humidity :			44~48%		
Test Engir	neer :	Stan Hsieh	and Ker	n Wu		Polarization : Horizontal			zontal		
Remark :		Spurious e	missions	within 30-	10th ha	rmonic were fo	und mor	e tha	n 20dB below	limit line.	
Frequency	ERP	Limit	Over	SPA	S.G.	. TX Cable	TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	er loss	Gai	n			
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm	n) (dB)	(dB	i)	(H/V)		
1558	-52.0	2 -13	-39.02	-58.29	-53.8	5 1.51	5.49	9	Н	Pass	
1559	-55.0	6 -42.15	-12.91	-60.29	-56.9	9 1.51	5.50)	Н	Pass	
2341	-55.7	7 -13	-42.77	-66.06	-57.6	9 1.98	6.0	5	Н	Pass	

-58.63

2.39

7.56

Н

Pass

3119

-55.61

-13

-42.61

-67.12

Band :		LTE Band	13			Temperature :		21~24°C	
Test Mode	:	5MHz QPS	SK RB S	ize 1 Offset	0 I	Relative Humidity :		44~48%	
Test Engir	neer :	Stan Hsieh	and Ke	n Wu	ı	Polarization : Vertical			
Remark :		Spurious e	mission	s within 30-	10th har	monic were fo	und more	e than 20dB below	/ limit line.
Frequency	ERF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna Polarization	Result
			Limit	Reading	Powe	r loss	Gaiı	า	
(MHz)	(dBn	n) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi) (H/V)	
1558	-53.7	2 -13	-40.72	-62.11	-55.55	1.51	5.49) V	Pass
1559	-55.6	8 -42.15	-13.53	-63.11	-57.52	2 1.51	5.50) V	Pass
2341	-54.5	7 -13	-41.57	-65.88	-56.49	1.98	6.05	5 V	Pass
3118	-53.8	4 -13	-40.84	-67.28	-56.86	3 2.39	7.56	S V	Pass

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 122 of 128
Report Template No.: BU5-FGLTE Version 1.1

Band :		LTE Band	13		1	Temperature :			21~24°C		
Test Mode	:	10MHz QF	SK RB	Size 1 Offse	et O	Relative Humidity :			44~48%		
Test Engin	eer :	Stan Hsieh	and Ke	n Wu		Polarization :			zontal		
Remark :	Remark: Spurious emissions within 30-10th I					rmonic were fo	und more	e tha	n 20dB below	limit line.	
Frequency	ERP	Limit	Over	SPA	S.G.		TX Ante	enna	Polarization	Result	
			Limit	Reading	Powe	er loss	Gai	n			
(MHz)	(dBm) (dBm)	(dB)	(dBm)	(dBm	n) (dB)	(dB	i)	(H/V)		
1555	-51.03	3 -13	-38.03	-59.96	-52.8	6 1.51	5.49	9	Н	Pass	
1594	-58.2	5 -42.15	-16.10	-65.81	-60.0	5 1.63	5.58	3	Н	Pass	

-55.67

-56.34

1.98

2.39

6.05

7.56

Н

Н

Pass

Pass

-40.75

-40.32

-67.04

-67.81

2332

3110.72

-53.75

-53.32

-13

-13

Band :		LTE Band	13		•	Temperature :		21~24°C		
Test Mode	::	10MHz QF	SK RB	Size 1 Offse	et 0	Relative Humi	dity :	44~48%		
Test Engir	neer :	Stan Hsieh	and Ke	n Wu		Polarization : Vertical				
Remark :		Spurious e	mission	s within 30-	10th ha	rmonic were fo	und more	e than 20dB below	/ limit line.	
Frequency	ERF	Limit	Over	SPA	S.G.	TX Cable	TX Ante	enna Polarization	Result	
			Limit	Reading	Powe	er loss	Gaiı	า		
(MHz)	(dBm	n) (dBm)	(dB)	(dBm)	(dBm) (dB)	(dBi) (H/V)		
1555	-52.4	9 -13	-39.49	-63.73	-54.3	2 1.51	5.49) V	Pass	
1579	-55.6	8 -42.15	-13.53	-65.39	-57.4	6 1.6	5.53	8 V	Pass	
2333.04	-52.0	7 -13	-39.07	-67.08	-53.9	9 1.98	6.05	5 V	Pass	
3110.72	-49.4	2 -13	-36.42	-67.23	-52.4	4 2.39	7.56	S V	Pass	

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 123 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.7.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the system simulator.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
- 2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 124 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.7.6 Test Result of Temperature Variation (FCC)

	BW 10MHz			
Temperature (°C)	Deviation (ppm)	Result		
50	0.0086			
40	0.0099			
30	0.0110			
20(Ref.)	0.0000			
10	0.0041	PASS		
0	0.0012			
-10	N/A – note			
-20	N/A – note			
-30	N/A – note			

Band :	LTE Band 13 (QPSK)	Limit (ppm):	2.5
--------	--------------------	--------------	-----

	BW 10MHz	
Temperature (°C)	Deviation (ppm)	Result
50	0.0013	
40	0.0044	
30	0.0102	
20(Ref.)	0.0000	
10	0.0032	PASS
0	0.0084	
-10	N/A – note	
-20	N/A – note	
-30	N/A – note	

Note: Device does not turn on, no transmission of signal.

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 125 of 128
Report Template No.: BU5-FGLTE Version 1.1

3.7.7 Test Result of Voltage Variation (FCC)

Band	Bandwidth	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
		4.2	0.0012		
LTE Band 4	10M	Normal	0.0085	2.5	PASS
		3.4	0.0118		
		4.2	0.0044		
LTE Band 13	10M	Normal	0.0047	2.5	PASS
		3.4	0.0027		

Remark:

- 1. Normal Voltage = 3.7V.
- 2. The manufacturer declared that the EUT could work properly between voltage $3.4V \sim 4.2V$.

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 126 of 128 Report Template No.: BU5-FGLTE Version 1.1

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201026480	30MHz~2.7GHz	Jan. 07, 2014	Apr. 24, 2014 ~ Apr. 26, 2014	Jan. 06, 2015	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Apr. 24, 2014 ~ Apr. 26, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 19, 2013	Apr. 24, 2014 ~ Apr. 26, 2014	Jul. 18, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	Apr. 14, 2014 ~ Apr. 17, 2014	Feb. 09, 2015	Radiation (03CH07-HY
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Apr. 14, 2014 ~ Apr. 17, 2014	Oct. 09, 2014	Radiation (03CH07-HY
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 22, 2013	Apr. 14, 2014 ~ Apr. 17, 2014	Aug. 21, 2014	Radiation (03CH07-HY
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz	Mar. 17, 2014	Apr. 14, 2014 ~ Apr. 17, 2014	Mar. 16, 2015	Radiation (03CH07-HY
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	Apr. 14, 2014 ~ Apr. 17, 2014	Nov. 28, 2014	Radiation (03CH07-HY
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Apr. 14, 2014 ~ Apr. 17, 2014	N/A	Radiation (03CH07-HY
Antenna Mast	ChainTek	M-400-0	114/8000604	N/A	N/A	Apr. 14, 2014 ~ Apr. 17, 2014	N/A	Radiation (03CH07-HY
SHF-EHF Horn Antenna	SCHWARZBEC K	BBHA 9170	BBHA91702 51	15GHz- 40GHz	Oct. 03, 2013	Apr. 14, 2014 ~ Apr. 17, 2014	Oct. 02, 2014	Radiation (03CH07-HY

Report No. : FG432436-10B Report Version : Rev. 02 Page Number : 127 of 128 Report Template No.: BU5-FGLTE Version 1.1

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	4.50
Confidence of 95% (U = 2Uc(y))	4.50

Report No. : FG432436-10B
Report Version : Rev. 02
Page Number : 128 of 128

Report Template No.: BU5-FGLTE Version 1.1