

# FCC Radio Test Report

## FCC ID: 2ABQOAMK-S2-02B


### Original Grant

**Report No.** : TB-FCC143182  
**Applicant** : Dongguan Meiluodi Electronics Co., Ltd  
**Equipment Under Test (EUT)**  
**EUT Name** : Bluetooth speaker  
**Model No.** : AMK-S2-02B  
**Brand Name** : MEILUODI  
**Receipt Date** : 2015-01-26  
**Test Date** : 2015-01-26 to 2014-01-29  
**Issue Date** : 2015-01-30  
**Standards** : FCC Part 15: 2014, Subpart C(15.247)  
**Test Method** : ANSI C63.4:2003  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :



**Approved& Authorized** :

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting .....	8
1.7 Test Facility.....	8
<b>2. TEST SUMMARY.....</b>	<b>9</b>
<b>3. CONDUCTED EMISSION TEST .....</b>	<b>10</b>
3.1 Test Standard and Limit.....	10
3.2 Test Setup.....	10
3.3 Test Procedure.....	10
3.4 Test Equipment Used.....	11
3.5 EUT Operating Mode .....	11
3.6 Test Data.....	11
<b>4. RADIATED EMISSION TEST .....</b>	<b>14</b>
4.1 Test Standard and Limit.....	14
4.2 Test Setup.....	15
4.3 Test Procedure.....	16
4.4 EUT Operating Condition .....	16
4.5 Test Equipment .....	17
<b>5. RESTRICTED BANDS REQUIREMENT .....</b>	<b>32</b>
5.1 Test Standard and Limit.....	32
5.2 Test Setup.....	32
5.3 Test Procedure.....	32
5.4 EUT Operating Condition .....	33
5.5 Test Equipment .....	33
<b>6. NUMBER OF HOPPING CHANNEL .....</b>	<b>46</b>
6.1 Test Standard and Limit.....	46
6.2 Test Setup.....	46
6.3 Test Procedure.....	46
6.4 EUT Operating Condition .....	46
6.5 Test Equipment .....	46
6.6 Test Data.....	46
<b>7. AVERAGE TIME OF OCCUPANCY.....</b>	<b>48</b>
7.1 Test Standard and Limit.....	48
7.2 Test Setup.....	48
7.3 Test Procedure.....	48

---



---

7.4 EUT Operating Condition .....	48
7.5 Test Equipment .....	48
7.6 Test Data .....	49
<b>8. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>61</b>
8.1 Test Standard and Limit .....	61
8.2 Test Setup .....	61
8.3 Test Procedure .....	61
8.4 EUT Operating Condition .....	61
8.5 Test Equipment .....	62
8.6 Test Data .....	62
<b>9. PEAK OUTPUT POWER TEST .....</b>	<b>70</b>
9.1 Test Standard and Limit .....	70
9.2 Test Setup .....	70
9.3 Test Procedure .....	70
9.4 EUT Operating Condition .....	70
9.5 Test Equipment .....	70
9.6 Test Data .....	70
<b>10. ANTENNA REQUIREMENT .....</b>	<b>75</b>
10.1 Standard Requirement .....	75
10.2 Antenna Connected Construction .....	75
10.2 Result .....	75

# 1. General Information about EUT

## 1.1 Client Information

**Applicant** : DongGuan Meiluodi Electronics Co., Ltd  
**Address** : No.16, Zhenxing Road, Shangjiao, Chang'an, Dongguan, Guangdong, 523876 China  
**Manufacturer** : DongGuan Meiluodi Electronics Co., Ltd  
**Address** : No.16, Zhenxing Road, Shangjiao, Chang'an, Dongguan, Guangdong, 523876 China

## 1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Bluetooth speaker	
Models No.	:	AMK-S2-02B	
Brand Name	:	MEILUODI	
Product Description	:	Operation Frequency: Bluetooth:2402~2480MHz	
		Number of Channel:	Bluetooth:79 Channels see note (2)
		Max Peak Output Power:	GFSK: 2.559dBm (Conducted Power)
		Antenna Gain:	0 dBi PCB Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) $\pi$ /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC power supplied by AC/DC Adapter DC Voltage supplied from Li-ion battery.	
Power Rating	:	Input: AC 100~240V 50/60Hz 0.2A Output: 5V 1A DC 3.7V 1000mAh from Li-ion battery	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

### Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) This Test Report is FCC Part 15.247 for Bluetooth, and test procedure in accordance with Public Notice: DA 00-705.
- (3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457

02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	<b>39</b>	<b>2441</b>	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	<b>78</b>	<b>2480</b>
25	2427	52	2454		
26	2428	53	2455		

(4) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### TX Mode



### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/DOC	Manufacturer	Used “√”
/	/	/	/	/
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	NO	0.8M	Accessories

### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	AC Charging with TX GFSK Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	AC Charging with TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode( $\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode( $\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test mode above.  
According to ANSI C63.4 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
TX Mode: GFSK (1 Mbps)  
TX Mode: 8-DPSK (3 Mbps)
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	BK3256 RF Test – V1.3		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

## 1.7 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **FCC List No.: (811562)**

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.207	Conducted Emission	PASS	N/A
15.205	Restricted Bands	PASS	N/A
15.247(a)(1)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	Dwell Time	PASS	N/A
15.247(b)(1)	Peak Output Power	PASS	N/A
15.247(b)(1)	Number of Hopping Frequency	PASS	N/A
15.247(c)	Radiated Spurious Emission	PASS	N/A
15.247(c)	Antenna Conducted Spurious Emission	PASS	N/A
15.247(a)	20dB Bandwidth	PASS	N/A
<b>Note:</b> N/A is an abbreviation for Not Applicable.			

### 3. Conducted Emission Test

#### 3.1 Test Standard and Limit

##### 3.1.1 Test Standard

FCC Part 15.207

##### 3.1.2 Test Limit

**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 3.2 Test Setup



#### 3.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 3.4 Test Equipment Used

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	Aug. 08, 2014	Aug.07, 2015
50ΩCoaxial Switch	Anritsu	MP59B	X10321	Aug. 08, 2014	Aug.07, 2015
L.I.S.N	Rohde & Schwarz	ENV216	101131	Aug. 08, 2014	Aug.07, 2015
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 08, 2014	Aug.07, 2015


### 3.5 EUT Operating Mode

Please refer to the description of test mode.

### 3.6 Test Data

Please see the next page.


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	AC Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.3620	42.66	10.02	52.68	58.68	-6.00	QP
2	*	0.3620	35.09	10.02	45.11	48.68	-3.57	AVG
3		1.0780	38.65	10.06	48.71	56.00	-7.29	QP
4		1.0780	30.68	10.06	40.74	46.00	-5.26	AVG
5		1.7940	32.69	10.06	42.75	56.00	-13.25	QP
6		1.7940	24.32	10.06	34.38	46.00	-11.62	AVG
7		2.4580	17.54	10.04	27.58	56.00	-28.42	QP
8		2.4580	7.35	10.04	17.39	46.00	-28.61	AVG
9		4.9780	19.54	9.96	29.50	56.00	-26.50	QP
10		4.9780	7.36	9.96	17.32	46.00	-28.68	AVG
11		16.1220	30.92	10.24	41.16	60.00	-18.84	QP
12		16.1220	18.37	10.24	28.61	50.00	-21.39	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	AC Charging with TX GFSK Mode 2402 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.3620	35.19	10.02	45.21	58.68	-13.47	QP
2	*	0.3620	25.68	10.02	35.70	48.68	-12.98	AVG
3		1.0820	30.90	10.06	40.96	56.00	-15.04	QP
4		1.0820	21.51	10.06	31.57	46.00	-14.43	AVG
5		1.8100	26.90	10.06	36.96	56.00	-19.04	QP
6		1.8100	18.08	10.06	28.14	46.00	-17.86	AVG
7		2.5340	26.55	10.04	36.59	56.00	-19.41	QP
8		2.5340	17.22	10.04	27.26	46.00	-18.74	AVG
9		4.3340	24.71	9.98	34.69	56.00	-21.31	QP
10		4.3340	15.62	9.98	25.60	46.00	-20.40	AVG
11		15.3740	23.48	10.25	33.73	60.00	-26.27	QP
12		15.3740	11.64	10.25	21.89	50.00	-28.11	AVG

**Emission Level= Read Level+ Correct Factor**

## 4. Radiated Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.209

#### 4.1.2 Test Limit

##### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

##### Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54

**Note:**


(1) The tighter limit applies at the band edges.

(2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


## 4.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

### 4.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

### 4.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.



## 4.5 Test Equipment


Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug.07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug.07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

## 4.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 kHz with Peak Detector for Average Values.

Test data please refer the following pages.

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		94.4284	54.33	-22.30	32.03	43.50	-11.47	peak
2		162.0414	45.65	-20.65	25.00	43.50	-18.50	peak
3		189.0743	51.93	-20.88	31.05	43.50	-12.45	peak
4		232.5318	45.27	-18.96	26.31	46.00	-19.69	peak
5		396.2415	44.40	-13.05	31.35	46.00	-14.65	peak
6	*	473.8347	56.58	-11.64	44.94	46.00	-1.06	peak

\*:Maximum data x:Over limit !:over margin

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		33.7986	42.99	-16.31	26.68	40.00	-13.32	peak
2		44.4308	50.05	-22.04	28.01	40.00	-11.99	peak
3		47.9940	50.86	-23.54	27.32	40.00	-12.68	peak
4		66.2662	57.76	-23.96	33.80	40.00	-6.20	peak
5	*	94.7600	64.35	-22.28	42.07	43.50	-1.43	peak
6		191.0738	48.17	-20.86	27.31	43.50	-16.19	peak

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.066	41.46	8.18	49.64	54.00	-4.36	AVG
2		4804.315	50.90	8.18	59.08	74.00	-14.92	peak

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.904	50.18	8.18	58.36	74.00	-15.64	peak
2	*	4803.904	41.58	8.18	49.76	54.00	-4.24	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.901	51.73	8.21	59.94	74.00	-14.06	peak
2	*	4881.997	43.34	8.21	51.55	54.00	-2.45	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.862	49.81	8.21	58.02	74.00	-15.98	peak
2	*	4881.883	40.36	8.21	48.57	54.00	-5.43	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.928	43.83	8.23	52.06	54.00	-1.94	AVG
2		4960.027	52.31	8.23	60.54	74.00	-13.46	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.970	39.21	8.23	47.44	54.00	-6.56	AVG
2		4960.135	49.64	8.23	57.87	74.00	-16.13	peak

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.760	50.61	8.18	58.79	74.00	-15.21	peak
2	*	4803.880	41.23	8.18	49.41	54.00	-4.59	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.720	51.32	8.18	59.50	74.00	-14.50	peak
2	*	4803.955	39.92	8.18	48.10	54.00	-5.90	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.510	52.11	8.21	60.32	74.00	-13.68	peak
2	*	4881.870	43.10	8.21	51.31	54.00	-2.69	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.780	41.53	8.21	49.74	54.00	-4.26	AVG
2		4881.870	50.35	8.21	58.56	74.00	-15.44	peak

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.670	52.32	8.23	60.55	74.00	-13.45	peak
2	*	4959.905	43.79	8.23	52.02	54.00	-1.98	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4959.465	51.02	8.23	59.25	74.00	-14.75	peak
2	*	4959.830	40.14	8.23	48.37	54.00	-5.63	AVG

Emission Level= Read Level+ Correct Factor

## 5. Restricted Bands Requirement

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard


FCC Part 15.209

FCC Part 15.205

#### 5.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBUV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54
<b>Note: All restriction bands have been tested, only the worst case is reported.</b>		

### 5.2 Test Setup



### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked



and then Quasi Peak detector mode re-measured.

- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

## 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 5.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015
Spectrum Analyzer	Rohde & Schwarz	FSP30	DE25181	Aug. 08, 2014	Aug. 07, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	101165	Aug. 08, 2014	Aug.07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 07, 2014	Mar.06, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	11909A	185903	Mar. 07, 2014	Mar.06, 2015
Pre-amplifier	HP	8447B	3008A00849	Mar. 07, 2014	Mar.06, 2015
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 07, 2014	Mar.06, 2015
Signal Generator	Rohde & Schwarz	SML03	IKW682-054	Feb. 11, 2014	Feb.10, 2015
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A


## 5.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 KHz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

**(1) Radiation Test**


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	55.17	0.77	55.94	74.00	-18.06	peak
2		2390.000	37.08	0.77	37.85	54.00	-16.15	AVG
3	*	2402.100	86.17	0.82	86.99	Fundamental Frequency		AVG
4	X	2402.300	88.37	0.82	89.19	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**


EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	51.50	0.77	52.27	74.00	-21.73 peak
2		2390.000	35.15	0.77	35.92	54.00	-18.08 AVG
3	*	2402.100	85.36	0.82	86.18	Fundamental Frequency AVG	
4	X	2402.200	87.15	0.82	87.97	Fundamental Frequency peak	

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.700	90.17	1.15	91.32	Fundamental Frequency		peak
2	*	2479.900	88.25	1.15	89.40	Fundamental Frequency		AVG
3		2483.500	66.37	1.17	67.54	74.00	-6.46	peak
4		2483.500	47.67	1.17	48.84	54.00	-5.16	AVG

**Emission Level= Read Level+ Correct Factor**


EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV		dB/m	dBuV/m	dB	Detector
1	*	2479.900	86.37	1.15	87.52	Fundamental Frequency		AVG
2	X	2480.000	88.61	1.15	89.76	Fundamental Frequency		peak
3		2483.500	65.06	1.17	66.23	74.00	-7.77	peak
4		2483.500	45.83	1.17	47.00	54.00	-7.00	AVG

Emission Level= Read Level+ Correct Factor


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	59.09	0.77	59.86	74.00	-14.14	peak
2		2390.000	34.75	0.77	35.52	54.00	-18.48	AVG
3	X	2401.800	88.36	0.82	89.18	Fundamental Frequency		peak
4	*	2402.000	81.24	0.82	82.06	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**


<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	50.16	0.77	50.93	74.00	-23.07	peak
2		2390.000	33.37	0.77	34.14	54.00	-19.86	AVG
3	X	2402.000	86.93	0.82	87.75	Fundamental Frequency		peak
4	*	2402.200	79.86	0.82	80.68	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	89.71	1.15	90.86	Fundamental Frequency		peak
2	*	2480.000	82.33	1.15	83.48	Fundamental Frequency		AVG
3		2483.500	67.34	1.17	68.51	74.00	-5.49	peak
4		2483.500	45.96	1.17	47.13	54.00	-6.87	AVG

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	N/A		





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.600	88.23	1.15	89.38	Fundamental Frequency		peak
2	*	2479.900	81.18	1.15	82.33	Fundamental Frequency		AVG
3		2483.500	67.25	1.17	68.42	74.00	-5.58	peak
4		2483.500	44.98	1.17	46.15	54.00	-7.85	AVG



**Emission Level= Read Level+ Correct Factor**

**(1) Conducted Test**



<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz / 2480 MHz		
<b>Remark:</b>	N/A		





EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	GFSK Hopping Mode		
Remark:	N/A		



EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 8-DPSK Mode 2402MHz / 2480 MHz		
Remark:	N/A		



EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	8-DPSK Hopping Mode		
Remark:	N/A		



## 6. Number of Hopping Channel

### 6.1 Test Standard and Limit


#### 6.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 6.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.


### 6.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015


### 6.6 Test Data

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode (GFSK/ 8-DPSK)		
Frequency Range	Quantity of Hopping Channel	Limit	
2402MHz~2480MHz	79	>15	
	79		

### GFSK Mode



### 8-DPSK Mode



## 7. Average Time of OcCupancy

### 7.1 Test Standard and Limit


#### 5.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 5.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of OcCupancy	0.4 sec

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

### 7.5 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015



## 7.6 Test Data

EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (GFSK DH1)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result		
2402	0.420	134.40	31.60	400	PASS		
2441	0.420	134.40					
2480	0.410	131.20					
GFSK Hopping Mode DH1							
2402 MHz							

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 420 μs  
-1.447 dB

Peak  
Log  
10  
dB/

Marker Δ  
420.000000 μs  
-1.447 dB

W1 S2  
S3 FS  
AA


Center 2.402 GHz  
Res BW 1 MHz

#VBW 1 MHz

Span 0 Hz  
Sweep 4 ms (401 pts)


**GFSK Hopping Mode DH1**

**2441 MHz**



**GFSK Hopping Mode DH1**

**2480 MHz**



EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (GFSK DH3)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result	
2402	1.720	275.20		31.60	400	PASS	
2441	1.720	275.20					
2480	1.740	278.40					

GFSK Hopping Mode DH3

2402 MHz

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 1.72 ms  
-1.056 dB

Peak

Log

10

dB/

Marker Δ

1.72000000 ms

-1.056 dB

W1 S2

S3 FS

AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Span 0 Hz

Sweep 8 ms (401 pts)


### GFSK Hopping Mode DH3

2441 MHz



### GFSK Hopping Mode DH3

2480 MHz



EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (GFSK DH5)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result	
2402	2.880	307.20		31.60	400	PASS	
2441	2.880	307.20					
2480	3.030	323.20					

GFSK Hopping Mode DH5

2402 MHz

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 2.88 ms  
-1.684 dB

Peak Log 10 dB/

Marker Δ 2.880000000 ms  
-1.684 dB

W1 S2

S3 FS

AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Span 0 Hz

Sweep 12 ms (401 pts)


### GFSK Hopping Mode DH5

2441 MHz



### GFSK Hopping Mode DH5

2480 MHz



EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (8-DPSK DH1)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result		
2402	0.430	137.60	31.60	400			
2441	0.420	134.40					
2480	0.400	128.00					
8-DPSK Hopping Mode DH1							
2402 MHz							

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 430 μs  
-1.763 dB

Peak

Log

10

dB/

Marker Δ

430.000000 μs

-1.763 dB

W1 S2

S3 FS

AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Span 0 Hz

Sweep 4 ms (401 pts)


**8-DPSK Hopping Mode DH1**

**2441 MHz**



**8-DPSK Hopping Mode DH1**

**2480 MHz**





EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (8-DPSK DH3)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result	
2402	1.720	275.20		31.60	400	PASS	
2441	1.740	278.40					
2480	1.720	275.20					

8-DPSK Hopping Mode DH3

2402 MHz

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 1.72 ms  
0.011 dB

Peak Log 10 dB/

Marker Δ 1.72000000 ms  
0.011 dB

W1 S2  
S3 FS  
AA


Center 2.402 GHz  
Res BW 1 MHz

#VBW 1 MHz

Span 0 Hz  
Sweep 8 ms (401 pts)


### 8-DPSK Hopping Mode DH3

2441 MHz



### 8-DPSK Hopping Mode DH3

2480 MHz



EUT:		Bluetooth speaker		Model Name :		AMK-S2-02B	
Temperature:		25 °C		Relative Humidity:		55%	
Test Voltage:		DC 3.7V					
Test Mode:		Hopping Mode (8-DPSK DH5)					
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result	
2402	2.880	307.20		31.60	400	PASS	
2441	2.880	307.20					
2480	2.880	307.20					
8-DPSK Hopping Mode DH5							
2402 MHz							

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 2.88 ms  
-0.189 dB

Peak

Log

10

dB/

Marker Δ

2.880000000 ms

-0.189 dB

W1 S2

S3 FS

AA

Center 2.402 GHz

Res BW 1 MHz


#VBW 1 MHz

Span 0 Hz

Sweep 12 ms (401 pts)


**8-DPSK Hopping Mode DH5**

**2441 MHz**



**8-DPSK Hopping Mode DH5**

**2480 MHz**



## 8. Channel Separation and Bandwidth Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247

#### 8.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25$ KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=30 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.


### 8.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

## 8.5 Test Equipment


Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

## 8.6 Test Data

<b>EUT:</b>	Bluetooth speaker	<b>Model Name :</b>	AMK-S2-02B
<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	958.3124	1047.00	698.00
2441	969.1948	1098.00	732.00
2480	960.0082	1089.00	726.00
<b>GFSK TX Mode</b>			
<b>2402 MHz</b>			
			


**GFSK TX Mode**

**2441 MHz**




**GFSK TX Mode**

**2480 MHz**



EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1538.70	1341.00	894.00
2441	1342.00	1342.00	894.67
2480	1351.30	1326.00	884.00


8-DPSK TX Mode  
2402 MHz






**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**


**2480 MHz**






### GFSK Hopping Mode

2441 MHz



### GFSK Hopping Mode

2480 MHz



EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	Hopping Mode (8-DPSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	1020.00	894.00	
2441	1020.00	894.67	
2480	1005.00	884.00	
8-DPSK Hopping Mode			
2402 MHz			

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 Δ 1.0200 MHz  
1.01 dB

Peak

Log

10

dB/

Marker Δ  
1.020000 MHz  
1.01 dB

Center 2.402 GHz

#Res BW 30 kHz

#VBW 100 kHz


Span 3 MHz

Sweep 5 ms (401 pts)

Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Freq	2.4018025 GHz	-4.862 dBm
1Δ	(1)	Freq	1.0200 MHz	1.01 dB


### 8-DPSK Hopping Mode

2441 MHz



### 8-DPSK Hopping Mode

2480 MHz



## 9. Peak Output Power Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.  
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 9.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 9.5 Test Equipment

Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Mar. 20, 2014	Mar. 19, 2015

### 9.6 Test Data

EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	2.248	21	
2441	2.559		
2480	2.240		
GFSK TX Mode			
2402 MHz			

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 2.4021350 GHz  
2.248 dBm

Peak  
Log  
10  
dB/

Marker  
2.402135000 GHz  
2.248 dBm

M1 S2  
S3 FC  
AA

Center 2.402 GHz  
#Res BW 3 MHz


#VBW 3 MHz

Sweep 5 ms (401 pts)

Span 3 MHz


**GFSK TX Mode**

**2441 MHz**



**GFSK TX Mode**

**2480 MHz**





EUT:	Bluetooth speaker	Model Name :	AMK-S2-02B
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	2.287	21	
2441	2.532		
2480	2.143		
8-DPSK TX Mode			
2402 MHz			

Agilent

Ref 15 dBm

Atten 25 dB

Mkr1 2.4019750 GHz  
2.287 dBm

Peak  
Log  
10  
dB/

Marker  
2.401975000 GHz  
2.287 dBm

M1 S2  
S3 FC  
AA


Center 2.402 GHz  
#Res BW 3 MHz

#VBW 3 MHz

Span 5 MHz  
Sweep 5 ms (401 pts)


**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**

**2480 MHz**



## 10. Antenna Requirement

### 10.1 Standard Requirement

#### 10.1.1 Standard

FCC Part 15.203

#### 10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 10.2 Antenna Connected Construction

The directional gain of the PCB antenna used for transmitting is 0 dBi. And the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 10.2 Result

The EUT antenna equipped a PCB Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna