



Compliance Certification Services Inc.

Report No: C140211S01-SF

FCC ID: 2ABQR-M100

Date of Issue :February 18, 2014

GSM 850-Right Head Cheek High CH190.....	3
GSM 850-Right Head Tilted High CH190.....	4
GSM 850-Left Head Cheek Middle CH190.....	6
GSM 850-Left Head Tilted Middle CH190.....	7
PCS 1900-Right Head Cheek Low CH512.....	8
PCS 1900-Right Head Tilted Low CH512.....	9
PCS 1900-Left Head Cheek Low CH51.....	11
PCS 1900-Left Head Tilted Low CH512.....	12
WCDMA Band II-Right Head Cheek Middle CH9400.....	13
WCDMA Band II-Right Head Tilted Middle CH9400.....	15
WCDMA Band II-Left Head Cheek Middle CH9400.....	16
WCDMA Band II-Left Head Tilted Middle CH9400.....	17
WCDMA Band V-Right Head Cheek High CH4233.....	18
WCDMA Band V-Right Head Tilted High CH4233.....	19
WCDMA Band V-Left Head Cheek High CH4233.....	21
WCDMA Band V-Left Head Tilted High CH4233.....	22
WIFI-Right Head Cheek Low CH1.....	23
WIFI-Right Head Tilted Low CH1.....	24
WIFI-Left Head Cheek Low CH1.....	25
WIFI-Left Head Tilted Low CH1.....	27
GPRS 850-Body Rear Low CH128.....	28
GPRS 850-Body Rear Middle CH190.....	29
GPRS 850-Body Rear High CH251.....	30
GPRS 850-Body-Edge 1 Low CH128.....	31
GPRS 850-Body-Edge 1 Middle CH190.....	32
GPRS 850-Body-Edge 1 High CH251.....	33
GPRS 850-Body-Edge 1 High CH251 Repeat.....	35
GPRS 850-Body-Edge 2 High CH251.....	36
GPRS 850-Body-Edge 4 High CH251.....	37
GPRS 1900-Body Rear Low CH512.....	38
GPRS 1900-Body-Edge 1 Low CH512.....	39
GPRS 1900-Body-Edge 2 Low CH512.....	41
GPRS 1900-Body-Edge 4 Low CH512.....	42
WCDMA Band II-Body Rear Middle CH9400.....	43
WCDMA Band II-Body-Edge 1 Middle CH9400.....	45
WCDMA Band II-Body-Edge 2 Middle CH9400.....	46
WCDMA Band V-Body Middle CH9400.....	47
WCDMA Band V-Body -Edge1 Middle CH9400.....	48
WCDMA Band V-Body -Edge2 Rear High CH4233.....	50
WIFI-Body Rear Low CH1.....	51



Compliance Certification Services Inc.

Report No: C140211S01-SF

FCC ID: 2ABQR-M100

Date of Issue :February 18, 2014

WIFI-Body-Edge 1 Low CH1	53
WIFI-Body-Edge 4 Low CH1	54



Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

GSM 850-Right Head Cheek High CH190**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 41.072$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Right Head Cheek High CH190/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.772 W/kg

GSM850/Right Head Cheek High CH190/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.312 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.637 W/kg; SAR(10 g) = 0.378 W/kg

Maximum value of SAR (measured) = 0.871 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

GSM 850-Right Head Tilted High CH190

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 41.072$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Right Head Tilted High CH190/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.846 W/kg

GSM850/Right Head Tilted High CH190/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 21.483 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.648 W/kg; SAR(10 g) = 0.416 W/kg

Maximum value of SAR (measured) = 0.866 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

GSM 850-Left Head Cheek Middle CH190**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Duty Cycle: 1:8.31764

Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 41.072$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Left Head Cheek Middle CH190/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.401 W/kg

GSM850/Left Head Cheek Middle CH190/Zoom Scan (6x6x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.925 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.554 W/kg

SAR(1 g) = 0.362 W/kg; SAR(10 g) = 0.244 W/kg

Maximum value of SAR (measured) = 0.454 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

GSM 850-Left Head Tilted Middle CH190**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM 850 (824.0 - 849.0 MHz);

Frequency: 836.6 MHz; Duty Cycle: 1:8.31764

Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 41.072$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GSM850/Left Head Tilted Middle CH190/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.365 W/kg

GSM850/Left Head Tilted Middle CH190/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.313 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.443 W/kg

SAR(1 g) = 0.319 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 0.386 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

PCS 1900-Right Head Cheek Low CH512

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 38.62$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Right Head Cheek Low CH512/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm. Maximum value of SAR (measured) = 0.252 W/kg

PCS1900/Right Head Cheek Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.490 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.476 W/kg

SAR(1 g) = 0.202 W/kg; SAR(10 g) = 0.088 W/kg

Maximum value of SAR (measured) = 0.333 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

PCS 1900-Right Head Tilted Low CH512

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 38.62$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Right Head Tilted Low CH512/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm. Maximum value of SAR (measured) = 0.275 W/kg

PCS1900/Right Head Tilted Low CH512/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.129 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.207 W/kg; SAR(10 g) = 0.087 W/kg

Maximum value of SAR (measured) = 0.308 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

PCS 1900-Left Head Cheek Low CH51**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 38.62$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Left Head Cheek Low CH512/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0233 W/kg

PCS1900/Left Head Cheek Low CH512/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.713 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.143 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.029 W/kg

Maximum value of SAR (measured) = 0.0864 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

PCS 1900-Left Head Tilted Low CH512**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: PCS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 38.62$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

PCS1900/Left Head Tilted Low CH512/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0988 W/kg

PCS1900/Left Head Tilted Low CH512/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.452 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.152 W/kg

SAR(1 g) = 0.073 W/kg; SAR(10 g) = 0.034 W/kg

Maximum value of SAR (measured) = 0.107 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WCDMA Band II-Right Head Cheek Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band 2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Right Head Cheek Middle CH9400/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.423 W/kg

WCDMA/Right Head Cheek Middle CH9400/Zoom Scan (6x6x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.497 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.773 W/kg

SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.137 W/kg

Maximum value of SAR (measured) = 0.474 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WCDMA Band II-Right Head Tilted Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band 2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2.0mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Right Head Tilted Middle CH9400/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.349 W/kg

WCDMA/Right Head Tilted Middle CH9400/Zoom Scan (7x7x9)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 4.390 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.665 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.119 W/kg

Maximum value of SAR (measured) = 0.398 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WCDMA Band II-Left Head Cheek Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band 2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Left Head Cheek Middle CH9400/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.128 W/kg

WCDMA/Left Head Cheek Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.894 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.099 W/kg; SAR(10 g) = 0.056 W/kg

Maximum value of SAR (measured) = 0.137 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WCDMA Band II-Left Head Tilted Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band 2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 38.518$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.73, 7.73, 7.73); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Left Head Tilted Middle CH9400/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.129 W/kg

WCDMA/Left Head Tilted Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.416 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.198 W/kg

SAR(1 g) = 0.094 W/kg; SAR(10 g) = 0.046 W/kg

Maximum value of SAR (measured) = 0.139 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WCDMA Band V-Right Head Cheek High CH4233**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.918$ S/m; $\epsilon_r = 40.99$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Right Head Cheek High CH4233/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.119 W/kg

WCDMA/Right Head Cheek High CH4233/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.637 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.174 W/kg

SAR(1 g) = 0.105 W/kg; SAR(10 g) = 0.065 W/kg

Maximum value of SAR (measured) = 0.131 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WCDMA Band V-Right Head Tilted High CH4233**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.918$ S/m; $\epsilon_r = 40.99$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Right Head Tilted High CH4233/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.161 W/kg

WCDMA/Right Head Tilted High CH4233/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 8.256 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.236 W/kg

SAR(1 g) = 0.129 W/kg; SAR(10 g) = 0.079 W/kg

Maximum value of SAR (measured) = 0.160 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WCDMA Band V-Left Head Cheek High CH4233**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.918$ S/m; $\epsilon_r = 40.99$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Left Head Cheek High CH4233/Area Scan (11x9x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0789 W/kg

WCDMA/Left Head Cheek High CH4233/Zoom Scan (6x6x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.824 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.0950 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.044 W/kg

Maximum value of SAR (measured) = 0.0760 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WCDMA Band V-Left Head Tilted High CH4233**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.918$ S/m; $\epsilon_r = 40.99$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.16, 9.16, 9.16); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Left Head Tilted High CH4233/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0710 W/kg

WCDMA/Left Head Tilted High CH4233/Zoom Scan (6x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.148 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.0880 W/kg

SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.041 W/kg

Maximum value of SAR (measured) = 0.0715 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WIFI-Right Head Cheek Low CH1

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.786 \text{ S/m}$; $\epsilon_r = 38.868$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WIFI/IEEE802.11b Right Head Cheek Low CH1/Area Scan (11x9x1):

Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0564 W/kg

WIFI/IEEE802.11b Right Head Cheek Low CH1/Zoom Scan (8x8x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.059 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.0910 W/kg

SAR(1 g) = 0.043 W/kg; SAR(10 g) = 0.022 W/kg

Maximum value of SAR (measured) = 0.0644 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WIFI-Right Head Tilted Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.786 \text{ S/m}$; $\epsilon_r = 38.868$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Right Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)


WIFI/IEEE802.11b Right Head Tilted Low CH1/Area Scan (11x10x1):Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0588 W/kg**WIFI/IEEE802.11b Right Head Tilted Low CH1/Zoom Scan (7x7x7)/Cube 0:**Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.962 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.0920 W/kg

SAR(1 g) = 0.042 W/kg; SAR(10 g) = 0.021 W/kg

Maximum value of SAR (measured) = 0.0640 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WIFI-Left Head Cheek Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.786 \text{ S/m}$; $\epsilon_r = 38.868$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)


WIFI/IEEE802.11b Left Head Cheek Low CH1/Area Scan (11x9x1):Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0651 W/kg**WIFI/IEEE802.11b Left Head Cheek Low CH1/Zoom Scan (7x7x7)/Cube 0:**Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$


Reference Value = 2.024 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.105 W/kg

SAR(1 g) = 0.054 W/kg; SAR(10 g) = 0.028 W/kg

Maximum value of SAR (measured) = 0.0782 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/12/2014

WIFI-Left Head Tilted Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.786$ S/m; $\epsilon_r = 38.868$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Left Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WIFI/IEEE802.11b Left Head Tilted Low CH1/Area Scan (11x10x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0301 W/kg

WIFI/IEEE802.11b Left Head Tilted Low CH1/Zoom Scan (8x7x7)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.486 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.0510 W/kg

SAR(1 g) = 0.024 W/kg; SAR(10 g) = 0.012 W/kg

Maximum value of SAR (measured) = 0.0364 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body Rear Low CH128**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:2.0797

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.943$ S/m; $\epsilon_r = 53.006$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 850/GPRS850 Body Rear Low CH128/Area Scan (7x7x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.718 W/kg

GPRS 850/GPRS850 Body Rear Low CH128/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.440 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.533 W/kg; SAR(10 g) = 0.315 W/kg

Maximum value of SAR (measured) = 0.728 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body Rear Middle CH190**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GPRS; Communication System Band: GPRS850; Frequency: 836.6 MHz; Duty Cycle: 1:2.0797

Medium parameters used: $f = 837$ MHz; $\sigma = 0.956$ S/m; $\epsilon_r = 52.88$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 850/GPRS850 Body Rear Middle CH190/Area Scan (7x7x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.824 W/kg

GPRS 850/GPRS850 Body Rear Middle CH190/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.026 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.15 W/kg

SAR(1 g) = 0.642 W/kg; SAR(10 g) = 0.375 W/kg

Maximum value of SAR (measured) = 0.821 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body Rear High CH251**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GPRS; Communication System Band: GPRS 850 (824.0 - 849.0 MHz);

Frequency: 848.6 MHz; Duty Cycle: 1:2.0797

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 850/GPRS850 Body Rear High CH251/Area Scan (7x7x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.00 W/kg

GPRS 850/GPRS850 Body Rear High CH251/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.804 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.756 W/kg; SAR(10 g) = 0.458 W/kg

Maximum value of SAR (measured) = 1.03 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 1 Low CH128

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.943$ S/m; $\epsilon_r = 53.006$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 1 Low CH128/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm. Maximum value of SAR (measured) = 1.09 W/kg

GPRS850/GPRS850 Body Edge 1 Low CH128/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.278 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.781 W/kg; SAR(10 g) = 0.433 W/kg

Maximum value of SAR (measured) = 1.22 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 1 Middle CH190**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.956$ S/m; $\epsilon_r = 52.88$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 1 Middle CH190/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.10 W/kg

GPRS850/GPRS850 Body Edge 1 Middle CH190/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.125 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.79 W/kg

SAR(1 g) = 0.769 W/kg; SAR(10 g) = 0.446 W/kg

Maximum value of SAR (measured) = 1.25 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 1 High CH251**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.66686

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 1 High CH251/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.28 W/kg

GPRS850/GPRS850 Body Edge 1 High CH251/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 30.591 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.29 W/kg

SAR(1 g) = 0.862 W/kg; SAR(10 g) = 0.485 W/kg

Maximum value of SAR (measured) = 1.47 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 1 High CH251 Repeat**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.66686

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 1 High CH251 Repeat/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.01 W/kg

GPRS850/GPRS850 Body Edge 1 High CH251 Repeat/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.608 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.434 W/kg

Maximum value of SAR (measured) = 0.932 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 2 High CH251**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.66686

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 2 High CH251/Area Scan (13x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.201 W/kg

GPRS850/GPRS850 Body Edge 2 High CH251/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.735 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.607 W/kg

SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.084 W/kg

Maximum value of SAR (measured) = 0.334 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

GPRS 850-Body-Edge 4 High CH251**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GSM; Communication System Band: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:2.66686

Medium parameters used: $f = 849$ MHz; $\sigma = 0.968$ S/m; $\epsilon_r = 52.759$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS850/GPRS850 Body Edge 4 High CH251/Area Scan (13x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0538 W/kg

GPRS850/GPRS850 Body Edge 4 High CH251/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.348 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.0720 W/kg

SAR(1 g) = 0.037 W/kg; SAR(10 g) = 0.022 W/kg


Maximum value of SAR (measured) = 0.0524 W/kg





Date of Issue :February 18, 2014

Date: 2/15/2014





Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

GPRS 1900-Body-Edge 1 Low CH512**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GPRS; Communication System Band: GPRS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:2.0797

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.512$ S/m; $\epsilon_r = 53.739$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS1900/GPRS1900 Body Edge 1 Low CH512/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.511 W/kg

GPRS1900/GPRS1900 Body Edge 1 Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.712 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.17 W/kg

SAR(1 g) = 0.716 W/kg; SAR(10 g) = 0.263 W/kg

Maximum value of SAR (measured) = 1.43 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

GPRS 1900-Body-Edge 2 Low CH512**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GPRS; Communication System Band: GPRS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:2.0797

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.512$ S/m; $\epsilon_r = 53.739$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 1900/Body Rear Low CH512/Area Scan (13x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.904 W/kg

GPRS 1900/Body Rear Low CH512/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.497 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.642 W/kg; SAR(10 g) = 0.285 W/kg

Maximum value of SAR (measured) = 1.01 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

GPRS 1900-Body-Edge 4 Low CH512**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: Generic GPRS; Communication System Band: GPRS1900; Frequency: 1850.2 MHz; Duty Cycle: 1:2.0797

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.512$ S/m; $\epsilon_r = 53.739$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

GPRS 1900/Body Rear Low CH512/Area Scan (9x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.00388 W/kg

GPRS 1900/Body Rear Low CH512/Zoom Scan (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.066 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.00746 W/kg

SAR(1 g) = 0.00243 W/kg; SAR(10 g) = 0.000667 W/kg

Maximum value of SAR (measured) = 0.00417 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

WCDMA Band II-Body Rear Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/Body Rear Middle CH9400/Area Scan (6x7x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.961 W/kg

WCDMA/Body Rear Middle CH9400/Zoom Scan (7x7x9)/Cube 0:



Measurement grid: dx=5mm, dy=5mm, dz=3mm


Reference Value = 3.787 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.586 W/kg; SAR(10 g) = 0.251 W/kg

Maximum value of SAR (measured) = 0.849 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

WCDMA Band II-Body-Edge 1 Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/WCDMA Band II Body Edge 1 Middle CH9400/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.451 W/kg

WCDMA/WCDMA Band II Body Edge 1 Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.161 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.545 W/kg; SAR(10 g) = 0.215 W/kg

Maximum value of SAR (measured) = 0.908 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/15/2014

WCDMA Band II-Body-Edge 2 Middle CH9400

DUT: Tablet PC; Type: M100; Serial: 860504020403580

Communication System: FDD WCDMA; Communication System Band: Band II; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.561$ S/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/WCDMA Band II Body Edge 2 Middle CH9400/Area Scan (13x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.406 W/kg

WCDMA/WCDMA Band II Body Edge 2 Middle CH9400/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.533 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.645 W/kg

SAR(1 g) = 0.297 W/kg; SAR(10 g) = 0.142 W/kg

Maximum value of SAR (measured) = 0.452 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

WCDMA Band V-Body Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.966$ S/m; $\epsilon_r = 52.786$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/WCDMA Band V Body Rear High CH4233/Area Scan (6x6x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.453 W/kg

WCDMA/WCDMA Band V Body Rear High CH4233/Zoom Scan (6x6x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.824 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.584 W/kg

SAR(1 g) = 0.358 W/kg; SAR(10 g) = 0.222 W/kg

Maximum value of SAR (measured) = 0.460 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

WCDMA Band V-Body -Edge1 Middle CH9400**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.966$ S/m; $\epsilon_r = 52.786$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/WCDMA Band V Body Rear High CH4233/Area Scan (10x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.783 W/kg

WCDMA/WCDMA Band V Body Rear High CH4233/Zoom Scan (7x7x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 27.091 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.612 W/kg; SAR(10 g) = 0.368 W/kg

Maximum value of SAR (measured) = 0.926 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/14/2014

WCDMA Band V-Body -Edge2 Rear High CH4233**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: FDD WCDMA; Communication System Band: Band V; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 847$ MHz; $\sigma = 0.966$ S/m; $\epsilon_r = 52.786$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(9.27, 9.27, 9.27); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WCDMA/WCDMA Band V Body Rear High CH4233/Area Scan (13x5x1):

Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.185 W/kg

WCDMA/WCDMA Band V Body Rear High CH4233/Zoom Scan (6x6x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.631 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.418 W/kg

SAR(1 g) = 0.149 W/kg; SAR(10 g) = 0.073 W/kg

Maximum value of SAR (measured) = 0.266 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WIFI-Body Rear Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.94 \text{ S/m}$; $\epsilon_r = 51.139$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)


WIFI/IEEE802.11b Body Rear Low CH1/Area Scan (6x7x1):Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.280 W/kg**WIFI/IEEE802.11b Body Rear Low CH1/Zoom Scan (7x7x7)/Cube 0:**Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$


Reference Value = 3.462 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.463 W/kg

SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.099 W/kg

Maximum value of SAR (measured) = 0.316 W/kg







Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WIFI-Body-Edge 1 Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.94 \text{ S/m}$; $\epsilon_r = 51.139$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)



WIFI/IEEE802.11b Body Edge 1 Low CH1/Area Scan (10x5x1):Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0681 W/kg**WIFI/IEEE802.11b Body Edge 1 Low CH1/Zoom Scan (7x7x7)/Cube 0:**Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.318 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.173 W/kg

SAR(1 g) = 0.052 W/kg; SAR(10 g) = 0.021 W/kg

Maximum value of SAR (measured) = 0.0928 W/kg





Test Laboratory: Compliance Certification Services Inc.

Date: 2/13/2014

WIFI-Body-Edge 4 Low CH1**DUT: Tablet PC; Type: M100; Serial: 860504020403580**

Communication System: IEEE 802.11b; Communication System Band: ISM 2.4GHz Band; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.94 \text{ S/m}$; $\epsilon_r = 51.139$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.08, 7.08, 7.08); Calibrated: 7/26/2013;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/25/2013
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.5(1059);
- SEMCAD X Version 14.6.8 (7028)

WIFI/IEEE802.11b Body Edge 4 Low CH1/Area Scan (13x5x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.289 W/kg**WIFI/IEEE802.11b Body Edge 4 Low CH1/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 10.046 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.476 W/kg

SAR(1 g) = 0.203 W/kg; SAR(10 g) = 0.097 W/kg

Maximum value of SAR (measured) = 0.319 W/kg

