



TQ-Systems GmbH Attn. Mr. Bernd Wein Johann-Georg-Halske-Strasse 1 87471 Durach Germany

Carsten Steinroeder 28.12.2015 Phone +49 (0) 2102 749 331 Fax +49 (0) 2102 749 350

Maximum Permissible Exposure Q1049

Dear Mr. Wein,

please find our Maximum Permissible Exposure calculations for the Q1025.

Best Regards

i.V.

Carsten Steinröder



Maximum Permissible Exposure

(as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure)

Frequency range (MHz)	Power density (mW/cm²)
300 - 1500	f/1500
1,500 - 100000	1.0

Calculations 5 GHz band

SAR Limit: 1 mW/cm²

Equation OET bulletin 65, page 18, edition 97-01: $S = P*G / (4\pi R^2)$

S = power density

P = power input to the antenna

 $\mathsf{G} = \mathsf{power} \ \mathsf{gain} \ \mathsf{of} \ \mathsf{the} \ \mathsf{antenna} \ \mathsf{in} \ \mathsf{the} \ \mathsf{direction} \ \mathsf{of} \ \mathsf{interest} \ \mathsf{relative} \ \mathsf{to} \ \mathsf{an} \ \mathsf{isotropic} \ \mathsf{radiator}$

R = distance to the centre of radiation of the antenna

			G		Р			S	
Operational Bands	Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain -numeric- (mW/cm²)	Output Power -conducted- (dBm)	Output Power -conducted- (mW)	Output Power (EIRP) (mW)	Limit (mW/cm²)	Power Density value (mW/cm²)	Margin to Limit (mW/cm²)
UNII Subband 1 (20 MHz)	5220	2	1.5849	9.40	8.71	13.80	1.0000	0.0027	0.9973
UNII Subband 1 (40 MHz)	5190	2	1.5849	13.20	20.89	33.11	1.0000	0.0066	0.9934
UNII Subband 2A (20 MHz)	5320	2	1.5849	na	NA	NA	1.0000	NA	NA
UNII Subband 2A (40 MHz)	5270	2	1.5849	NA	NA	NA	1.0000	NA	NA
UNII Subband 2C (20 MHz)	5500	2	1.5849	NA	NA	NA	1.0000	NA	NA
UNII Subband 2C (40 MHz)	5510	2	1.5849	NA	NA	NA	1.0000	NA	NA
UNII Subband 3 (20 MHz)	5745	2	1.5849	10.30	10.72	16.98	1.0000	0.0034	0.9966
UNII Subband 3 (40 MHz)	5755	2	1.5849	13.60	22.91	36.31	1.0000	0.0072	0.9928

Distance to Antenna (R) in cm:	20