

Compliance Testing, LLC

Previously Flom Test Lab EMI, EMC, RF Testing Experts Since 1963 toll-free: (866) 311-3268 fax: (480) 926-3598

http://www.ComplianceTesting.com info@ComplianceTesting.com

Test Report

Prepared for: FLYHT Aerospace Solutions Ltd.

Model: AFIRS 228S Automated Flight Information Reporting System

Description: Dual Channel Iridium Satcom System that incorporates Iridium 9523 and 9602

FCC ID: 2ABRJ-228S

To

FCC Part 1.1310

Date of Issue: October 17, 2013

On the behalf of the applicant: FLYHT Aerospace Solutions Ltd.

200W, 1144-29th Avenue NE Calgary, Alberta T2E 7P1

Attention of: Derek Graham, Chief Operating Officer

Ph: (403) 250-9956

E-Mail: dgraham@flyht.com

Prepared By
Compliance Testing, LLC
3356 N San Marcos PI, Suite 107
Chandler, AZ 85225-7176
(866) 311-3268 phone / (480) 926-3598 fax
www.compliancetesting.com

Project No: p1380011

Alex Macon

Project Test Engineer



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	October 17, 2013	Alex Macon	Original Document
2.0	January 30, 2014	Alex Macon	Added FCC ID



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to http://www.compliancetesting.com/labscope.html for current scope of accreditation.

Testing Certificate Number: 2152.01



FCC OATS Reg, #933597

IC Reg. #2044A-1

Non-accredited tests contained in this report:

N/A



dBi

Description

Dual channel Iridium satcom system used in aircrafts that incorporates Iridium 9523 and 9602.

This is a mobile device used in Controlled Exposure environment.

Limits - Controlled Exposure 0.3-3.0 MHz: 47 CFR 1.1310 3.0-30 MHz: Table 1, (A) 30-300 MHz:

3.0-30 MHz: Limit [mW/cm²] = $(900/f^2)$ 30-300 MHz: Limit [mW/cm²] = 1.0 300-1500 MHz: Limit [mW/cm²] = f/3001500-100,000 MHz Limit [mW/cm²] = 5

Limit $[mW/cm^2] = 100$

Test Frequencies, MHz 1618.725 – 1625.979

Power, Conducted, mW (P) 9230 Antenna Gain Isotropic 3dBi Antenna Gain Numeric (G) 2.0

Antenna Gain Numeric (G) Antenna Type

Distance (R) 20 cm 20 cm

Power Density Calculations Formula = $S = PG / 4\pi R^2$

Power Density (S) = 3.674Limit = 5.0

The Power Density is below the Limit.

The SAR measurement is not necessary.

END OF TEST REPORT