



# FCC RF Test Report

APPLICANT : Soundhawk Corporation  
EQUIPMENT : BT HeadSet  
BRAND NAME : SOUNDHAWK  
MODEL NAME : SHK001  
MARKETING NAME : Smart Listening System  
FCC ID : 2ABW3SC-1  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Apr. 24, 2014 and testing was completed on May 17, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT .....	6
1.6 Testing Location .....	6
1.7 Applicable Standards.....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>7</b>
2.1 Descriptions of Test Mode .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 TEST RESULT .....</b>	<b>11</b>
3.1 Number of Channel Measurement .....	11
3.2 Hopping Channel Separation Measurement .....	13
3.3 Dwell Time Measurement.....	20
3.4 20dB Bandwidth Measurement .....	23
3.5 Peak Output Power Measurement .....	30
3.6 Conducted Band Edges Measurement .....	32
3.7 Conducted Spurious Emission Measurement .....	39
3.8 Radiated Band Edges and Spurious Emission Measurement .....	49
3.9 AC Conducted Emission Measurement.....	60
3.10 Antenna Requirements.....	64
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>65</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>66</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR442473	Rev. 01	Initial issue of report	Sep. 19, 2014



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	RSS-210 A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	RSS-210 A8.1(b)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	RSS-210 A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	RSS-210 A8.1(a)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	RSS-210 A8.1(b)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	RSS-210 A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	RSS-210 A8.5	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.22 dB at 2483.500 MHz
3.9	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 10.70 dB at 0.526 MHz
3.10	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

Soundhawk Corporation

20380 Town Center Lane, Suite 215, Curpertino, CA 95014

## 1.2 Manufacturer

FIH Mobile Limited

No. 4, Mingsheng St., Tu-Cheng Dist., New Taipei City 23679, Taiwan

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	BT HeadSet
Brand Name	SOUNDHAWK
Model Name	SHK001
Marketing Name	Smart Listening System
FCC ID	2ABW3SC-1
EUT supports Radios application	Bluetooth v3.0 EDR
HW Version	PVT
SW Version	0.6.5
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 9.43 dBm (0.0088 W) Bluetooth EDR (2Mbps) : 7.77 dBm (0.0060 W) Bluetooth EDR (3Mbps) : 7.75 dBm (0.0060 W)
Antenna Type	PIFA Antenna type with gain -0.28 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH08-HY

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	8.59 dBm	6.51 dBm	6.44 dBm
Ch39	2441MHz	9.38 dBm	7.67 dBm	7.62 dBm
Ch78	2480MHz	<b>9.43 dBm</b>	7.77 dBm	7.75 dBm

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
  2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

## 2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :EUT + BT MIC + Charging Case with USB Cable (Charging from Adapter)		
Remark:			
1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. “BT MIC” means Bluetooth Microphone.			




## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m

## 2.5 EUT Operation Test Setup

For Bluetooth function, the RF utility, "BlueTest3" was installed in EUT which was programmed in order to make the EUT get into the engineering modes to contact with Bluetooth base station for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW  $\geq$  1% of the span; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~26°C
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%
<b>Number of Hopping (Channel)</b>	<b>Adaptive Frequency Hopping (Channel)</b>	<b>Limits (Channel)</b>	<b>Pass/Fail</b>
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 13.MAY.2014 19:32:34



Date: 13.MAY.2014 19:36:50

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels; RBW  $\geq$  1% of the span;  
VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.5973	Pass
39	2441	1.002	0.5973	Pass
78	2480	1.002	0.5973	Pass


**Channel Separation Plot on Channel 00 - 01**



Date: 13.MAY.2014 18:36:05




### Channel Separation Plot on Channel 39 - 40



Date: 13.MAY.2014 18:37:01

### Channel Separation Plot on Channel 77 - 78




Date: 13.MAY.2014 18:38:02



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8240	Pass
39	2441	1.008	0.8320	Pass
78	2480	1.002	0.8280	Pass


**Channel Separation Plot on Channel 00 - 01**

Date: 13.MAY.2014 18:39:22






### Channel Separation Plot on Channel 39 - 40



Date: 13.MAY.2014 18:40:42

### Channel Separation Plot on Channel 77 - 78




Date: 13.MAY.2014 18:42:10



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8160	Pass
39	2441	1.008	0.8160	Pass
78	2480	1.002	0.8160	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 13.MAY.2014 18:47:33




### Channel Separation Plot on Channel 39 - 40



Date: 13.MAY.2014 18:48:26

### Channel Separation Plot on Channel 77 - 78



Date: 13.MAY.2014 18:49:20

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



### 3.3.5 Test Result of Dwell Time

<b>Test Mode :</b>	DH5	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.92	0.31	0.4	Pass
AFH	20	53.33	2.92	0.16	0.4	Pass

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 9.MAY.2014 22:44:27

### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.896
39	2441	0.896
78	2480	0.896


**20 dB Bandwidth Plot on Channel 00**



Date: 13.MAY.2014 19:41:12




### 20 dB Bandwidth Plot on Channel 39



Date: 13.MAY.2014 19:44:36

### 20 dB Bandwidth Plot on Channel 78




Date: 13.MAY.2014 19:48:58

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.236
39	2441	1.248
78	2480	1.242


### 20 dB Bandwidth Plot on Channel 00



Date: 13.MAY.2014 19:06:28




### 20 dB Bandwidth Plot on Channel 39



Date: 13.MAY.2014 19:12:37

### 20 dB Bandwidth Plot on Channel 78




Date: 13.MAY.2014 19:14:51



Test Mode :	3Mbps	Temperature :	24~26℃
Test Engineer :	Jun Yang	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.224
39	2441	1.224
78	2480	1.224

**20 dB Bandwidth Plot on Channel 00**

Date: 13.MAY.2014 19:18:40




20 dB Bandwidth Plot on Channel 39



Date: 13.MAY.2014 19:21:54

20 dB Bandwidth Plot on Channel 78



Date: 13.MAY.2014 19:24:37

## 3.5 Peak Output Power Measurement

### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	8.59	20.97	Pass
39	2441	9.38	20.97	Pass
78	2480	9.43	20.97	Pass

**Note:** For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.51	20.97	Pass
39	2441	7.67	20.97	Pass
78	2480	7.77	20.97	Pass

<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Jun Yang	<b>Relative Humidity :</b>	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	6.44	20.97	Pass
39	2441	7.62	20.97	Pass
78	2480	7.75	20.97	Pass

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz ( $\geq 1\%$  span=10MHz), VBW = 300kHz ( $\geq$  RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**Low Band Edge Plot on Channel 00**



Date: 13.MAY.2014 19:41:40

**High Band Edge Plot on Channel 78**




Date: 13.MAY.2014 19:49:58




Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

### Low Band Edge Plot on Channel 00



Date: 13.MAY.2014 19:06:53


### High Band Edge Plot on Channel 78




Date: 13.MAY.2014 19:15:11



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**Low Band Edge Plot on Channel 00**


Date: 13.MAY.2014 19:19:05

**High Band Edge Plot on Channel 78**


Date: 13.MAY.2014 19:25:05

### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

**1Mbps Hopping Mode Low Band Edge Plot**


Date: 13.MAY.2014 19:42:08


**1Mbps Hopping Mode High Band Edge Plot**


Date: 13.MAY.2014 19:52:50




Test Mode :	2Mbps	Temperature :	24~26℃
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

### 2Mbps Hopping Mode Low Band Edge Plot



Date: 13.MAY.2014 19:08:00

### 2Mbps Hopping Mode High Band Edge Plot




Date: 13.MAY.2014 19:15:49




Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Jun Yang	Relative Humidity :	48~51%

## 3Mbps Hopping Mode Low Band Edge Plot



Date: 13.MAY.2014 19:19:45

## 3Mbps Hopping Mode High Band Edge Plot



Date: 13.MAY.2014 19:25:35

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.7.4 Test Setup



### 3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**



Date: 13.MAY.2014 19:43:08

**1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**




Date: 13.MAY.2014 19:43:30




<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~26℃
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	48~51%
		<b>Test Engineer :</b>	Jun Yang

### 1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 13.MAY.2014 19:45:51

### 1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 13.MAY.2014 19:46:12




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 13.MAY.2014 20:39:10


1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 13.MAY.2014 20:39:32



Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 13.MAY.2014 19:09:01

**2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 13.MAY.2014 19:11:55



Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**

Date: 13.MAY.2014 19:13:42


**2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**

Date: 13.MAY.2014 19:14:04




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 13.MAY.2014 19:17:39


2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 13.MAY.2014 19:18:01



Test Mode :	3Mbps	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 13.MAY.2014 19:20:47

**3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 13.MAY.2014 19:21:09



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 13.MAY.2014 19:23:33

**3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 13.MAY.2014 19:23:55



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Jun Yang

**3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 13.MAY.2014 19:27:38

**3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**

Date: 13.MAY.2014 19:28:00



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.73dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.




### 3.8.6 Duty cycle correction factor for average measurement

#### DH5 on time (One Pulse) Plot on Channel 39



Date: 17.MAY.2014 09:38:50

#### DH5 on time (Count Pulses) Plot on Channel 39



Date: 17.MAY.2014 09:40:29

**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.90 / 100 = 5.80 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.73 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.90 \text{ ms} \times 20 \text{ channels} = 58.0 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2$  hops

Thus, the maximum possible ON time:

$$2.90 \text{ ms} \times 2 = 5.80 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.80 \text{ ms}/100\text{ms}) = -24.73 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	48~49%
		<b>Test Engineer :</b>	Ivan Chiang

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2349.96	50.35	-23.65	74	44.8	32.19	7.5	34.14	116	244	Peak
2349.96	25.62	-28.38	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2376.06	50.09	-23.91	74	44.46	32.26	7.52	34.15	174	149	Peak
2376.06	25.36	-28.64	54	-	-	-	-	-	-	Average

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	48~49%
		<b>Test Engineer :</b>	Ivan Chiang

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.5	65.78	-8.22	74	59.82	32.47	7.71	34.22	109	68	Peak
2483.5	41.05	-12.95	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.53	60.79	-13.21	74	54.83	32.47	7.71	34.22	127	167	Peak
2483.53	36.06	-17.94	54	-	-	-	-	-	-	Average

**Note:** Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73dB)

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

**Note:** Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2402 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2402	105.95	-	-	100.28	32.29	7.55	34.17	116	244	Peak
2402	81.22	-	-	-	-	-	-	-	-	Average
4803	48.82	-25.18	74	64.35	34.89	8.55	58.97	100	0	Peak
4803	24.09	-29.91	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2402 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2402	98.47	-	-	92.8	32.29	7.55	34.17	174	149	Peak
2402	73.74	-	-	-	-	-	-	-	-	Average
4806	48.54	-25.46	74	64.05	34.89	8.57	58.97	100	0	Peak
4806	23.81	-30.19	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)



<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2442 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2442	107.16	-	-	101.34	32.4	7.63	34.21	170	263	Peak
2442	82.43	-	-	-	-	-	-	-	-	Average
4884	45.71	-28.29	74	61.02	34.93	8.63	58.87	100	0	Peak
4884	20.98	-33.02	54	-	-	-	-	-	-	Average
7323	48.58	-25.42	74	57.5	36.63	12.94	58.49	100	0	Peak
7323	23.85	-30.15	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2442 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2442	98.91	-	-	93.09	32.4	7.63	34.21	108	181	Peak
2442	74.18	-	-	-	-	-	-	-	-	Average
4884	45.96	-28.04	74	61.27	34.93	8.63	58.87	100	0	Peak
4884	21.23	-32.77	54	-	-	-	-	-	-	Average
7323	45.97	-28.03	74	54.89	36.63	12.94	58.49	100	0	Peak
7323	21.24	-32.76	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2480 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30	16.99	-23.01	40	29.6	18.4	0.82	31.83	-	-	Peak
128.82	15.57	-27.93	43.5	34.08	11.6	1.67	31.78	-	-	Peak
243.57	18.84	-27.16	46	36.67	11.66	2.28	31.77	-	-	Peak
491.1	21.39	-24.61	46	32.64	17.4	3.23	31.88	-	-	Peak
646.5	23.53	-22.47	46	32.77	19.03	3.77	32.04	-	-	Peak
785.8	24.76	-21.24	46	32.64	19.9	4.16	31.94	105	132	Peak
2480	106.54	-	-	100.58	32.47	7.71	34.22	109	68	Peak
2480	81.81	-	-	-	-	-	-	-	-	Average
4962	49.73	-24.27	74	64.8	34.98	8.7	58.75	100	0	Peak
4962	25	-29	54	-	-	-	-	-	-	Average
7440	46.75	-27.25	74	55.8	36.61	13.05	58.71	100	0	Peak
7440	22.02	-31.98	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)



<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	48~49%
<b>Test Engineer :</b>	Ivan Chiang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2480 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30.54	17.67	-22.33	40	30.65	18.02	0.83	31.83	-	-	Peak
121.53	14.26	-29.24	43.5	32.26	12.16	1.62	31.78	-	-	Peak
272.19	16.46	-29.54	46	33.09	12.73	2.41	31.77	-	-	Peak
458.2	21.69	-24.31	46	33.44	16.96	3.14	31.85	-	-	Peak
659.1	24.26	-21.74	46	33.59	18.9	3.81	32.04	-	-	Peak
951	26.71	-19.29	46	32.28	20.81	4.65	31.03	100	256	Peak
2480	100.49	-	-	94.53	32.47	7.71	34.22	127	167	Peak
2480	75.76	-	-	-	-	-	-	-	-	Average
4962	46.75	-27.25	74	62.26	34.98	8.26	58.75	100	0	Peak
4962	22.02	-31.98	54	-	-	-	-	-	-	Average
7440	41.03	-32.97	74	52.66	36.61	10.47	58.71	100	0	Peak
7440	16.3	-37.7	54	-	-	-	-	-	-	Average

**Note:** 1. Other harmonics are lower than background noise.

2. Average Emission Level = Peak Emission Level + duty cycle correction factor (-24.73)

### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Slash Huang	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	EUT + BT MIC + Charging Case with USB Cable (Charging from Adapter)		




#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	50.1	Off	L1	19.3	15.1	65.2
0.198000	47.0	Off	L1	19.3	16.7	63.7
0.230000	45.0	Off	L1	19.4	17.4	62.4
0.262000	42.2	Off	L1	19.3	19.2	61.4
0.294000	39.4	Off	L1	19.4	21.0	60.4
0.534000	42.7	Off	L1	19.4	13.3	56.0

#### Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	35.3	Off	L1	19.3	19.9	55.2
0.198000	31.5	Off	L1	19.3	22.2	53.7
0.230000	29.0	Off	L1	19.4	23.4	52.4
0.262000	27.2	Off	L1	19.3	24.2	51.4
0.294000	24.2	Off	L1	19.4	26.2	50.4
0.534000	34.9	Off	L1	19.4	11.1	46.0

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	20~22℃
<b>Test Engineer :</b>	Slash Huang	<b>Relative Humidity :</b>	45~47%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	EUT + BT MIC + Charging Case with USB Cable (Charging from Adapter)		


**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	46.7	Off	N	19.4	19.3	66.0
0.166000	43.4	Off	N	19.3	21.8	65.2
0.182000	43.8	Off	N	19.3	20.6	64.4
0.222000	40.6	Off	N	19.4	22.1	62.7
0.318000	34.9	Off	N	19.4	24.9	59.8
0.526000	38.2	Off	N	19.4	17.8	56.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	32.0	Off	N	19.4	24.0	56.0
0.166000	27.6	Off	N	19.3	27.6	55.2
0.182000	30.5	Off	N	19.3	23.9	54.4
0.222000	27.5	Off	N	19.4	25.2	52.7
0.318000	25.8	Off	N	19.4	24.0	49.8
0.526000	35.3	Off	N	19.4	10.7	46.0



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.





## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	May 09, 2014~ May 13, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 28, 2014	May 09, 2014~ May 13, 2014	Jan. 27, 2015	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 28, 2014	May 09, 2014~ May 13, 2014	Jan. 27, 2015	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz ~ 26.5GHz	Jan. 15, 2014	May 15, 2014 ~ May 17, 2014	Jan. 14, 2015	Radiation (03CH08-HY)
Bilog Antenna	Teseq GmbH	CBL6112D	35379	30MHz~2GHz	Oct. 10, 2013	May 15, 2014 ~ May 17, 2014	Oct. 09, 2014	Radiation (03CH08-HY)
Horn Antenna	ESCO	3117	000143261	1GHz~18GHz	Jan. 16, 2014	May 15, 2014 ~ May 17, 2014	Jan. 15, 2015	Radiation (03CH08-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz~40GHz	Oct. 03, 2013	May 15, 2014 ~ May 17, 2014	Oct. 02, 2014	Radiation (03CH08-HY)
Amplifier	SONOMA	310N	187231	9kHz~1GHz	May 12, 2014	May 15, 2014 ~ May 17, 2014	May 11, 2015	Radiation (03CH08-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	Jul. 09, 2013	May 15, 2014 ~ May 17, 2014	Jul. 08, 2014	Radiation (03CH08-HY)
Pre Amplifier	Agilent	8449B	3008A02665	1GHz~26.5GHz	Sep. 04, 2013	May 15, 2014 ~ May 17, 2014	Sep. 03, 2014	Radiation (03CH08-HY)
Turn Table	Chaintek	Chaintek 3000	N/A	0~360 Degree	N/A	May 15, 2014 ~ May 17, 2014	N/A	Radiation (03CH08-HY)
Antenna Mast	MF	MFA520BS	N/A	1m~4m	N/A	May 15, 2014 ~ May 17, 2014	N/A	Radiation (03CH08-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/0001	9 kHz~30 MHz	Jul. 03, 2012	May 15, 2014 ~ May 17, 2014	Jul. 03, 2014	Radiation (03CH08-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	May 10, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	May 10, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	May 10, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 10, 2014	N/A	Conduction (CO05-HY)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.30
---	------