

FCC PART 15.247



TEST REPORT

For

BMC Medical Co., Ltd.

5/F Main Building, No.19 Gucheng Street West, Shijingshan, Beijing 100043, P.R.China

FCC ID: 2ABWVYH600AYH600B

Report Type: Original Report	Product Type: Portable Diagnostic System
Test Engineer: Ares Liu	
Report Number: R2BJ140225050-00A	
Report Date: 2014-04-29	
	Sula Huang
Reviewed By: RF Engineer	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §2.1093 – RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY.....	10
EUT SETUP	10
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	16
APPLICABLE STANDARD	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST PROCEDURE	16
TEST DATA	16
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA	28
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	32

APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST EQUIPMENT LIST AND DETAILS.....	48
TEST DATA	48
FCC §15.247(d) - BAND EDGES TESTING	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST EQUIPMENT LIST AND DETAILS.....	54
TEST DATA	54

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *BMC Medical Co., Ltd.*'s product, model number: *YH-600B Pro (FCC ID: 2ABWVYH600AYH600B)* (the "EUT") in this report was a *Portable Diagnostic System*, which was measured approximately: 8.0 cm (L) x 6.0cm (W) x 2.5 cm (H), rated input voltage: 1 × 1.5V AA alkaline battery.

** All measurement and test data in this report was gathered from production sample serial number: 140225050 (Assigned by BACL.Dongguan). The EUT was received on 2014-02-26.*

Objective

This report is prepared on behalf of *BMC Medical Co., Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ABWVYH600AYH600B

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

EUT Exercise Software

CSR Blue suite 2.5.0

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Not Applicable*
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

Not Applicable*: The EUT is battery operated equipment.

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted output power = 4.99 dBm (3.16 mW) at 2402 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 $= 3.16/5 \cdot (\sqrt{2.402}) = 0.98 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2013-05-06	2014-05-05
Sunol Sciences	Antenna	JB3	A060611-1	2011-09-06	2014-09-05
HP	Amplifier	8447E	2434A02181	2013-09-06	2014-09-05
R&S	Spectrum Analyzer	FSEM	DE31388	2013-05-07	2014-05-06
ETS-Lindgren	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-18
R&S	Spectrum Analyzer	FSP 38	100478	2013-06-16	2014-06-15
Ducommun Technologies	horn antenna	ARH-4223-02	1007726-01 1304	2013-06-16	2014-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2013-09-06	2014-09-05

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

14.09 dB at 7440 MHz in the Vertical polarization of EDR Mode ($\pi/4$ -DQPSK)

Test Data**Environmental Conditions**

Temperature:	22.6 °C
Relative Humidity:	68 %
ATM Pressure:	101.7 kPa

The testing was performed by Ares Liu on 2014-03-22.

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)	(dB)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	93.36	PK	H	25.65	4.42	27.13	96.30	N/A	N/A
2402	66.11	AV	H	25.65	4.42	27.13	69.05	N/A	N/A
2402	95.45	PK	V	25.65	4.42	27.13	98.39	N/A	N/A
2402	68.57	AV	V	25.65	4.42	27.13	71.51	N/A	N/A
2390	36.21	PK	V	25.61	4.39	27.13	39.08	74.00	34.92
2390	22.29	AV	V	25.61	4.39	27.13	25.16	54.00	28.84
4804	44.36	PK	V	30.59	5.98	27.26	53.67	74.00	20.33
4804	26.89	AV	V	30.59	5.98	27.26	36.20	54.00	17.80
7206	33.57	PK	V	34.09	7.45	26.30	48.81	74.00	25.19
7206	23.02	AV	V	34.09	7.45	26.30	38.26	54.00	15.74
1605	39.66	PK	V	23.81	3.25	26.90	39.82	74.00	34.18
1605	24.16	AV	V	23.81	3.25	26.90	24.32	54.00	29.68
3214	37.54	PK	V	27.88	6.52	27.48	44.46	74.00	29.54
3214	24.52	AV	V	27.88	6.52	27.48	31.44	54.00	22.56
356.4	35.12	QP	H	15.46	2.30	21.66	31.22	46.00	14.78
Middle Channel: 2441(MHz)									
2441	92.46	PK	H	25.75	4.4	27.18	95.43	N/A	N/A
2441	65.27	AV	H	25.75	4.4	27.18	68.24	N/A	N/A
2441	94.82	PK	V	25.75	4.4	27.18	97.79	N/A	N/A
2441	67.88	AV	V	25.75	4.4	27.18	70.85	N/A	N/A
4882	43.62	PK	V	30.79	6.08	27.26	53.23	74.00	20.77
4882	25.91	AV	V	30.79	6.08	27.26	35.52	54.00	18.48
7323	34.17	PK	V	34.38	7.51	26.53	49.53	74.00	24.47
7323	23.48	AV	V	34.38	7.51	26.53	38.84	54.00	15.16
1612	39.57	PK	V	23.82	3.27	26.90	39.76	74.00	34.24
1612	24.21	AV	V	23.82	3.27	26.90	24.40	54.00	29.60
3214	36.88	PK	V	27.88	6.52	27.48	43.80	74.00	30.20
3214	25.04	AV	V	27.88	6.52	27.48	31.96	54.00	22.04
165.8	35.26	QP	H	12.34	1.55	21.44	27.71	43.50	15.79
356.4	34.82	QP	H	15.46	2.30	21.66	30.92	46.00	15.08
High Channel: 2480(MHz)									
2480	91.36	PK	H	25.85	4.48	27.22	94.47	N/A	N/A
2480	64.19	AV	H	25.85	4.48	27.22	67.30	N/A	N/A
2480	94.25	PK	V	25.85	4.48	27.22	97.36	N/A	N/A
2480	68.37	AV	V	25.85	4.48	27.22	71.48	N/A	N/A
2483.5	49.52	PK	V	25.86	4.49	27.23	52.64	74.00	21.36
2483.5	28.64	AV	V	25.86	4.49	27.23	31.76	54.00	22.24
4960	45.12	PK	V	31.00	5.90	27.27	54.75	74.00	19.25
4960	27.34	AV	V	31.00	5.90	27.27	36.97	54.00	17.03
7440	34.31	PK	V	34.66	7.58	26.56	49.99	74.00	24.01
7440	23.18	AV	V	34.66	7.58	26.56	38.86	54.00	15.14
1615	40.33	PK	V	23.83	3.28	26.91	40.53	74.00	33.47
1615	25.08	AV	V	23.83	3.28	26.91	25.28	54.00	28.72
3214	37.26	PK	V	27.88	6.52	27.48	44.18	74.00	29.82
3214	26.12	AV	V	27.88	6.52	27.48	33.04	54.00	20.96
356.4	35.27	QP	H	15.46	2.30	21.66	31.37	46.00	14.63

EDR Mode ($\pi/4$ -DQPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	91.23	PK	H	25.65	4.42	27.13	94.17	N/A	N/A
2402	64.19	AV	H	25.65	4.42	27.13	67.13	N/A	N/A
2402	93.18	PK	V	25.65	4.42	27.13	96.12	N/A	N/A
2402	65.03	AV	V	25.65	4.42	27.13	67.97	N/A	N/A
2390	35.21	PK	V	25.61	4.39	27.13	38.08	74.00	35.92
2390	22.13	AV	V	25.61	4.39	27.13	25.00	54.00	29.00
4804	43.52	PK	V	30.59	5.98	27.26	52.83	74.00	21.17
4804	24.37	AV	V	30.59	5.98	27.26	33.68	54.00	20.32
7206	32.19	PK	V	34.09	7.45	26.30	47.43	74.00	26.57
7206	23.04	AV	V	34.09	7.45	26.30	38.28	54.00	15.72
1605	39.35	PK	V	23.81	3.25	26.90	39.51	74.00	34.49
1605	24.22	AV	V	23.81	3.25	26.90	24.38	54.00	29.62
3215	38.01	PK	V	27.89	6.52	27.48	44.94	74.00	29.06
3215	25.12	AV	V	27.89	6.52	27.48	32.05	54.00	21.95
356.4	34.63	QP	H	15.46	2.30	21.66	30.73	46.00	15.27
Middle Channel: 2441(MHz)									
2441	90.85	PK	H	25.75	4.4	27.18	93.82	N/A	N/A
2441	64.63	AV	H	25.75	4.4	27.18	67.60	N/A	N/A
2441	92.41	PK	V	25.75	4.4	27.18	95.38	N/A	N/A
2441	65.14	AV	V	25.75	4.4	27.18	68.11	N/A	N/A
4882	43.21	PK	V	30.79	6.08	27.26	52.82	74.00	21.18
4882	25.11	AV	V	30.79	6.08	27.26	34.72	54.00	19.28
7323	34.26	PK	V	34.38	7.51	26.53	49.62	74.00	24.38
7323	24.15	AV	V	34.38	7.51	26.53	39.51	54.00	14.49
1612	40.22	PK	V	23.82	3.27	26.90	40.41	74.00	33.59
1612	24.31	AV	V	23.82	3.27	26.90	24.50	54.00	29.50
3214	36.85	PK	V	27.88	6.52	27.48	43.77	74.00	30.23
3214	24.25	AV	V	27.88	6.52	27.48	31.17	54.00	22.83
165.8	35.63	QP	H	12.34	1.55	21.44	28.08	43.50	15.42
356.4	34.57	QP	H	15.46	2.30	21.66	30.67	46.00	15.33
High Channel: 2480(MHz)									
2480	90.42	PK	H	25.85	4.48	27.22	93.53	N/A	N/A
2480	63.26	AV	H	25.85	4.48	27.22	66.37	N/A	N/A
2480	91.67	PK	V	25.85	4.48	27.22	94.78	N/A	N/A
2480	65.11	AV	V	25.85	4.48	27.22	68.22	N/A	N/A
2483.5	47.23	PK	V	25.86	4.49	27.23	50.35	74.00	23.65
2483.5	26.24	AV	V	25.86	4.49	27.23	29.36	54.00	24.64
4960	43.95	PK	V	31.00	5.90	27.27	53.58	74.00	20.42
4960	26.21	AV	V	31.00	5.90	27.27	35.84	54.00	18.16
7440	35.11	PK	V	34.66	7.58	26.56	50.79	74.00	23.21
7440	24.23	AV	V	34.66	7.58	26.56	39.91	54.00	14.09
1615	41.26	PK	V	23.83	3.28	26.91	41.46	74.00	32.54
1615	25.06	AV	V	23.83	3.28	26.91	25.26	54.00	28.74
3214	38.14	PK	V	27.88	6.52	27.48	45.06	74.00	28.94
3214	26.23	AV	V	27.88	6.52	27.48	33.15	54.00	20.85
356.4	34.29	QP	H	15.46	2.30	21.66	30.39	46.00	15.61

EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	90.43	PK	H	25.65	4.42	27.13	93.37	N/A	N/A
2402	64.26	AV	H	25.65	4.42	27.13	67.20	N/A	N/A
2402	92.47	PK	V	25.65	4.42	27.13	95.41	N/A	N/A
2402	66.15	AV	V	25.65	4.42	27.13	69.09	N/A	N/A
2390	35.21	PK	V	25.61	4.39	27.13	38.08	74.00	35.92
2390	22.09	AV	V	25.61	4.39	27.13	24.96	54.00	29.04
4804	42.28	PK	V	30.59	5.98	27.26	51.59	74.00	22.41
4804	25.74	AV	V	30.59	5.98	27.26	35.05	54.00	18.95
7206	33.69	PK	V	34.09	7.45	26.30	48.93	74.00	25.07
7206	23.10	AV	V	34.09	7.45	26.30	38.34	54.00	15.66
1602	38.96	PK	V	23.80	3.24	26.90	39.10	74.00	34.90
1602	24.03	AV	V	23.80	3.24	26.90	24.17	54.00	29.83
3214	38.11	PK	V	27.88	6.52	27.48	45.03	74.00	28.97
3214	24.29	AV	V	27.88	6.52	27.48	31.21	54.00	22.79
356.4	35.34	QP	H	15.46	2.30	21.66	31.44	46.00	14.56
Middle Channel: 2441(MHz)									
2441	89.15	PK	H	25.75	4.4	27.18	92.12	N/A	N/A
2441	63.89	AV	H	25.75	4.4	27.18	66.86	N/A	N/A
2441	91.36	PK	V	25.75	4.4	27.18	94.33	N/A	N/A
2441	65.44	AV	V	25.75	4.4	27.18	68.41	N/A	N/A
4882	45.26	PK	V	30.79	6.08	27.26	54.87	74.00	19.13
4882	26.34	AV	V	30.79	6.08	27.26	35.95	54.00	18.05
7323	35.11	PK	V	34.38	7.51	26.53	50.47	74.00	23.53
7323	24.28	AV	V	34.38	7.51	26.53	39.64	54.00	14.36
1610	41.11	PK	V	23.82	3.27	26.90	41.30	74.00	32.70
1610	25.37	AV	V	23.82	3.27	26.90	25.56	54.00	28.44
3214	37.12	PK	V	27.88	6.52	27.48	44.04	74.00	29.96
3214	26.32	AV	V	27.88	6.52	27.48	33.24	54.00	20.76
165.8	36.54	QP	H	12.34	1.55	21.44	28.99	43.50	14.51
356.4	35.12	QP	H	15.46	2.30	21.66	31.22	46.00	14.78
High Channel: 2480(MHz)									
2480	88.79	PK	H	25.85	4.48	27.22	91.90	N/A	N/A
2480	62.46	AV	H	25.85	4.48	27.22	65.57	N/A	N/A
2480	90.72	PK	V	25.85	4.48	27.22	93.83	N/A	N/A
2480	65.14	AV	V	25.85	4.48	27.22	68.25	N/A	N/A
2483.5	48.69	PK	V	25.86	4.49	27.23	51.81	74.00	22.19
2483.5	27.85	AV	V	25.86	4.49	27.23	30.97	54.00	23.03
4960	46.32	PK	V	31.00	5.90	27.27	55.95	74.00	18.05
4960	26.44	AV	V	31.00	5.90	27.27	36.07	54.00	17.93
7440	35.12	PK	V	34.66	7.58	26.56	50.80	74.00	23.20
7440	24.17	AV	V	34.66	7.58	26.56	39.85	54.00	14.15
1615	41.26	PK	V	23.83	3.28	26.91	41.46	74.00	32.54
1615	25.24	AV	V	23.83	3.28	26.91	25.44	54.00	28.56
3214	38.26	PK	V	27.88	6.52	27.48	45.18	74.00	28.82
3214	25.41	AV	V	27.88	6.52	27.48	32.33	54.00	21.67
356.4	35.79	QP	H	15.46	2.30	21.66	31.89	46.00	14.11

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa

* The testing was performed by Ares Liu on 2014-03-22.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR Mode (GFSK)	Low	2402	1.000	0.611	Pass
	Adjacent	2403			
	Middle	2441	1.012	0.611	Pass
	Adjacent	2442			
	High	2480	1.004	0.611	Pass
	Adjacent	2479			
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.002	0.810	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.802	Pass
	Adjacent	2442			
	High	2480	1.003	0.811	Pass
	Adjacent	2479			
EDR Mode (8-DPSK):	Low	2402	1.000	0.805	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.802	Pass
	Adjacent	2442			
	High	2480	1.003	0.802	Pass
	Adjacent	2479			


Note: Limit = $2/3 \times 20\text{dB}$ bandwidth

BDR Mode (GFSK):




Date: 22.MAR.2014 15:30:46

Middle Channel



Date: 22.MAR.2014 15:33:08


High Channel



Date: 22.MAR.2014 15:35:06

EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Date: 22.MAR.2014 15:38:15

1


Middle Channel



Date: 22.MAR.2014 15:41:24

1

High Channel




Date: 22.MAR.2014 15:45:04

1

EDR Mode (8-DPSK):


Low Channel



Date: 22.MAR.2014 15:48:33

1


Middle Channel



Date: 22.MAR.2014 15:53:30

1

High Channel



Date: 22.MAR.2014 15:55:34

1

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa

* The testing was performed by Ares Liu on 2014-03-22.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.917
	Middle	2441	0.917
	High	2480	0.917
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.215
	Middle	2441	1.203
	High	2480	1.217
EDR Mode (8-DPSK):	Low	2402	1.207
	Middle	2441	1.203
	High	2480	1.203

BDR Mode (GFSK):




Date: 22.MAR.2014 15:29:57

Middle Channel




Date: 22.MAR.2014 15:32:36


High Channel



Date: 22.MAR.2014 15:34:23


*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**

Date: 22.MAR.2014 15:37:35

Middle Channel

Date: 22.MAR.2014 15:40:39


High Channel



Date: 22.MAR.2014 15:44:26


EDR Mode (8-DPSK):

Low Channel




Date: 22.MAR.2014 15:47:43

Middle Channel



Date: 22.MAR.2014 15:52:31

High Channel



Date: 22.MAR.2014 15:55:01

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa

* The testing was performed by Ares Liu on 2014-03-22.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 22.MAR.2014 16:48:27

EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15


Number of Hopping Channels



Date: 22.MAR.2014 16:50:53

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 22.MAR.2014 16:52:53

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa

* The testing was performed by Ares Liu on 2014-03-22.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.412	0.132	0.4	Pass
	Middle	0.416	0.133	0.4	Pass
	High	0.416	0.133	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
DH3	Low	1.687	0.270	0.4	Pass
	Middle	1.687	0.270	0.4	Pass
	High	1.687	0.270	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
DH5	Low	2.936	0.313	0.4	Pass
	Middle	2.936	0.313	0.4	Pass
	High	2.936	0.313	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel




Date: 22.MAR.2014 15:59:17

DH1: Middle Channel




Date: 8.MAY.2014 16:47:35

DH1: High Channel




Date: 8.MAY.2014 16:48:02

DH3: Low Channel




Date: 22.MAR.2014 16:18:44

DH3: Middle Channel




Date: 22.MAR.2014 16:19:05

DH3: High Channel




Date: 22.MAR.2014 16:19:10

DH5: Low Channel




Date: 22.MAR.2014 16:33:00

DH5: Middle Channel



Date: 22.MAR.2014 16:32:53

DH5: High Channel




Date: 22.MAR.2014 16:32:48

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.432	0.138	0.4	Pass
	Middle	0.432	0.138	0.4	Pass
	High	0.432	0.138	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
DH3	Low	1.687	0.270	0.4	Pass
	Middle	1.687	0.270	0.4	Pass
	High	1.687	0.270	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
DH5	Low	2.936	0.313	0.4	Pass
	Middle	2.936	0.313	0.4	Pass
	High	2.936	0.313	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel




Date: 22.MAR.2014 16:15:02

DH1: Middle Channel




Date: 22.MAR.2014 16:15:15

DH1: High Channel




Date: 22.MAR.2014 16:15:20

DH3: Low Channel




Date: 22.MAR.2014 16:28:16

DH3: Middle Channel




Date: 22.MAR.2014 16:28:10

DH3: High Channel




Date: 22.MAR.2014 16:19:44

DH5: Low Channel




Date: 22.MAR.2014 16:33:21

DH5: Middle Channel



Date: 22.MAR.2014 16:33:39


DH5: High Channel



Date: 22.MAR.2014 16:33:44


EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.432	0.138	0.4	Pass
	Middle	0.432	0.138	0.4	Pass
	High	0.432	0.138	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
DH3	Low	1.687	0.270	0.4	Pass
	Middle	1.687	0.270	0.4	Pass
	High	1.687	0.270	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
DH5	Low	2.936	0.313	0.4	Pass
	Middle	2.936	0.313	0.4	Pass
	High	2.936	0.313	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel


Date: 22.MAR.2014 16:15:55

DH1: Middle Channel




Date: 22.MAR.2014 16:15:51

DH1: High Channel




Date: 22.MAR.2014 16:15:46

DH3: Low Channel




Date: 22.MAR.2014 16:28:44

DH3: Middle Channel




Date: 22.MAR.2014 16:29:00

DH3: High Channel




Date: 22.MAR.2014 16:29:05

DH5: Low Channel




Date: 22.MAR.2014 16:34:12

DH5: Middle Channel



Date: 22.MAR.2014 16:34:07

DH5: High Channel



Date: 22.MAR.2014 16:34:03

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa

* The testing was performed by Ares Liu on 2014-03-22.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	4.99	30
	Middle	2441	3.91	30
	High	2480	2.74	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	2.11	30
	Middle	2441	0.86	30
	High	2480	-0.58	30
EDR Mode (8-DPSK)	Low	2402	2.23	30
	Middle	2441	0.95	30
	High	2480	-0.33	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):

Output Power, Low Channel




Date: 22.MAR.2014 15:29:49

Output Power, Middle Channel



Date: 22.MAR.2014 15:32:29


Output Power, High Channel



Date: 22.MAR.2014 15:34:15


EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 22.MAR.2014 15:37:27

Output Power, Middle Channel



Date: 22.MAR.2014 15:40:31


Output Power, High Channel



Date: 22.MAR.2014 15:44:18


EDR Mode (8-DPSK):

Output Power, Low Channel




Date: 22.MAR.2014 15:47:35

Output Power, Middle Channel



Date: 22.MAR.2014 15:52:23

Output Power, High Channel



Date: 22.MAR.2014 15:54:53

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to the test equipment, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-06-16	2014-06-15


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	36%
ATM Pressure:	101.7 kPa


* The testing was performed by Ares Liu on 2014-03-22.

Test Result: Compliance*BDR Mode (GFSK):***Band Edge, Left Side**


Date: 22.MAR.2014 15:31:51

Band Edge, Right Side

Date: 22.MAR.2014 15:36:23

*EDR Mode ($\pi/4$ -DQPSK):***Band Edge, Left Side**


Date: 22.MAR.2014 15:40:02

Band Edge, Right Side

Date: 22.MAR.2014 15:46:42


EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 22.MAR.2014 15:51:14

Band Edge, Right Side



Date: 22.MAR.2014 15:57:08

***** END OF REPORT *****