

# **FCC PART 15.247 TEST REPORT**

For

# Roam Data Inc.

280 Summer St Boston, Massachusetts

FCC ID: 2ABY6-MOB30AA

Report Type: **Product Type:** 

Mobile Payment Terminal Original Report

Lion Xiao

Sola Hugof

Test Engineer: Lion Xiao

Report Number: RXM160719050-00A

**Report Date:** 2016-08-02

Sula Huang

**Reviewed By:** RF Leader

Bay Area Compliance Laboratories Corp. (Dongguan) **Test Laboratory:** 

No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

# **TABLE OF CONTENTS**

| GENERAL INFORMATION                                     | 4  |
|---|----|
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)      | 4  |
| Objective   |    |
| RELATED SUBMITTAL(S)/GRANT(S)                           |    |
| TEST METHODOLOGY  |    |
| TEST FACILITY   |    |
| SYSTEM TEST CONFIGURATION                               | 5  |
| DESCRIPTION OF TEST CONFIGURATION                       | 5  |
| EUT Exercise Software                                   |    |
| EQUIPMENT MODIFICATIONS                                 | 5  |
| SUPPORT EQUIPMENT LIST AND DETAILS                      | 5  |
| EXTERNAL CABLEBLOCK DIAGRAM OF TEST SETUP               |    |
|   |    |
| SUMMARY OF TEST RESULTS                                 | 6  |
| FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE        | 7  |
| APPLICABLE STANDARD                                     | 7  |
| FCC §15.203 - ANTENNA REQUIREMENT                       | 8  |
| APPLICABLE STANDARD                                     |    |
| ANTENNA CONNECTOR CONSTRUCTION                          |    |
| FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS           | 9  |
| APPLICABLE STANDARD                                     |    |
| MEASUREMENT UNCERTAINTY                                 |    |
| EUT SETUP   |    |
| EMI TEST RECEIVER SETUP                                 |    |
| TEST PROCEDURE  | 10 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION                |    |
| TEST EQUIPMENT LIST AND DETAILS<br>TEST RESULTS SUMMARY |    |
| TEST DATA   |    |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS  |    |
| APPLICABLE STANDARD                                     |    |
| MEASUREMENT UNCERTAINTY                                 |    |
| EUT SETUP.  |    |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP             | 15 |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS                         |    |
| CORRECTED AMPLITUDE & MARGIN CALCULATION                |    |
| TEST RESULTS SUMMARY                                    |    |
| TEST DATA   | 16 |
| FCC §15.247(a) (1) - CHANNEL SEPARATION TEST            |    |
| APPLICABLE STANDARD                                     |    |
| TEST EQUIPMENT LIST AND DETAILS                         |    |
| TEST PROCEDURE  | 22 |
| LENLUALA  | ,, |

| FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING                | 28 |
|---|----|
| APPLICABLE STANDARD   | 28 |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS.                            |    |
| TEST DATA   |    |
| FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST | 34 |
| APPLICABLE STANDARD   |    |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS.                            |    |
| TEST DATA   |    |
| FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)   | 38 |
| APPLICABLE STANDARD   | 38 |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS.                            |    |
| TEST DATA   |    |
| FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT          | 54 |
| APPLICABLE STANDARD   |    |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS.                            |    |
| Test Data   |    |
| FCC §15.247(d) - BAND EDGES TESTING                         | 56 |
| APPLICABLE STANDARD   |    |
| TEST PROCEDURE  |    |
| TEST EQUIPMENT LIST AND DETAILS.                            |    |
| Tect Data   |    |

### **GENERAL INFORMATION**

### **Product Description for Equipment under Test (EUT)**

The *Roam Data Inc.*'s product, model number: *MOBY-3000 (FCC ID: 2ABY6-MOB30AA)* (the "EUT") in this report was a *Mobile Payment Terminal*, which was measured approximately: 7.7 cm (L) x 5.3 cm (W) x 1.3 cm (H), rated input voltage: DC 3.7V from chargeable battery or DC5V charging from USB port.

Report No.: RXM160719050-00A

All measurement and test data in this report was gathered from production sample serial number: 160719050 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-20.

### **Objective**

This report is prepared on behalf of *Roam Data Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2ABY6-MOB30AA.

### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 4 of 59

# **SYSTEM TEST CONFIGURATION**

### **Description of Test Configuration**

The system was configured for testing in engineering mode.

### **EUT Exercise Software**

Test software: Bluetooth MP Tool was used during testing for swith the test modes, the maximum power was configured by the system default value.

### **Equipment Modifications**

No modification was made to the EUT.

# **Support Equipment List and Details**


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| DELL         | Laptop      | PP11L | QDS-BRCM1017  |

### **External Cable**

| Cable Description | Shielding<br>Type | Ferrite Core | Length (cm) | From Port | То  |
|-------------------|-------------------|--------------|-------------|-----------|-----|
| USB Cable         | no                | no           | 50          | Laptop    | EUT |

### **Block Diagram of Test Setup**

AC power line conducted emissions:



FCC Part 15.247 Page 5 of 59

# **SUMMARY OF TEST RESULTS**

| FCC Rules                             | Description of Test              | Result     |
|---------------------------------------|----------------------------------|------------|
| FCC §15.247 (i) & \$1.1310 & \$2.1093 | RF Exposure                      | Compliance |
| §15.203                               | Antenna Requirement              | Compliance |
| §15.207 (a)                           | Conducted Emissions              | Compliance |
| §15.205, §15.209,<br>§15.247(d)       | Spurious Emissions               | Compliance |
| §15.247 (a)(1)                        | 20 dB Bandwidth                  | Compliance |
| §15.247(a)(1)                         | Channel Separation Test          | Compliance |
| §15.247(a)(1)(iii)                    | Time of Occupancy (Dwell Time)   | Compliance |
| §15.247(a)(1)(iii)                    | Quantity of hopping channel Test | Compliance |
| §15.247(b)(1)                         | Peak Output Power Measurement    | Compliance |
| §15.247(d)                            | Band Edges                       | Compliance |

Report No.: RXM160719050-00A

FCC Part 15.247 Page 6 of 59

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RXM160719050-00A

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

#### **Measurement Result**

The max tune-up conducted power is 5.7dBm (3.72 mW). [(max. power of channel, mW)/(min. test separation distance, mm)][ $\sqrt{f(GHz)}$ ] = 3.72/5\*( $\sqrt{2}$ .48) = 1.2 < 3.0

So the stand-alone SAR evaluation is not necessary.

FCC Part 15.247 Page 7 of 59

# FCC §15.203 - ANTENNA REQUIREMENT

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RXM160719050-00A

#### **Antenna Connector Construction**

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 1.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

FCC Part 15.247 Page 8 of 59

# FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### **Applicable Standard**

FCC§15.207

### **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{\rm lab}$  is less than or equal to  $U_{\rm cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} U_{cispr})$ , exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} U_{\text{cispr}})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cispr}$ 

| Measurement   | $U_{ m cispr}$ |
|---|----------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB         |

# **EUT Setup**



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 9 of 59

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter of laptop was connected to a 120 VAC/60 Hz power source.

### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |  |  |
|------------------|--------|--|--|
| 150 kHz – 30 MHz | 9 kHz  |  |  |

#### **Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### **Corrected Amplitude & Margin Calculation**

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 $V_C$ : corrected voltage amplitude  $V_R$ : reading voltage amplitude  $A_c$ : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 10 of 59

### **Test Equipment List and Details**

| Manufacturer | Description        | Model   | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|--------------------|---------|------------------|---------------------|-------------------------|
| R&S          | EMI Test Receiver  | ESCS 30 | 830245/006       | 2015-12-10          | 2016-12-09              |
| R&S          | L.I.S.N            | ESH2-Z5 | 892107/021       | 2016-07-16          | 2017-07-15              |
| N/A          | Coaxial Cable      | 1.8m    | N/A              | 2016-05-06          | 2017-05-06              |
| R&S          | Two-line V-network | ENV 216 | 3560.6550.12     | 2015-11-26          | 2016-11-25              |
| R&S          | Test Software      | EMC32   | Version8.53.0    | N/A                 | N/A                     |

Report No.: RXM160719050-00A

### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

### 14.8 dB at 0.340821 MHz in the Neutral conducted mode

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 29.5°C    |
|--------------------|-----------|
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 100.2 kPa |


The testing was performed by Lion Xiao on 2016-07-26.

FCC Part 15.247 Page 11 of 59

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting

# AC120 V, 60 Hz, Line:




| Frequency<br>(MHz) | QuasiPeak<br>(dBµV) | Bandwidth<br>(kHz) | Line | Corr. (dB) | Margin<br>(dB) | Limit<br>(dBµV) | Comment    |
|--------------------|---------------------|--------------------|------|------------|----------------|-----------------|------------|
| 0.151200           | 43.1                | 9.000              | L1   | 10.2       | 22.8           | 65.9            | Compliance |
| 0.343548           | 34.6                | 9.000              | L1   | 10.3       | 24.5           | 59.1            | Compliance |
| 0.409372           | 30.5                | 9.000              | L1   | 10.2       | 27.2           | 57.7            | Compliance |
| 1.453260           | 31.5                | 9.000              | L1   | 10.4       | 24.5           | 56.0            | Compliance |
| 2.047133           | 34.2                | 9.000              | L1   | 10.4       | 21.8           | 56.0            | Compliance |
| 2.478557           | 34.0                | 9.000              | L1   | 10.4       | 22.0           | 56.0            | Compliance |

| Frequency<br>(MHz) | Average<br>(dBµV) | Bandwidth<br>(kHz) | Line | Corr. (dB) | Margin<br>(dB) | Limit<br>(dBµV) | Comment    |
|--------------------|-------------------|--------------------|------|------------|----------------|-----------------|------------|
| 0.340821           | 33.7              | 9.000              | L1   | 10.3       | 15.5           | 49.2            | Compliance |
| 0.375019           | 32.5              | 9.000              | L1   | 10.3       | 15.9           | 48.4            | Compliance |
| 0.409372           | 29.7              | 9.000              | L1   | 10.2       | 18.0           | 47.7            | Compliance |
| 2.063510           | 29.5              | 9.000              | L1   | 10.4       | 16.5           | 46.0            | Compliance |
| 2.252540           | 28.0              | 9.000              | L1   | 10.4       | 18.0           | 46.0            | Compliance |
| 2.420011           | 28.9              | 9.000              | L1   | 10.4       | 17.1           | 46.0            | Compliance |

FCC Part 15.247 Page 12 of 59

# AC120 V, 60 Hz, Neutral:



| Frequency<br>(MHz) | QuasiPeak<br>(dBµV) | Bandwidth<br>(kHz) | Line | Corr. (dB) | Margin (dB) | Limit<br>(dBµV) | Comment    |
|--------------------|---------------------|--------------------|------|------------|-------------|-----------------|------------|
| 0.150000           | 43.1                | 9.000              | N    | 10.2       | 22.9        | 66.0            | Compliance |
| 0.173134           | 39.9                | 9.000              | N    | 10.1       | 24.9        | 64.8            | Compliance |
| 0.343548           | 35.7                | 9.000              | N    | 10.3       | 23.4        | 59.1            | Compliance |
| 0.378019           | 33.6                | 9.000              | N    | 10.2       | 24.7        | 58.3            | Compliance |
| 1.967177           | 33.6                | 9.000              | N    | 10.4       | 22.4        | 56.0            | Compliance |
| 2.252540           | 34.5                | 9.000              | N    | 10.4       | 21.5        | 56.0            | Compliance |

| Frequency<br>(MHz) | Average<br>(dBµV) | Bandwidth<br>(kHz) | Line | Corr. (dB) | Margin<br>(dB) | Limit<br>(dBµV) | Comment    |
|--------------------|-------------------|--------------------|------|------------|----------------|-----------------|------------|
| 0.340821           | 34.4              | 9.000              | N    | 10.3       | 14.8           | 49.2            | Compliance |
| 0.375019           | 33.5              | 9.000              | N    | 10.2       | 14.9           | 48.4            | Compliance |
| 1.816511           | 28.9              | 9.000              | N    | 10.4       | 17.1           | 46.0            | Compliance |
| 1.845692           | 30.8              | 9.000              | N    | 10.4       | 15.2           | 46.0            | Compliance |
| 1.875341           | 29.8              | 9.000              | N    | 10.4       | 16.2           | 46.0            | Compliance |
| 2.216927           | 27.6              | 9.000              | N    | 10.4       | 18.4           | 46.0            | Compliance |

FCC Part 15.247 Page 13 of 59

# FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

### **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{\text{lab}}$  is less than or equal to  $U_{\text{cispr}}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{\text{lab}} U_{\text{cispr}})$ , exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} U_{\text{cispr}})$ , exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of  $U_{cispr}$ 

| Measurement  |        |  |  |  |  |
|--|--------|--|--|--|--|
| Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz) | 6.3 dB |  |  |  |  |
| Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)                   | 5.2 dB |  |  |  |  |
| Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)                  | 5.5 dB |  |  |  |  |


### **EUT Setup**

#### **Below 1GHz:**



FCC Part 15.247 Page 14 of 59

#### **Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz   | 120 kHz | QP       |
| Above 1 GHz       | 1MHz    | 3 MHz     | /       | PK       |
| Above I GHZ       | 1MHz    | 10 Hz     | /       | Ave.     |

### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 15 of 59

### **Test Equipment List and Details**

| Manufacturer             | Description       | Model               | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------------------|-------------------|---------------------|------------------|---------------------|-------------------------|
| R&S                      | EMI Test Receiver | ESCI                | 100224           | 2015-08-03          | 2016-08-02              |
| Sunol<br>Sciences        | Antenna           | JB3                 | A060611-3        | 2014-11-06          | 2017-11-05              |
| HP                       | Amplifier         | 8447E               | 2434A02181       | 2015-09-01          | 2016-09-01              |
| Agilent                  | Spectrum Analyzer | E4440A              | SG43360054       | 2015-11-23          | 2016-11-22              |
| ETS-Lindgren             | Horn Antenna      | 3115                | 9808-5557        | 2015-09-06          | 2018-09-06              |
| Mini-Circuit             | Amplifier         | ZVA-213-S+          | 054201245        | 2016-02-19          | 2017-02-19              |
| R&S                      | Spectrum Analyzer | FSP 38              | 100478           | 2015-11-23          | 2016-11-22              |
| Ducommun<br>Technolagies | Horn Antenna      | ARH-4223-02         | 1007726-01 1304  | 2014-06-16          | 2017-06-15              |
| Quinstar                 | Amplifier         | QLW-<br>18405536-JO | 15964001001      | 2015-09-06          | 2016-09-06              |
| N/A                      | Coaxial Cable     | 14m                 | N/A              | 2016-05-06          | 2017-05-06              |
| N/A                      | Coaxial Cable     | 8m                  | N/A              | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C</u>, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

#### 9.20 dB at 2390 MHz in the Horizontal polarization

#### **Test Data**

### **Environmental Conditions**

| Temperature:       | 28.7°C    |
|--------------------|-----------|
| Relative Humidity: | 68 %      |
| ATM Pressure:      | 100.2 kPa |


<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-27.

FCC Part 15.247 Page 16 of 59

Test mode: Transmitting

# 1) Below 1GHz (BDR mode middle channel is the worst case):


### **Horizontal:**



| Frequency<br>(MHz) | Receiver<br>Reading<br>(dBµV) | Detector<br>(PK/QP/Ave) | Correction<br>Factor<br>(dB/m) | Cord.<br>Amp.<br>(dBµV/m) | Limit<br>(dBµV/m) | Margin<br>(dB) |
|--------------------|-------------------------------|-------------------------|--------------------------------|---------------------------|-------------------|----------------|
| 106.6300           | 33.80                         | QP                      | -7.90                          | 25.90                     | 43.50             | 17.60          |
| 144.4600           | 33.37                         | QP                      | -6.97                          | 26.40                     | 43.50             | 17.10          |
| 216.2400           | 36.99                         | QP                      | -8.89                          | 28.10                     | 46.00             | 17.90          |
| 231.7600           | 36.69                         | QP                      | -7.99                          | 28.70                     | 46.00             | 17.30          |
| 252.1300           | 34.93                         | QP                      | -7.73                          | 27.20                     | 46.00             | 18.80          |
| 298.6900           | 36.74                         | QP                      | -5.84                          | 30.90                     | 46.00             | 15.10          |

FCC Part 15.247 Page 17 of 59

### Vertical:



| Frequency<br>(MHz) | Receiver<br>Reading<br>(dBµV) | Detector<br>(PK/QP/Ave) | Correction<br>Factor<br>(dB/m) | Cord.<br>Amp.<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------------------|-------------------------|--------------------------------|---------------------------|-------------------|----------------|
| 103.7200           | 36.00                         | QP                      | -8.60                          | 27.40                     | 43.50             | 16.10          |
| 216.2400           | 34.79                         | QP                      | -8.89                          | 25.90                     | 46.00             | 20.10          |
| 231.7600           | 35.09                         | QP                      | -7.99                          | 27.10                     | 46.00             | 18.90          |
| 288.0200           | 31.70                         | QP                      | -5.90                          | 25.80                     | 46.00             | 20.20          |
| 399.5700           | 29.89                         | QP                      | -3.59                          | 26.30                     | 46.00             | 19.70          |
| 507.2400           | 29.25                         | QP                      | -1.55                          | 27.70                     | 46.00             | 18.30          |

FCC Part 15.247 Page 18 of 59

# 2) 1G-25GHz:

BDR Mode (GFSK):

| Frequency |                       | eceiver    | Ry A  | ntenna     | Cable | Amplifier | Corrected | FCC 1    | 5.247  |
|-----------|-----------------------|------------|-------|------------|-------|-----------|-----------|----------|--------|
| •         | Reading               | Detector   | Polar | Factor     | loss  | Gain      | Amplitude | Limit    | Margin |
| (MHz)     | (dBµV)                | (PK/QP/AV) | (H/V) | (dB)       | (dB)  | (dB)      | (dBµV/m)  | (dBµV/m) | (dB)   |
|           | Low Channel: 2402 MHz |            |       |            |       |           |           |          | (ub)   |
| 2402      | 68.71                 | PK         | Н     | 25.65      | 3.66  | 0.00      | 98.02     | N/A      | N/A    |
| 2402      | 58.25                 | AV         | Н     | 25.65      | 3.66  | 0.00      | 87.56     | N/A      | N/A    |
| 2402      | 65.67                 | PK         | V     | 25.65      | 3.66  | 0.00      | 94.98     | N/A      | N/A    |
| 2402      | 55.73                 | AV         | V     | 25.65      | 3.66  | 0.00      | 85.04     | N/A      | N/A    |
| 2390      | 29.16                 | PK         | Н     | 25.61      | 3.63  | 0.00      | 58.40     | 74.00    | 15.60  |
| 2390      | 14.60                 | AV         | Н     | 25.61      | 3.63  | 0.00      | 43.84     | 54.00    | 10.16  |
| 4804      | 41.16                 | PK         | Н     | 30.59      | 5.06  | 27.41     | 49.40     | 74.00    | 24.60  |
| 4804      | 35.60                 | AV         | Н     | 30.59      | 5.06  | 27.41     | 43.84     | 54.00    | 10.16  |
| 7206      | 36.64                 | PK         | Н     | 34.09      | 6.61  | 25.91     | 51.43     | 74.00    | 22.57  |
| 7206      | 28.15                 | AV         | Н     | 34.09      | 6.61  | 25.91     | 42.94     | 54.00    | 11.06  |
| 9608      | 32.11                 | PK         | Н     | 36.74      | 8.53  | 27.55     | 49.83     | 74.00    | 24.17  |
| 9608      | 20.10                 | AV         | Н     | 36.74      | 8.53  | 27.55     | 37.82     | 54.00    | 16.18  |
| 3131      | 40.96                 | PK         | Н     | 27.62      | 6.93  | 27.43     | 48.08     | 74.00    | 25.92  |
| 3131      | 28.53                 | AV         | Н     | 27.62      | 6.93  | 27.43     | 35.65     | 54.00    | 18.35  |
|           |                       |            |       | iddle Chan |       |           |           |          |        |
| 2441      | 67.15                 | PK         | Н     | 25.75      | 3.76  | 0.00      | 96.66     | N/A      | N/A    |
| 2441      | 57.72                 | AV         | Н     | 25.75      | 3.76  | 0.00      | 87.23     | N/A      | N/A    |
| 2441      | 64.77                 | PK         | V     | 25.75      | 3.76  | 0.00      | 94.28     | N/A      | N/A    |
| 2441      | 54.13                 | AV         | V     | 25.75      | 3.76  | 0.00      | 83.64     | N/A      | N/A    |
| 4882      | 40.79                 | PK         | Н     | 30.79      | 5.19  | 27.42     | 49.35     | 74.00    | 24.65  |
| 4882      | 34.66                 | AV         | Н     | 30.79      | 5.19  | 27.42     | 43.22     | 54.00    | 10.78  |
| 7323      | 36.53                 | PK         | Н     | 34.38      | 6.75  | 25.88     | 51.78     | 74.00    | 22.22  |
| 7323      | 28.13                 | AV         | Н     | 34.38      | 6.75  | 25.88     | 43.38     | 54.00    | 10.62  |
| 9764      | 30.36                 | PK         | Н     | 36.81      | 8.62  | 27.20     | 48.59     | 74.00    | 25.41  |
| 9764      | 18.90                 | AV         | Н     | 36.81      | 8.62  | 27.20     | 37.13     | 54.00    | 16.87  |
| 3131      | 40.19                 | PK         | Н     | 27.62      | 6.93  | 27.43     | 47.31     | 74.00    | 26.69  |
| 3131      | 28.20                 | AV         | Н     | 27.62      | 6.93  | 27.43     | 35.32     | 54.00    | 18.68  |
| 3190      | 37.26                 | PK         | Н     | 27.81      | 6.26  | 27.38     | 43.95     | 74.00    | 30.05  |
| 3190      | 25.57                 | AV         | Н     | 27.81      | 6.26  | 27.38     | 32.26     | 54.00    | 21.74  |
|           | I                     |            |       | High Chann |       |           |           | , ,      |        |
| 2480      | 66.70                 | PK         | Н     | 25.85      | 3.68  | 0.00      | 96.23     | N/A      | N/A    |
| 2480      | 56.74                 | AV         | Н     | 25.85      | 3.68  | 0.00      | 86.27     | N/A      | N/A    |
| 2480      | 63.81                 | PK         | V     | 25.85      | 3.68  | 0.00      | 93.34     | N/A      | N/A    |
| 2480      | 53.98                 | AV         | V     | 25.85      | 3.68  | 0.00      | 83.51     | N/A      | N/A    |
| 2483.5    | 28.57                 | PK         | Н     | 25.86      | 3.67  | 0.00      | 58.10     | 74.00    | 15.90  |
| 2483.5    | 14.78                 | AV         | Н     | 25.86      | 3.67  | 0.00      | 44.31     | 54.00    | 9.69   |
| 4960      | 40.71                 | PK         | Н     | 31.00      | 5.34  | 27.43     | 49.62     | 74.00    | 24.38  |
| 4960      | 34.39                 | AV         | H     | 31.00      | 5.34  | 27.43     | 43.30     | 54.00    | 10.70  |
| 7440      | 35.33                 | PK         | H     | 34.66      | 6.89  | 25.97     | 50.91     | 74.00    | 23.09  |
| 7440      | 27.21                 | AV         | H     | 34.66      | 6.89  | 25.97     | 42.79     | 54.00    | 11.21  |
| 9920      | 32.87                 | PK         | H     | 36.87      | 8.71  | 26.66     | 51.79     | 74.00    | 22.21  |
| 9920      | 20.92                 | AV         | H     | 36.87      | 8.71  | 26.66     | 39.84     | 54.00    | 14.16  |
| 3131      | 40.79                 | PK         | H     | 27.62      | 6.93  | 27.43     | 47.91     | 74.00    | 26.09  |
| 3131      | 28.34                 | AV         | Н     | 27.62      | 6.93  | 27.43     | 35.46     | 54.00    | 18.54  |

FCC Part 15.247 Page 19 of 59

EDR Mode ( $\pi/4$ -DOPSK):

| Frequency | R              | eceiver                | Rx A           | ntenna      | Cable        | Amplifier    | Corrected          | FCC 1          | 5.247          |
|-----------|----------------|------------------------|----------------|-------------|--------------|--------------|--------------------|----------------|----------------|
| (MHz)     | Reading (dBµV) | Detector<br>(PK/QP/AV) | Polar<br>(H/V) | Factor (dB) | loss<br>(dB) | Gain<br>(dB) | Amplitude (dBµV/m) | Limit (dBµV/m) | Margin<br>(dB) |
|           |                |                        | ]              | Low Chann   | el: 2402 N   | МНz          |                    |                |                |
| 2402      | 70.24          | PK                     | Н              | 25.65       | 3.66         | 0.00         | 99.55              | N/A            | N/A            |
| 2402      | 58.09          | AV                     | Н              | 25.65       | 3.66         | 0.00         | 87.40              | N/A            | N/A            |
| 2402      | 67.82          | PK                     | V              | 25.65       | 3.66         | 0.00         | 97.13              | N/A            | N/A            |
| 2402      | 55.97          | AV                     | V              | 25.65       | 3.66         | 0.00         | 85.28              | N/A            | N/A            |
| 2390      | 29.80          | PK                     | Н              | 25.61       | 3.63         | 0.00         | 59.04              | 74.00          | 14.96          |
| 2390      | 15.24          | AV                     | Н              | 25.61       | 3.63         | 0.00         | 44.48              | 54.00          | 9.52           |
| 4804      | 38.94          | PK                     | Н              | 30.59       | 5.06         | 27.41        | 47.18              | 74.00          | 26.82          |
| 4804      | 30.38          | AV                     | Н              | 30.59       | 5.06         | 27.41        | 38.62              | 54.00          | 15.38          |
| 7206      | 32.10          | PK                     | Н              | 34.09       | 6.61         | 25.91        | 46.89              | 74.00          | 27.11          |
| 7206      | 20.04          | AV                     | Н              | 34.09       | 6.61         | 25.91        | 34.83              | 54.00          | 19.17          |
| 9608      | 30.87          | PK                     | Н              | 36.74       | 8.53         | 27.55        | 48.59              | 74.00          | 25.41          |
| 9608      | 18.70          | AV                     | Н              | 36.74       | 8.53         | 27.55        | 36.42              | 54.00          | 17.58          |
| 3131      | 40.87          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.99              | 74.00          | 26.01          |
| 3131      | 28.90          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 36.02              | 54.00          | 17.98          |
|           |                |                        | M              | iddle Chan  | nel: 2441    | MHz          |                    |                |                |
| 2441      | 69.16          | PK                     | Н              | 25.75       | 3.76         | 0.00         | 98.67              | N/A            | N/A            |
| 2441      | 57.33          | AV                     | Н              | 25.75       | 3.76         | 0.00         | 86.84              | N/A            | N/A            |
| 2441      | 66.09          | PK                     | V              | 25.75       | 3.76         | 0.00         | 95.60              | N/A            | N/A            |
| 2441      | 54.81          | AV                     | V              | 25.75       | 3.76         | 0.00         | 84.32              | N/A            | N/A            |
| 4882      | 38.08          | PK                     | Н              | 30.79       | 5.19         | 27.42        | 46.64              | 74.00          | 27.36          |
| 4882      | 30.47          | AV                     | Н              | 30.79       | 5.19         | 27.42        | 39.03              | 54.00          | 14.97          |
| 7323      | 32.23          | PK                     | Н              | 34.38       | 6.75         | 25.88        | 47.48              | 74.00          | 26.52          |
| 7323      | 20.77          | AV                     | Н              | 34.38       | 6.75         | 25.88        | 36.02              | 54.00          | 17.98          |
| 9764      | 30.22          | PK                     | Н              | 36.81       | 8.62         | 27.20        | 48.45              | 74.00          | 25.55          |
| 9764      | 18.79          | AV                     | Н              | 36.81       | 8.62         | 27.20        | 37.02              | 54.00          | 16.98          |
| 3131      | 40.54          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.66              | 74.00          | 26.34          |
| 3131      | 28.29          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 35.41              | 54.00          | 18.59          |
| 3610      | 38.43          | PK                     | Н              | 29.04       | 4.61         | 27.28        | 44.80              | 74.00          | 29.20          |
| 3610      | 26.88          | AV                     | Н              | 29.04       | 4.61         | 27.28        | 33.25              | 54.00          | 20.75          |
| 2400      | 60.52          | DIZ                    |                | High Chann  |              |              | 00.05              | NT/A           | 3.7/4          |
| 2480      | 68.52          | PK                     | Н              | 25.85       | 3.68         | 0.00         | 98.05              | N/A            | N/A            |
| 2480      | 56.78          | AV                     | Н              | 25.85       | 3.68         | 0.00         | 86.31              | N/A            | N/A            |
| 2480      | 65.64          | PK                     | V              | 25.85       | 3.68         | 0.00         | 95.17              | N/A            | N/A            |
| 2480      | 53.69          | AV                     | V              | 25.85       | 3.68         | 0.00         | 83.22              | N/A            | N/A            |
| 2483.5    | 29.12          | PK                     | Н              | 25.86       | 3.67         | 0.00         | 58.65              | 74.00          | 15.35          |
| 2483.5    | 15.07          | AV                     | Н              | 25.86       | 3.67         | 0.00         | 44.60              | 54.00          | 9.40           |
| 4960      | 38.83          | PK                     | H              | 31.00       | 5.34         | 27.43        | 47.74              | 74.00          | 26.26          |
| 4960      | 30.19          | AV                     | H              | 31.00       | 5.34         | 27.43        | 39.10              | 54.00          | 14.90          |
| 7440      | 32.25          | PK                     | H              | 34.66       | 6.89         | 25.97        | 47.83              | 74.00          | 26.17          |
| 7440      | 20.91          | AV                     | H              | 34.66       | 6.89         | 25.97        | 36.49              | 54.00          | 17.51          |
| 9920      | 32.85          | PK                     | H              | 36.87       | 8.71         | 26.66        | 51.77              | 74.00          | 22.23          |
| 9920      | 20.69          | AV                     | Н              | 36.87       | 8.71         | 26.66        | 39.61              | 54.00          | 14.39          |
| 3131      | 40.62          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.74              | 74.00          | 26.26          |
| 3131      | 28.08          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 35.20              | 54.00          | 18.80          |

FCC Part 15.247 Page 20 of 59

EDR Mode (8-DPSK):

| Frequency | R              | eceiver                | Rx A           | ntenna      | Cable        | Amplifier    | Corrected          | FCC 1             | 5.247       |
|-----------|----------------|------------------------|----------------|-------------|--------------|--------------|--------------------|-------------------|-------------|
| (MHz)     | Reading (dBµV) | Detector<br>(PK/QP/AV) | Polar<br>(H/V) | Factor (dB) | loss<br>(dB) | Gain<br>(dB) | Amplitude (dBµV/m) | Limit<br>(dBµV/m) | Margin (dB) |
|           |                |                        | J              | Low Chann   | el: 2402 N   | MHz          | •                  |                   |             |
| 2402      | 70.81          | PK                     | Н              | 25.65       | 3.66         | 0.00         | 100.12             | N/A               | N/A         |
| 2402      | 58.70          | AV                     | Н              | 25.65       | 3.66         | 0.00         | 88.01              | N/A               | N/A         |
| 2402      | 67.10          | PK                     | V              | 25.65       | 3.66         | 0.00         | 96.41              | N/A               | N/A         |
| 2402      | 55.13          | AV                     | V              | 25.65       | 3.66         | 0.00         | 84.44              | N/A               | N/A         |
| 2390      | 29.57          | PK                     | Н              | 25.61       | 3.63         | 0.00         | 58.81              | 74.00             | 15.19       |
| 2390      | 15.56          | AV                     | Н              | 25.61       | 3.63         | 0.00         | 44.80              | 54.00             | 9.20        |
| 4804      | 40.07          | PK                     | Н              | 30.59       | 5.06         | 27.41        | 48.31              | 74.00             | 25.69       |
| 4804      | 32.62          | AV                     | Н              | 30.59       | 5.06         | 27.41        | 40.86              | 54.00             | 13.14       |
| 7206      | 34.61          | PK                     | Н              | 34.09       | 6.61         | 25.91        | 49.40              | 74.00             | 24.60       |
| 7206      | 22.24          | AV                     | Н              | 34.09       | 6.61         | 25.91        | 37.03              | 54.00             | 16.97       |
| 9608      | 30.21          | PK                     | Н              | 36.74       | 8.53         | 27.55        | 47.93              | 74.00             | 26.07       |
| 9608      | 18.03          | AV                     | Н              | 36.74       | 8.53         | 27.55        | 35.75              | 54.00             | 18.25       |
| 3131      | 40.01          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.13              | 74.00             | 26.87       |
| 3131      | 28.76          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 35.88              | 54.00             | 18.12       |
|           |                |                        | M              | Iiddle Chan | nel: 2441    | MHz          |                    |                   |             |
| 2441      | 69.33          | PK                     | Н              | 25.75       | 3.76         | 0.00         | 98.84              | N/A               | N/A         |
| 2441      | 57.27          | AV                     | Н              | 25.75       | 3.76         | 0.00         | 86.78              | N/A               | N/A         |
| 2441      | 66.31          | PK                     | V              | 25.75       | 3.76         | 0.00         | 95.82              | N/A               | N/A         |
| 2441      | 54.56          | AV                     | V              | 25.75       | 3.76         | 0.00         | 84.07              | N/A               | N/A         |
| 4882      | 40.04          | PK                     | Н              | 30.79       | 5.19         | 27.42        | 48.60              | 74.00             | 25.40       |
| 4882      | 28.85          | AV                     | Н              | 30.79       | 5.19         | 27.42        | 37.41              | 54.00             | 16.59       |
| 7323      | 32.43          | PK                     | Н              | 34.38       | 6.75         | 25.88        | 47.68              | 74.00             | 26.32       |
| 7323      | 20.16          | AV                     | Н              | 34.38       | 6.75         | 25.88        | 35.41              | 54.00             | 18.59       |
| 9764      | 30.23          | PK                     | Н              | 36.81       | 8.62         | 27.20        | 48.46              | 74.00             | 25.54       |
| 9764      | 18.12          | AV                     | Н              | 36.81       | 8.62         | 27.20        | 36.35              | 54.00             | 17.65       |
| 3131      | 40.18          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.30              | 74.00             | 26.70       |
| 3131      | 28.31          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 35.43              | 54.00             | 18.57       |
| 3610      | 37.97          | PK                     | Н              | 29.04       | 4.61         | 27.28        | 44.34              | 74.00             | 29.66       |
| 3610      | 25.42          | AV                     | Н              | 29.04       | 4.61         | 27.28        | 31.79              | 54.00             | 22.21       |
|           | Υ              | r                      |                | High Chann  |              |              | Y                  |                   |             |
| 2480      | 68.95          | PK                     | Н              | 25.85       | 3.68         | 0.00         | 98.48              | N/A               | N/A         |
| 2480      | 56.10          | AV                     | Н              | 25.85       | 3.68         | 0.00         | 85.63              | N/A               | N/A         |
| 2480      | 65.24          | PK                     | V              | 25.85       | 3.68         | 0.00         | 94.77              | N/A               | N/A         |
| 2480      | 53.39          | AV                     | V              | 25.85       | 3.68         | 0.00         | 82.92              | N/A               | N/A         |
| 2483.5    | 28.41          | PK                     | Н              | 25.86       | 3.67         | 0.00         | 57.94              | 74.00             | 16.06       |
| 2483.5    | 14.94          | AV                     | Н              | 25.86       | 3.67         | 0.00         | 44.47              | 54.00             | 9.53        |
| 4960      | 39.78          | PK                     | Н              | 31.00       | 5.34         | 27.43        | 48.69              | 74.00             | 25.31       |
| 4960      | 31.22          | AV                     | Н              | 31.00       | 5.34         | 27.43        | 40.13              | 54.00             | 13.87       |
| 7440      | 32.49          | PK                     | Н              | 34.66       | 6.89         | 25.97        | 48.07              | 74.00             | 25.93       |
| 7440      | 20.13          | AV                     | Н              | 34.66       | 6.89         | 25.97        | 35.71              | 54.00             | 18.29       |
| 9920      | 29.99          | PK                     | Н              | 36.87       | 8.71         | 26.66        | 48.91              | 74.00             | 25.09       |
| 9920      | 17.95          | AV                     | Н              | 36.87       | 8.71         | 26.66        | 36.87              | 54.00             | 17.13       |
| 3131      | 40.71          | PK                     | Н              | 27.62       | 6.93         | 27.43        | 47.83              | 74.00             | 26.17       |
| 3131      | 28.29          | AV                     | Н              | 27.62       | 6.93         | 27.43        | 35.41              | 54.00             | 18.59       |

FCC Part 15.247 Page 21 of 59

### **Applicable Standard**

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RXM160719050-00A

### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Test Procedure**

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace.
- 3. Measure the channel separation.

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 30.1°C    |
|--------------------|-----------|
| Relative Humidity: | 53 %      |
| ATM Pressure:      | 100.2 kPa |

<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-26.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 22 of 59

Test Mode: Transmitting

1 00 /


| Mode    | Channel | Frequency<br>(MHz) | Channel<br>Separation<br>(MHz) | Limit (MHz) |
|---------|---------|--------------------|--------------------------------|-------------|
|         | Low     | 2402               | 0.996                          | 0.624       |
| GFSK    | Middle  | 2441               | 1.004                          | 0.600       |
|         | High    | 2480               | 1.004                          | 0.592       |
| / 4     | Low     | 2402               | 1.000                          | 0.820       |
| $\pi/4$ | Middle  | 2441               | 1.000                          | 0.820       |
| DQPSK   | High    | 2480               | 1.004                          | 0.820       |
| 8DPSK   | Low     | 2402               | 1.000                          | 0.860       |
|         | Middle  | 2441               | 0.996                          | 0.848       |
|         | High    | 2480               | 1.004                          | 0.852       |

Report No.: RXM160719050-00A

*Note: Limit=*  $(2/3) \times 20dB$  *bandwidth* 


### BDR Mode (GFSK):

### **Low Channel**




FCC Part 15.247 Page 23 of 59

### **Middle Channel**




### **High Channel**




FCC Part 15.247 Page 24 of 59

# EDR Mode ( $\pi/4$ -DQPSK):






### **Middle Channel**



FCC Part 15.247 Page 25 of 59


### Report No.: RXM160719050-00A

# **High Channel**




### EDR Mode (8-DPSK):

#### **Low Channel**




FCC Part 15.247 Page 26 of 59

### **Middle Channel**



### **High Channel**



FCC Part 15.247 Page 27 of 59

### **Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RXM160719050-00A

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 30.1°C    |  |
|--------------------|-----------|--|
| Relative Humidity: | 53 %      |  |
| ATM Pressure:      | 100.2 kPa |  |

<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-26.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 28 of 59

Test Mode: Transmitting

| Mode                     | Channel | Frequency<br>(MHz) | 20 dB<br>Bandwidth<br>(MHz) |
|--------------------------|---------|--------------------|-----------------------------|
| DDD 14 1                 | Low     | 2402               | 0.936                       |
| BDR Mode<br>(GFSK)       | Middle  | 2441               | 0.900                       |
| (GF5K)                   | High    | 2480               | 0.888                       |
| EDD V 1                  | Low     | 2402               | 1.230                       |
| EDR Mode<br>(π/4-DQPSK): | Middle  | 2441               | 1.230                       |
| (M4-DQ1 5K).             | High    | 2480               | 1.230                       |
|                          | Low     | 2402               | 1.290                       |
| EDR Mode<br>(8-DPSK):    | Middle  | 2441               | 1.272                       |
| (0-D1 5K).               | High    | 2480               | 1.278                       |


# BDR Mode (GFSK):

### Low Channel




FCC Part 15.247 Page 29 of 59

### **Middle Channel**




### **High Channel**




FCC Part 15.247 Page 30 of 59

### *EDR Mode (\pi/4-DQPSK):*

### **Low Channel**




### **Middle Channel**



FCC Part 15.247 Page 31 of 59


### Report No.: RXM160719050-00A

# **High Channel**




### EDR Mode (8-DPSK):

#### **Low Channel**




FCC Part 15.247 Page 32 of 59

### **Middle Channel**



### **High Channel**



FCC Part 15.247 Page 33 of 59

### **Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RXM160719050-00A

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

### **Environmental Conditions**

| Temperature:       | 31.2°C    |  |
|--------------------|-----------|--|
| Relative Humidity: | 54 %      |  |
| ATM Pressure:      | 100.2 kPa |  |

<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-27.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 34 of 59


Report No.: RXM160719050-00A

Test Mode: Transmitting

BDR Mode (GFSK):

| Frequency Range (MHz) | Number of<br>Hopping Channel | Limit |
|-----------------------|------------------------------|-------|
| 2400-2483.5           | 79                           | ≥15   |

# **Number of Hopping Channels**




FCC Part 15.247 Page 35 of 59

# EDR Mode ( $\pi/4$ -DQPSK):

| Frequency Range<br>(MHz) | Number of<br>Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5              | 79                           | ≥15   |

Report No.: RXM160719050-00A

# **Number of Hopping Channels**




FCC Part 15.247 Page 36 of 59

# EDR Mode (8-DPSK):

| Frequency Range<br>(MHz) | Number of<br>Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5              | 79                           | ≥15   |

Report No.: RXM160719050-00A

# **Number of Hopping Channels**



FCC Part 15.247 Page 37 of 59

#### **Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RXM160719050-00A

#### **Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 \* channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length \* hope rate/ number of hopping channels \* 31.6s Hop rate=1600/s

#### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 31.2°C    |
|--------------------|-----------|
| Relative Humidity: | 54 %      |
| ATM Pressure:      | 100.2 kPa |

<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-27.

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 38 of 59

Test Mode: Transmitting

BDR Mode (GFSK):


| Mode | Channel   | Pulse<br>Width<br>(ms) | Dwell<br>Time<br>(s) | Limit (s)   | Result     |  |
|------|---|------------------------|----------------------|-------------|------------|--|
|      | Low   | 0.388                  | 0.124                | 0.4         | Compliance |  |
| DH1  | Middle  | 0.382                  | 0.122                | 0.4         | Compliance |  |
| DIII | High  | 0.382                  | 0.122                | 0.4         | Compliance |  |
|      | Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s |                        |                      |             |            |  |
|      | Low   | 1.650                  | 0.264                | 0.4         | Compliance |  |
| DH3  | Middle  | 1.656                  | 0.265                | 0.4         | Compliance |  |
| DHS  | High  | 1.650                  | 0.264                | 0.4         | Compliance |  |
|      | Note: Dwell tin   | ne=Pulse time (        | $ms) \times (1600/$  | (4/79) ×31. | 6 s        |  |
|      | Low   | 2.910                  | 0.310                | 0.4         | Compliance |  |
| DH5  | Middle  | 2.900                  | 0.309                | 0.4         | Compliance |  |
| DIIS | High  | 2.910                  | 0.310                | 0.4         | Compliance |  |
|      | Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s                |                        |                      |             |            |  |

# **DH1: Low Channel**




FCC Part 15.247 Page 39 of 59

# **DH1: Middle Channel**




# DH1: High Channel




FCC Part 15.247 Page 40 of 59

**DH3: Low Channel** 




#### **DH3: Middle Channel**




FCC Part 15.247 Page 41 of 59

# DH3: High Channel




#### **DH5:** Low Channel




FCC Part 15.247 Page 42 of 59

# **DH5: Middle Channel**



# **DH5: High Channel**




FCC Part 15.247 Page 43 of 59

# *EDR Mode (\pi/4-DQPSK):*


| Mode  | Channel   | Pulse<br>Width<br>(ms) | Dwell<br>Time<br>(s) | Limit (s) | Result     |  |
|-------|---|------------------------|----------------------|-----------|------------|--|
|       | Low   | 0.394                  | 0.126                | 0.4       | Compliance |  |
| 2DH1  | Middle  | 0.392                  | 0.125                | 0.4       | Compliance |  |
| 2ДП1  | High  | 0.390                  | 0.125                | 0.4       | Compliance |  |
|       | Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s |                        |                      |           |            |  |
|       | Low   | 1.656                  | 0.265                | 0.4       | Compliance |  |
| 2DH3  | Middle  | 1.656                  | 0.265                | 0.4       | Compliance |  |
| 20113 | High  | 1.656                  | 0.265                | 0.4       | Compliance |  |
|       | Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$        |                        |                      |           | .6 s       |  |
|       | Low   | 2.910                  | 0.310                | 0.4       | Compliance |  |
| 2DH5  | Middle  | 2.910                  | 0.310                | 0.4       | Compliance |  |
| 2DП3  | High  | 2.910                  | 0.310                | 0.4       | Compliance |  |
|       | Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s                |                        |                      |           |            |  |

# **2DH1: Low Channel**




FCC Part 15.247 Page 44 of 59

# **2DH1: Middle Channel**




# 2DH1: High Channel




FCC Part 15.247 Page 45 of 59

#### **2DH3: Low Channel**




#### 2DH3: Middle Channel




FCC Part 15.247 Page 46 of 59

# 2DH3: High Channel




#### **2DH5: Low Channel**




FCC Part 15.247 Page 47 of 59

# 2DH5: Middle Channel



# 2DH5: High Channel




FCC Part 15.247 Page 48 of 59

# EDR Mode (8-DPSK):


| Mode  | Channel  | Pulse<br>Width<br>(ms) | Dwell<br>Time<br>(s)  | Limit (s)   | Result     |  |
|-------|--|------------------------|-----------------------|-------------|------------|--|
|       | Low  | 0.392                  | 0.125                 | 0.4         | Compliance |  |
| 3DH1  | Middle   | 0.390                  | 0.125                 | 0.4         | Compliance |  |
| SDIII | High   | 0.390                  | 0.125                 | 0.4         | Compliance |  |
|       | Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s |                        |                       |             |            |  |
|       | Low  | 1.656                  | 0.265                 | 0.4         | Compliance |  |
| 3DH3  | Middle   | 1.656                  | 0.265                 | 0.4         | Compliance |  |
| SDIIS | High   | 1.656                  | 0.265                 | 0.4         | Compliance |  |
|       | Note: Dwell tin  | ne=Pulse time (        | $ms) \times (1600/4)$ | 4/79) ×31.6 | S          |  |
|       | Low  | 2.920                  | 0.311                 | 0.4         | Compliance |  |
| 3DH5  | Middle   | 2.910                  | 0.310                 | 0.4         | Compliance |  |
| SDIIS | High   | 2.920                  | 0.311                 | 0.4         | Compliance |  |
|       | Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s |                        |                       |             |            |  |

# **3DH1: Low Channel**




FCC Part 15.247 Page 49 of 59

# **3DH1: Middle Channel**




#### 3DH1: High Channel




FCC Part 15.247 Page 50 of 59

**3DH3: Low Channel** 




#### **3DH3: Middle Channel**




FCC Part 15.247 Page 51 of 59

# **3DH3: High Channel**




#### **3DH5: Low Channel**




FCC Part 15.247 Page 52 of 59

# **3DH5: Middle Channel**



# 3DH5: High Channel



FCC Part 15.247 Page 53 of 59

# FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

#### **Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: RXM160719050-00A

#### **Test Procedure**

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

#### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 31.2°C    |
|--------------------|-----------|
| Relative Humidity: | 54 %      |
| ATM Pressure:      | 100.2 kPa |

<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-27.

Test Result: Compliance.

FCC Part 15.247 Page 54 of 59

Test Mode: Transmitting

| Mode                    | Channel | Frequency<br>(MHz) | Peak Output<br>power<br>(dBm) | Limit<br>(dBm) |
|-------------------------|---------|--------------------|-------------------------------|----------------|
|                         | Low     | 2402               | 4.07                          | 30             |
| BDR Mode<br>(GFSK)      | Middle  | 2441               | 3.40                          | 30             |
| (Gr 5K)                 | High    | 2480               | 2.64                          | 30             |
|                         | Low     | 2402               | 5.45                          | 30             |
| EDR Mode<br>(π/4-DQPSK) | Middle  | 2441               | 4.81                          | 30             |
| (M4-DQI SIC)            | High    | 2480               | 4.10                          | 30             |
|                         | Low     | 2402               | 5.66                          | 30             |
| EDR Mode<br>(8-DPSK)    | Middle  | 2441               | 5.11                          | 30             |
| (0-DI 5K)               | High    | 2480               | 4.47                          | 30             |

Note: The data above was tested in conducted mode.

FCC Part 15.247 Page 55 of 59

# FCC §15.247(d) - BAND EDGES TESTING

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

#### **Test Equipment List and Details**

| Manufacturer | Description       | Model           | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|-------------------|-----------------|------------------|---------------------|-------------------------|
| R&S          | Spectrum Analyzer | FSP 38          | 100478           | 2015-11-23          | 2016-11-22              |
| N/A          | Coaxial Cable     | 0.1m            | N/A              | 2016-05-06          | 2017-05-06              |
| E-Microwave  | DC Blocking       | EMDCB-<br>00036 | 0E01201047       | 2016-05-06          | 2017-05-06              |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 31.2°C    |
|--------------------|-----------|
| Relative Humidity: | 54 %      |
| ATM Pressure:      | 100.2 kPa |


<sup>\*</sup> The testing was performed by Lion Xiao on 2016-07-27.

FCC Part 15.247 Page 56 of 59


# Test Result: Compliance

#### BDR Mode (GFSK):

# Band Edge, Left Side



# Band Edge, Right Side




FCC Part 15.247 Page 57 of 59


# EDR Mode (π/4-DQPSK):

# Band Edge, Left Side

Report No.: RXM160719050-00A



# Band Edge, Right Side




FCC Part 15.247 Page 58 of 59


#### EDR Mode (8-DPSK):

#### Band Edge, Left Side

Report No.: RXM160719050-00A



# Band Edge, Right Side



\*\*\*\*\*END OF REPORT\*\*\*\*

FCC Part 15.247 Page 59 of 59